

AN ANALYSIS OF A PART OF
A CONTINUOUS CONCRETE BRIDGE

Thesis for the Degree of B. S.

MICHIGAN STATE COLLEGE

Takashi Nakamura

1949

**SUPPLEMENTARY
MATERIAL**
IN BACK OF BOOK

An Analysis of a Part of a
Continuous Concrete Bridge

A Thesis Submitted to
The Faculty of
MICHIGAN STATE COLLEGE
of
AGRICULTURE AND APPLIED SCIENCE
by

Tokashi Nakamura
Candidate for the Degree of
Bachelor of Science

June 1949

THES

C.1

PREFACE

The purpose of this thesis is to put into practice some of the theory learned by the author in a course in indeterminate structures. The method used here is neither the best nor the easiest, but it makes possible the application of the fundamental principles necessary for the design of a continuous concrete bridge.

The drawing of influence line diagrams makes up the major part of this thesis. These diagrams can be drawn with the aid of a handbook of frame constants or the Portland Cement Association publication entitled "Continuous Concrete Bridges." The author used the method of moment distribution chiefly because of his lack of foundation to thoroughly understand and appreciate the other shortcut methods available.

The author would like to take this opportunity to express his deep appreciation to Professor William A. Bradley, of the C.E. Dept. of Mich. State College, whose kind and patient assistance made this thesis possible. The author also goes to Mr. Porter of the Mich. State Co. who generously gave the author the plan for the bridge; Mr. Murray, also of the Mich. State Co., who made possible the comparison of this analysis with the actual design; and last but not least to Professor C. L. Allen, head of the C.E. Dept. of Mich. State College, whose constructive criticism aided in the organization of this thesis.

TN

TABLE OF CONTENTS

	page
Loading Specifications — — — — —	1
Brief Outline of Superstructure Slab Analysis — — — —	3
Moment Distribution for Influence Line Diagram (Analysis of slab design) — — — — —	5
Influence Line Diagrams for Slab Analysis — — — —	9
Analysis of Slab Design	
Loading, impact, stresses — — — — —	22
Wheel load distribution — — — — —	23
Maximum moments at sections along slab, max. shear —	23
Maximum total moments diagram — — — — —	24
Checking slab at point of maximum moment in span 1&2 —	25
Checking slab at point of maximum negative moment —	26
Checking negative moment steel at abutments — — —	27
Checking steel cutoffs — — — — —	29
Checking shear and bond — — — — —	30
Checking slab cross steel — — — — —	31
Brief Outline of Crossbeam Analysis — — — — —	32
Moment Distribution for Influence Line Diagram (Analysis of pier design) — — — — —	33
Influence Line Diagrams for Crossbeam Analysis — — —	38
Analysis of Crossbeam Design	
Load distribution — — — — —	57
Maximum moments at sections along beam — — — —	58
Maximum shear along crossbeam — — — — —	59

Maximum total shear diagram — — — — —	60
Checking beam at point of maximum positive moment —	61
Checking beam at point of maximum negative moment —	62
Checking bond, checking shear — — — — —	63
Checking vertical stirrups — — — — —	64
Checking cantilever section of crossbeam — — — —	65
Conclusion — — — — —	66
Bibliography — — — — —	67

LOADING SPECIFICATIONS (AASHTO-44)

3.2.1 - Loads.

Structures shall be proportioned for the following loads where they exist:

- (a) dead load.
- (b) live load.
- (c) impact or dynamic effect of live load.
- (d) wind loads.
- (e) other forces, when they exist.

3.2.2 - Dead Load.

The dead load shall consist of the weight of the structure complete, including the roadway, sidewalks, and ---

3.2.3 - Live Load.

The live load shall consist of the weight of the applied moving load of vehicles, cars and pedestrians.

3.2.4 - Overload Provision.

The following provision for overload shall apply to all loading except the H-20 and H-15-S16 loadings.

3.2.5 - Highway Loadings.

(See loading diagram for loading (a))

3.2.8 - (a) - Loading for Maximum Stresses.

The type of loading, whether lane loading or truck loading, to be used, and whether the span be simple or continuous, shall be that loading which produces the maximum stress.

For continuous spans, the lane loading shall be continuous or discontinuous, as may be necessary to produce maximum stresses, and the so concentrated load or loads as specified in paragraph 4 shall be placed in such position as to produce maximum stresses.

(paragraph 4 applies to H loading only)

3.2.9-Resisting Inboard Intensity.

Where maximum stresses are produced in any member by loading any number of traffic lanes simultaneously, the following percentages of the resisting live load stresses shall be used in view of improbable coincident maximum loading:

Four lanes or more ----- 75%

3.2.11-(a)-Sidewalk Loading.

Sidewalk floors, stringers, and their immediate supports, shall be designed for a live load of 25 pounds per square foot of sidewalk area. ---

3.2.12.-Impact.

$$I = \frac{57}{L+125} \quad (\text{maximum 30 percent})$$

I = impact fraction (to be mult by ratio LL stress, and this increment added to the total stress.)

L = length of the shortest span.

3.2.13-Longitudinal Forces.

(not considered in design by Mich State Highway Dept.)

3.2.14.-Wind Loads.

(not considered in design by Mich State Highway Dept.)

DISTRIBUTION OF LOADS

3.3.2 - Distribution of Loads and Design of Concrete Slabs

(a) Bending Moment.

Case C - Main reinforcement Parallel to Traffic

Span over 12 feet

$$\text{Wheel loads: } E = \frac{10N+WL}{2L}$$

E = width of slab over which a wheel load is applied.

N = max. number of lanes or traffic permissible.

W = width of roadway between curbs or walls.

BRIEF OUTLINE OF SUPERSTRUCTURE SLAB ANALYSIS

I-Loading to obtain maximum effects.

A-Influence line diagrams

1- These diagrams show the effect upon a particular section of the slab as a unit load is passed across the structure.

2- The method of moment distribution is used to obtain the effect of the unit load at the various sections.

a- In obtaining the carry over factors, a foot width of slab is used. The moment of inertia is calculated by using the outside dimensions of the foot width of slab.

3- The reactions upon the slab as the load crosses the structure are found, and the various points on the influence line (any moment or shear) are obtained by using these reactions.

B-Loading the influence line diagrams

1- Having drawn the influence line diagrams for the various critical sections, the max. moment or shear for each section is found by loading the diagram to obtain the max. effect. Both truck train and lane loading are used, and whichever gives the max. is taken as the controlling moment or shear.

a- The max. effect by truck train method is obtained by moving the truck train over the diagram until the max. condition is obtained (following AASHTO specs).

I - Analysis of slab design



A - Maximum total moment diagram

- 1- After the max moment on each critical section is found and tabulated (see page 23), a max. total moment diagram is drawn from which the steel cut-off can be determined. (see page 24 + 25).

B - Checking slab at critical sections

- 1- The slab is checked for max. and min. positive and negative moments. (see page 25 + 26).
- 2- Shearing and bond stresses are determined at the critical sections (see page 26).

MOMENT DISTRIBUTION FOR INFLUENCE LINE DIAGRAM (ANALYSIS OF SLAB BEAM)



12" width of slab

$$I_{slab} = 2.58 \times 10^6 = \frac{1}{12} (12) (17)^3$$

$$= 442 \text{ in}^4$$

$$CK_{ba} = \frac{2.1}{1} = \frac{5.49 \times 10^6}{12.5} = 442$$

$$CK_{cb} = \frac{1.1}{1} = \frac{4.42 \times 10^6}{12.5} = 449$$

$$\sum CK = 891$$

$$r_{ba} = \frac{442}{891} = .497$$


$$r_{cb} = \frac{449}{891} = .503$$

$$CK_{bc} = 445$$


$$r_{bc} = .504$$

$$-K_{cb} = -440$$


$$r_{cb} = .496$$




$$M_{ba} = \frac{P_{ab}}{12} (1 + \frac{1}{2} r_{ba}) = \frac{1}{12} (12.5) \left(\frac{5.49 \times 10^6}{12.5} \right) (1 + 2 \times .497) = 432 \text{ K-ft}$$




$$M_{ba} = \frac{(12)(203)}{2(33.3)^2} (2 + 33.3) = 550 \text{ k-ft}$$




$$M_{ba} = \frac{(14)(193)}{2(33.3)^2} (4 + 33.3) = 576 \text{ k-ft}$$




$$M_{ba} = \frac{(15)(183)}{2(33.3)^2} (5 + 33.3) = 598 \text{ k-ft}$$




$$M_{bc} = \frac{3PL}{16} = \frac{(3)(22.2)}{16} = 6.24 \text{ k·ft}$$



$$M_{bc} = \frac{15.2(22.2)}{2(22.2)^2} (22.2 + 22.2) = 6.16 \text{ k·ft}$$




$$M_{bc} = \frac{29.3(10)}{2(29.3)^2} (29.3 + 29.3) = 3.91 \text{ k·ft}$$




$$M_{bc} = \frac{P_0 x^2}{2} = \frac{(5)(37)^2}{(42)^2} = -3.95 \text{ k·m}$$

$$M_{cd} = \frac{(5)(14)^2}{(42)^2} = +1.520 \text{ k·m}$$




$$M_{bc} = \frac{(10)(37)(25)^2}{(42)^2} = -0.91 \text{ k·m}$$

$$M_{cd} = \frac{(10)(14)^2(25)}{(42)^2} = 1.97 \text{ k·m}$$



$$M_{bc} = M_{cb} = \frac{P_L}{8} = \frac{40}{8} = 5.20 \text{ k·m}$$

INTERIOR LINE DRAWING FOR FLAG A.D. 1911



Section for work on the flag design


Scale: 1" = 12'-0"

H20-S16-44

Maximum stress due to either lane or truck loading controls.

conc. load $\left\{ \begin{array}{l} 16,000 \text{ # for mom.} \\ 25,000 \text{ # for shear} \end{array} \right.$

uniform load - 640 # per lin. ft. at lane (10' wide)



Max. moments:

By lane loading:

$$+(122.5 \times 0.4 + 707 \times 0.4) = +205 \text{ k}\#$$

$$-(25.3 \times 0.4 \times 2 + 107 \times 0.8) = -51.7 \text{ k}\#$$

By truck-train loading:
(Cont.)

$$\frac{+291 \text{ k}\#}{2.05} \left. \vphantom{\frac{+291 \text{ k}\#}{2.05}} \right\} \text{ control}$$

Design moments:

$$\text{DL/ft width of slab} = 150 \left(\frac{17}{12} \right) / 1$$

$$= .212 \text{ k/ft of length}$$

$$\text{DL moment} = (122.5 - 50.6) 212$$

$$= \underline{+15.2 \text{ k}\#/\text{ft width-slab}}$$

* LL moment:

$$+\frac{291 \text{ k}\#}{(2)(5.25)} = +27.7 \text{ k}\#/\text{ft width-slab}$$


$$\text{impact} = .3(27.7) = +8.32 \text{ k}\#/\text{ft width-slab}$$

% reduction = 25%

$$\text{total L.L. moment} = 75(27.7 + 8.32)$$

$$= \underline{+27.2 \text{ k}\#/\text{ft width-slab}}$$

$$= \underline{-10.5 \text{ k}\#/\text{ft width-slab}}$$



M₁₁

* see computation sheet for wheel load placement (pg. 113)

Horizontal - "e" = 0.00'
Vertical - "f" = 2.0

Max moment:

By truck-train loading:

$$\left. \begin{array}{l} +128.2 \text{ kft} \\ -110.9 \text{ kft} \end{array} \right\} \text{ control}$$

Design moments/ft width - slab

$$\text{D.L. moment} = (75.0 - 51.26) \cdot 2/2$$


$$= +49.2 \text{ kft}$$

L.L. moment:

$$\text{total } +M = 196 \times 0.929 = +182 \text{ kft}$$

$$\text{total } -M = 110.4 \times 0.929 = -103 \text{ kft}$$

4.92



M_2

scale:
horizontal - 1" = 12' - 0"
vertical - 1" = 2.0

Taxation is

100

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

100-17869

100

100




75, rue de la Harpe

$$\text{D.L. moment} = -(10 \times 5 - 10 \times 2,22) = -3,82 \text{ kNm}$$

7-10-11

[illegible]

$$f(x) = \frac{1}{2} + \frac{1}{2} \cos 2x + \frac{1}{2} \sin 2x$$



5

1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525

541

353

2.13

A = 795

22.2'

Max. moment:

By truck-train loading:

$\left. \begin{array}{l} +252.1 \text{ k}\# \\ -133 \text{ k}\# \end{array} \right\} \text{ control}$

Design moments/ft width - slab

DL moment = $(92.4 - 63.9) \cdot 2.12$

= $\pm 6.24 \text{ k}\#$

LL moment:

total +M = $252.1 \times 0.929 = +234 \text{ k}\#$

total -M = $133 \times 0.929 = -123 \text{ k}\#$

A = 63.9

229

1.22


0.56 0.56

A = 12.9

0.44

M₄

Scale:
horizontal - 1" = 12'-0"
vertical - 1" = 20



Max. moment
 at center of span


$$M = \frac{wL^2}{8}$$

Design moment $M_d = 1012 \times 10^3$
 Dimension $= (1012 \times 10^3) / 212$

$$= 4774$$

LL moment:

total $M = 1012 \times 10^3$
 total $M = 1012 \times 10^3$



M₇

scale:
 horizontal - 1" = 12'-0"
 vertical - 1" = 200

Max. reaction:

By lane loading:

$$+(1457 \times .64 + 26) = +353 \text{ k}$$

$$-(2.82 \times .64 + .11 \times 26) = -4.7 \text{ k}$$

By truck-train loading:

$$\left. \begin{array}{l} +49.6 \text{ k} \\ -64 \text{ k} \end{array} \right\} \text{ control}$$


Design reaction/ft width - slab

D.L. reaction = $(1457 - 282) / 2.12$


= $+243 \text{ k}$

L.L. reaction = $(496) / 0.929$

= $+462 \text{ k}$



See also:
 horizontal - "A" = 13.94
 vertical - "B" = 0.23



Max. shear:

By truck-train loading:

$$\frac{2.5 \times 3.3 \times 10^3}{6 \times 10^3} \text{ control}$$

Design shear at width = 8.00

D.L. shear = $(2.5 \times 3.3 \times 10^3)$

$$= 8.25 \times 10^3$$

L.L. shear = $(5.0 \times 3.3 \times 10^3)$

$$= 16.5 \times 10^3$$

S₁

scale
 horizontal - 1" = 2'-0"
 vertical - 1" = 6'-0"

Max. shear:

By truck-trail loading:

$$\left. \begin{array}{l} +54.4' \\ -4.51' \end{array} \right\} \text{control}$$

1000


Design shear / ft width-slab

[L. shear:

$$+(21) 2.2 = +44.2'$$

LL shear:

$$+(54.4)(.9920) = 53.94'$$



total:
horizontal = 1.0000"
vertical = 1.0000"

S₂

ANALYSIS OF SLAB DESIGN

SPAN:

Clear: $31'-11\frac{1}{2}" - 39'-9" - 31'-11\frac{1}{2}"$


C/C : $3329' - 4200' - 3329'$

WIDTH:

Two - 44' clear roadways

LOADING:

H20 - S16 - 44



IMPACT:

$$I = \frac{50}{L+125} \approx .30$$

$$I = \frac{50}{333+125} = .1316 \quad \therefore \text{use } .30$$

STRESSES:

$$f'_c = 3000$$

$$f_s = 18000$$

$$f_c = 1000$$

$$n = 10$$

$v = 60$ - no web reinforcement or special anchorage

$= 90$ - " " " with " "

$= 140$ - with " " no " "

$= 180$ - " " " and " "

$u = 100$ - with no special anchorage

$= 150$ - with special anchorage

WHEEL LOAD DISTRIBUTION:

$$E = \frac{10N + W}{4N}$$

$$E = \frac{10 \times 5 + 25}{4 \times 5} = \frac{175}{22} = 5.25'$$

∴ moment & shear / ft width of slab due to live load only =

$$\frac{\text{moment, or shear due to wheel load}}{2 \times 5.25}$$

MAXIMUM MOMENTS @ SECTIONS ALONG SLAB:


SPAN	SECTION	DL MOMENT (K.ft)	LL + IMPACT MOM (K.ft)	TOTAL (K.ft)
1 & 3	0	0	0	0
	11.1'	+16.0	+26.0	+42.00
	11.1'	+16.0	-6.4	+9.60
	14.0'	+15.9	+26.6	+42.50
	14.0'	+15.9	-8.25	+7.65
	22.2'	+6.04	+23.4	+29.44
	22.2'	+6.04	-12.8	-6.76
2	33.3'	-31.2	-21.7	-52.90
	33.3'	-31.2	+4.36	-26.84
	43.3'	+4.90	+18.2	+23.10
	43.3'	+4.90	-10.3	-5.40
	54.3'	+15.2	+27.0	+42.20
	54.3'	+15.2	-10.3	+4.90

MAXIMUM SHEAR:

$$\text{At } R_a = +7.1^k$$


$$\text{At } R_a = +9.7^k$$

MAXIMUM TOTAL MOMENTS



Scale: 1" = 10'-0"

CHECKING SLAB AT POINT OF MAX MOM. IN SPAN 1 & 2:



$$12x\left(\frac{x}{2}\right) = 25 - (15.5 - x)$$

$$6x^2 = 400 - 25.5x$$

$$x^2 + 4.2x - 22.7 = 0$$

$$x = \frac{-4.2 \pm \sqrt{4.2^2 + 4(22.7)}}{2} = \frac{-4.2 + 16.3}{2} = 6.3"$$

$$C_{jt} = B.M. = 425 \text{ K'}.$$

$$C = \frac{12x^2 \pm f_c}{2} = \frac{40000 \times 12}{2 \times 1}$$

$$f_c = \frac{1012 \text{ K'}}{12} \quad \text{all walls} = 1000 \text{ K'}$$

$$A_s f_s = T - C = \frac{42500 \times 2}{16.4}$$

$$f_s = \frac{4250 \times 2}{2.5 \times 16.4} = 19900 \text{ K'}$$


$$\text{allowable} = 18000 \text{ K'}$$

allowable by Mich State Highway Specs.

$$f_c = 1850 \text{ K'}$$

$$f_s = 18000 \text{ K'}$$

CHECKING SLAB AT POINT OF MAX. NEGATIVE MOM:



$$12x\left(\frac{x}{2}\right) = 32.7(15.5 - x)$$

$$6x^2 = 507 - 32.7x$$

$$x^2 + 5.55x - 84.5 = 0$$

$$x = \frac{-5.55 + \sqrt{(5.55)^2 + 4(84.5)}}{2} = \frac{-5.55 + 19.2}{2} = 6.82"$$

$$C_{jd} = B.M. = -52.9 \text{ kft}$$

$$C = \frac{52.9 \times 12}{13.23} = 48,000 \text{ #}$$

$$C = \frac{12 \times 6.82}{2} f_c = 48,000$$

$$f_c = 1170 \text{ psi, allowable} = 1000 \text{ psi}$$

$$T = A_s f_s = \frac{48,000}{3.27} = 14,700 \text{ psi}$$


$$\text{allowable} = 18,000 \text{ psi}$$

allowables by Mich State Highway Dept.

$$f_c = 1350 \text{ psi}$$

$$f_s = 18,000 \text{ psi}$$

CHECKING NEGATIVE MOMENT STEEL @ ABUTMENTS:



Assume slab fixed at section A-A.

From influence line diagram max reaction at end
 $= (2.49 + 4.60) = 7.09 \text{ K/ft}$

$$M = 709 \times 10 = 709 \text{ K-ft/ft width of slab}$$


Using Mich State Highway Dept. spec.,

$$f_c = 3000 \text{ psi}$$

$$f_s = 18000 \text{ psi}$$

$$f_s = 18000 \text{ psi}$$

$$n = 10$$



$$12x\left(\frac{x}{2}\right) = 10(15.5 - x)$$

$$6x^2 = 155 - 10x$$

$$x^2 + 1.667x - 25.83 = 0$$

$$x = \frac{-1.667 \pm \sqrt{(1.667)^2 + 4(25.83)}}{2} = \frac{-1.667 + 10.3}{2} = 4.31''$$

$$Cjd = 70.900 \text{ in}^2$$

$$C = \frac{70.900}{14.33} = 5040''$$

$$\frac{12(4.31)}{2} f_c = 5040$$

$$f_c = \underline{195 \text{ psi}} \quad \text{allowable} = 1250 \text{ psi}$$


$$A_s f_s = 5040$$

$$f_s = \underline{5040 \text{ psi}} \quad \text{allowable} = 18000 \text{ psi}$$

CHECKING STEEL CUTOFFS:

(see maximum total moment diagram)

1. At points 2' on each side of point of max. negative moment
 steel required = 17.51 sq. ft. width of span.
 steel provided = 22.7 sq."
2. At points 10' on each side of point of max. negative moment
 steel required = 0.28 sq" per foot width of span.
 steel provided = 1.27 sq"
3. No negative moment steel required beyond point 18' on each
 side (+15 sq. ft. steel = 18' x .75'). Steel already cut in first span
 beyond 2' from pier.
4. For positive moment in spans one and two, steel required at
 points 10' from pier = 1.64 sq"
 steel provided = 1.69 sq"
5. For negative moment at end of end, Main Store Highway, Day's
 design and finally placed a safe amount of steel.
 (see computation sheet for negative analysis)



CHECKING SHEAR & BOND:

$$v = \frac{V}{b_j d}$$

$$V_{\max.} @ R_b = 97^k$$

$$v = \frac{9722}{125(34)} = 22.2 \text{ %} \quad \text{allowable} = 60 \text{ %}$$

$$u = \frac{V}{\Sigma o_j d}$$

$$@ \text{ point of max negative moment } \Sigma o = 12.5"$$


$$u = \frac{9722}{125(12.5)} = 62.0 \text{ %} \quad \text{allowable} = 100 \text{ %}$$

$$@ \text{ reaction } R_a, \Sigma o = 6.3"; \quad V = 71^k$$

$$u = \frac{7100}{6.3(12.25)} = 92.2 \text{ %} \quad \text{allowable} = 150 \text{ %}$$

$$@ \text{ points 10' from point of max neg. mom. in span 2 } \Sigma o = 8.0"$$

$$V = 3570^k \quad (\text{revising influence line diag. } S_E, \uparrow \text{ loading to get max. effect})$$



$$u = \frac{3570}{8.0(12.4)} = 36.2 \text{ %} \quad \text{allowable} = 100 \text{ %}$$

CHECKING SLAB CROSS STEEL:

AASHTO. Specs. - 3.2.2 (c)

Percentage of main reinforcement to be placed at bottom of slab normal to the main steel =

$$\frac{100}{\sqrt{S}} \leq 50\%$$

S = effective span of slab

$$\frac{100}{\sqrt{32}} = 17.7\%$$

17.7% (2.58) = .46 sq/ft length of slab - required

.51 sq/ft provided ($\frac{3}{8}$ " p)

By Mich State Highway Dept. Specs.

For spans over 20':

middle half - 25% of main reinforcement

other sections - 15% " " "

$$.25(2.58) = .645 \text{ sq/ft length of slab}$$

$$.15(2.58) = .387 \text{ sq/ft " " " } \left. \vphantom{.15(2.58)} \right\} \text{ required}$$

.62 sq for middle half

.38 sq for remaining section } provided

Temperature steel to be placed at top of slab normal to main reinforcement =

$$\frac{1}{8} \text{ sq/ft width of surface (123 sq)} \text{ required}$$

.293 sq provided

BRIEF OUTLINE OF CROSSBEAM ANALYSIS

I-Loading to obtain maximum effect

A-Influence line diagrams

- 1- See slab analysis outline.

B-Loading the influence line diagrams

- 1- The live load to be distributed upon the beam to obtain the maximum effect is determined from the influence line diagram R_0 (see page 57).

1- Maximum dead load and live load reactions per foot width of slab obtained from R_0 gives the maximum dead load and live load upon the crossbeam per linear foot of beam.

- 2- Dead load and live load effect of slabs w_k is also included (see page 57).

II - Analysis of beam design

A-Checking maximum moments on beam

- 1- The max. positive and negative moments on the beam are determined by properly loading the beam, and the reinforcing steel is checked (see pages 58, 61 & 62).

B-Checking bending and bond stresses


- 1- See page 63

C-Checking stresses

- 1- See pages 64 & 65.


MOMENT DISTRIBUTION FOR INFLUENCE LINE DIAGRAM (ANALYSIS OF PER DECKING)

Beam:




$$I_b = \frac{1}{12}bh^3 = \frac{1}{12}(25)(25)^3 = 6289.58$$

Column:



$$I_c = \frac{1}{12}bh^3 = \frac{1}{12}(25)(25)^3 = 6289.58$$





$$\left. \begin{aligned} CK_{bn} &= \frac{5 \times 12^3 \times 25^3}{4 \times 25^3} = 1205 \\ CK_{bc} &= \frac{4 \times 12^3 \times 25^3}{4 \times 25^3} = 1205 \end{aligned} \right\} \sum CK = 1277 \quad \begin{aligned} r_{bn} &= 2.41 \\ r_{bc} &= 2.41 \end{aligned}$$

$$\left. \begin{aligned} CK_{cd} &= \frac{4 \times 21^3 \times 25^3}{4 \times 25^3} = 1205 \\ CK_{de} &= \frac{4 \times 21^3 \times 25^3}{4 \times 25^3} = 1205 \end{aligned} \right\} \sum CK = 2749 \quad \begin{aligned} r_{cd} &= 2.41 \\ r_{de} &= 2.41 \end{aligned}$$

$$CK_{ef} = \frac{4 \times 11^3 \times 25^3}{4 \times 25^3} = 1205 \quad r_{ef} = 2.41$$


Note:

Because of the heavy uniform deck load & wide column spacing, the slenderness was considered in the following analysis.




$$M_{bc} = \frac{P_{uc} L^2}{2} = \frac{15 (16)^2}{2} = 290 \text{ k-ft}$$

$$M_{cd} = \frac{(15) (5)^2}{2} = 0.937 \text{ k-ft}$$




$$M_{bc} = M_{cd} = \frac{PL}{8} = \frac{21}{8} = 2.625 \text{ k-ft}$$




$$M_{bc} = \frac{P_0 L^2}{8} = \frac{(5)(5)^2}{8} = 0.907 \text{ k-ft}$$

$$M_{cd} = \frac{15(5)^2}{8} = 2.907 \text{ k-ft}$$




$$M_{cd} = \frac{P_0 b^2}{L^2} = \frac{(5)(16)^2}{(21)^2} = 2.90 \text{ kft}$$

$$M_{dc} = \frac{(16)(5)^2}{(21)^2} = 0.907 \text{ kft}$$



$$M_{cd} = M_{dc} = \frac{PL}{8} = \frac{21}{8} = 2.63 \text{ kft}$$

INFLUENCE LINE DIAGRAMS FOR CROSSBEAM ANALYSIS:



Sections for wire-influence line diagrams are shown

7.71'
3.71'

Q=80

A=297

Q=217

7.71

Design moment at M_1

DL of beam = $150 \frac{\text{ft}}{\text{ft}} \times (25 \text{ ft} \times 50 \text{ ft}) = 1125 \frac{\text{K}}{\text{ft}}$ length of beam

* D.L. moment:

DL of beam = $297(1125) = -334 \text{ K}$

DL of sidewalk = $217(55) = -1195$

DL of slab = $217(55) = -2002 \text{ K}$
 total = -4179 K

* LL moment:

LL on sidewalk = $217(232) = -500$

LL of traffic = $50(532) = -474$
 total = -974 K

* see computation sheet on cross frame analysis for load distribution (see p. 10.57)

M_1

scale:
 horizontal - 1" = 10'-0"
 vertical - 1" = 20K



Design moment at M_2

DL moment:

$$DL \text{ of beam} = .125(329) = -37.0 \text{ kft}$$

$$DL \text{ of sidewalk} = 551(134) = -72.8$$

$$DL \text{ of slab} = 894(329) = -224.0$$

$$\text{total} = -494.8 \text{ kft}$$

LL moment:

$$LL \text{ on sidewalk} = 322(134) = -512$$

$$LL \text{ of traffic} = 532.22(5) = -135.0$$

$$\text{total} = -145.2 \text{ kft}$$

$$\text{Total (+) L.L. mom} = 592(329) = +195.5 \text{ kft}$$

M_2

scale
horizontal = 1"=10'-0"
vertical = 1"=100k

354

133

120

A = 31.0

3.71'

Q = 106

A = 612

Q = 446

A = 6.4

.44

.45

.23

A = 12

.09 .10 .02

A = 0.32

.03

.01

A = 0.03

Design moment: M_d

DL moment:

$$DL \text{ of beam} = 1.125(19.33) = + 21.9 \text{ k}\cdot\text{ft}$$

$$DL \text{ of sidewalk} = 5.51(4.46) = - 24.6$$

$$DL \text{ of slab} = 8.94(19.33) = + 172.2$$

$$\text{total} = + 170.2 \text{ k}\cdot\text{ft}$$

LL moment:

$$LL \text{ on sidewalk} = 3.82(4.46) = - 17.0$$

$$LL \text{ of traffic} = 5.92(6.72) = - 39.8$$

$$\text{total} = - 56.8 \text{ k}\cdot\text{ft}$$

$$\text{Total (+) LL moment} = 5.92(32.2) = + 190.8 \text{ k}\cdot\text{ft}$$

M_d

Scale:
horizontal 1" = 10'-0"
vertical 1" = 10 k\cdot\text{ft}

Design moment at M₅

D.L. moment:

$$\text{D.L. of beam} = 1.125(2.33) = +2.68 \text{ kft}$$

$$\text{D.L. of sidewalk} = 55.1(0.06) = +0.93$$

$$\text{D.L. of slab} = 894(2.33) = +21.30$$

$$\text{total} = \underline{\underline{+24.31 \text{ kft}}}$$


L.L. moment:

$$\text{L.L. on sidewalk} = 3.82(0.06) = +0.23$$

$$\text{L.L. of traffic} = 5.92(14.23) = +84.80$$


$$\text{total} = \underline{\underline{+85.03 \text{ kft}}}$$

$$\text{Total (-) L.L. mom.} = 5.92(12) = \underline{\underline{-71.0 \text{ kft}}}$$



M₅

scale:
horizontal - 1" = 10'-0"
vertical - 1" = 1.0 kft



Design moment of M_0

DL moment:


DL of beam = $1125(3.25) = -4.2$
 DL of sidewalk = $55(4.42) = +24.5$
 DL of slab = $+94(0.25) = +23.5$
 total = $+43.8$

LL moment:

LL on sidewalk = $222(4.42) = +97.7$
 LL of traffic = $55(4.32) = +23.8$
 total = $+121.5$
 Total (-) LL mom. = $552(4.42) = +243.8$

M_0

section:
 horizontal = $10'-0"$
 vertical = $1'-10"$



Design moment at M₇

DL moment:

$$DL \text{ of Leqm} = 1125(549) = -617 \text{ Kt}$$

$$DL \text{ of truss} = 551(287) = +158$$

$$DL \text{ of slab} = 894(249) = -2220$$

$$\text{Total} = -2282 \text{ Kt}$$

LL moment:


$$LL \text{ of side walk} = 382(287) = +110$$

$$LL \text{ of truss} = 592(500) = +296$$

$$\text{Total (+) LL mom} = 592(425) = +250 \text{ Kt}$$

M₇

Scale:
horizontal - 1" = 10'-0"
vertical - 1" = 10 Kt



$$D.L. \text{ of beam} = 1.125(9.0) = +3.34 \text{ kft}$$

$$D.L. \text{ of sidewalk} = 5.51(1.82) = +10.02$$

$$D.L. \text{ of slab} = 3.34(3.0) = +10.02$$

$$\text{total} = +40.2 \text{ kft}$$

L.L. moment:

$$L.L. \text{ on sidewalk} = 3.52(1.82) = +6.95$$

$$L.L. \text{ of traffic} = 5.92(1.81) = +10.75$$

$$\text{total} = +17.7 \text{ kft}$$

$$\text{Total (-) L.L. moment} = 5.92(1.81) = -10.75 \text{ kft}$$

M_8

Scale:
horizontal = 1" = 10'-0"
vertical = 1" = 10 kft

Design moment at M₃

D.L. moment:

$$D.L. \text{ of beam} = 1.25(7.4) = +9.25$$

$$D.L. \text{ of side walls} = 5(1.4) = +7.0$$

$$D.L. \text{ of slabs} = 8.94(7.74) = +69.22$$

$$\text{total} = +85.47$$

L.L. moments:

$$L.L. \text{ on side walls} = 5(2.14) = +10.7$$

$$L.L. \text{ on traffic} = 5(2.2) = +11.0$$

$$\text{total} = +21.7$$

$$\text{Total (-) L.L. moment} = 59.2(27) = 1608.6$$

338

109

A=275

47

24

A=181

A=28

A=6.4

27

44

44

A=6.3

22

40

41

108

108

104

A=14

A=207

M₃

mod. to:
horizontal = 10'-0"
vertical = 1'-0"

Design moment of M_{10}

DL moment:

DL of beam = $125(8.95) = +1118.75$

DL of middle = $55(4) = +220$

DL of end = $194(9.95) = +1930.3$

total = 3269.05


LL moment:

LL on span, $0.7 = 2(2.4) = -4.8$


LL on track = $5.8(10) = 58$

total = 53.2

Total (+, LL max) = $3269.05 + 53.2 = 3322.25$




Scale:
 Horizontal = 1" = 10'-0"
 Vertical = 1" = 10k



1411

100' 100' 100'
 100' 100' 100'
 100' 100' 100'



Design moment at M_{12}

Sec M_{11}

M_{12}

scale:
horizontal - 1" = 10'-0"
vertical - 1" = 10k

371'

a=371

A=7.71

a=40

1.2000

Design shear at S₁

DL shear:

$$DL \text{ of beam} = 1125(771) = - 867 \text{ k}$$

$$DL \text{ of sidewalk} = 551(371) = -2140$$

$$DL \text{ of slab} = 894(771) = -68990$$

$$\text{total} = -94.0 \text{ k}$$

LL shear:


$$LL \text{ on sidewalk} = 3.82(371) = -1420$$

$$LL \text{ of traffic} = 592(400) = -2370$$

$$\text{total} = -379 \text{ k}$$

S₁

scale:
horizontal - 1"=10'-0"
vertical - 1"=3k



Design of Road Cross-section

DL (mm)

$$DL = 12.8 \times 0.74 = 9.472$$

$$DL = 12.8 \times 0.72 = 9.216$$

$$DL = 12.8 \times 0.70 = 8.96$$

$$DL = 12.8 \times 0.68 = 8.704$$

DL (mm)

$$DL = 12.8 \times 0.74 = 9.472$$


$$DL = 12.8 \times 0.72 = 9.216$$

$$DL = 12.8 \times 0.70 = 8.96$$

$$Total (mm) = 9.472 + 9.216 + 8.96 + 8.704 = 36.352$$

36.352 mm
 height of road cross-section
 36.352 mm

36.352



Vertical curve data


DL segment

DL on segment = $1125' \times 0.23\% = 258.75'$
 DL on segment = $55' \times 13\% = 71.5'$
 DL on segment = $594' \times 10.5\% = 622.7'$
 Total = $1453.0'$

LL segment

LL on segment = $242' \times 0.23\% = 55.66'$
 LL on segment = $592' \times 11\% = 65.12'$
 Total = $120.78'$


Total (+) LL segment = $532' \times 11.94\% = 634.75'$



Segment length from 10+00 to 10+50 = 0.047

Segment length from 10+50 to 11+00 = 0.049

S_4



Design speed at S.C.

DL shear:

$$DL \text{ at } 100' = 125(9.24) = -10.40'$$

$$DL \text{ at } 500' = 125(9.24) = -10.40'$$

$$LL \text{ at } 100' = 125(9.24) = -10.40'$$

$$LL \text{ at } 500' = 125(9.24) = -10.40'$$

LL shear:

$$LL \text{ on } 500' = 125(9.24) = -10.40'$$

$$LL \text{ at } 100' = 125(9.24) = -10.40'$$

$$Total = -20.80'$$

$$Total (-) LL shear = 92.144' = 92.14'$$

1000

shear at point 105' from S.C. - max = 12.24'

shear at point 5' from S.C. - max = -10.40'

5

0+25 0+25



0+25 0+25




0+25 0+25

shear
horizontal - 12.24'
vertical - 12.24'

Design = 4500 ft. S_v
(from C. & G. 25)


Total D.L. error = +22.8
Total (+) error = +22.8
Total (-) error = -22.8



Sum of
Vertical
Errors

S_v

ANALYSIS OF CROSS-BEAM LOAD DISTRIBUTION.



Maximum load on beam due to traffic & weight of slab:

- total DL = 884 $\frac{\text{K}}{\text{ft}}$ weight of slab

- total LL = 532 $\frac{\text{K}}{\text{ft}}$ weight of slab

Maximum load on beam due to sidewalk load:

- DL = 150 $\frac{\text{K}}{\text{ft}} \times (9.33 \text{ ft}) = 1400 \frac{\text{K}}{\text{ft}}$ weight of sidewalk/traffic lane

- LL = 80 $\frac{\text{K}}{\text{ft}} \times (9.33 \text{ ft}) = 746 \frac{\text{K}}{\text{ft}}$ weight of sidewalk/traffic lane

- total DL = (1400 + 884) $\frac{\text{K}}{\text{ft}} = 2284 \frac{\text{K}}{\text{ft}}$ weight of sidewalk

- total LL = (746 + 532) $\frac{\text{K}}{\text{ft}} = 1278 \frac{\text{K}}{\text{ft}}$ weight of sidewalk

• See diagram Rb

MAXIMUM MOMENTS AT SECTIONS ALONG BEAM:

SPAN	SECTION	D L MOM (K-F)	LL + IMP MOM (K-F)	TOTAL (K-F)
0	M ₁ - 0'	-417.9	-130.4	-548.3
1 + 4	M ₂ - 0'	-404.8	-182.2	-587.0
		-404.8	+19.6	-385.2
	M ₃ - 5.0'	+60	-44.6	-15.6
		+60	+116.5	+122.5
	M ₄ - 105'	+170.2	-56.4	+113.8
		+170.2	+190.5	+360.7
	M ₅ - 160'	+243	+55.0	+103.3
		+243	-71.0	-46.7
	M ₆ - 210'	-38.1	+36.7	-1.4
		-38.1	-275.0	-313.1
2 + 3	M ₇ - 210'	-334.9	+40.6	-294.3
		-334.9	-259.0	-593.9
	M ₈ - 260'	+40.2	+84.5	+124.7
		+40.2	-74.9	-34.7
	M ₉ - 313'	+184.7	+174.3	+359.0
		+184.7	-75.2	+109.5
	M ₁₀ - 370'	+82.9	-72.6	+10.3
		+82.9	+124.3	+207.2
	M ₁₁ - 420'	-327.3	-25.5	-352.8
		-327.3	+57.4	-269.9


maximum positive moment = +207.2 K-F @ M₁₀

maximum negative moment = -593.9 K-F @ M₇

MAXIMUM SHEAR ALONG CROSS-BEAM:


SPAN	SECTION	DL SHEAR (K)	LL SHEAR (K)	TOTAL
0	S ₁ - 0	- 98.0	- 27.9	- 125.9
1 # 4	S ₂ - 0	+106.8	+22.6	+129.4
	5.0'			+ 9.6
	10.5'			+ 15.2
	10.5'			- 21.0
	16.0'			- 92.9
	S ₃ - 21.0'	-104.3	-72.3	-176.5
2 # 3	S ₄ - 0	+106.8	+70.7	+177.5
	5.0'			+10.2
	10.5'			+20.0
	10.5'			- 18.6
	16.0'			-108.1
	S ₅ - 21.0'	-92.9	-63.1	-156.0
3	S ₆ - 0	+92.9	+63.1	+156.0

MAXIMUM TOTAL SHEAR DIAGRAM:



Support
horizontal force = 0.0 k
vertical force = 17.0 k

CHECKING BEAM AT POINT OF MAX POSITIVE MOMENT



Compression: $C = 0.85 f'_c b a$
 Tension: $T = A_s f_y$

$$C = T \Rightarrow 0.85 f'_c b a = A_s f_y$$

$$a = \frac{A_s f_y}{0.85 f'_c b} = \frac{4 \times 60,000}{0.85 \times 20,000 \times 24} = 1.18 \text{ in}$$

$$C = 0.85 \times 20,000 \times 24 \times 1.18 = 480,000 \text{ lb}$$

$$T = 4 \times 60,000 = 240,000 \text{ lb}$$

$$C > T \Rightarrow \text{Compression controls}$$

$$\rho = \frac{A_s}{b d} = \frac{4 \times 0.44}{24 \times 26} = 0.028$$

$$\rho_{min} = 0.01$$

$$20,000 \times 24 \times 26 = 12,480,000 \text{ lb-in}$$

$$12,480,000 > 12,000,000 \text{ lb-in}$$

$$12,480,000 > 12,000,000 \text{ lb-in}$$

$$12,480,000 > 12,000,000 \text{ lb-in}$$

$$12,480,000 > 12,000,000 \text{ lb-in}$$

$$12,480,000 > 12,000,000 \text{ lb-in}$$

$$12,480,000 > 12,000,000 \text{ lb-in}$$

$$12,480,000 > 12,000,000 \text{ lb-in}$$

* note:

Min. steel reqd., Dept. spec. for design of beam



$$\rho_{min} = \frac{14,000}{f_y d} = \frac{14,000}{60,000 \times 26} = 0.009$$

$$\rho_{min} = 0.009$$

$$\rho_{min} = 0.009$$

$$\rho_{min} = 0.009$$

CHECKING BEAM AT POINT OF MAX NEGATIVE MOM.



compression ... $C = 0.85 f_c a_s$... moment ...
 $C_s = (0.85 f_c) a_s = 4.75 \times 30 = 128.0 \text{ k}$
 $C_c = (2 f_c) (a_s - d) = 10.75 \times 29.25 = 313.9 \text{ k}$
 $d = 29.4"$

$$2270 f_c = 59,300 \times 12 \text{ in}^2$$

$$* f_c = 2.6 \text{ ksi}$$

$$\text{all w/ } e = 1850 \text{ psi}$$

$$C = T = 22.8 \text{ k} = 242,000 \text{ lb}$$

$$T = A_s f_s = 242,000 \text{ lb}$$

$$* f_c = 2.6 \text{ ksi} \text{ allowable} = 1.6 \text{ ksi}$$

$$f_s = 36 \text{ ksi} = 36 \text{ ksi} \text{ allowable} = 1.6 \text{ ksi}$$

since the entire beam was reinforced as illustrated, it was not necessary to check any other section for moment.

*note:

By Mich State Highway Dept Method:

$$M_{max} = (-22.8 \text{ k} - \frac{10.75 \text{ k}}{2}) = -16.9 \text{ k}$$

$$f_c = 1.6 \text{ ksi}$$

$$f_s = 22.8 \text{ ksi}$$

CHECKING BOND:

$$u = \frac{V}{\Sigma o, d}$$

At point of max. negative moment; $\Sigma o = 25"$

$V_{max.} = 160,000 \#$ at face of column

$$u = \frac{160,000}{25 \times 29.4} = \underline{198 \#/\text{in}^2}$$

allowable = $150 \#/\text{in}^2$ with special anchorage

Without impact, $V = 143,000 \#$

$$u = \underline{139 \#/\text{in}^2}$$

At point of inflection; $\Sigma o = 29"$

From max. total moment table, point of inflection $\cong 5'$ from support.

From max. total shear diagram;

$$V \cong 102,000 \#$$

$$u = \frac{102,000}{29 \times 30.5} = \underline{122 \#/\text{in}^2} \quad \text{allowable} = 100 \#/\text{in}^2 \text{ without S.A.}$$

Without impact, $V \cong 90,000 \#$

$$u = \underline{107 \#/\text{in}^2}$$

CHECKING SHEAR:

$$v = \frac{V}{b, d}$$


$V_{max.}$ without impact = $142,000 \#$

$$v = \frac{142,000}{25 \times 29.4} = \underline{162 \#/\text{in}^2}$$

allowable = $180 \#/\text{in}^2$ with web reinforcement & S.A.

CHECKING VERTICAL STIRRUPS:

Since the stirrup spacing is symmetrical for each span; and also symmetrical about the center line of the span, only one half of the span is analyzed for max. shear.




total load to be carried = $\frac{10\% \times 25}{2} (30) = 18,000$

number of stirrups required = $\frac{121}{19.2} = 6.2$, say 7

number provided #7.

theoretical spacing shows that stirrups should be closer together.

CHECKING CANTILEVER SECTION OF CROSS-BEAM



$$v = \frac{V}{b \cdot d} = \frac{125920}{30 \times 294} = 141 \frac{1}{2} \text{ psi}$$

each stirrup takes 19,200 #

$$\text{total load to be carried} = \frac{4 \times 1.3 (80)}{2} = 42420 \text{ #}$$

$$\text{number of stirrups required} = \frac{42420}{19200} = 2.2 \text{ say } 3$$

number provided = 7.

therefore, spacing shows that stirrups are properly placed.

CONCLUSION

Due to the limited time allowed for the writing of this thesis, the author was not able to go through the complete analysis. For anyone wishing to complete this work a suggestive outline is:

I - Analysis of pier.

A - Check column.

B - Check footing.

II - Analysis of abutment *

A - Check the four cases specified by Mich. S.H.D.

III - Analysis of railing.

The completed analysis of the slab showed that the concrete and steel stresses are within allowable limits. Upon a comparison of this work with the design by the Mich. S.H.D., it was found that the design was based on the H20 loading, while the H20 + S16 loading was used for this analysis. This difference was somewhat compensated by the fact that an additional dead load for future wearing surface was included in the design but not in this analysis.

The crossbeam analysis showed that the steel is overstressed by $20,000 \frac{lb}{sq. in.}$ for negative moment (without impact). This can be due to the different method used for design and this analysis. The Highway Dept. used the approximate method of loading the various spans and using the maximum effect thus obtained; whereas influence line diagrams were drawn for this analysis, and maximum effect was obtained by properly loading the diagrams. The difference in loading can

* see thesis by Robert C. McLarvy for this analysis.

Bond and shearing stresses for both the slab and beam are within allowable limits.

The object of this thesis - that of putting into application some of the theory learned in a course in indeterminate structures - was fulfilled.

BIBLIOGRAPHY:

- The American Association of State Highway Officials,
Standard Specs. for Highway Bridge, Fourth Edition.
L.C. Maugh, Statically Indeterminate Structures,
John Wiley and Sons.
Portland Cement Association, Continuous Concrete Bridges,
Second Edition.
Hale Sutherland and Raymond C. Reese, Introduction to
Reinforced Concrete Design, John Wiley and Sons.
American Concrete Institute, Reinforced Concrete Design
Handbook, First Edition.

MICHIGAN STATE UNIVERSITY LIBRARIES



3 1293 03196 7361