

THESIS



This is to certify that the

thesis entitled

MAXIMIZING POULTRY EXCRETA DEHYDRATION WITH VENTILATING AIR USING A SIMULATION MODEL

presented by

of a strong explanationary analysis provided a strong party of the strong party of the

John Elvin Dixon

has been accepted towards fulfillment of the requirements for

Ph.D. degree in Agricultural Engineering

Major professor

Date\_December 1978

**O**-7639

PLACE IN RETURN BOX to remove this checkout from your record.
TO AVOID FINES return on or before date due.

DATE DUE	DATE DUE	DATE DUE
NOW DO WING	AUG 0 2 2005	

MSU Is An Affirmative Action/Equal Opportunity Institution clicic/detectus.pm3-p.1

# MAXIMIZING POULTRY EXCRETA DEHYDRATION WITH VENTILATING AIR USING A SIMULATION MODEL

By

John Elvin Dixon

## A DISSERTATION

Submitted to
Michigan State University
in partial fulfillment of the requirements
for the degree of

DOCTOR OF PHILOSOPHY

Department of Agricultural Engineering



ABSTRACT

A STATE OF THE STA

## MAXIMIZING POULTRY EXCRETA DEHYDRATION WITH VENTILATING AIR USING A SIMULATION MODEL

Ву

John Elvin Dixon

The shift from an agrarian to an urban society along with chemical fertilizers and high labor costs has focused attention upon the need to manage animal wastes so as not to be offensive or a hazard to the environment. Common methods of animal waste management include use as a fertilizer, aerobic treatment, anaerobic treatment, and composting. Many animal operations do not easily lend themselves to all, and in some cases none, of these waste management systems because of economics, land limitation, or urban encroachment. Some systems are also resource wasteful. Because of these problems other waste management systems such as incineration, pyrolysis, hydroponic culture, and drying are being evaluated by researchers and innovative agriculturalists.

This study was undertaken to provide an analytical tool that would help evaluate the feasibility of drying poultry excreta. The tool was a simulation model designed to estimate the excreta drying potential of mechanical ventilating systems commonly provided for commercial egg production houses. The simulation model was based on



psychrometric calculations in combination with constant-rate drying theory.

The basis of the simulation model and the test facilities for model verification was a commercial-type laying house at the Michigan State University Poultry Science Research and Teaching Center, near East Lansing, Michigan. The laying house had a capacity of approximately 5000 hens and was equipped with a three-tier cage system, dropping boards, and under-cage mechanical scrapers for manure removal. The laying house was fully enclosed, insulated, and equipped with thermostatically controlled mechanical ventilation.

The system was managed as a small commercial unit. Feed and water were provided by hand-filling continuous troughs along each row of cages. Artificial light provided a diurnal photoperiod of 14 hours. The thermostats were set to operate each of the four fans in steps of about two degrees Fahrenheit and to maintain an inside dry-bulb temperature between 55 and 60°F when possible. Manure was scraped from the pens daily.

Psychrometric data collected on three summer days and two winter days were used for verification of the simulation model. Curvilinear regression curves for accumulated total moisture removed from the poultry house and for accumulated moisture evaporated from the manure followed their respective data points closely. Each of the paired set of verification curves had the same general shape and magnitude except for one of the low air flow winter days.

The critical factors for maximizing in-house manure drying were the drying surface area and the manure drying rate. The larger



the surface area the greater the drying. The simulation model indicated that any system that would increase the manure drying surface area would also increase manure drying. The drying rate was a function of no less than seven variables. For a given material such as poultry manure in a given poultry house, these several variables were considered constant.

The variables which influenced the manure drying rate the most were the inside wet-bulb depression and the ventilating rate. The wet-bulb depression in turn was influenced directly by the inside dry-bulb temperature and indirectly by the outside dewpoint temperature. The ventilating rate was limited by the heat available. Maximum drying was possible with a high inside dry-bulb temperature, a low outside dewpoint temperature, and maximum air exchange. The weather determined the outside dewpoint temperature, but management practices and bird heat available influenced the inside dry-bulb temperature.

Approved Mel L Camay
Major Professor

Department Chairman



#### ACKNOWLEDGMENTS

The author wishes to express his appreciation to Dr. M. L. Esmay for serving as major professor and for his guidance, encouragement, patience, and personal interest; to Dr. G. L. Park for serving on the doctoral committee and administering a preliminary examination; to Dr. T. C. Surbrook for serving on the doctoral committee; to Dr. C. J. Flegal for serving on the doctoral committee and assisting with the poultry house operation; to Dr. C. C. Sheppard for assistance with the poultry house operation; to Dr. J. B. Gerrish for counsel and assistance with instrumentation of the poultry house; and to Dr. H. C. Zindel for assistance in obtaining funds to carry out the research. Appreciation is also extended to my family for their patience and understanding. Special thanks goes to Winifred for her typing.

This page would not be complete without thanking the Agricultural Engineering Department at the University of Idaho for financial and moral support and the faculty and staff of the Agricultural Engineering Department at Michigan State University for providing physical facilities, financial support, and personal encouragement.



## TABLE OF CONTENTS

LIST OF TABLES		P	age
1. INTRODUCTION	LIST OF	TABLES	٧
1. INTRODUCTION	LIST OF	FIGURES	vii
1.1   General Remarks   1   1.2   Objectives	Chapter		
1.2 Objectives	1.	INTRODUCTION	1
1.3 Waste Management Systems   3			
2.1   Definition and Explanation of System Modeled			
2.2 External Environment and System Parameters   12	2.	MODEL DEVELOPMENT	8
2.3 Hypothesis for Drying Manure 14 2.3.1 Drying Theory 15 2.3.2 Heat Balance 18 2.3.3 Moisture Balance 21 2.4 Mathematical Models of Subsystems 22 2.4.1 Supplemental Heat, Q <sub>S</sub> 22 2.4.2 Heat Flow Through Exterior Building Surfaces, Q <sub>b</sub> 22 2.4.3 Sensible Heat of the Animals, Q <sub>a</sub> 25 2.4.4 Heat from Evaporated Moisture, Q <sub>e</sub> 26 2.4.5 Heat from Mechanical and Lighting Systems, Q <sub>m</sub> 25 2.4.6 Heat from Temperature Change in Ventilating Air, Q <sub>v</sub> 2.4.7 Moisture in Incoming Ventilating Air, M <sub>o</sub> 28 2.4.8 Moisture from Animal Respiration, M <sub>r</sub> 28 2.4.9 Moisture Evaporated from Manure, M <sub>m</sub> 29 2.4.10 Moisture Evaporated from Manure, M <sub>m</sub> 29 2.4.10 Moisture Evaporated from Waterers, M <sub>w</sub> 31 2.5 Outline of Computer Program 33 3. MODEL VERIFICATION 39 3.1 Experimental Facilities and Equipment 40 3.2 Experimental Procedure 43 3.2.1 Psychrometric Data Collection and Analysis 43			
2.3.1 Drying Theory 2.3.2 Heat Balance 2.3.2 Moisture Balance 2.4.4 Mathematical Models of Subsystems 2.2.4.2 Supplemental Heat, Qs 2.4.2 Heat Flow Through Exterior Building Surfaces, Qb 2.4.3 Sensible Heat of the Animals, Qa 2.5 2.4.4 Heat from Evaporated Moisture, Qe 2.4.5 Heat from Mechanical and Lighting Systems, Qm 2.4.6 Heat from Temperature Change in Ventilating Air, Qv 2.4.7 Moisture in Incoming Ventilating Air, Mo 2.4.8 Moisture in Incoming Ventilating Air, Mo 2.4.9 Moisture Evaporated from Manure, Mm 2.4.9 Moisture Evaporated from Waterers, Mw 3.5 Outline of Computer Program 3. MODEL VERIFICATION 3.1 Experimental Facilities and Equipment 40 3.2 Experimental Procedure 43 3.2.1 Psychrometric Data Collection and Analysis 43		2.2 External Environment and System Parameters	
2.3.1 Drying Theory		2.3 Hypothesis for Drying Manure	14
2.3.2 Heat Balance		2.3.1 Drying Theory	15
2.3.3 Moisture Balance  2.4 Mathematical Models of Subsystems  2.2 2.4.1 Supplemental Heat, Qs		2.3.2 Heat Balance	18
2.4 Mathematical Models of Subsystems   22   2.4.1 Supplemental Heat, Qs   2.4.2 Heat Flow Through Exterior Building Surfaces, Qb			
2.4.1 Supplemental Heat, Q <sub>s</sub>			
Surfaces, Qb			
2.4.3   Sensible Heat of the Animals, Q   25		2.4.1 Suppremental Heat, Qs	
2.4.4   Heat from Evaporated Moisture, \( \tilde{Q}_{e} \)		Surfaces, Qb	
2.4.5 Heat from Mechanical and Lighting Systems, Qm		2.4.3 Sensible Heat of the Animals, Qa	
2.4.6   Heat from Temperature Change in Ventilating Air, Qv. 26   Ventilating Air, Qv. 26   Ventilating Air, Qv. 26   Ventilating Air, Mo. 28   2.4.8   Moisture from Animal Respiration, Mr. 28   2.4.9   Moisture Evaporated from Manure, Mm. 29   2.4.10   Moisture Evaporated from Manure, Mm. 31   2.5   Outline of Computer Program 33   Ventilation Venti		2.4.5 Heat from Mechanical and Lighting	
2.4.7   Moisture in Incoming Ventilating Air, Mo   28		Systems, $Q_m$	26
2.4.7   Moisture in Incoming Ventilating Air, Mo   28		Ventilating Air, $Q_V$	26
2.4.8 Moisture from Animal Respiration, M <sub>P</sub>			28
2,4.9 Moisture Evaporated from Manure, Mm		2.4.8 Moisture from Animal Respiration, Mr	28
2.4.10 Moisture Evaporated from Waterers, "M <sub>W</sub> 31 2.5 Outline of Computer Program			
2.5 Outline of Computer Program			
3. MODEL VERIFICATION			
3.1 Experimental Facilities and Equipment		2.5 Outline of Computer Program	33
3.2 Experimental Procedure	3.	MODEL VERIFICATION	39
3.2 Experimental Procedure		3.1 Experimental Facilities and Equipment	40
3.2.1 Psychrometric Data Collection and Analysis . 43			43
		3.2.2 Simulation Model Evaluation	49




Chapter								Page
	3.3 Verification Results							51 51
	3.3.2 Winter Conditions	:	:	:	:	:	:	51 52
4.	RESULTS FROM MODEL USE							68
5.	SUMMARY AND CONCLUSIONS							84
	5.1 Summary							84 86 87
APPENDI	CES							88
Α.	COMPUTER PROGRAM LISTING							89
В.	EXAMPLES OF INTERMEDIATE COMPARISON GRAPHS							126
С.	VERIFICATION MANAGEMENT FACTOR, DESIGN, AND INPUT VALUES							136
LIST OF	REFERENCES							142



# LIST OF TABLES

Table		Page
2.1	A listing of parameters requiring numeric definition , with appropriate units of measurement	15
2.2	Heat production at various levels of ambient temperature for S. C. White leghorn hens (Phillips, 1970)	25
3.1	Accumulated total pounds of moisture removed from the poultry house. A comparison of collected data versus simulation model calculations	66
3.2	Accumulated pounds of moisture evaporated from the manure in poultry house. A comparison of collected data versus simulation model calculations	67
4.1	Manure moisture removed and moisture content for a typical month of January as calculated by the simulation model	78
4.2	Manure moisture removed and moisture content for a typical month of April as calculated by the simulation model	79
4.3	Manure moisture removed and moisture content for a typical month of July as calculated by the simulation model	80
4.4	Manure moisture removed and moisture content for a typical year as calculated by the simulation model	81
4.5	Management factor, design, and input values as used for operating the model with average weather data	83
C.1	Management factor, design, and input values as used for verifying the model with data collected August 12, 1974	137
C.2	Management factor, design, and input values as used for verifying the model with data collected August 13, 1974	138




lable			Salar	Page
C.3	Management factor, design, and for verifying the model with	data collected		
	August 20, 1974		 	. 139
C.4	Management factor, design, and for verifying the model with	data collected		
	January 6, 1975		 	. 140
C.5	Management factor, design, and for verifying the model with	data collected		
	January 7, 1975		 	. 141



## LIST OF FIGURES

igure		P	age
2.1	The interrelation of the simulation model inputs and outputs		9
2.2	Floor plan of the commercial-type poultry house used as the base for the simulation. The circled symbols, Il, Ol, etc., indicate points of measurement for incoming and outgoing air	•	10
2.3	Flow chart of computer program		34
3.1	Accumulated total moisture removed from the poultry house during the day of August 12, 1974. The two curves result from curvilinear regression calculations based on the two separate sets of data		56
3.2	Accumulated moisture evaporated from the manure in the poultry house during the day of August 12, 1974. The two curves result from curvilinear regression calculations based on the two separate sets of data		57
3.3	Accumulated total moisture removed from the poultry house during the day of August 13, 1974. The two curves result from curvilinear regression calculations based on the two separate sets of data	•	58
3.4	Accumulated moisture evaporated from the manure in the poultry house during the day of August 13, 1974. The two curves result from curvilinear regression calculations based on the two separate sets of data		59
3.5	Accumulated total moisture removed from the poultry house during the day of August 20, 1974. The two curves result from the curvilinear regression calculations based on the two separate sets of data .		60
3.6	Accumulated moisture evaporated from the manure in the poultry house during the day of August 20, 1974. The two curves result from curvilinear regression calculations based on the two separate sets of data		61




-	igure	Statement of the State of the S	Page
	3.7	Accumulated total moisture removed from the poultry house during the day of January 6, 1975. The two curves result from curvilinear regression calcu- lations based on the two separate sets of data	62
	3.8	Accumulated moisture evaporated from the manure in the poultry house during the day of January 6, 1975. The two curves result from curvilinear regression calculations based on the two separate sets of data	63
	3.9	Accumulated total moisture removed from the poultry house during the day of January 7, 1975. The two curves result from curvilinear regression calculations based on the two separate sets of data	64
	3.10	Accumulated moisture evaporated from the manure in the poultry house during the day of January 7, 1975. The two curves result from curvilinear regression calculations based on the two separate sets of data	65
	4.1	The moisture removed from manure during a typical month of January as calculated by the simulation model	70
	4.2	The moisture content of manure for a typical month of January as calculated by the simulation model	71
	4.3	The moisture removed from manure during a typical month of April as calculated by the simulation model	72
	4.4	The moisture content of manure for a typical month of April as calculated by the simulation model	73
	4.5	The moisture removed from manure during a typical month of July as calculated by the simulation model .	74
	4.6	The moisture content of manure for a typical month of July as calculated by the simulation model	75
	4.7	Representative daily moisture removal from manure throughout the year as calculated by the simulation model	76
	4.8	Representative daily manure moisture content throughout the year as calculated by the simulation model .	77



igure		Page
B.1	An example of a comparison graph used for evaluation during verification of the simulation model with the measured data. This graph showed that the incoming air dry-bulb temperature as used in the model was in fact equal to that of the collected data	127
B.2	An example of a comparison graph used for evaluation during verification of the simulation model with the measured data. This graph showed that the incoming air dewpoint temperature as used in the model was in fact equal to that of the collected data	128
B.3	An example of a comparison graph used for evaluation during verification of the simulation model with the measured data. This graph showed that the incoming air humidity ratio was in fact equal to that of the collected data	129
B.4	An example of a comparison graph used for evaluation during verification of the simulation model with the measured data. This graph showed that the outgoing air dry-bulb temperature as calculated by the simulation model follows very closely to the measured value	130
B.5	An example of a comparison graph used for evaluation during the verification of the simulation model with measured data. This graph showed that the outgoing air dewpoint temperature as calculated by the simulation model follows very closely to the measured value	131
B.6	An example of a comparison graph used for evaluation during the verification of the simulation model with measured data. This graph showed that the humidity ratio of the outgoing air as calculated by the simulation model follows very closely to the measured value	132
B.7	An example of a comparison graph used for evaluation during the verification of the simulation model with measured data. This graph showed that incoming air and outgoing air humidity ratio difference was greater for the measured data than as calculated by the simulation model for all but two hours of	
	the day	133



igure		Page
B.8	An example of a comparison graph used for evaluation during the verification of the simulation model with measured data. This graph showed that the air flow through the poultry house as calculated by the simulation model follows very closely to the measured value	134
B.9	An example of a comparison graph used for evaluation during the verification of the simulation model with measured data. This graph showed that the evaporation from the poultry house during one hour as calculated by the simulation model followed the same trend as that which was calculated from measured data. The two curves result from curvilinear regression calculations based on the two separate sets of data	135



#### INTRODUCTION

## 1.1 General Remarks

The problem of handling, storage, and disposal of animal manure has existed since the beginning of animal husbandry. Until recent years distribution of domestic animals was extensive and the manure along with other wastes was disposed of without problems within the normal habitat of the animal. The earliest husbandrymen were nomadic and the animal waste disposal systems consisted of natural distribution within the pasture and grazing areas. As the history of animal husbandry progressed with the more sophisticated farming systems, the animals were concentrated on more confined land areas. Prior to the mid-twentieth century, the number of animals and the area of the land upon which they were kept was in reasonable balance. The balance was such that the fertilizer value of the waste was considered and treated as a resource for the crops grown on the land.

The general availability and economic feasibility of chemical fertilizers for principal plant nutrients during the twentieth century caused the crop farmers to shun animal manure as the primary source of plant nutrients. At the same time animal production was subjected to higher labor costs and the economy of scale brought about concentration of large herds of animals in confined housing systems. Large concentrations of animals created waste material



handling problems. What had been an asset and resource has now become a disposal problem.

Disposal of animal waste should not, in fact, be the objective.

Rather, the raw product should be converted to a stable usable form and removed from the point of production. Removal from the source in an unstable form is often no solution, only a transfer in location. The waste disposal problem with its associated air and water pollution problems still exists, but at a new location.

Historically, raw manure mixed with litter has been stored in open stacks and periodically transported and spread upon the land. Recently, the potential of air and water pollution has caused constraints to be placed on operations of this type. The U.S. Environmental Protection Agency has been established and given authority to regulate operations that have the potential of creating pollution and/or a nuisance.

With the encroachment of urban population onto agricultural land, odors resulting from the storage, transportation, and spreading processes often have been declared a nuisance. Furthermore, the past practice of spreading raw solid or liquid manure upon frozen ground has been curtailed because of stream polluting potential. Frozen ground had the advantage of making fields easily accessible during the winter and the cold weather minimized odors. This curtailment has led to a search for new methods of treatment, storage, and handling which minimize odors and water pollution.



## 1.2 Objectives

The principal objective of this dissertation was to develop a vertified analytical tool for evaluating in-house drying of poultry manure.

The secondary objective was to provide the basis for applying the simulation model tool for maximizing in-house poultry manure drying. The base provided by this secondary objective will allow manipulating design and management parameters such as building insulation, minimum ventilating rate, bird density, and in-house temperature so as to determine maximum in-house drying of manure.

## 1.3 Waste Management Systems

In their publication pertaining to livestock-waste management, Miner and Smith (1975) discussed various methods for treating, utilizing, or disposing of manure. Commonly accepted methods of utilizing or treating manure are: (1) use as a soil amendment and fertilizer for plants, (2) treatment by an oxidation ditch, (3) treatment by an aerobic lagoon, (4) treatment by an anaerobic lagoon or holding pond, and (5) treatment by composting. Some experimental utilization systems and treatment processes with limited use include: (1) treatment by incineration, (2) treatment by pyrolysis, (3) use in hydroponic culture, (4) treatment by the Barriered Landscape Water Renovation System (BLWRS), and (5) treatment by drying.

Traditionally, as pointed out above, and as noted in these publications, manure has been disposed of or utilized without "treatment" as a soil amendment and fertilizer for plants. With the



increased animal density and larger herds and flocks of recent years, manure treatment necessarily has required serious consideration.

It is possible to treat manure by several methods. Most of these treatments involve some biological process. Sanitary engineers have developed aerobic processes among others for municipal sewage treatment. In the aerobic process oxygen-requiring microorganisms are stimulated through appropriate enviornmental control to digest the raw manure mixture and change it to a more stable form. Ultimately, however, the various components even though stable, such as water and sludge, must be disposed of some place. Sanitary engineers also have used anaerobic processes. The anaerobic process involves microorganisms too, but an environment must be maintained that excludes oxygen. Again, after this primary treatment there is ultimately a need for disposal of the sludge and impure water.

Both of the two basic biological treatment methods have been and are being used for treatment of animal manure. The most common aerobic systems for liquid manure treatment are oxidation in an aerobic lagoon and oxidation through mechanical mixing. Anaerobic systems being used are the anaerobic digester and the stabilization pond (anaerobic lagoon). Each of these systems was discussed by Miner and Smith (1975).

Composting is another aerobic treatment process. The process differs from those mentioned above because the manure is treated in or near the solid state. Composting of manure was discussed by Singley et al. (1975), and Miner and Smith (1975).




The Barriered Landscape Water Renovation System (BLWRS) treats animal wastes in the near liquid state. The principal objective of this system is to remove nitrogen and phosphorous from the manure. These nutrients along with other solid constituents are removed from the liquid by filtering through a specifically designed and constructed soil profile. Erickson et al. (1971) described this system.

Hydroponic culture has also been tried for removing nutrients from animal wastes in the near liquid state. Systems of this type also were discussed by Miner and Smith (1975). Two other methods of processing manure discussed by Miner and Smith (1975) are incineration and pyrolysis. Incineration involves the complete combustion of the manure. High moisture (above 60 percent) manures require an additional fuel source to sustain the combustion. In their discussion of this subject Davis et al. (1972) noted that it is possible to salvage most of the potash and phosphorous in the ash for use as fertilizer. The nitrogen can be salvaged as ammonia from the flue gases. Sobel and Ludington (1966) noted that in the incineration process the energy tied up in volatile solids is used in the combustion of the organic portions of the manure.

The pyrolysis process involves holding the manure within a temperature range of 480-1830°F in an oxygen-deficient atmosphere. The products are gases (hydrogen, water vapor, methane, carbon dioxide, carbon monoxide, ethylene, etc.), oils, and ash.

Drying of manure also was discussed by Miner and Smith (1975).

Drying of poultry excreta in fact has been discussed by several



writers. Ludington (1963) discussed dehydration and its economics. Surbrook (1969) and Surbrook et al. (1971) evaluated drying poultry and other animal excreta with a mechanical drier. Bressler and Bergman (1971) described a system of drying with extra in-house circulating fans located over the excreta collected under a sloping-wire-floor type house. Stirring of manure was also included with the "Bressler" system. With this system, Bressler and Bergman (1971) reduced the manure moisture content in the house to values of from 23.8 percent to 50.5 percent. Gerrish et al. (1973) described an in-house pre-drying system which used only the ventilating air of a cage-type laying house and the periodic waste heat from a mechanical drier and after-burner. Preliminary results from actual tests with this system were presented by Flegal et al. (1974). Conclusions were enumerated in subsequent reports by Sheppard et al. (1974), Esmay et al. (1975a, 1975b), and Zindel et al. (1977).

Mechanical drying of excreta may be too expensive if the amount of water to be evaporated with fossil fuel energy is great. These drying costs can be offset to some extent if the dry manure is processed for a feed supplement. Drying costs can be minimized by removing as much water as possible in the poultry house before the manure is mechanically dried. In-house water removal for poultry manure was described by Esmay et al. (1975a). They showed that drying poultry excreta from its original voided moisture content of approximately 80 percent wet basis (wb) to 12.5 percent wb required the removal of 77.5 pounds of water for each 100 pounds of excreta. (Approximately 100 pounds of excreta per day is produced by 370 hens.)



About one gallon of fuel oil would be required to evaporate the 77.5 pounds of water from the excreta using a typical fuel oil with heating value of 144,000 Btu per gallon and a drier efficiency of 57 percent as found by Surbrook (1969).

Commercial laying operations may be from 100 to 1000 times this size. A commercial egg producer, therefore, would have a daily fuel requirement of from 100 to 1000 gallons per day, if all drying was accomplished by the use of fuel oil. This approach is impractical and not used commercially. Under typical housing conditions some drying of excreta by ventilating air takes place shortly after it is voided and continues within the laying house during normal operations. Results of in-house drying have been reported by Esmay et al. (1975b), Flegal et al. (1974), Lampman et al. (1967), Sobel (1972), Oheimb and Longhouse (1974), Dixon et al. (1976), and Zindel et al. (1977). The drying or removal of water prior to mechanical drying reduces the fuel requirement and thus its treatment cost.

Some system of maximizing in-house water removal is, therefore, desirable. A mathematical model or simulation of the pre-drying process would provide an effective analysis tool.




#### 2. MODEL DEVELOPMENT

### 2.1 Definition and Explanation of System Modeled

The system defined by this study was the environment produced with a 5000 bird egg laying operating unit. The operation unit was defined as the house enclosing the laying hens and the equipment used to manage the operation. Inputs to the system considered to be most important to the model were the manure from the birds, heat, and moisture. Outputs were moisture removed from the manure and manure moisture content. Along with these inputs and outputs there were other related inputs, i.e., feed, water, ventilating air, and hens. Associated outputs were eggs and ventilating air. The interrelation of these inputs and outputs is shown in Figure 2.1.


The simulation was based on a commercial-type, cage, laying house. Figure 2.2 shows a floor plan of the laying house. Hens were confined in wire cages with three hens per cage in alternate rows and four hens per cage in the other rows. The cages were in double rows three tiers high with manure dropping boards under the top two tiers. Periodically the manure was scraped from the dropping boards into the floor-pit beneath the bottom tier. A commercial, cable-operated pit scraper was used to move the manure to a cross conveyor, i.e., a conventional dairy-barn, gutter cleaner. Cleaning was manually controlled on a daily basis for this study.






The interrelation of the simulation model inputs and outputs. Figure 2.1.





Floor plan of the commercial-type poultry house used as the base for the simulation. The circled symbols, Il, Ol, etc., indicate points of measurement for incoming and outgoing air. Figure 2.2.



Ventilation for the laying house was provided by thermostatically controlled exhaust fans in conjunction with a manually controlled damper air inlet. The damper was so arranged that all winter-time ventilating air was drawn through the attic. This arrangement allowed for a relatively constant inside temperature except during summer and extremely cold weather. No supplemental cooling or heating was provided. This system was discussed extensively by Gerrish et al. (1973).

The primary measure of effectiveness was the amount of water removed from the manure in the house by the ventilating air. The moisture removed from the manure is a function of the drying rate, exposed surface area, and the drying time. The effect of the water holding capacity of the ventilating air and the heat energy from the birds was accounted for when calculating the drying rate.

The manure moisture content, which was a function of the moisture removed, was another means of expressing the effectiveness of the simulation. Perry et al. (1973) defined moisture content of a solid as the ratio of the moisture quantity per unit weight of the dry or wet solid. When the wet-solid weight is used as the ratio base, it is referred to as moisture content, wet basis. The moisture content, wet basis, is the quantity used in the simulation.

The manure moisture content (wet basis) was calculated from the above definition by first calculating the water removed from the manure. To calculate the water removed for a given weather condition and cage laying house, the inside dry-bulb temperature and ventilating rate were first determined. For normal operation the



inside temperature was set between 55 and 60°F and the ventilating rate was estimated by solving a heat balance equation. With the inside temperature and ventilating rate known or estimated, the inside wet-bulb temperature was determined and from this the drying rate was calculated. The water removed from the manure was calculated by multiplying the drying rate by the manure surface area and the lapsed time of manure exposure to the ventilating air.

## 2.2 External Environment and System Parameters

Certain parameters must be known or assumed for the simulation. For the system discussed here these were (a) outside air psychrometrics, (b) the quantity and moisture content of the excreted material, (c) the physical parameters of the building and ventilating system, and (d) the poultry operation management practices including number and weight of hens housed.

Data from the U.S. Weather Service provided the base information for the needed psychrometric data for the outside air used for ventilation. The appropriate weather service data were given as the barometric pressure, the maximum and minimum dry-bulb temperature, and a dewpoint temperature for a day. Average values as prepared by the Weather Service were used as representative of a day in a given month for the analysis of drying within a month. For analysis of annual effects of weather upon drying, average monthly data from the Weather Service were used as a representative day for a given month.



The model was constructed to make calculations based on a fraction of a day. For the simulation calculations it was therefore necessary to make an estimate of the weather situation at various times throughout a given day. Phillips (1970) formulated equations which estimated the temperature function as it varies with time through a day. His function was

for  $0 < t \le 6$   $T = T_m + R_2 (1 + \cos((t+18)/30)\pi)),$ for  $6 < t \le 15$   $T = T_m + R_2 (1 + \cos((t-12)/18)\pi)),$ for  $15 < t \le 24$  $T = T_m + R_2 (1 + \cos((t-30)/30)\pi)),$ where  $T = \text{outside dry-bulb temperature}, ^F,$   $T_m = \text{minimum outside dry-bulb temperature},$ 

 $R_2$  = one-half outside temperature range, and

t = time, hours per 24-hour clock.

Phillips also states that the dewpoint temperature can be considered constant for the day but this was not found to give a reasonable estimate of the dewpoint temperature as measured. A more reasonable estimate of the dewpoint temperature for East Lansing was found by calculating a linear regression equation for the dewpoint temperature based on the dry-bulb temperature. The data used for the regression calculations were the data collected for verification of the model.



 $Y_{dp} = 6.48 + 0.8X_{db}$ 

where Y<sub>dp</sub> = dewpoint temperature, °F, and

X<sub>db</sub> = dry-bulb temperature, °F.

The correlation coefficient for these data was 0.98. With the above equations and pertinent weather data, it was possible to calculate all needed psychrometric quantities for the incoming ventilating air. The equations and data needed for these psychrometric calculations were available through a package of algorithms developed by Bakker-Arkema and Lerew (1972). The psychrometric quantities in this package were: dry-bulb, wet-bulb, and dewpoint temperatures; enthalpy; absolute humidity (humidity ratio); latent heat; actual and saturation vapor pressures; relative humidity; and specific volume.

The moisture content of the freshly voided excreta has been determined by Esmay et al. (1975b) to be 80 percent (wet basis). The excreta produced by laying hens consisted of 0.272 pounds per henday of freshly voided excreta at 80 percent moisture content.

The physical and operational parameters will vary with each installation. The needed quantities for the simulation are listed in Table 2.1 along with appropriate units of measurement for use in the simulation model.

## 2.3 Hypothesis for Drying Manure

The drying rate of a specific material gave a characteristic which was used to estimate the water removed from the substance. As will be noted later, determination of the theoretical drying rate



required knowledge of the drying air temperature, humidity, and velocity plus specific material characteristics. Heat balance theory and the theory of moisture balance in ventilating air lend themselves to estimating the temperature and humidity of the air in the system. The hypothesis was that these theories can be combined through a computer simulation to estimate the water removed from manure in a poultry laying house.

Table 2.1. A listing of parameters requiring numeric definition with appropriate units of measurement.

Parameter	Units of Measurement
bird number	hens
bird weight	pounds
building ceiling height	feet
building length	feet
building width	feet
day, end of	hour
day, start of	hour
excreta moisture content	decimal fraction
excreta production rate	pounds/hen-day
insulation, ceiling "R"	hour-square feet-°F/Btu
insulation, wall "R"	hour-square feet-°F/Btu
lighting energy	watts
ventilating rate, maximum	cubic feet/minute
ventilating rate, minimum	cubic feet/minute
waterer length	feet
waterer surface width	feet.

### 2.3.1 Drying Theory

Perry et al. (1973) presented a discussion of solids-drying fundamentals. From this it was noted there were two principal types



or periods of solids-drying: the constant-rate period and the falling-rate period. As the name implies, the rate at which drying occurs during the first period was constant while that in the second was not. When a plot was made of the drying rate versus time, there was a sharp change from a horizontal line curve to an exponential curve with negative slope at the point of this rate change. This point has been called the critical moisture content.

It was apparent by unit analysis that the amount of water removed from a drying material would be obtained, if the drying rate,  $m_{\rm p}$ , were known, i.e.,

water removed = m,A0,

where m<sub>r</sub> = constant drying rate, lbs/sq ft - hr

A = surface area, sq ft, and

 $\theta$  = time span, hr.


If the period of drying were the falling rate period, the equation must be used in its more general form, i.e., as a differential equation, and the term,  $\mathbf{m_r}$ , can be better represented by dW/d0, where dW is the differential quantity of water removed in time period, d0.

Perry et al. (1963, 1973) presented formula to estimate  $dW/d\theta$  for the constant-rate period and the falling-rate period. Only the constant-rate period was of interest in this presentation.

Perry et al. (1963, 1973) stated that the constant drying rate can be estimated as

$$dW/d\theta = h_t A(t-t_s')/\lambda = k_g A(p_s-p),$$

where  $dW/d\theta$  = drying rate, 1b of water/hr,



h<sub>t</sub> = total heat transfer coefficient, Btu/hr
-sq ft -°F,

A = surface area, sq ft,

 $\lambda$  = latent heat of evaporation at t', Btu/lb,

 $k_q$  = mass transfer coefficient, lb/hr-sq ft-atm,

t = dry-bulb temp, °F,

t' = temperature of evaporating surface, °F,

P<sub>S</sub> = vapor pressure of water at surface temp, atm, and

p = partial pressure of water in the air, atm.

Wells (1972) referenced Perry et al. (1963) and stated (Bagnoli contributed to the <u>Chemical Engineers' Handbook</u> by Perry et al.),

"The use of the heat transfer coefficient is preferred in estimating drying rates because they are usually more reliable (Bagnoli et al., 1963). Small errors in temperature have negligible effect on the heat-transfer coefficient, but do introduce relatively large errors in partial pressure estimates and hence in the mass transfer coefficient.

The critical value to determine in evaluating the drying rate was the heat transfer coefficient,  $h_{\rm t}$ . Perry et al. (1963) stated that  $h_{\rm t}$  =  $h_{\rm c}$ , the convective heat transfer coefficient, when heat was transferred by convection only. They also gave the formula


$$h_c = \alpha G^n/D_c^m$$

where  $h_{C}$  = convective heat transfer coefficient, Btu/hrsq ft -°F,

G = mass velocity, 1b/hr-sq ft,

 $\boldsymbol{D}_{\boldsymbol{C}}$  = a characteristic dimension, ft, and

 $\alpha,m,n$  = constants.




Perry et al. (1963) suggested the value, G, be determined from the relationship: weight rate of flow divided by the cross-sectional area. Perry also pointed out that the value,  $D_{\rm C}$ , for a plate can be represented by the length of drying solid over which the air-stream passes. From the discussion and examples used by Perry et al. (1963) and by Wells (1972) it was apparent that m = 1-n and that these constants along with  $\alpha$  were specific to a material and drying conditions.

Wells (1972) ran extensive laboratory tests involving the drying of poultry manure. Although he did not calculate the constants,  $\alpha$  and n in the equation for  $h_{_{\rm C}}$ , he provided measured values for the "evaporation heat required," temperatures, velocities, etc. so that these constants could be determined. Dixon et al. (1976) and Dixon et al. (1978) evaluated these data for the constants. For American Engineering Units they found them to be:

n = 0.4029 and  $\alpha = 0.1222$ .

## 2.3.2 Heat Balance

Since the equation,  $dW/d\theta^{\cdot} = h_t A(t-t_s')/\lambda$ , was to be the basis for determining the drying rate, a means of estimating the temperatures, t and  $t_s'$ , was necessary. The dry-bulb temperature, t, was that of the air passing over the drying manure. The temperature of the evaporating surface,  $t_s'$ , can be taken as the wet-bulb temperature of the air according to Perry et al. (1973). Wells (1972), however, in work involving the drying of poultry manure found the surface temperature to be 0.5°C higher than the wet-bulb temperature. Since



the wet-bulb temperature was used for calculating the drying rate parameters, n and  $\alpha$ , the wet-bulb temperature was used for  $t_s'$ . The dry-bulb temperature was a predetermined inside temperature, between 55 and 60°F, unless the weather was extreme. For extreme weather conditions the dry-bulb temperature was estimated from a heat balance analysis of the laying house. A moisture balance analysis provided a means to estimate the wet-bulb temperature. The assumption was made that the dry-bulb and wet-bulb temperatures of the outgoing ventilating air were representative of the air that passes over the manure being dried within the laying house.

The basic equation for sensible heat balance was given by the Structures and Environment Handbook (1975) as

$$Q_{s} + Q_{b} + Q_{a} + Q_{e} + Q_{m} + Q_{v} = 0,$$

where  $Q_s$  = supplemental heat, Btu/hr,

 $Q_b$  = heat flow through exterior building surfaces, Btu/hr,


Q<sub>a</sub> = sensible heat from housed animals, Btu/hr,

 $Q_e$  = heat from moisture evaporated or condensed, Btu/hr,

 $Q_{\rm m}$  = heat from mechanical systems and lighting, Btu/hr, and

 $Q_V$  = heat from temperature change in ventilating air, Btu/hr.

Each of the elements in this equation, except  $Q_S$  and  $Q_m$ , was a function of the inside temperature. When the physical parameters of the building, the management practices, and flock size were defined, it



was possible to estimate the inside temperature. To make this estimate the exterior environmental temperature and psychrometric characteristics were necessary as well as an iterative technique for an approximate solution of the heat balance equation. The result of the solution to the heat balance equation gave a function from which the temperature was estimated. An appropriate iterative technique, the Newtonian convergence, was used by Phillips (1970). The convergence was based on Newton's method (Smith et al., 1947) for finding roots of a function, f(x). Through some means, an estimate of a root,  $x_1$ , was made. By evaluating the function at  $x_1$ , the equation for the tangent-line through  $x_1$  was written as

$$y - f(x_1) = f'(x_1) (x-x_1).$$


This line intersected the x-axis when y = 0. Solving the tangent-line equation for x with y = 0 gave

$$x = x_1 - f(x_1)/f'(x_1),$$

a new estimate of the root. The process was repeated until an acceptably small error was obtained. Phillips (1970) adapted Newton's method to a digital computer for evaluation of a heat balance function as follows:

$$t_{n+1} = t_n - \frac{f(t_n)}{f'(t_n)},$$

where  $t_{n+1}$  = new approximation to the solution,  $t_n \ = \ previous \ approximation \ value,$   $f(t_n) \ = \ net \ heat \ flow \ across \ system \ boundaries \ at$   $temperature \ t_n, \ and$ 



 $f'(t_n)$  = first derivative of  $f(t_n)$  which was determined by the following central finite difference approximation:

$$f'(t_n) = \frac{f(t_n+0.1) - f(t_n - 0.1)}{0.2}$$

## 2.3.3 Moisture Balance

The basic equation for moisture balance of the ventilating air was adapted from the <u>Structures and Environment Handbook</u> (1975) as follows:

$$M_{o} + M_{r} + M_{m} + M_{w} - M_{v} = 0$$
,  
where  $M_{o}$  = moisture in incoming ventilating air, lbs/hr,  
 $M_{r}$  = moisture from animal respiration, lbs/hr,  
 $M_{m}$  = moisture evaporated from manure, lbs/hr,  
 $M_{w}$  = moisture evaporated from waterers, lbs/hr,

 $M_v = moisture$  in outgoing ventilating air, lbs/hr.

This equation assumes there was no water spillage or other evaporating surfaces.

The equation indicates each element, except  $\mathrm{M}_\mathrm{V}$ , added moisture to the ventilating air. Since the mechanical ventilating system kept the air inside the laying house turbulent, the humidity of the inside air was assumed to be that of the moisture in the outgoing ventilating air,  $\mathrm{M}_\mathrm{V}$ . The equation was, therefore, solved for  $\mathrm{M}_\mathrm{V}$  to obtain the moisture in the outgoing ventilating air in terms of pounds of moisture per hour.

When the ventilating rate was known, the humidity ratio was calculated as follows:



 $H = M_{V}/V_{r}$ 

where H = humidity ratio, lbs of water vapor/lb of air,

 $V_{n}$  = ventilating rate, pounds of air/hour, and

 $M_v = (previously defined).$ 

### 2.4 Mathematical Models of Subsystems

The following paragraphs present the basis for evaluation of each element in the heat balance and moisture balance equations. Since the element,  $\mathbf{M}_{\mathbf{V}}$ , in the moisture balance equation was the sum of the other elements, it will not be discussed further. Some elements were determined directly from given data or assumptions. Estimates for others required more rigorous calculations and some required the use of approximation techniques.

# 2.4.1 Supplemental Heat, $Q_S$

The system as defined had no supplemental heat. As a result this quantity was assigned the value zero.

# 2.4.2 Heat Flow Through Exterior Building Surfaces, Qb


The heat flow through exterior building surfaces,  $\boldsymbol{Q}_{b},$  was determined from the following sum:

 $Q_b = q_{bw} + q_{bc} + q_{bf}$ 

where  $q_{bw}$  = heat flow through the building walls, Btu/hr,

 $q_{bc}$  = heat flow through the building ceiling, Btu/hr, and

 $q_{hf}$  = heat flow through the building floor, Btu/hr.



Esmay (1969) **presented** the following equation as a means of estimating a steady state heat flow through a composite of materials:

$$Q = UA(t_i - t_0),$$

where 0 = overall heat flow, Btu/hr,

U = overall coefficient of heat transmission, Btu/hrsq ft-°F,

A = area normal to direction of heat flow, sq ft, and  $\bf t_0$  = inside and outside temperature,  $^{\rm o}F.$ 

The value, U, was determined from the equation (Esmay, 1969):

$$U = 1/(1/f_0 + L_1/k_1 + L_2/k_2 + ... 1/a + 1/f_i),$$

where  $L_1$ ,  $L_2$ , ... = thickness of respective material, inches,  $k_1$ ,  $k_2$ , ... = thermal conductivity of respective material, Btu/hr-so  $ft^-oF/in$ ,

a = thermal conductivity of an air space, Btu/hr-sq ft-°F, and

 $f_i$  and  $f_o$  = the inside and outside surface conductance, Btu/hr-sq ft- $^{\circ}F$ .

The general equation was adapted to the poultry building and  $% \left( \mathbf{r}\right) =\mathbf{r}^{\prime }$  qave the equations

$$q_{bw} = A_{bw}U_{bw}(t_i-t_o)$$
 and

$$q_{bc} = A_{bc}U_{bc}(t_i-t_o),$$

where the subscripts "bw" and "bc" represent the building walls and building ceiling, respectively.

Phillips (1970) developed an equation to estimate the heat loss from a concrete floor slab in a poultry building,  ${\bf q}_{\rm bf}.$ 



The equation was

 $q_{bf} = k_s p A_{bf}(t_{bf}-t_{bo}),$ 

where  $k_s$  = inside surface heat transfer coefficient, Btu/hr-sq ft- $^{\circ}$ F,

p = portion of floor exposed to environment, decimal
 fraction,

Abf = floor area, sq ft,

 $t_{\rm hf}$  = surface temperature of floor, °F, and

 $t_{\rm bo}$  = environmental temperature adjacent to floor, °F.

In the presentation of his work, Phillips (1970) found the value of  $\mathbf{k}_{\mathrm{S}}$  to be 1.65 Btu/hr-sq ft-°F for a concrete floor slab in a poultry house. The variable, p, was more explicitly defined as that portion of the floor not covered by manure. In the development of this equation for use in a simulation he suggested the floor surface temperature,  $\mathbf{t}_{\mathrm{bf}}$ , be assigned an initial value equal to the mean outside temperature for the day plus 5 degrees. This value was approximately equal to the mean expected interior temperature for the day and was intended to eliminate long-term storage effects.

Subsequent values were determined by means of the equation

 $(t_{bf})_{new} = (t_{bf})_{old} - q_{bf}/(0.25CA_{bf}m_{bf}),$ 

where  $(t_{bf})_{new}$  = slab temperature for next time period, deg F,

> $(t_{bf})_{old}$  = slab temperature for present time period, deg F,

> > C = specific heat of floor, and



 ${
m m_{
m bf}}$  = mass of one square foot of slab plus mass of sufficient fill below the slab to make up a total thickness of 10 inches.

In evaluating  $\mathbf{m}_{\mathbf{bf}}$  he suggested four inches of concrete plus six inches of sand be assumed for all simulations. This yielded a mass of 120 lbs. per square foot of floor space.

## 2.4.3 Sensible Heat of the Animals, $Q_a$

Phillips (1970) developed a mathematical model for the sensible heat,  $Q_a$ , from laying hens using data from Ota and McNalley (1961). The data used by Phillips were used for this simulation (see Table 2.2). The data were interpolated by using the computer subroutine entitled TABLI as developed by Llewellyn (1965).

Table 2.2. Heat production at various levels of ambient temperature for S. C. White leghorn hens (Phillips, 1970).

Ambient Temperature °F	Sensible Heat (BTU/Hour (Lb))		Latent Heat (BTU/Hour (Lb))	
	Day	Night	Day	Night
26	11.1	6.9	1.7	1.6
34	8.3	6.8	2.1	2.0
47	7.3	6.1	2.3	1.9
56	6.6	5.3	3.2	2.6
64	6.5	5.1	3.3	2.2
74			3.4	2.0
84	6.3	3.6	4.2	3.5
94	.2	.6	5.3	4.7



### 2.4.4 Heat from Evaporated Moisture, Qe

The heat used to evaporate moisture,  $\mathbf{Q}_{\mathbf{e}}$ , was determined from the latent heat of vaporization definition (Weast, 1970). This definition yielded the equation

$$Q_0 = -Wh_1$$
,

where W = weight of evaporated moisture, lbs, and

 $h_1$  = the latent heat of vaporization, Btu/lb.

# 2.4.5 Heat from Mechanical and Lighting Systems, Qm

Phillips (1970) calculated the energy added to the laying house system through mechanical and electrical means,  $\mathbf{Q}_{\mathrm{m}}$ , from the equation

$$Q_m = CAK$$
,

where C = the conversion factor 3.413 Btu/watt-hour,

A = the floor area of the laying house, sq ft, and

K = the energy input per unit area, watts/sq ft.

The total lighting energy, AK, was determined by summing the wattage of all the lights. The mechanical energy was small and neglected.

### 2.4.6 Heat from Temperature Change in Ventilating Air, $Q_V$

Since all latent heat effects in the ventilating air were accounted for in  $\mathbf{Q}_{\mathbf{e}}$ , the term  $\mathbf{Q}_{\mathbf{v}}$  accounted for sensible heat effects only. The sensible heat change in the ventilating air was, therefore, the sum of the change in heat of the air,  $\mathbf{q}_{\mathbf{va}}$ , plus the change in heat of the water vapor within the air  $\mathbf{q}_{\mathbf{va}}$ , i.e.,



$$Q_v = q_{va} + q_{vw}$$

The equation for the change in heat energy of the dry ventilating air,  $\mathbf{q}_{\mathrm{Va}}$ , was adapted from the definition of heat capacity as noted by Weast (1970) such that

$$q_{va} = M_a C_a (t_1 - t_2),$$

where  $M_a$  = mass rate of ventilating air, lbs/hr, and  $C_a$  = the heat capacity of air, Btu/lb-°F.

In a like manner the equation for the change in heat energy of the water vapor in the ventilating air,  $q_{\nu\omega}$ , was determined to be

$$q_{vw} = M_v^{C_w}(t_1 - t_2),$$

where  $M_V^{}$  = mass rate of water vapor in ventilating air, lbs/hr,

 $C_w$  = heat capacity of water vapor, Btu/lb-°F, and

 $t_1$ - $t_2$  = temperature change of the air and water vapor mixture. °F.

The water vapor mass rate,  $M_{_{\mbox{\scriptsize V}}}$ , was calculated from the relationship (Esmay, 1969),


$$M_v = WM_a$$
,

where W = humidity ratio of the mixture, lbs of moisture/
 lb of dry air, and

 $M_{y}$  and  $M_{a}$  = (as previously defined).

Combining these equations gave

$$Q_v = M_a(C_a + WC_w)(t_1 - t_2).$$



## 2.4.7 Moisture in Incoming Ventilating Air, Mo

The moisture in the incoming ventilating air,  $\mathrm{M}_0$ , was determined from given or assumed data about the weather. From these data, a dry-bulb and dewpoint temperature was generated for a specific time of day as discussed earlier. The outside dewpoint temperature was assumed to be constant at the reported value for that day except at times when the dry-bulb temperature was less than this value. For that situation and time the dewpoint temperature was set at the dry-bulb temperature. These temperatures along with the ventilating rate were used to calculate the moisture in the incoming air,  $\mathrm{M}_0$ , as

$$M_0 = M_a W_0$$
,

where  $\rm W_{O}$  = the humidity ratio of the incoming air as determined from psychrometric relationships, lbs of moisture/lb of dry air, and

 $M_a = (as previously defined).$ 

## 2.4.8 Moisture from Animal Respiration, Mr

The latent heat in respired air from laying hens,  $\mathbf{Q}_1$ , was determined from data presented by Ota and McNalley and adapted by Phillips (1970). An equation for the moisture from animal respiration,  $\mathbf{M}_r$ , was written from the definition for latent heat as given by Weast (1970). The equation was

$$M_r = Q_1/h_1,$$



where  $h_1$  = the latent heat of vaporization at the body temperature of a laying hen, Btu/lb, and  $Q_1$  = latent heat from housed animals, Btu/hr.

## $\begin{array}{ccc} \textbf{2.4.9} & \underline{\textbf{Moisture Evaporated from}} \\ & \underline{\textbf{Manure, M}_{m}} \end{array}$

The moisture evaporated from the manure,  $\mathbf{M}_{m},$  was calculated from the water removal equation:

$$M_m = A_m m_m \theta + I$$
,

where  $A_m$  = surface area of the manure, sq ft,

 $m_m$  = constant drying rate of manure, 1bs/sq ft-hr,

 $\theta$  = (as previously defined), and


I = moisture evaporated due to manure energy level when voided.

Since the modeled system scraped the manure from the dropping boards daily, the boards were covered with wet manure. The dropping board surface was therefore used as the manure drying surface in the simulation model.

The method for calculating the constant drying rate of manure,  $m_{\rm m}$ , was discussed in section 2.3.1.

The wet-bulb temperature for use in that equation was determined by use of the Newtonian convergence procedure discussed in section 2.3.2. The hypothesis was that the sum of initial ventilating air moisture content plus the moisture added to the air while passing through the poultry house was equal to the final moisture content. The Newtonian convergence equation was

$$F(x) = W_0 + E_m + R - W_i,$$



where W = humidity ratio of outside air,

 $\mathbf{E}_{\mathbf{m}}$  = moisture added per unit weight of ventilating air from drying manure,

 $\mathbf{E}_{\mathbf{W}}$  = moisture added per unit weight of ventilating air from the waterers,

R = moisture added per unit weight of ventilating air from bird respiration, and

 $W_i$  = humidity ratio of the outgoing ventilating air.

The units for all terms were pounds of moisture per pound of dry air.

The moisture evaporated due to the manure energy level as voided, I, was calculated from the equation

$$I = q_i/h_1,$$

where q; = heat given up by the manure, Btu, and

 $h_1$  = latent heat of vaporization at average temperature difference, Btu/lb.

The heat given up by the manure,  $q_i$ , was calculated from the equation:

$$q_i = W_m C_m (t_h - t_i)$$

where W = weight of manure produced during one iteration, lbs.,

 $C_m$  = specific heat of manure, Btu/lb-°F,

t<sub>h</sub> = hen body temperature, °F, and

t; = laying house temperature, °F.

The hen body temperature was defined as 107.1°F by Esmay (1969). The specific heat of the manure,  $\rm C_m$ , was estimated to be 0.87 Btu/lb-°F. This estimate was made by noting the voided manure moisture content was 80 percent and that water has a specific heat of one. The dry



matter specific heat was estimated at 0.35 Btu/lb- $^\circ$ F by averaging the specific heat values of cellulose, clay sand, silica, wood, sugar, steric acid, and Urea as given by Perry et al. (1973). A weighted average of the two values was then used for the value of  $\mathrm{C_m}$ .

### 2.4.10 Moisture Evaporated from Waterers, Mw

The moisture evaporated from the waterers,  $\mathbf{M}_{\mathbf{W}}$ , was calculated from the water removal equation discussed previously. With appropriate subscripts the equation becomes:

$$M_w = m_w A_w \theta$$
,

where  $\mathbf{m}_{\mathbf{W}}$  = mass flow rate of water from a free surface,  $\label{eq:lbs/sq} \mathbf{lbs/sq} \ \, \mathbf{ft}\text{-hr} \, ,$ 

 $A_{w}$  = surface area of waterers, sq ft, and  $\theta$  = (previously defined).

The surface area of the waterers,  $A_{\mathbf{w}}$ , was determined by measuring the surface area of each waterer and summing these areas.

Calculation of the mass flow rate of water vapor from a free surface,  $m_{\rm W}$ , was calculated from Stefan's law. Holman (1963) integrated the equation for the law and presented the equation:

$$m_{\text{wt}} = \frac{Dp_a w_m A}{R_0 T (x_2 - x_1)} \ln(p_2/p_1),$$

where  $m_{\rm wt}$  = the total mass flow of water, lb/hr,

D = diffusion coefficient,  $ft^2/hr$ ,

p<sub>a</sub> = barometric pressure, psi,

 $w_m$  = molecular weight,



A = area, sq in,

R<sub>o</sub> = universal gas constant, lb-ft/lb-°R,

T = temperature of environmental air, °R,

 $x_2$  = elevation of vessel rim, ft,

 $x_1$  = elevation of water surface in vessel, ft,

 $\mathbf{p}_{1}$  = partial pressure of the air at the water surface, psi.

The value for the mass flow rate of water vapor, m., was determined by dividing the above equation by the area, A. Weast (1970) gave a value for the diffusion coefficient, D, as 0.239 sq cm/sec at 8°C and Holman (1963) gave a value of 0.256 sq cm/ sec at 25°C. The value used for D was that calculated by interpolation using the poultry house dry-bulb temperature. The molecular weight of water and the universal gas constant were given by Holman at 18 and 1545 lb-ft/lb-°R, respectively. Holman (1963) noted the partial pressure of the air at the water surface, p1, was the barometric pressure minus saturated water vapor pressure while the air vapor pressure,  $\mathbf{p}_2$ , was the barometric pressure minus the ambient air water vapor pressure. The saturated water vapor pressure was determined from the inside dry-bulb temperature and the ambient air water vapor pressure was determined from the inside dry-bulb and wet-bulb temperatures using the psychrometric algorithm discussed earlier. The difference in elevation,  $x_2-x_1$ , was estimated from onsite



measurements and the barometric pressure was obtained from weather records.

#### 2.5 Outline of Computer Program

The theory and mathematical algorithms discussed above were incorporated into subroutines for computer computation. In the simulation these subroutines were activated and controlled by a main or executive program. A flow chart of the executive program is shown by Figure 2.3 and a listing of the computer program is presented as Appendix A.

The computer program was set up to either operate in a verification mode based on actually recorded input ventilating air conditions or a simulation mode based on U.S. Weather Service type information. This being the case, the first step of the model determined the mode and number of days to be simulated from input data.

The first operation for starting the simulation of daily drying was to initialize or numerically define the fixed parameters. This was followed by determining the appropriate psychrometric values for the outside air at one-hour intervals for the specific day. The coldest outside temperature at which the inside predetermined temperature can be maintained was then determined. Next, the simulation determined the daily amount of excreta produced. With these data available the simulation started the iterative process and determined the amount of excreta produced up to the time of the specific iteration. The next step was to specify whether it was







Figure 2.3. Flow chart of computer program.







Figure 2.3. Cont'd.






Figure 2.3. Cont'd.




"daytime" (lights on) or "night time" (lights off) for the specific iteration so the correct metabolic and mechanical heat production would be determined.

These operations were followed by two questions of logic involving the outside dry-bulb temperature. With the first the outside dry-bulb was compared with the pre-determined inside temperature. If the outside temperature was higher, an inside higher temperature was calculated. If the outside temperature was lower, a second question of logic determined if the outside temperature was less than the previously calculated outside minimum temperature. When the outside temperature was less than this minimum, a lower inside temperature was calculated. When the outside temperature was between these values, the inside temperature was set at a predetermined value. Each of these branches in the simulation required a different calculation sequence.

Maintaining the pre-determined inside temperature was done by varying the ventilating rate. This rate was determined for each iteration. An initial guess ventilating rate was made and the calculated rate was determined by the Newtonian convergence procedure.

When the outside temperature was higher than the predetermined value (summer conditions) the ventilating rate was set at its maximum and the inside temperature was determined. Again the Newtonian convergence technique was used. This required an initial guess for the inside temperature with subsequent determination of the inside temperature.




When the outside temperature was less than the coldest outside temperature which will allow maintenance of the pre-determined inside temperature, the ventilating rate was set at its minimum value. With this ventilating rate (winter conditions) the inside temperature was determined using the same technique as for summer conditions.

With the appropriate inside temperature and ventilating rate, the drying rate was calculated and subsequently the quantity of water evaporated from the manure and waterers for the specific iteration was determined. These values were added to like quantities from previous iterations. The moisture content of the manure at the end of the iteration was calculated also at this time in the simulation sequence. The last regular step of the iterative sequence was to file or store the results of the calculations.

At the end of the iteration the time was checked. If it was midnight, weather data for the next day were read and psychrometric data for the outside air were calculated for the new day.

If appropriate, the process was repeated for the next iteration.

When the iterative process was complete, results from the moisture content and water removed calculations were printed in tabular form.



#### MODEL VERIFICATION


A STATE OF THE PARTY OF THE PAR

The model was verified by operating a commercial-type cage laying house from October, 1973, through January, 1975. At various times throughout this period psychrometric data were collected for analysis. The principal data collected were dry-bulb and wet-bulb temperature and the ventilating air-flow rate. Data were collected to make a moisture balance of the ventilating air flowing through the poultry house. The moisture added to the air in the poultry house section of the building was partitioned into respired moisture and moisture added from drying. The moisture from drying was calculated as the difference between the moisture added and respired moisture. As noted earlier, the respired moisture from the chickens can be calculated from the equation:

$$M_r = Q_1/h_1$$

and the latent heat output,  $Q_1$ , from chickens can be found from data by Ota and McNalley (1961). These data (see Table 2.2) were used in conjunction with the latent heat of vaporization,  $h_1$ , to calculate the respired moisture,  $M_r$ .

The moisture from drying came from two sources: drying of the manure and evaporation from waterers. Calculations of moisture removed based on psychrometric data were made from data collected every 30 minutes. The purpose of the psychrometric data collection and analysis was to determine the moisture in the ventilation air as



it passed selected locations in the poultry house during a 30-minute period. The moisture added to the air while passing between these locations during the 30-minute period was then calculated by difference.

For verification the water removed from the poultry house as determined from the collected data and as determined by the simulation model were compared.

#### 3.1 Experimental Facilities and Equipment

The floor plan of the experimental facilities is illustrated by Figure 2.2. The operation of the experimental facilities was the same as described earlier.

All temperature and air velocity data were collected with an instrument manufactured by Information Instruments, Inc. The temperatures were measured with thermister sensors; one dry and one with a cotton wick kept wet with distilled water from a continuous source. The air velocity was measured with revolving, 3-cup anemometers. The results of these measurements were transferred electrically to a central point and recorded on paper tape. The equipment was programmed to collect data for about 3 minutes two times each hour, resulting in 5 to 7 data records every 30 minutes of operation. The instrument was designed to record temperatures in degrees Celsius. Since some temperatures for outside air were expected to be below 0°C and the paper tape had no provisions for recording minus temperatures, the instrument was calibrated with an off-set of about 28°C. A special circuit was built to give consistently the electrical




equivalent of 0°C. This circuit was connected to one of the temperature stations and served the following three functions: (1) a defined source for the offset when processing the data, (2) a compensator for minor electrical variations within the instrument, and (3) a known temperature source for checking the equipment during operation.

Raw data from the paper tape were processed and placed on a magnetic tape stored at the Michigan State University Computer

Center (Tape No. LTT 5319). The stored data consisted of: (a) clock time of acquisitioned data, (b) temperature data, (c) anemometer counts for air velocity, and (d) a range factor for the velocity counts. The equipment was capable of measuring the temperature at 60 locations and the air velocity at 8 locations during a 30-second cycle. There were 71 pieces of data stored on the tape for each time designation but only 3 velocity count locations and 12 temperature locations were needed for this study. The date of data acquisition was identified by reference to a name assigned to each file of paper-tape data placed on the magnetic tape. A hard copy listing of the data was made immediately after the data were stored on the magnetic tape. The paper tapes were stored as a back-up data source.

The quantity of ventilating air passing through the poultry building during a 30-minute data-collecting cycle was determined by calibrating the poultry-house ventilating system against the velocity count readings obtained from the recording equipment. The calibration was made by using a hot-wire anemometer to measure the air velocity at 64 locations in the drying tunnel just before the




ventilating air entered the exhaust fans. The velocity measuring procedure followed that recommended by the ASHRAE Guide and Data Book (1965). When making the calibration, one of the five ventilating fans was operated while all other fans were inoperative. During this period the recording velocity-count equipment was operated and the velocity was measured with the hot-wire anemometer. Six sets (replications) of velocity-count records and hot-wire anemometer data were collected. The beginning time and ending time of each data set were noted so that the velocity-count data and the hot-wire anemometer data could be paired. This process was repeated five times, but each time an additional fan was made operative. The velocity-count data collected during the time required to collect the hot-wire anemometer data were averaged and paired with the average velocity as found by the hot-wire anemometer. The final result was five pairs of data with six replications. A linear regression analysis was made of these data pairs. The resulting equation was

Y = 54.4838 + 0.2569x

where Y = ventilating air velocity, feet/min, and

x = number of counts as recorded on the paper tape. Not all of the ventilating air passed by the hot-wire anemometer location because of a clearance hole around the manure removal conveyor. This was accounted for by making a separate calibration. The hole was divided into five representative parts. Each part was measured and its area calculated. The procedure of replications, fan activation, and recording equipment operation was repeated but



only one hot-wire anemometer reading was taken for each area. This reading was multiplied by the respective area, resulting in a flow rate with units of cubit feet per minute. This flow rate was paired to an average of the velocity counts as before. These data pairs were analyzed by a linear regression analysis, which resulted in the equation

v = 229.467 + 1.059x

where y = flow rate of ventilating air through hole, cfm, and x = (as previously defined).

## 3.2 Experimental Procedure

#### 3.2.1 Psychrometric Data Collection and Analysis

Psychrometric data were collected by measuring representative dry-bulb and wet-bulb temperatures of the ventilating air at various locations in the poultry building. These locations are designated on the floor plan in Figure 2.2 as II, I2, I3 for the incoming air, and 01, 02, and 03 for outgoing air from the laying house. The ventilating air velocity measurements were made at locations 01, 02, and 03. The analysis was based on the premise that all drying was done with the ventilating air. It was also assumed that the difference in total added moisture in the ventilating air between any two measuring locations was added from one or more of the following sources: (a) drying of the manure, (b) respiration from the chickens, and (c) evaporation from the watering troughs. Other sources were assumed negligible. In cases of water spillage from the waterers



or other sources, the collected data were discarded from the analysis. A further assumption was that the data collected at the end of a 30-minute period were representative of the conditions during that period.

The difference in total moisture in ventilating air between two locations expressed as an equation is

$$P_a = P_i - P_i$$

where  ${\rm P}_{\rm a}$  = the moisture added to the ventilating air during  $$\rm movement$  from location j to location i, lbs., and

 $P_i, P_j$  = moisture in ventilating air at location i and j, respectively. lbs.

The equation for the flow rate of moisture in ventilating air was given by Esmay (1969) and modified to read

$$M_i = M_a W_i$$
,

where M<sub>i</sub> = the moisture flow rate at location i, lbs. of moisture/hr.

 $M_a$  = mass flow rate, lbs of air/hr, and

 $W_i$  = the humidity ratio of the air at location i, lbs moisture/lb of dry air.


The results of this equation were multiplied by a lapsed time to yield the total moisture in pounds, i.e.,

$$P_i = M \theta$$

where  $\theta$  = lapsed time, hours, and

 $P_i$  and  $M_i$  = (as previously defined).

The collected data were used to estimate the true values of  $W_{ij}, M_{aj}$ , and  $\theta$ . The humidity ratio,  $W_{ij}$ , was calculated from algorithms



prepared by Bakker-Arkema and Lerew (1972) using the dry-bulb and wet-bulb temperature data. The processing of these temperature and velocity-count data was done by a computer program prepared for that purpose. Data gathered during a specific 24-hour or longer testing period were treated the same by the program. Minor adjustments in station number designations were sometimes required when processing data from different testing periods because of malfunctions of the temperature-measuring equipment. A data record (71 pieces of data) was read from the magnetic tape and, when appropriate, the clock time set equal to variables defined as the time for data immediately preceding data being processed, the first time reading of the calendar day, and the time of the beginning of the 30-minute programmed cycle of data collection. The readings from those stations recording dry-bulb and wet-bulb temperatures and velocities were combined with another instrument reading cycle and averaged by summing and counting each individual reading. The two instrument recording cycles were combined into one 60-minute calculating cycle by processing only the hour and ignoring the minute portion of the time record. Only those readings not equal to zero were summed and counted. The results of this process yielded an arithmetic average of the readings taken at a specific location during a one-hour cycle. The readings for the electrically preset offset temperature were processed in a like manner. If during data collection or upon reviewing the collected data an equipment malfunction of one of the data-collection stations was observed, the data from that station were set equal to zero. The effect was to eliminate those data



from consideration. The temperature data were collected as paired data; e.g., at Station II there was a dry-bulb temperature and a wet-bulb temperature, at Station I2 the same things, etc. These averaged data pairs were checked for the larger value and interchanged if the "wet-bulb" was larger than the "dry-bulb." This switch was necessary to accommodate the idiosyncrasies of the psychrometric algorithms and the data-collecting equipment. In theory the two temperatures can be equal, but the wet-bulb temperature cannot be larger than the dry-bulb temperature. During freezing weather no true wet-bulb temperature of the incoming air was recorded because the water supply would freeze and damage the equipment. Since under freezing conditions the humidity ratio is very low even at 100 percent relative humidity, saturated incoming air was assumed by allowing the dry-bulb and wet-bulb temperatures to be equal. The electronics of the equipment was not precise enough, however, to signal exactly the same temperature to within one-tenth of a degree. The result was that the recorded wet-bulb temperature was sometimes slightly larger than the dry-bulb temperature. After the comparison check and switch, if needed, the dry-bulb temperatures and the wetbulb temperatures of each location were averaged; i.e., the dry-bulb temperatures at locations II, I2, and I3 were averaged and the wetbulb temperatures at locations II, I2, and I3 were averaged, etc. The result was one dry-bulb and one wet-bulb temperature to represent 10 to 14 readings in the ventilating air stream taken simultaneously at three locations over two time periods of about 3 minutes.



The algorithm for calculation of psychrometric data was prepared for use with American Engineering Units. Because of this, all calculations were made with these units. Since the temperature data were collected in metric units, they were converted to degrees Fahrenheit and degrees Rankine after the offset factor was subtracted from the averaged number representing temperature. The dry-bulb and wet-bulb temperatures, expressed in degrees Rankine, were combined with U.S. Weather Service data for the barometric pressure at East Lansing, Michigan, to determine the humidity ratio of the ventilating air.

The value for the velocity-count, x, for use in the two equations derived by linear regression analysis was obtained by averaging the velocity-count data collected at locations 01, 02, and 03. The processing of the velocity-count data was carried out simultaneously with and similarly to the processing of the temperature data; i.e., the 10 to 14 readings at each location were averaged, then the averages from the three locations were averaged. The result was one arithmetic average velocity-count for those data collected during the one-hour calculating cycle.


The flow rate of the ventilating air through the poultry house for each one-hour cycle was calculated from the equation

q = AY + y

where q = poultry house air-flow rate, cfm,

 $\label{eq:A} A = cross-sectional \ area \ of \ the \ drying \ tunnel, \ sq \ ft,$  and

Y and y = (as previously defined).



To obtain the mass-flow rate, M<sub>a</sub>, the volume-flow rate, q, was multiplied by 60 minutes per hour and divided by the specific volume of the ventilation air as calculated from the outgoing dry-bulb and wet-bulb temperatures, i.e.,

$$M_a = 60q/v$$
,

where v = specific volume of ventilating air, cu ft/lb,

and

 $M_a$  and q = (as previously defined).

$$\theta = t_m - t_k$$

where  $\mathbf{t}_{\mathrm{m}}$  = clock time at the end of the currently processed data cycle, hours, and


 $t_k$  = clock time at the end of the previously processed data cycle, hours.

For the specific poultry house the area, A, was equal to 49.5 square feet. Combining this area with the above analysis into one function and rounding to 5 significant figures yields

$$P_A = (t_m - t_k)(W_i - W_i)(1/v)(826.53x+175,580.),$$

where all variables have been previously defined.

This function expresses the moisture added to the ventilating air in terms of the recorded data and psychrometric terms calculated from recorded data.



## 3.2.2 Simulation Model Evaluation

The model was evaluated by comparing a performance variable as determined from measured data to that same variable as calculated by the simulation model. The ultimate performance variable to compare was the evaporation from manure during the test day. Another performance variable was the total moisture removed from the poultry house during the test day and a third performance variable was the evaporation from the poultry house during one specific hour of a test day. Of these the total moisture removed from the poultry house during the test day was determined with the least amount of intermediate calculation from the collected data. As a result it was used extensively in the initial verification comparisons.

It was necessary to adjust the simulation model to give results similar to the collected data. During this period of evaluation, it was found useful to compare initial input values and intermediately calculated values. All of the comparisons were made graphically by using appropriate peripheral equipment in connection with the computer. The effect of this capability was that appropriate calculated data from the verification measurements could be combined with comparable calculations from the simulation model and plotted to form a graph for review.

The principal input variables for the model were dry-bulb temperature and dewpoint temperature. Other input variables were considered constant for a specific day. Intermediate values of interest were: humidity ratio of incoming air, dry-bulb temperature



of out-going air, dewpoint temperature of out-going air, humidity ratio of out-going air, incoming and out-going humidity ratio difference, and air flow through the poultry house. Examples of comparison graphs for each of these variables versus time are presented in Appendix B. The values calculated for each of the intermediate variables helped evaluate errors in the simulation model. After operating the simulation model and comparing the graphical results, adjustments were made in the model. Following the adjustments it was operated again and compared. This process was continued many times. Each time it was necessary to make comparison graphs for most, if not all validation test days. As noted above, the principal basis of performance evaluation was the graph of total moisture removed from the poultry house during the test day. (See Figure 3.1 for an example.)

The evaporation from manure during the test day for the verification data was calculated by difference. As explained earlier, the psychrometric data and the air flow measurements provided the information to calculate the amount of moisture added to the air as it passed through the poultry house. The results of these calculations provided the total moisture added to the ventilating air. Since the sources of added moisture were the moisture from drying manure, the surface of the waterers, and the respiration from the hens, the moisture from the drying manure could be calculated as the difference from the total added moisture and the other two sources. The estimates used for the moisture from the waterers and from hen respiration were as calculated from the evaporation equation



(section 2.4.10) and the respiration equation (section 2.4.8), respectively. The calculated value for the moisture from the drying manure was further modified by uniformly distributing the error between the verification data and the simulation data among the three sources of added moisture. This modified value was used to prepare the "data" line on the graphs of evaporation from manure during the day. (See Figure 3.2 for an example.)

The simulation model performance acceptability was a qualitative judgment based upon how well the curve of a specific variable versus time matched the shape of the verification (collected data) curve. The individually paired data point values were also considered in the performance acceptability evaluation.

## 3.3 Verification Results

# 3.3.1 Summer Conditions

Data collected during three summer days were suitable for use as verification data. These data were obtained August 12, 13, and 20, 1974. For each of the three days, performance variable graphs were prepared. The graphs, prepared with the simulation model in its acceptable form, are presented as Figures 3.1, 3.2, 3.3, 3.4, 3.5, and 3.6. Simultaneously a tabulated graph was made of management factor, design, and input values used in the simulation. These tabulations are presented in Appendix C.

# 3.3.2 Winter Conditions

Data collected during two winter days were suitable for use as verification data. These data were obtained January 6 and 7, 1975.




As with the summer data, performance variable graphs were prepared. Similarly, tabulations were made of management factor, design, and input values used during the simulation. The graphs are presented as Figures 3.7, 3.8, 3.9, and 3.10. The tabulations are in Appendix C.

It should be pointed out that certain winter condition adjustments were required of the simulation model to accommodate a unique situation of the experimental poultry house. When operating the mechanical dryer it was found necessary to have at least one of the main ventilating fans in operation to prevent combustion gases from entering the laying hen portion of the poultry house. As a result, the minimum ventilating rate in the simulation model was increased to include this effect during the time of mechanical drying on the appropriate verification test dates. This was done by adjusting the minimum ventilating rate to that actually measured on the verification test date.

# 3.4 Discussion of Verification

A review of the graphs showing the accumulated total moisture removed from the poultry house during the day, i.e., Figures 3.1, 3.3, 3.5, 3.7, and 3.9, showed that the "data" curves and the "simulation" curves followed very closely their respective data points. A comparison of the paired curves also showed the general shape of the curves to be similar. It was noted, however, that the curve shapes were better matched for the summer data than the winter data. When comparing the departure of the paired curves it was noted that the



curves for the date August 13, 1974, had the greatest deviation for the summer data and that for January 6, 1975, for the winter data. For August 13, 1974, the largest deviation occurred at the twenty-fourth hour of the day, i.e., when the ordinate values were the largest and thus the accumulated error was the largest. As noted from Table 3.1, the numerical difference of the plotted data points was 282.09 (2977.10-2695.01) pounds of moisture. For January 6, 1975, the largest difference occurred at the fourteenth hour and was 420.87 (1035.19-614.32) pounds of moisture. With the "data" value as the base, the errors for the two extreme values were 9.5 and 68.5 percent, respectively. There is no known explanation for the large deviation in the January 6, 1975, graph. The only known different management practice on that date was that the mechanical dryer did not operate. Some of the difference might be attributed to measurement error, however.


A review of the graphs showing the evaporation from manure during the day, i.e., Figures 3.2, 3.4, 3.6, 3.8, and 3.10, showed that the "data" and the "simulation" curves followed very closely their respective data points with the possible exception of the "data" curve for January 6, 1975. For this graph there was considerable variation between the plotted points and the curvilinear regression curve. When comparing the paired curves, it was noted that each pair involving the summer data was more nearly the same shape than those of the winter data. Some of this difference in appearance can be explained by noting that the scaled length for the ordinate of the winter data was less than one-half the scaled length




of that for the summer data. It was also noted that the paired curves for the data of January 6, 1975, were not well matched. Although no reason for this discrepancy was found, it was noted that the data points for the "data" curve for this date seemed more random than all other curves.

Some of the difference in the paired verification curves might be attributed to measurement error. Several factors are involved with measurement error including accuracy, sensitivity, response time, and readability. For the most part, the magnitude of these factors is limited by the specific measuring equipment. Accuracy can be checked by a calibration procedure and can often be adjusted as was the case for the equipment used for this study. The specific measurements made in this study were dry-bulb temperature, wet-bulb temperature, and air speed. The measurement of each contributed to measurement error but this discussion has been limited to the readability of the dry-bulb and wet-bulb temperatures and their effects upon the "data" quantity graphed in Figures 3.1, 3.3, 3.5, 3.7, and 3.9. This quantity is the total moisture removed from the poultry house.

The readability of temperature was limited by the paper tape recording equipment to the equivalent of 1.8°F. Information appropriate for January 7, 1975, was selected to illustrate the extreme effects of an error of one readability unit, i.e., 1.8°F, upon the graphed "data" quantity. For that date the average inside air temperatures were 55.80°F dry-bulb and 50.47°F wet-bulb. The average



incoming air temperatures were 37.00°F drv-bulb and 35.98°F wetbulb. Also for that date the average ventilating rate was 8388 cubic feet per minute. If the readability error potential is added to or subtracted from these average temperatures to give inside temperatures of 55.62°F dry-bulb and 50.68°F wet-bulb and incoming temperatures of 37.18°F dry-bulb and 35.82°F wet-bulb, the humidity ratio change was the largest possible. For the smallest humidity ratio the dry-bulb and wet-bulb temperatures were 55.98, 50.32, 36.82, and 36.12°F, respectively. For a one-hour period at the average ventilating rate and the large humidity ratio difference, the total moisture added to the air would be 105.7 pounds. For the low humidity ratio difference the total moisture added to the air would be 84.9 pounds per hour. The difference between these two values, 20.8 pounds per hour, can be called the average range of readability effect upon the total moisture removed from the poultry house. The "data" quantity graphed in Figure 3.10, however, accumulates over a 24-hour time period. For the extreme case the readability error would also accumulate over the 24-hour period and be equal to 501.2 pounds of moisture. Table 3.1 shows the difference between the collected data and the simulation model on January 7, 1975, to be 274.7 (1983.50-1708.83) pounds after 24 hours. This is less than 501.2 pounds. Calculations for the data collected on the other dates showed similar relationships. This indicated that the "simulation" quantity graphed by the figures fell within the envelope formed by measurement error variation.






Figure 3.1. Accumulated total moisture removed from the poultry house during the day of August 12, 1974. The two curves result from curvilinear regression calculations based on the two separate sets of data.






Figure 3.2. Accumulated moisture evaporated from the manure in the poultry house during the day of August 12, 1974. The two curves result from curvilinear regression calculations based on the two separate sets of data.






Figure 3.3. Accumulated total moisture removed from the poultry house during the day of August 13, 1974. The two curves result from curvilinear regression calculations based on the two separate sets of data.






Figure 3.4. Accumulated moisture evaporated from the manure in the poultry house during the day of August 13, 1974. The two curves result from curvilinear regression calculations based on the two separate sets of data.






Figure 3.5. Accumulated total moisture removed from the poultry house during the day of August 20, 1974. The two curves result from the curvilinear regression calculations based on the two separate sets of data.







Figure 3.6. Accumulated moisture evaporated from the manure in the poultry house during the day of August 20, 1974. The two curves result from curvilinear regression calculations based on the two separate sets of data.






Figure 3.7. Accumulated total moisture removed from the poultry house during the day of January 6, 1975. The two curves result from curvilinear regression calculations based on the two separate sets of data.






Figure 3.8. Accumulated moisture evaporated from the manure in the poultry house during the day of January 6, 1975. The two curves result from curvilinear regression calculations based on the two separate sets of data.






Figure 3.9. Accumulated total moisture removed from the poultry house during the day of January 7, 1975. The two curves result from curvilinear regression calculations based on the two separate sets of data.








Figure 3.10. Accumulated moisture evaporated from the manure in the poultry house during the day of January 7, 1975. The two curves result from curvilinear regression calculations based on the two separate sets of data.



Accumulated total pounds of moisture removed from the poultry house. A comparison of collected data versus simulation model calculations. Table 3.1.

0.0 COL. SIM. COL. SIM. COL. SIM. "COL. COL. COL. COL. COL. COL. COL. COL.	CLOCK		8/12/74	8/1	8/13/74	8/20	8/20/74	1/6	1/6/75	1/1	7/75
0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0	TIME, HOURS	06	SIM. MODEL	COL. DATA		COL. DATA	SIM. MODEL	COL.	SIM. MODEL		SIM. MODEL
88.28 64.33 91.57 89.34 101.51 68.79 31.12 58.66 49.19 56 104.01 101.01 101.01 101.02 10.05 177.60 121.95 202.15 105.01 101.01 101.01 101.02 1	0		0.0	0.0		0.0	0.0	0.0	0.0		0.0
162.91 120.95 17760 121.05 204.05 1564 59.95 111.10 10110 1110 1244.91 125.50 126.50 222.72.88 316.94 2021.5 95.74 1811.2 1691.5 173 324.91 195.50 227.28 346.94 2021.5 95.74 1811.2 1691.5 173 322.23 268.98 346.11 366.94 369.35 267.05 257.24 386.25 554.87 599.407.67 357.26 2156.26 299.36 286.15 173 22.43 326.25 554.87 599.44 565.15 403.11 526.76 299.37 280.94 389.36 50.25 57.25 57.26 57.24 386.25 57.25 57.25 57.26 57.25 598.04 57.25 57	-	. 2		5	.3	2	7	-	9	49.19	6
246, 91 195, 56 267, 95 272, 18 316, 96, 95 156, 26 239, 98 266, 13 522, 25 26.08 3 246, 14 556, 99 407, 67 259, 93 156, 26 239, 98 266, 13 252, 25 260, 28 346, 14 556, 99 407, 67 259, 93 156, 26 239, 98 266, 13 252, 25 24, 456, 46 26, 48 20, 75 37, 66 238, 46 269, 98 266, 13 253, 48 207, 48 26, 48 27, 48 26, 48 27, 48 26, 48 27, 48 26, 48 27, 48 26, 48 27, 48 26, 48 27,		6.29	20.0	77.6			٠.	. 0	7	101.10	1
332.23 266.88 346.14 556.69 407.67 269 35 166.26 239,98 266.13 233 422.23 220.28 456.16 442.56 482.57 203.14 286.65 544.7 500.44 656.15 403.11 286.76 509.94 389.50 223 522.14 386.55 544.7 500.44 655.15 403.11 286.76 509.94 389.50 223 523.14 586.75 578.45 579.46 570.47 730.49 595.52 380.13 520.09 1744 570 570.40 570 570.40 570 570.40 570 570.40 570 570.40 570 570 570 570 570 570 570 570 570 57	~	44.9	95.5	67.9	2.1	6		· .	-	169.15	173.62
4.22.23 32.24, 4.56.16 442.56 488.07 337.26 213.66 299.53 328.00 229 5.23.44 388.65 554.87 509.44 563.15 403.11 256.76 360.94 389.35 353 5.25.44 388.65 554.87 509.44 563.15 403.11 256.76 360.94 389.35 353 726.37 578.42 638.47 606.78 730.49 996.62 295.53 438.00 150.25 427 726.37 578.42 719.48 719.48 719.57 730.49 905.04 74 402.58 598.04 18 598.87 574 912.07 790.07 994.52 906.49 905.04 828.74 428.17 684.52 703.56 617.44 1109.39 106.34 1111.83 1155.62 1175.19 1132.56 511.76 81.86 778 1109.39 136.49 1256.29 1228.03 1271.61 1109.69 511.66 94.37 778.81.86 1200.00 1219.48 1275.29 1285.03 1271.61 1109.69 511.66 94.37 881.86 1200.00 1219.48 1275.29 1776.79 770.03 51.67 77 881.86 1200.00 1219.48 1275.29 1285.03 1271.61 1109.69 511.66 94.37 881.86 1256.29 1386.41 111.83 1128.20 1285.03 1271.61 1109.69 511.60 942.11 111.11 1154.41 1154.41 1154.41 1154.41 1156.41	<b>.</b>	32.2	8.09	46.1	9.9	9	6	56.2	6	266.13	0
523,44 388.65 554.87 509.44 563.15 403.11 226.76 360.94 389.35 353 652.94 388.65 554.87 509.44 563.15 403.11 226.76 360.94 389.35 353 652.34 48.67 74.57 719.46 704.37 710.65 72 8.98 625.53 748.07 71 65.37 570.15 520.05 517.40 77 75.57 775.45 770.15 570.1	2	22.2	24.2	56.1	2.5	0	7	13.4	5	328.00	00
632.98 483.92 638.47 606.78 652.28 498.96 295.53 438.07 450.25 427 725.39 479.46 704.47 730.49 595.52 340.13 520.05 817.44 506 82.94 677.51 821.57 800.31 811.56 501.47 402.36 581.04 590.87 912.70 790.07 943.32 906.09 905.04 828.74 428.17 684.52 703.56 690 1006.01 919.61 1028.84 1026.00 1074.77 732.00 446.43 773.60 778.56 690 11006.01 919.61 1028.84 1026.00 1074.77 732.00 446.43 773.60 7784.56 718 11006.01 919.61 11028.84 1026.00 1074.77 732.00 446.43 773.60 7784.56 718 11006.01 1210.48 1736.25 1173.19 1132.56 517.32 861.72 881.66 97.75 778.61 1200.00 1210.48 1756.28 1423.85 1410.69 1503.56 644.37 1055.10 1138.10 1200.79 1200.70 1200.70 12	9	23.4	88.6	54.8	9.4	Τ.	Ε.	56.7	6	389.35	9
726.37 578.45 719.46 704.37 730.49 595.5 340.15 520.05 817.44 500 812.00 790.75 1821.75 800.31 811.56 5101.47 1402.36 598.06 199.81 181.56 7011.47 402.36 598.06 199.81 181.56 190.40 828.74 488.17 684.52 703.56 649 1200.39 1916.1128 814.1058.00 1074.27 972.00 449.47 684.52 703.56 649 1100.39 105.31 1111.83 1155.62 1173.59 1735.66 517.32 864.52 703.56 649 1100.39 105.13 1111.83 1155.62 1173.59 1735.56 517.32 864.52 703.56 649 1205.51 1135.51 1135.56 1735 864.52 703.56 140.75 1205.39 1135.52		632.98	83.9		606.7	,	6	2	8.0	0.2	7
825.07 990.75 821.77 800.31 811.55 701.44 402.56 998.04 899.87 574 912.70 995.32 996.49 905.04 828.74 402.85 598.04 899.87 574 912.70 995.32 996.49 905.04 828.74 188.17 684.52 703.56 708.56 1109.88 1065.34 1111.83 1153.62 1175.19 1132.56 517.32 861.72 861.72 878.56 718 1200.00 1219.48 1750.50 1275.50 1275.56 1275.56 5175.28 861.72 878.65 718 1200.00 1219.48 1750.50 1275.5		726.37	78.4		704.3	0	5	Ξ.	0.0	7.4	0
992.70 790.07 943.32 906.49 905.04 828.74 428.77 684.52 705.56 649 1006.91 9106.81 86 706.09 910.00.00.0943.32 906.49 905.04 828.74 428.77 7684.52 705.56 706.56 11006.81 1006.91 910.61 1102.88 1056.12 1175.19 1135.56 517.32 861.32 861.72 881.86 796 11006.81 81.86 706 1100.81 81.86 706 81.86 706 81.8		825.94	77.5		800.3	-	7	5	8.0	9.8	-
1006.91 910.61 1028.84 1026.40 1074.27 972.00 464.45 773.60 7784.56 778 1199.38 1065.34 1111.83 1153.62 1173.19 1132.56 517.32 861.72 881.86 778 1199.38 1065.34 1111.83 1153.62 1173.19 1132.56 517.32 861.72 881.86 778 1200.38 1200.39 1225.03 1225		912.70	90.0		906.4	٠,	7	Ε.	4.5	3.5	9.
1200. 08 1063.34 1111.83 1153.62 1173.19 1132.56 517.32 861.72 881.86 796 1200. 00 1219.48 1230.39 1285.03 1271.61 1309.69 581.66 947.89 962.77 878 1366.49 1356.28 4425.85 44919.69 1503.36 6442.22 1035.19 1057.15 946 1407.63 1560.32 1875.28 1487.55 14107.32 8 6442.22 1035.19 1057.15 946 1407.63 1560.33 1887.28 1487.56 1570.40 1387.28 799.42 1135.11 11351.44 1138 11351.44 1138 11351.44 1138 11351.44 1138 11351.44 1138 11351.44 1138 11351.44 1138 11351.44 1138 11351.44 1138 11351.44 1138 11351.44 1138 11351.42 11351.43 11351.43 11351.43 11351.44 1138 11351.44 1138 11351.42 11351.43 1		1006.91	19.6		1026.4	<u>;</u>	0	-	3.6	4.5	00
1200.00 1219,48 1230.39 1285.03 1271.61 1309.69 581.66 947.89 962.77 878 1305.19 1365.29 1386.49 1356.28 1427.85 1419.69 1503.36 644.23 1035.19 1055.15 944 1107.63 1560.38 11875.65 1570.40 1587.16 1033.35 644.23 1135.10 11057.15 1057.15 1077.15 1107.16 1107.16 1107.15 1107.16 1107.17 1		1109.38	63.3		1153.6	3	2	٣.	1.7	1.8	9
1355.29 1386.49 1556.28 1433.85 1419.69 1503.36 614.32 1035.19 1057.15 944 1407.51 1105.60 138 1487.56 1570.00 1587.16 1003.37 731.59 1137.16 11517.6 1049 11407.51 11407.51 11517.16 11517.6 1049 11407.51 11407.51 11517.16 11517.6 1049 1175.00 11407.51 11407.52 1950.20 1175.00 1	~	1200.00	219 4	230.3	285.0	271.6	3.005	8.1.6	-	962.77	7
1407.63 1560.38 1487.56 1570.40 1587.16 1103.32 771.35 1117.16 1151.76 1049 1514.66 1741.11 1654.38 1778.07 1766.7 1903.28 799.42 11951.14 11351.44 1138 11351.44 1138 1751.25 1140, 1190.79 11082.11 1882.5 1936.28 2104.30 831.10 1269.79 11551.44 1138 1175.27 2088.43 1992.28 2043.30 2133.15 2304.24 976.56 1345.03 1457.34 1364 2028.14 2259.54 2205.67 2205.68 1440.85 1259.28 1247.74 2588.10 2516.44 11251.14 1496.54 11675.27 14676.25 14	17	305.2	386.4	356.2	423.8	419.6	503.3	14.3	-	1057.15	
1514, 56 174, 11 1534, 38 1776, 07 1766, 97 1903, 28 799, 42 1195, 11 1251, 44 1188 175, 04 11910, 79 1208, 21 1825, 12 1250, 20 8 2104, 50 811, 10 1262, 79 1562, 20 1254, 1857, 27 208, 83 1992, 28 2045, 51 1351, 15 2344, 49 476, 56 1345, 10 1457, 10 1374, 1	15	407.6	560.3	487.5	570.4	587.1	703.3	21.3		1151.76	0.0
1715.04 1910.79 1208.21 1882.25 1930.28 2104.30 831.10 1269.79 1365.20 1224 1875.20 1224 1875.20 1224 1875.20 1224 1875.20 1224 1875.20 1234 1304.24 976.51 1345.03 1457.34 1304.20 12028.14 2259.54 2205.57 2207.55 2275.55 2505.98 1065.53 14196.28 1378.73 1340.25 1415.85 1378.73 1360.55 1415.25 1415.85 1378.73 1360.57 1525 1526.56 2435.69 2424.45 2386.01 2316.42 2888.64 1175.31 1496.24 1575.51 1575 1575 1575 1575 1575 1575 1	16	514.5	741.1	634.3	726.0	766.9	903.2	4.66	_	1251.44	. 7
1875.27 2088.43 1992.28 2043.30 2133.15 2304.24 976.56 1345.03 1457.34 1304 2028.14 2259.54 2205.67 2207.65 2275.65 2505.98 1066.53 1419.85 1578.78 1384 2205.76 245.56 2424.74 2358.01 2316.42 2888.64 1125.11 1496.45 141.676.52 1467 2257.64 2555.64 2555.69 2424.74 2358.01 2316.42 2598.64 1125.11 1496.54 11753.11 1552 2502.12 2652.38 27 2628.57 2455.69 2735.69 1285.92 1617.25 11552 2502.12 2652.38 27 2883.57 2617.09 2883.54 2484.01 1755.28 1617.06 1585 275.67 2873.69 1200.00 1891.56 1647 275.67 2873.69 1200.00 1891.56 1647 275.67 2873.69 1200.00 1891.56 1647 275.67 2873.69 1200.00 1891.57 3782.59 1782.59 1782.59 1782.59 1783.59 17885.90 1708	17	715.0	910.7	808.2	882.2	930.2	104.3	51.1	_	1362.20	
2028.14 2259.54 2205.67 2207.65 2275.65 2265.98 1066.53 1419.85 1578.78 1384 2205.62 2455.69 2424.74 2358.01 2316.42 2888.64 1125.11 1496.42 1776.52 1462 2357.64 2554.87 2628.57 2455.62 2441.05 2794.69 1286.64 1155.54 11555.41 1155.51 1525 2500.12 2659.13 2659.13 2883.57 2617.09 2883.57 2617.09 2883.57 2617.09 2883.57 2617.09 2883.57 2617.09 2655.11 255.54 2617.25 1811.06 1585 2755.07 2847.59 120 2655.11 2675.25 2783.59 120 2655.11 2675.25 2783.59 120 1757.25 1811.06 1585 2755.07 2847.59 120 2655.11 2782.59 3016.48 1472.54 1741.73 1983.50 1708	18	875.2	4.880	992.2	043.3	133.1	304.2	76.5		1457.34	1.7
2205.76 2435.69 2124.74 2388.01 2316.42 2888.64 1173.11 1496.24 1176.52 1462.25 236.74 2554.87 2628.75 2455.20 2441.05 2793.69 1206.41 1555.41 1755.51 1525.25 240.12 2567.14 255.41 2657.85 2588.29 2588.29 2573.67 2883.69 1288.39 1677.25 1811.05 2793.69 1288.39 1677.25 1811.05 2793.69 1288.39 1678.39 1678.36 1649.25 2750.07 2847.59 2788.35 2750.07 2873.69 1288.35 1709 2685.31 2017.55 1811.05 1647.25 2750.07 2847.24 2977.10 2665.01 2782.39 3016.48 1472.54 1741.73 1983.59 1708	10	128.1	259.5	0.5 F	207.	275.	2505.9	'n	8	578.7	84.1
2567.04 2554.87 268.77 2455.62 2441.05 2793.69 1206.41 1555.41 1753.51 1523 2562.12 2656.86 2780.53 2588.29 2573.67 2873.69 1285.92 1617.25 1811.06 1585 2655.11 2760.57 2883.57 2617.09 2685.34 2948.40 1375.58 16791.00 1891.56 1647 2750.07 2847.24 2977.10 2655.01 2782.59 3016.48 1472.54 1741.73 1983.50 1708	200	205 7	25.0	7 11	25.0	316	2688 6	-	406.2	676.5	62.1
2502.12 2659.86 2780.53 2538.29 2573.67 2873.69 1785.92 1617.25 1811.06 1585 26 25.02 1617.25 1811.06 1585 2655.17 2766.57 2883.57 2617.09 2685.34 2484.00 1757.58 165910 1891.56 1640 2750.07 2847.24 2977.10 2655.01 2782.59 3016.48 1472.54 1741.73 1983.50 1708	21	367.6	554.8	28.5	455	411	2793.6	-	555.4	753.5	23.7
2635.71 2760.57 2883.57 2617.09 2685.34 2948.40 1375.58 1679110 1891.36 1647 2750.07 2847.24 2977.10 2695.01 2782.39 3016.48 1472.54 1741173 4983.50 1708	22	502.1	659.8	80.5	538.	573.	2873.6	6	617.2	811.0	85
2750.07 2847.24 2977.10 2695.01 2782.39 3016.48 1472.54 1741:73 1983.50 1708	23	635.7	760.5	83.5	617.	£85.	2948.4	5	679.1	891.3	47.0
	24	750.0	847.2	77.1	695.	782.	3016.4	5	74117	983.5	08.8



Accumulated pounds of moisture evaporated from the manure in poultry house. comparison of collected data versus simulation model calculations. Table 3.2.

				**	200	
SIM. MODEL	0.0	66	30.06 41.51 53.08 65.48	77.61 89.71 106.93 125.28 138.71	171.03 188.20 204.33 219.26 233.14 246.44	259.38 272.35 283.79 295.63
1/7/ COL. DATA	0.0	9.8	29.38 50.77 62.55 74.77	82.77 93.22 112.60 159.04 155.82	193.31 212.82 231.70 249.17 270.65	315.35 334.57 351.09 360.57
75 SIM. MODEL	0.0	9.1.	31.98 42.46 53.81 64.81	77.13 88.93 100.68 114.14 128.56 142.63	154.86 168.38 180.44 192.29 204.95	228.87 240.81 251.79 264.93 278.06
1/6/75 COL. DATA M	0.0	8.6	84.08 64.57 66.82 80.78	108.68 137.04 146.88 188.47 248.79 276.96	287.95 341.36 298.62 291.47 310.10	270.19 284.77 279.91 282.04 283.68
774 SIM. MODEL	0.0	1.0	57.01 75.48 93.29 110.37	23.500	360.10 429.89 502.39 575.00 649.18 721.59	794.78 855.23 885.63 930.81
8/20/74 COL. DATA M	0.0	38.3	119.23 147.52 164.81 187.22	96.7 02.8 115.8 36.5 86.9	350.46 409.49 474.12 541.16 606.34 677.44	737.65 777.62 808.63 837.72 865.40
SIM. MODEL	0.0	5.8	85.95 109.78 133.17 151.54	71. 889. 009. 32. 59.	325.07 362.80 404.02 451.36 500.87	610.63 663.55 703.23 738.29 769.30
8/13/7 COL. DATA	0.0	C 12.	84.66 106.76 137.55	81. 94. 15. 60.	313.06 348.09 386.13 431.18 483.39 540.82	610.08 683.65 760.88 823.72 865.02
74 SIM. MODEL	0.0	6.5	54.80 73.31 89.49 106.34	4.00000	338.17 397.58 459.89 524.40 584.95 648.42	708.54 770.63 813.69 851.75
8/12/74 COL. DATA M	0.0	IC IC	75.82 104.38 133.00 168.43	89. 02. 21. 38. 63.	333.00 377.90 426.56 479.85 540.53	654.10 714.27 764.15 808.00 852.26
CLOCK TIME, HOURS	0	1 2	0 2 t a	7 8 9 10 11 12	13 14 15 16 17	19 20 21 22 23



## 4. RESULTS FROM MODEL USE

The simulation model was operated four times using average weather data. Each simulation operation was selected to typify the amount of manure-drying that might occur in a poultry house near Lansing, Michigan, during (1) winter conditions, (2) summer conditions, (3) spring conditions, and (4) throughout the year.

The data averaged for the first three simulation operations were the dry-bulb and dewpoint temperatures for the 10-year period 1968 through 1977. Weather for the month of January was used to represent winter conditions, the month of July summer conditions, and the month of April represented spring conditions. Since the model calculates the moisture removed from the manure on a daily basis, a dry-bulb and dewpoint temperature was required for each day of the representative month. The 10-year average for the specific day was used and calculated from National Weather Service data (U.S. Department of Commerce, 1977a). For the calculations representing the manure drying throughout the year, representative weather data in each month of the year were selected. The representative data were the average dry-bulb and dewpoint temperatures for each month of the year as determined by the National Weather Service (U.S. Department of Commerce, 1977b) for Lansing, Michigan.

The results from operating the simulation model are presented graphically with two graphs for each operating condition.



The first graph shows the moisture removed from the manure each day of the month as calculated by the simulation model. The same graph also shows the corresponding dry-bulb and dewpoint temperatures as determined from weather data. The second graph shows the manure moisture content for each day of the month and the same corresponding dry-bulb and dewpoint temperatures. The graphs for January are presented as Figures 4.1 and 4.2, for April as Figures 4.3 and 4.4, and for July as Figures 4.5 and 4.6. Graphs for the year as a whole are presented as Figures 4.7 and 4.8. The same basic pattern was used for the year as a whole graphs as those for the individual months. The data from which the graphs were prepared are presented as Tables 4.1, 4.2, 4.3, and 4.4. Table 4.5 lists the management factor, design, and input values used for operating the simulation model.

A review of the graphs indicated more moisture would be removed from the poultry house and more manure drying would occur during summer months than in other seasons. This seemed reasonable and was expected. When comparing the summer conditions to the winter conditions in the poultry house, there was more ventilating air and the air had a larger potential moisture-holding capacity during the summer. For example, the average ventilating rate at noon as calculated by the simulation model for the month of July was 20,400 cubic feet per minute and for January was 5,410 cubic feet per minute. Similarly, the average potential evaporation of the air for July was 103.7 pounds of water and for January was 74.5 pounds of water. (The potential evaporation was calculated as the difference of the







Figure 4.1. The moisture removed from manure during a typical month of January as calculated by the simulation model.






Figure 4.2. The moisture content of manure for a typical month of January as calculated by the simulation model.






Figure 4.3. The moisture removed from manure during a typical month of April as calculated by the simulation model.






Figure 4.4. The moisture content of manure for a typical month of April as calculated by the simulation model.






Figure 4.5. The moisture removed from manure during a typical month of July as calculated by the simulation model.






Figure 4.6. The moisture content of manure for a typical month of July as calculated by the simulation model.







Figure 4.7. Representative daily moisture removal from manure throughout the year as calculated by the simulation model.






Figure 4.8. Representative daily manure moisture content throughout the year as calculated by the simulation model.



Table 4.1. Manure moisture removed and moisture content for a typical month of January as calculated by the simulation model.

DAY OF MONTH	MANURE MCISTURE REMOVED. POUNDS	MANURE MOISTURE CONTENT, PERCENT	AVERAGE DRY-BULB TEMPERATURE, DEGREES F	AVERAGE DEWPOINT TEMPERATURE, DEGREES F
1	503.4	68.1	19.	14.
2	437.9	68.8	21.	17.
	476.1	69.2	22.	18.
4	529.1	67.3	17.	13.
5	565.0	65.8	13.	7.
6	530.6	67.2	17.	11.
7	55R.4	66.1	14.	9.
8	566.4	65.7	13.	7.
9	529.1	67.3	17.	11.
10	495.4	68.5	20.	15.
11	518.2	67.7	13.	13.
12	540.9	66.8	16.	10.
13	518.4	67.7	13.	12.
14	499.9	63.4	20.	15.
15	538.2	66.9	16.	11.
16	507.3	68.1	19.	13.
17	496.7	68.5	20.	15.
18	462.9	69.7	23.	18.
19	451.9	73.0	24.	18.
20	436.5	68.9	21.	16.
21	440.5	70.4	25.	19.
22	428.8	70.8	26.	20.
23	463.6	69.7	23.	18.
24	434.2	70.6	25.	18.
25	427.1	70.8	26.	20.
26	433.8	70.5	25.	18.
27	406.0	68.9	21.	15.
28	475.0	69.2	22.	19.
29	441.3	70.4	25.	19.
30	475.3	69.2	22.	17.
31	464.5	69.6	23.	16.




Table 4.2. Manure moisture removed and moisture content for a typical month of April as calculated by the simulation model.

_				
DAY OF MONTH	MANURE MBISTURE REMOVED, POUNDS	MANURE MOISTURE CONTENT, PERCENT	AVERAGE DRY-BULB TEMPERATURE, DEGREES F	AVERAGE DEWPOINT TEMPERATURE, DEGREES F
		70.0		
1	321.6	73.8	39.	30.
2	333.1	73.5 73.5	39.	30 <b>.</b> 29 <b>.</b>
3	333.6		38.	29.
4	332.9	73.5	37.	29.
5	339.4	73.3	35.	24.
6	339.7	73.3	38.	24.
7	349.1	73.1	39.	26.
. 8	342.6	73.3	39.	24.
C	3.2.0	.5.5		
9	338.3	73.4	39.	25.
10	357.9	72.9	42.	27.
11	351.5	73.0	43.	27.
12	402.2	71.6	49.	32.
13	333.0	72.0	48.	34.
14	339.6	72.0	47.	34.
15	401.8	71.6	50.	37.
16	435.3	70.6	52.	40.
17	449.1	70.1	53.	41.
13	456.8	69.9	54.	44.
19	414.6	71.2	51.	40.
20	446.6	70.2	53.	40.
21	456.9	69.9	54.	41.
22	332.4	72.2	49.	.41.
2.3	380.5	72.2	49.	30.
2.4	331.3	73.6	43.	33.
25	343.8	73.2	43.	32.
26	389.5	72.0	47.	32.
27	422.0	71.0	51.	35.
2.8	383.9	72.1	49.	38.
29	414.5	71.2	51.	40.
30	452.3	70.0	53.	43.



Table 4.3. Manure moisture removed and moisture content for a typical month of July as calculated by the simulation model.

DAY	MANURE MOISTURE REMOVED.	MANURE MCISTURE CONTENT.	AVERAGE DRY-BULB TEMPERATURE,	AVERAGE DEWPOINT TEMPERATURE:
MONTH	POUNDS	PERCENT	DEGREES F	DEGREES F
1	788.3	52.4	70.	58.
2	772.5	53.7	69.	56.
3	750.5	55.4	68.	58.
4	750.0	55.4	68.	59.
5	746.7	55.7	68.	58.
6	773.7	53.€	69.	57.
7	316.1	50.0	71.	59.
8	834.4	49.3	72.	62.
9	813.9	50.2	71.	61.
10	783.9	52.4	70.	61.
11	774.0	53.6	69.	58.
12	756.1	55.0	68.	58.
13	836.6	43.0	72.	60.
14	377.3	43.7	74.	63.
15	855.9	46.0	73.	62.
16	814.9	50.1	71.	ó0.
17	835.9	48.1	72.	60.
18	815.0	50.1	71.	62.
19	832.3	48.5	72.	64.
20	815.0	50.1	71.	62.
21	793.6	52.0	70.	60.
22	514.0	50.2	71.	60.
23	814.5	50.1	71.	62.
24	809.2	50.6	71.	64.
25	791.3	52.2	70.	61.
26	746.7	55.7	68.	59.
27	785.4	52.4	70.	60.
28	750.0	55.4	·8.	58.
29	727.7	57.0	67.	59.
30	793.7	52.0	70.	59.
31	314.0	50.2	71.	62.



Table 4.4. Manure moisture removed and moisture content for a typical year as calculated by the simulation model.

MONTH OF YEAR	MANURE MOISTURE REMOVED, LBS/DAY	MANURE MOISTURE CONTENT, PERCENT	AVERAGE DRY-BULB TEMPERATURE, DEGREES F	AVERAGE DEWPOINT TEMPERATURE, DEGREES F
1	452.8	70.0	24.	18.
2	445.9	70.2	25.	19.
3	351.1	73.0	33.	24.
4	353.6	73.0	46.	34.
5	511.9	67.9	57.	46.
6	720.2	57.5	67.	56.
7	825.4	49.1	72.	59.
8	795.2	51.8	71.	59.
9	607.9	63.8	62.	52.
10	414.4	71.2	51.	41.
11	313.8	74.0	38.	31.
12	408.5	71.4	28.	22.


inside and outside humidity ratios times the ventilating air mass.) Both of these conditions tend to increase moisture removal and manure drying. A high dewpoint temperature would tend to reduce moisture removal and manure drying. Although the dewpoint temperature was high during the summer (see Figures 4.5 and 4.6), it apparently was low enough when combined with other factors, to allow considerable drying in the poultry house according to the simulation model calculations. As a result of this seasonal difference, the simulation model can be expected to calculate manure moisture removal with a seasonal cycle effect. This is in contrast to the situation reported by Esmay et al. (1975). In their presentation they stated the "in-house drying" of poultry manure was not seasonal. However,



their report mentioned four drying phases: in-house drying, movement drying, belt drying, and heated air mechanical drying. The moisture removed from the manure as calculated by the simulation model includes the in-house drying phase and the movement drying phase. Furthermore, the movement drying as reported by Esmay et al. (1975) was influenced by the season of the year. A comparison of the simulation model moisture content calculations for the yearly condition as reported in Figures 4.7 and 4.8 with similar data from Esmay et al. (1975) indicated the simulation model may calculate too much drying, especially during summer conditions.

As the graphs were studied it was noted that the least moisture was removed from the manure and the manure moisture content was highest for the month of April. Although seasonal differences were expected, minimum drying during the spring was not. This difference was found to be more noticeable when the average bird weight was less than the average weight of the birds in the verified system. Since the simulation model has the capability to vary such factors, the difference was emphasized by using a smaller than normal average bird weight as noted by Table 4.5.

At first it was thought the low drying in April was caused by the lower dewpoint temperature and thus the higher potential evaporation of the outside January air. This in itself did not prove to be true. Further study of the simulation model calculations showed that the drying rate in January during the day was about the same as in April but at night the January drying rate was larger



than the April drying rate. For example, the drying rate based on average conditions at noon was 0.0050 pounds of moisture per square foot-hour for January and 0.0051 pounds of moisture per square foot-hour for April. For average conditions at midnight the drying rate for January was 0.0065 pounds of moisture per square foot-hour but only 0.0036 pounds of moisture per square foot-hour for April. The net effect was more drying in January than in April.

Table 4.5. Management factor, design, and input values as used for operating the model with average weather data.

92.25 38.00 8.25 14.11 23.68 3242.35 1728.00 0.33
5000.00 3.25 107.10 80.00 0.87 0.27
60.00 20421.34 5406.01
1.00 0.00 24.00 1.00



#### 5. SUMMARY AND CONCLUSIONS

## 5.1 Summary

A simulation model which calculates the manure moisture removed and the manure moisture content in a poultry laying house was prepared and verified. The simulation model was based on psychrometric calculations in combination with constant-rate drying theory.

The basis of the simulation model and the test facilities for model verification was a commercial-type laying house near East Lansing, Michigan. The laying house had a capacity of approximately 5000 hens and used a three-tier cage system with dropping boards and under-cage mechanical scrapers for manure removal. The laying house was fully enclosed, insulated, and used mechanical ventilation with thermostatic control.

The verification system was managed as a small commercial unit at the Michigan State University Poultry Science Research and Teaching Center. Feed and water was provided by hand filling continuous troughs along each row of cages. Eggs were also gathered by hand. Only artificial light was provided to give a photoperiod equal to 14 hours. The thermostats for control of ventilation were set to operate four fans in steps of about two degrees Fahrenheit and to maintain an inside dry-bulb temperature at between 55 and 60°F where possible. Manure was scraped from the pens daily.



Verification data collected on three summer days and on two winter days were satisfactory for comparison with the simulation model generated data. Curvilinear regression curves prepared from the two sources of data for accumulated total moisture removed from the poultry house and for accumulated moisture evaporated from the manure in the poultry house followed their respective data points very closely. Each of the paired curves used for verification purposes had the same general shape and magnitude except one. The exception was for the accumulated moisture evaporated from the manure on January 6, 1975. No known reason was found for this discrepancy. It was noted, however, that the manure moisture evaporation data collected from the laying house were more random on that date than other days of data collection.

The critical factors for maximizing in-house drying of poultry manure were the manure drying rate and the drying surface area. A large surface area provided for maximum drying. Since the manure was removed daily, the scraping of the dropping boards maximized the exposed surface area of manure. The simulation model indicated any system increasing the manure drying surface area would tend to increase manure drying. The drying rate was a function of no less than seven variables. Some of these variables were material specific and some were configuration specific. For a given material, i.e., poultry manure, and a given poultry house, these were considered constant. The variables which influenced the manure drying rate the most were the inside wet-bulb depression and the ventilating rate. The wet-bulb depression in turn was influenced directly



by the inside dry-bulb temperature and indirectly by the outside dewpoint temperature. To maximize manure drying, a high drying rate was desirable. To obtain a high drying rate a high inside dry-bulb temperature and low outside dewpoint was desirable. The weather determined the outside dewpoint temperature, but management practices influenced the inside dry-bulb temperature.

#### 5.2 Conclusions

The following conclusions are the result of preparing and verifying a simulation model to estimate the in-house drying of poultry manure.

- A computer simulation model based on known drying theory and verified by experimental psychrometric data was formulated to simulate the fecal moisture removed from a poultry house by ventilating air.
- The data from the simulation model matched the experimental summer psychrometric data closely but the match of the winter data was not as close due to the greater effect of measurement error upon the lower ventilating air movement and smaller wet-bulb depression.
- The simulation model provided a means of effectively evaluating the controllable management and design factors of a poultry house to maximizing in-house drying of the poultry manure.
- A simulation run of the model for seasonal variation of moisture evaporation from a poultry house showed the greatest



potential for moisture removal to be in the summer and minimum potential to be during the spring and autumn seasons.


#### 5.3 Recommendations for Future Research

The results of this research suggest the need for additional work in the following areas:

- A better verified model to estimate the outside dewpoint temperature than the one used in this study. The outside dewpoint temperature has considerable impact on the drying rate and thus the moisture removed from manure during in-house drying. An accurate estimate of the outside dewpoint temperature, therefore, is desirable when using the simulation model.
- 2. A verification study independent of this research using a different approach would be desirable. The collected verification data used for this study were based on the psychrometric characteristics of the ventilating air. Adjustments resulting from verification of the simulation model based on the measurement of the moisture content of the manure and the mass of manure produced by the laying hens could improve the accuracy of the simulation model.
- 3. Additional laboratory studies be conducted to determine a more suitable mathematical model for the drying rate of manure. The model for the drying rate as used in the simulation model was reported by Perry et al. (1963, 1973). These authors noted the drying rate model was material specific. The objectives of the laboratory studies should be to develop a model specific to manure.



APPENDICES




# APPENDIX A

COMPUTER PROGRAM LISTING




### APPENDIX A

```
PROGRAM
                                    DRYLSN
                                                                    CINH00070
C THIS PROGRAM (ORYLSN) SIMULATES THE ENVIRONMENT IN A POULTRY HOUSE
                                                                    CINHODORO
C WHEN GIVEN THE MAXIMUM AND MINIMUM OUTSIDE TEMPERATURE. THE
C ATMOSPHERIC PRESSURE, THE DUTSIDE DEW POINT, THE NUMBER OF CHICKENS, CINHOO100
C THE HOUR TO START SIMULATION AND THE DATE. A VALUE FOR THE MANURE CINHOCILD
C MDISTURE CONTENT AS FOUND FROM VARIEICATION DATA CAN ALSO BE CINHOCILD
 INCLUDED. BUT IS NOT REQUIRED.
C THE OUTPUT FROM THE PROGRAM IS A TABLE OF THE MANURE MOISTURE
C CONTENT FOR EACH TIME PERIOD (HOUR) THROUGHOUT THE SIMULATED 'DAY' C AND THE MOISTURE REMOVED FROM THE MANURE FOR THAT 'DAY'. FOR EACH
                                                                    C15H00160
                                                                    CINHO0170
C OF THESE 'DAYS', THE INSIDE ENVIRONMENTAL CONDITIONS ARE ALSO
                                                                    CINHO0180
 GIVEN. THIS TABLE IS PROVIDED FOR EACH 'CYCLE' OF MANURE REMOVAL
 (APPROXIMATELY 24 HOURS).
C AN ADDITIONAL DUTPUT TABLE GIVES A SUMMARY OF END CONDITION OF THE
C MANURE FOR EACH 'DAY'. THE SUMMARY TABLE LIST THE MANURE MOISTURE
C CONTENT IN PERCENT AND THE WATER REMOVED FROM THE MANURE DURING
C THAT PERIOD. APPROPRIATE WEATHER AND OTHER INPUT DATA IS ALSO
                                                                    CINH00240
C SUPPLIED WITH THE LISTING.
                                                                     C INH00260
                                                                    C1NH20270
                                                                    C1NH00280
C TO USE THE PROGRAM THE FOLLOWING DATA CARDS ARE NEEDED:
                                                                    CINH00290
C 1ST CARD- NUMBER OF 'CYCLES' OR DATA-DAY PAIRS (COLUMNS 1 & 2)
                                                                   CINHOO300
C DEBUGGING INDEX, MBUG, (1=0N, 0=CFF) COLUMN 4, VARIFICATION INDEX, CINHO0310
C NNW, (0=VARIFICATION, 1=SIMULATION) COLUMN 6.
                                                                    CINHO0320
C 2ND CARD- NUMBER OF INTERATIONS IN A SPECIFIC 'CYCLE', THE INSIDE
                                                                    C1NH00330
 'SET' TEMPERATURE, DEGREES R, AND THE AVERAGE WEIGHT OF THE HENS,
                                                                  CINH00340
C LBS, A CARD REQUIRED FOR EACH DATA-DAY PAIR (CGLUMNS 1 & 2, 3 THRU 8,CINHO0350
C AND 9 THRU 14. RESPECTIVELY.
                                                                    C I NHO 0 360
C 3RO & 4TH CARD- WEATHER DATA AND OTHER INPUT CONDITIONS FOR A
                                                                    CINH00370
C SPECIFIC DATA-DAY PAIR (SEE FORMAT BELOW). THE 4TH CARD IS FOR THE
                                                                   C 1111100380
 SECOND DATE IN THE 24-HOUR CYCLE (A DUPLICATE CARD IS REQUIRED IF
                                                                    C1NH00390
C THE CYCLE IS ALL THE SAME DATE).
                                                                    CINHADAGA
                                                                    CINHO0410
                                                                    CIMHOG420
  EGRMAT FOR CARDS 3 AND 4 (BOTH THE SAME)
                                                                    C 1NH00430
                                                                    CINHO0440
    COLUMNS NOS.
                    DATA AND UNITS
                                                                    CINHODASO
     1 & 2
                      .CO. HINOM
                                                                     CINH00460
      3 & 4
                       DAY .NO.
                                                                    C INH00470
      5 & 6
                       YEAR .NO.
                                                                    CINHOGARO
     CINHO0490
                                                                  CINH00500
                                                                    C1NH00510
                                                                    CINH00520
                                                                   CINHO0530
                                                                    CINH00540
                       TIME OF DAY SIMULATION BEGINS, HOURS (24-HR) CINHO0550
    **25,26,27,28
                       AS MEASURED MANURE MCISTURE CONTENT, PERCENT CINHO0560
   **29 THRU 24
                       AS MEASURED TOTAL MUISTURE REMOVED FROM HOUSE CINHO0570
                        DURING ONE CYCLE, LBS.
                                                                     CINHO0580
                                                                    C 1NH00590
                                                                    CINHODADO
C * AN ESTIMATE WILL BE CALCULATED IF THE INPUT VALUE EQUALS ZERO.
                                                                    C I NHOO6 10
C ** NOT USED IN CALCULATIONS, OUTPUT ONLY
                                                                    C1NH00620
                                                                    C1UH00630
                                                                    CINHODAGO
CINHOOSSO
                THE PSYCHROMETRIC FUNCTION SUBROUTINE
                                                                    CINH00670
                PREPARED BY LEREW (1971) INCLUDE THE
                                                                    C.I.NH00630
                FOLLOWING ACRUNYMS:
                                                                    C1NH00690
                ENDBUP-ENTHALPY, STU/LB
                                                                    CINH00700
                HADBRN-HUMIDITY RATION, LB OF H20/LB OF DA
                                                                   CINH00710
                                                                    CINH00720
```



```
HAPV-HUMIDITY RATIO . LB OF H20/LB OF DA
                                                                       CINH00730
                HLOB-LATENT HEAT OF EVAPORATION, BTU/LB
                                                                        CINHO0740
                 PSDB-SATURATED VAPOR PRESSURE, PSI
                                                                        CINH00750
                 PVDBWB-VAPOR PRESSURE OF AIR-WATER MIXTURE, PSI
                                                                        CINHO0760
                 PVHA-VAPOR PRESSURE OF AIR WATER MIXTURE, PSI
                 RHDBHA-RELATIVE HUMIDITY, DECIMAL
                                                                        CINHO0780
                 RHPSPV-RELATIVE HUNIDITY, DECIMAL
                 VSDBHA-SPECIFIC VOLUME, CU.FI./LB
                WBOBHA-WETBULB TEMPERATURE, DEGREES R
                 (AS MCDIFIED BY DIXON ET AL, 1976)
  DEFINITION OF TERMS
                                                                        CINH00860
                                                                        CINHOOSSO
  AMC-MCISTURE CONTENT OF MATERIAL, WET BASIS, DECIMAL FRACTION
                                                                        CINHODAGO
 AT-ARRAY VALUE FOR ATMOSPHERE PRESSURE, PSI
                                                                        CINHODSON
C ATAP-ATMOSHERIC PRESSURE FOR A SPECIFIC DAY, PSI
                                                                        C1NH00910
C AVSCLT-AVERAGE SCL-AIR TEMPERATURE, DEGREES F
                                                                        C.INH00920
 AVTO-ARRAY VALUE FUR AVERAGE DUTSIDE DRY BULB TEMPERATURE, DEGREES F CINHO0930
  AVIDBO-AVERAGE DUTSIDE TEMPERATURE, DEGREES F
C BLTH-BUILDING LENGTH. FEET
                                                                        CINH00950
C BR-ARRAY VALUE FOR BIRD NUMBER.
                                                                        C1NH00960
  BRDS-NO. OF BIRDS IN BUILDING
                                                                        CINH00970
  BROTMP-BODY TEMPERATURE OF A CHICKEN, DEGREES R
                                                                        CINHODORO
C BTIM- A HOLD VALUE FOR BTIME
                                                                        CINHODOSO
C BTIME-THE TIME OF DAY THE LOOP IS TO BEGIN. HOURS
                                                                        C LMH01000
C BTIMEN-ARRAY VALUE FOR BEGINNING TIME, HOURS
C STIMN-ARRAY VALUE OF CLOCK TIME FOR BEGINNING OF RUN, HOURS
                                                                        CINH01010
                                                                        C TNH01020
C CPA-THERMAL CAPACITY OF AIR, BTU PER LB. DEGREES R
                                                                        CINH01030
C CPV-THERMAL CAPACITY OF WATER VAPOR, BTU PER LB. DEGREES R
C CRITMP-LOWEST OUTSIDE TEMPERATURE AT WHICH INSIDE OPTIMUM (SET)
                                                                        CINH01040
                                                                        CINH01050
     TEMPERATURE CAN BE MAINTAINED, DEGREES R
                                                                        CINH01060
C DF - EXCRETA DISTRIBUTION FACTOR, FRACTION OF DAILY EXCRETA PRODUCED CINHO1070
         DURING PERICO OF *DT*, LB.
                                                                        CINH01080
C DH-INSIDE AND OUTSIDE HUMIDITY RATIO DIFFERENCE, LBS OF H20 PER LB
                                                                        CINH01090
     DRY AIR
                                                                        CINH01100
C DPF-ARRAY VALUE FOR DUTSIDE DEWPOINT TEMPERATURE, DEGREES F
                                                                        CINH01110
C DPHA-DEMPOINT TEMPERATURE, DEGREES R
C DRPNUM-NUMBER OF DROPPINGS OF EXCRETA AS ACCUMULATED THRU THE DAY
                                                                        CINH01120
                                                                        CINHO1130
C DRPSAR-SURFACE AREA OF DROPPINGS, SQ. FEET
                                                                        CINHOIIAO
C DRYM- (SEE DRYRTM)
                                                                        CINHO1150
C DAYRTM-THE DRYING RATE AS CALCULATED. LBS. OF WATER PER HOUR-SU.FT.
                                                                        CINH01160
C DEVSUE-TOTAL SURFACE AREA FOR DRYING, SO. FEET
                                                                        CINHO1170
C DRYTW-THE EVAPORATION RATE FROM THE WATERERS, LBS PER HOUR-SQ FT
                                                                        C 1NHO 1 180
  DRYK- (SEE DRYRTH)
                                                                        C18H01190
C DT-LENGTH OF ITERATION, HOURS
                                                                        CINHO1200
C EDRYTM-A VARIFICATION VALUE: END OF MECHANICAL DRYER SPEKATING TIME, CINHO1210
     CLOCK TIME HOURS
                                                                        CINH01220
  ELPWAR-AN INDEX FOR LIGHTS, ON=1, OFF=0
                                                                        CINH01230
C EVAPDI-WATER EVAPORATED FROM WATERERS AND MANURE PLUS RESPIRED H20,
                                                                        CINH01240
      185.
                                                                        CINH01250
C EVAPSM-ACCUMULATIVE SUM OF WATERER AND MANURE EVAPORATION, LBS.
                                                                        C INHO1260
  EVPOTT-TOTAL MGISTURE ADDED TO THE AIR, LBS.
                                                                        CINH01270
C EVPH20-WATER EVAPORATED FROM WATERS, LBS. PER HOUR
                                                                        C I NHO 1 2 80
         DURING *DT*, LBS
                                                                        CINHO1290
C EVPH2S-ARRAY VALUE FOR SUM OF WATER EVAPORATED FROM WATERS. LBS
                                                                        CINH01300
C EVPH2T-SUM OF WATER EVAPORATED FROM WATERS, LBS
                                                                        CINHO1310
  EVPMRT-SUM OF WATER EVAPORATED FROM MANURE. LBS
                                                                         CINHO1320
C EVPOTT-ACCUMULATIVE SUM OF POTENTIAL EVAPORATION BASED ON THE
                                                                         CINHO1330
      VENTILATING AIR CAPACITY. LBS GF H2G.
                                                                         CINH01340
C EVPPOT-POTENTIAL EVAPORATION BASED ON THE VENTILATING AIR CAPACITY, CINHO1350
      LBS OF H20.
                                                                         CINHO1360
  EVPMUR-MATER EVAPORATED FROM MANUFE, LBS. PER HOUR
                                                                         CINH01370
C EVPRMV-ARRAY VALUE FOR TOTAL WATER REMOVED FROM MANURE DURING ONE RUNCINHO1380
      (DAY), LBS
                                                                         CINH01390
 EVPSUM-TOTAL WATER REMOVED FROM THE MANURE, LBS
                                                                         CINHOLADO
  EVPT-THE A YOUNT OF WATER EVAPORATED FROM THE MANURE DURING *DT*, LBS.CINHO1410
 EVPTTL-TOTAL WATER EVAPORATED IN HOUSE, LBS.
  EXCOME-THE MOISTURE CONTENT OF MANURE AS DEFICATED, DECIMAL FRACTION CINHO1430
C EXSMIS-HEIGHT OF MANURE IN THE HOUSE MINUS EVAPORATED MOISTURE, LBS. CINHO1440
```

•



```
CINH01450
C EXHTD-MANURE PRODUCED DURING TIME DT. LBS
C EXWITDY-WEIGHT OF EXCRETA PER DAY, LBS.
C EXWISH-MEIGHT OF EXCRETA AS ACCUMULATED THRU THE DAY, LBS
C FLOW-THE VENTILATION RATE AT THE ITERATION TIME. CFM
C HA-HUMIDITY RATIO FOR CUTSIDE AIR, LB OF HZC PER LB OF DA
                                                                        CINHO1490
C HADP-HUMIDITY RATIO, LB OF H20 PER LB OF DA
                                                                        CINHO1500
C HADPI-INSIDE HUMICITY RATIG BASED ON INSIDE DEMPOINT TEMPERATURE, LB CINHO1510
     OF H2C PER LB OF DA.
                                                                        CINHO1520
  HADPO-GUTSIDE HUMIDITY RATIO BASED ON UUTSIDE DEMPOINT TEMPERATURE. CINHO1530
     LBS OF H2G PER LB OF DA.
  HAI-HUMIDITY RATIO FOR INSIDE AIR AS CALCULATED FROM SUMS OF MOISTURECINHO1550
        SOURCES, LB CF H20 PER LB CF DA
                                                                       C10501560
C HAIN-ABSOLUTE HUMIDITY OF INSIDE AIR, LBS PER LB
C HEIT-BUILDING HEIGHT, FEET
                                                                        CINHO1580
C HLDB-LATENT HEAT OF VAPORIZATION. BTU PER LB
                                                                        CINH01590
C HIMC-MOISTURE CONTENT OF MANURE ASFOUND FROM EXPERIMENTAL DATA AT MSUCINHO1600
C H7MN-ARRAY VALUE FOR H7MC
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
C ID-CALENDAR DAY (DATE)
                                                                        CINH01630
C TON-ARRAY VALUE FOR CALENDAR DAY-FINAL DAY OF RUN.
C INDIC-AN INDEX TO CHANGE SLAR TEMPERATURE E.G. DAILY RATHER THAN EACHCINHO1650
         CALCULATION
C IY-CALENDAR YEAR (DATE)
                                                                        CINH01670
C IYN-ARRAY VALUE FOR CALENDAR MONTH
                                                                        C.TNH01680
                                                                        CINH01690
C 1-A POINTER FOR THE CLOCK TIME BEING CALCULATED
                                                                       CINH01700
C LTIME- LAST TIME PERIOD OF A RUN (DAY). HOURS
                                                                       CINHO1710
C MBUG-AN INTEGER CODE USED FOR DEBUGGING THE *MAIN+
                                                                        CINH01720
C MID- AHOLD VALUE FOR ID
                                                                       C INHO1730
C MIDN-ARRAY VALUE FOR CALENDAR DAY-INITIAL DAY OF RUN
                                                                       C1NH01740
C MM-COUNTER FOR NUMPER OF OUTPUT LINES PER DAY.
                                                                       C INHO1 750
C MMIN-DELAYED HOLD VALUE FOR MN. DEGREES F
                                                                        CINHO1760
C MMXN-DELAYED HOLD VALUE FOR MX. DEGREES F
                                                                       CINH01770
C MN-MINIMUM OUTSIDE TEMPERATURE FOR THE DAY, JEGREES F
                                                                       C1NH01780
C MNN- CUTPUT VALUE FOR MN. DEGREES F
                                                                        CINH31790
C MU-CALENDAR MCNTH(CATE)
                                                                        CINHO1800
C MON-ARRAY VALUE FOR CALENDAR MONTH
                                                                        CINHO1810
C MTIME-ALAPSED TIME COUNTER DURING RUN, NO. OF DT,S
                                                                        C IMM01820
C MX-MAXIMUM OUTSIDE TEMPERATURE FOR THE DAY, DEGREES F
                                                                        CINHO1830
C MXN- OUTPUT VALUE FOR MX, DEGREES F
                                                                        CINH01840
C NN-NUMBER OF RUNS (DAYS) FOR WHICH CALCULATIONS ARE DESIRED.
                                                                        C1NH01850
C NNM-INDICATOR DESIGNATING THAT WEATHER GENERATED BY *NETHER* IS FOR CINHO1860
C VARIFCATION (=0) OR FOR SIMULATION (=1). CINHO1870
C GNEFAN-A VERIFICATION VALUE: THE CAPACITY OF GNE VENTILATING FAN, CFMCINHOISBO
C PATM-ATMOSPHERIC PRESSURE, PSI
                                                                        CINH01890
C PCTMCH-THE PERCENT MGISTURE CONTENT AFTER DRYING FOR *DT* AND AS IF CINHO1900
         IT WERE THE FIRST *DT*
C PCTMCT-THE PERCENT MOISTURE CONTENT OF THE MANURE AT THE DESIGNATED CINHO1920
         TIME
                                                                        CINH01930
C PC-MOISTURE CONTENT OF MANURE AT END OF RUN, PERCENT
C POULTRY FARM SLDG NO. 7. PERCENT
                                                                        CINHO1950
C GADDED-ACCUMULATED HEAT ADDED TO THE POULTRY HOUSE FROM ALL SOURCES CINHO1950
                                                                        CINH01970
      BTII
c
  CAH-NET HEAT ADDED TO HOUSE, BTU PER HOUR
                                                                        CINH01980
C OCCUNST-THE SUM OF HEAT BALANCE FACTORS REMAINING CONSTANT DURING
                                                                        CINH01990
     CONVERGENCE CALCULATIONS, BTU PER HR.
                                                                        CINH02000
C QUITOT-LATENT HEAT PRODUCTION OF BIRDS, BTU PER HOUR
                                                                        CINH02010
  QLTGTS-TOTAL RESPIRED MUISTURE FRUM BIRDS, LBS
                                                                        CINH02020
C OMECH-MECHANICAL HEAT ADDED INSIDE HOUSE, BTU PER HR
                                                                       C INHO2030
C QS-SENSIBLE HEAT PRODUCTION OF BIRDS, BTU PER HOUR
                                                                        CINH02040
C R-INTERMEDIATE VALUE TO DEFINE THE LENGTH OF A FUN.
                                                                        C [NH02050
C RANGE-OUTSIDE DAILY TEMPERATURE RANGE, DREGREES F
                                                                        C 1NH02060
C RSPWTR-RESPIRATION RATE OF BIRDS, LBS PER HUUR
C RUNLGT-NUMBER OF INTERACTIONS EACH COMPUTER RUN (CYCLE LENGTH)
                                                                        CINH02080
C SDRYTM-A VARIFICATION VALUE: BEGINNING OF MECHANICAL DRYEK OPERATING CINHO2090
                                                                        C1NH02100
      TIME, CLOCK TIME HOURS
C SOLT-ADJUSTED CEILING SOL-AIR TEMPERATURE. DEGREES F
                                                                        CINH02110
C ST-ADJUSTED CEILING SOL-AIR TEMPERATURE, DEGREES F
                                                                        C1NH02120
C TAV-AVERAGE SOL-AIR TEMPERATURE, DEGREES F
                                                                        CINH02130
C TH-OUTSIDE DRYBULB TEMPERATURE FOR OUTPUT, DEGREES F
                                                                        CINH02140
                                                                       CINH02150
C TOB-DUTSIDE DRY BULB TEMPERATURE. DEGREES R
C TOBG2-GUTSIDE WALL SURFACE TEMPERATURE, DEGREES R
                                                                       CINH02160
```



```
C TOP-OUTSIDE DEW POINT TEMPERATURE, DEGREES R
C TOPF-CUTSIDE DEMPOINT TEMPERATURE (U.S. WEATHER SERVICE), DEGREES F
                                                                    C1NH02130
 TOPI- INSIDE DEMPOINT TEMPERATURE, DEGREES F
                                                                     CINH02190
  TEMPI-THE INSIDE TEMPERATURE DATAINED BY CLAVERGENCE, DEGREES R
                                                                     CINH02200
 TGES-AN INTERMEDIATE GUESS VALUE USED FUR CONVERGENCE, DEGREES &
                                                                     CINH02210
C TI-TEMPERATURE INSIDE HOUSE AS CARRIED BY MAIN PROGRAM. DEGREES R
 TIDP-INSIDE DEWPOINT TEMPERATURE AT "TIME MINUS DI," DEGREES R
  TIME-CLOCK TIME, 24-HOUR CLOCK
 TIN-TEMPERATURE, INSIDE HOUSE, DEGREES F(USED IN SUBROUTINES)
                                                                     C1NH02250
C IMIN-A CALCULATED TEMPERATURE WHICH THE MIN. VENTILATION RATE CAN
                                                                     CINH02260
     HOLD; AN GUTSIDE TEMPERATURE
                                     DEGREES 8
C TDEI-INSIDE DRYBULB TEMPERATURE, DEGREES F
C TDB0-OUTSIDE DRYBULB TEMPERATURE AS CALCULATED BY *WETHER*, DEGREES FCINHO2290
C TOPI-INSIDE DEWPOINT TEMPERATURE, DEGREES F
  TDPO-OUTSIDE DEW POINT TEMPERATURE AS CALCULATED BY *WETHER*, DEGREE FC1NH02310
  THINE-MINIMUM TEMP FOR THE DAY, DEGREES F
                                                                     CINH02320
C TMINE-MINIMUM TEMP FOR THE DAY, DEGREES R
                                                                     CINH02330
 TC-CUTSIDE WALL SURFACE TEMPERATURE, DEGREES F
                                                                     CINH02340
  TP-DEWPOINT TEMPERATURE FOR OUTPUT, DEGREES F, OUTSIDE
                                                                     CINH02350
C TSET-DESIRED INSIDE TEMPERATURE, DEGREES R
 TSLAB-TEMPERATURE OF FLOOR SLAB, DEGREES R AND F
                                                                     C1NH02370
C TWBI- INSIDE WETBULB TEMPERATURE, DEGREES R
                                                                     C INH02380
C U-FLOATING POINT VALUE OF STARTING POINTER
                                                                     CINH02390
C UNTEVP-TOTAL WATER EVAPORATED IN UNIT TIME, LBS. PER HOUR
                                                                     CINH02400
C UXAREA-THE HEAT TRANSMISSION COEFICIENT FOR THE BLDG., BTU PER HOUR CINHO 2410
         DEGREE R
                                                                     CINH02420
C VELMAS-MASS AIR FLOW RATE, LBS/MIN.
                                                                     CINH02430
C VENTRY-THE VENTILATION RATE IN THE HOUSE AT TIME OF CALCULATION,
                                                                     CINH02440
        CFM CUTSIDE AIR
                                                                     CINH02450
  VRMIND-A VARIFICATION VALUE: MINIMUM VENTILATION RATE DURING DRYER
                                                                     CINH02460
C VRGESS-AN INTERMEDIATE GUESS VALUE FOR THE VENTILATION RATE. CFM
                                                                     CINH02470
C VRMAX-MAXIMUM VENTILATION RATE OF HOUSE, CFM
                                                                     CINH02480
C VRMIN-MINIMUM VENTILATION RATE OF HOUSE, CFM
                                                                     CINH02490
C WATLGT-LENGTH OF WATERERS. FEET
                                                                     CINH02500
C WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE, SQ FT
                                                                     CINH02510
C WATTSQ-ELECTRICAL POWER APPLIED TO BUILDING, WATTS PER SQ. FOOT
                                                                     CINH02520
C WATWOT-WIDTH OF WATERING TROUGHS. WATER SUPFACE. FEET
                                                                     C1NH02530
C WEDHA-WET BULB TEMPERATURE. DEGREES R
                                                                     CINH02540
C WBRD-AVERAGE BIRD WEIGHT. LBS.
                                                                     CINH02550
C WBT I HA - INSIDE WET BULB TEMPERATURE (CALCULATED), DEGREES R
                                                                     C I NHO 2560
C WIDTH-BUILDING WIDTH, FEET
                                                                     CINH02570
C WIMETR- SUM OF MANURE EXCRETED, LBS
                                                                     CINH02580
                                                                     CINH02590
                                                                     CINH02600
                                                                     CINH02610
  CEMMON/BIRDS/WERD, BRDS
                                                                      INH02630
      CCMMON/BLOG/ELTH, WIDTH, HE IT
                                                                      INH02640
                                                                      INH02650
      C CMMON/BUG/IBUG
      CCMMON/CARD/BTIME.HTMC.MX.MN.SDRYTM.EDRYTM
                                                                      TNH02660
      CCMMON/C/EXCDMC.EXWTD.EXWTSM.EVPART.DT
                                                                      INH02670
      CCMMON/PRESS/PATM
                                                                      INH02680
      COMMON/E VP/ORPSAR, WATSAR
                                                                      INH02690
      COMMON/RATE/DRPNUM
                                                                      INH02700
                                                                      INH02710
      CCMMON/DRY/DRYM. ORYW
      COMMON/WR/TD80(48),TDP0(48),TD81(48),TIME(48),MTIME,TDP1(48)
                                                                      INH02720
        COMMGN/KR1/FLOW(48), EVPT(48), EVPSUM(48), PCTMCH(48), PCTMCT(48)INH02730
      CUMMON/WITHE/AVIDBO, RANGE, ATMP, MG, ID, IY, TDPF, VARDIA
                                                                      INH02740
      CDMMDN/31/EVAPDT(48), EVPDTT(48), EVPH2S(48), QLTGTS(48), DPF(48)
      CCMM3N/82/MON( 48), MIDN( 48), IDN( 48), IYN( 48), BTIMN( 48)
                                                                      INH02760
      CCMMON/B3/BTIMEN( 48).H7MCN( 48).PC( 48).TB(48).TP(48).EVPRMV(46) INHO2770
      CCMMON/84/MXN(48), MMXN(48), MNN(48), MMN(48), MR(48), AT(48), AVTD(48) INHO2780
      CEMMON/CRT/RCL, RWL, SPM, EXRATE
      DIMENSION EVPPOT(43), EVPOTT(48), DH(48)
                                                                      TUH02800
      INTEGER RUNLGT
                                                                       INH02810
      REAL MX. MN
                                                                       INH02820
      DIMENSION CADDED(48)
                                                                       INH02830
      DATA QADDED/48*0./
                                                                       INH02840
                                                                     CINH02850
  CINH02870
      IF NNW=0, NN SHOULD=1
                                                                     C1NH02880
```




```
READ 22,111, MBUG, NNW
                                                                       INH02890
   22 FORMAT(312)
                                                                        INH02900
     DU225 M=1,48
                                                                        INH02910
      TOBO(M)=0.
                                                                        INH02920
                                                                        TNH02930
      TOB1(M)=0.
                                                                        INH02940
                                                                        INH02950
      TOPI(M)=0.
                                                                        INH02960
     EVPSUM(M)=0.
                                                                        INH02990
      PETMEH(M)=0.
                                                                        INH03000
                                                                        INH03020
      EVPH2S (M) = 0.
                                                                        INH03040
      QLTOTS(M)=0.
           (M)=0.
                                                                        INH03060
      TP
           (M)=0.
                                                                        INH03070
     DPF
           (M)=0.
                                                                        INH03080
     EVPRMV(M)=0.
                                                                        INH03090
      a.R
           (M)=0.
                                                                        1NH03100
     AT
            (M)=0.
                                                                        INH03110
     AVTD (M)=O.
                                                                        INH03120
     EVPPOT (M)=0.
                                                                        TMH03130
      EVPOTT(M)=0.
                                                                        INH03140
     DH
            (M)=0.
                                                                        INH03150
     MOH
            (M)=0
                                                                        INH03160
      MIDN (M)=0
                                                                        INH03170
      IDN
            (M)=0
                                                                        INH03180
      IYN
            (M)=0
                                                                        1NH03190
      BTIMN (M)=0.
                                                                        INH03200
      BTIMEN (M)=0.
                                                                        INH03210
      H7MCN (M)=0.
                                                                        INH03220
      PC
            (M)=0.
                                                                        INH03230
      MMNN
          (M)=0
                                                                        INH03240
      MNN
            (M) = 0
                                                                        INH03250
      MMXN (M)=0
                                                                        INH03260
      MXN
           (M)=0
                                                                        INH03270
 225 CONTINUE
                                                                        INH03280
                                                                       CINH03290
 Č
                                                                       CINH03310
      DO 3 N=1,NN
                                                                        INH03320
      READ 25, LTIME, TSET, ABRD
                                                                        1NH03330
   25 FORMAT(12, 2F6.2)
                                                                        INH03340
      EXCD 4C=0.8
                                                                        INH03350
      EXRATE=.272
                                                                        INH03360
      CALL ABLUCK
                                                                        INH03370
      AVT080 = 58.+459.67
                                                                        INH03380
      BRDTMP=107.1+459.67
                                                                        INH03390
     BRDS = 4500.
                                                                        INH03400
      BLTH = 92.25
                                                                        INH03410
      DT=1.0
                                                                        INH03420
     ELPKAR=1.
                                                                        INH03430
      EVPH2S(1)=0.
                                                                         INH03440
      EVPDTT(1)=0.
                                                                        INH03450
      EVPCTT(1)=0.
                                                                        INH03460
      HEIT = 8.25
                                                                        INH03470
      IBUG=1
                                                                        INH03480
                                                                         INH03490
      IBUG=5
      IBUG=0
                                                                        INH03500
                                                                         INH03510
      INDIC = 1
      PATM=14.6
                                                                         INH03520
      QLTCTS(1)=0.
                                                                        INH03530
                                                                        INH03540
      SPM= . 87
      TDB=50.+459.67
                                                                         INH03550
                                                                        INH03560
      TDP=40.+459.67
      IF(TSET.E0.0..GR.TSET.GT.520.) TSET=56.+459.67
                                                                        INH03570
      TIMETSET
                                                                        INH03580
      TI=TSET
                                                                        INH03590
      TIDP=TSET-1.
                                                                        INH03600
```



```
VPMAX=(54.4338+0.2569*1270.)*49.5+229.467+1.059*1270.
                                                                 111403610
     VRMIN= (54.4838+0.2569# 180.)#49.5+229.467+1.059# 180.
                                                                  INH03620
C -IN CALIBRATING THE 4 FANS IT WAS FOUND 3 FANS PRODUCED APPROXIMATLY CINHO3630
     THE SAME FLOW AS 4. THIS IS ATTRIBUTED TO TURBULANCE.
                                                                 C1NH03640
     DNEFAN= (VRMAX-VRMIN)/3.
                                                                  INH03650
     VRMIND=VRMIN+ONEFAN
                                                                  INH03660
     WATLGT = 24. * 72.
                                                                  INH03670
      WIDTH = 38.
                                                                  14403680
     WATWDT=4./12.
                                                                  INH03690
     CALL WETHER (NNW. TMINE)
                                                                  INH03700
     TSL AB= AVTDB0+459.67+5.
                                                                  INH03710
     IF(ID.EQ.7.AND.IY.EQ.75) VRMIN=6613.67
                                                                  INH03720
     IF(ID.EQ.6.AND.IY.EQ.75) VKMIN=6706.75
                                                                  INH03730
     BTIME=0.
                                                                  INH03740
     DF=(1./24.)*DT
                                                                  INH03750
     OMECH =2*19*25*3.413
                                                                  INH03760
     R=LTIME/DT
                                                                  INH03770
     RUNLGT = R
                                                                  INH03780
     U=BTIME/DT+0.5
                                                                  INH03790
     K = II
                                                                  INH03800
     IF(U.LT.1.) K=1
                                                                  INH03810
     TIME(1)=BTIME+DT
                                                                  1 NH03820
     WATTSU=(QMECH/(BLTH+HIDTH))/3.413
                                                                  INH03830
     MID=ID
                                                                  INH03840
     BTIM=BTIME
                                                                  INH03850
     MON (N) = MO
                                                                  INHORRAGO
     MICHINI = MID
                                                                  INH03870
     100(00)=10
                                                                  INH03880
     I \times I \setminus \{11\} = I \times I
                                                                  INH03890
     BTIMN(N)=BTIM
                                                                  INH03900
     BILMEN(N)=-1.
                                                                  INH03910
     H7MCN (N)=H7MC
                                                                  INH03920
     MXN(N)=MX
                                                                  INH03930
     MMXN(N)=MX
                                                                  INH03940
     MINICIO = MN
                                                                  INH02950
     MMNG(N)=MN
                                                                  INH03960
     RP(N)=BPDS
                                                                  INH03970
     AT(N)=ATMP
                                                                  INH03980
     AVTD(N)=AVTDBC
                                                                  INHORGO
     OPF (N)=TOPF
                                                                  INH04000
     FXWTSM=0.
                                                                  INH04010
     EVPTTL=0.
                                                                  INH04020
      EVPH2T=0.
                                                                  INH04030
     EVPMRT=0.
                                                                  INH04040
     EVAPSM=0.
                                                                  INHOGOSO
     TMIN=CRITMP(ISEL, TOPE
                           +459.67, VRMIN, WATTSQ. 0.0)
                                                                  INH04060
                                                                  INH04070
     TGES=TSET
                                                                 CINH04030
 CINH04100
     CALL FOSTRT (BLTH, KIDTH, FEIT, RWL, RCL, QMECH, WATLGT, VATWOT, WBRD, BRDS, INHO4110
    WBRDTMP-459.67, EXCOMC, DF, SPM, EXPATE,
                                                      TMIN-459.67, INHO4120
    SDT. BTIME.R. INDIC. ELPWAR. TSET-459. 67. VRMAX. VKM IN. TSLAB-459.67)
                                                                  INH04130
                                                                 CINH04140
Ċ
 C1NH04160
     DB 4 J=1.RUNLGT
                                                                  INH04170
     TC8=TD8C(J-1+K)+459.67
                                                                  INHO4180
     TDP=TOPC(J-1+K)+459.67
                                                                  INH04190
     T6(J)=T08-459.67
                                                                  INH04200
     TP(J)=TDP-459.67
                                                                  INH04210
      C IB:IG
                                                               IBUC INH04220
     IF(IBUG.EQ.0) GO TO 999
                                                                  INH04230
     PRINT 990, K, IDB, TDP, TIME (MIIME), MTIME
                                                                  TNHO4240
  990 FORMAT(1X,5(10HDKYINHS )/16X,'K',14X,'TDB', 14X,'TDP',14X,'TIME'INH04250
                                                                MT I NH04260
    A,14X,
    11ME '/8x, 13, 10x, 3E14.4, 19)
                                                                  INH04270
  999 CONTINUE
                                                                  INH04280
      IBUC INH04 290
     IF (MBUG.EQ.0) GD TO 900
                                                                  INH04300
                                                                 CINH04310
```



```
CINH04330
     I=J-1
                                                           INH04340
     DO 9 L=1.3
                                                           INH04350
   IF(I.EQ.O) I=1
     PRINT 2.
             TB(1), TP(1),FLGW(1),TDB1(1),TDP1(1),EVPT(1),EVPSUM(1) 1NH04380
    1.PCTMCH(I).PCTMCT(I).TIME(I)
                                                           INH04390
     PRINT 4122, TIME(1), EVAPOT(1), EVPPOT(1), EVPPAS(1), OLICIS(1), EVPSUM(1NH04400
    al), EVPOTT(1), EVPOTT(1), QADDED(1)
                                                           INH04410
  888 FORMAT (1X,20(15),30(1HD))
                                                           INH24420
 900 CONTINUE
C *******DETERMINE THE AMOUNT OF EXCRETA AND THE DRYING SURFACE AREA**CINHO4450
     CALL EXCRAT (BRDS, DF, EXWT SM, EXWTD)
                                                           INH04470
                                                           INH04480
     CALL DRYSRF (EXSMHS, WATLGT, WATWOT, DRPSAR, WATS AR, DRYSUF)
                                                          CINH04500
C *********DETERMINE IF LIGHTS ARE ON OR OFF AND SET INDEX. FLPWR.
                                                          CINH04510
     IF(TIME(J).LT.7..OR.TIME(J).GE.21.) GO TO 310
                                                           INH04530
     FIPWAR =1 -
                                                           INH04540
     GO TO 311
                                                           INH04550
  310 CONTINUE
                                                           INH04560
     ELPWAR = 0.
                                                           INH04570
  311 CONTINUE.
                                                           INH04580
                                                          CINH04590
C
                                                          CINH04610
     IE(TOB.GE. ISET) GO TO 10
                                                           INH04620
                                                          CINH04630
ć
 *******CHECK TO SEE IF GUTSIDE COLDER THAN POSSIBLE TO MAINTAIN TSET CINHO4640
                                                          CINH04650
     IFITDB.LT.THINIGO TO 20
                                                          C 1NH04670
r
                                                          C I NHO4 700
     VRGESS=0.5+(VRMAX +VRMIN)
                                                           14404710
     CALL VENRAT (WATTSQ, ELPWAR, TDB, TSET, TDP, TIDP, AVTDBO,
                                                           INH04720
    1TSLAB, VPGESS, INDIC, 1, QCBNST, VENTET, VRMAX )
                                                           INH04730
     IF(TIME(J).GT.SDRYIM.AND.TIME(J).LT.EDRYTM.AND.VENTRT.LT.VRMIND) VINHO4740
    LENTRY=VRMIND
                                                           INH04750
     IF(VENTRI.EQ.VRMIND) GO TO 30
                                                           INH04750
     IFIVENTRY.GT.VRMAX) GO TO 10
                                                           INH04770
     IF(VENTRT.LT.VRMIN) GO TO 20
                                                           INH04780
     TI=TSET
                                                           INH04790
     GO TO 11
                                                           INHOLDO
C
                                                          CINH04810
č
 C 1 NHO 4830
  10 VENTRT=VRMAX
                                                           INH04840
     TGE S= . 5 + ( TOB+TSET)
                                                           INH04850
     GO TO 30
                                                           INH04860
                                                          CINH04870
 C1NH04890
  20 VENTOT-VOMIN
                                                           INH04900
     IF(TIME(J).GT.SDRYTM.AND.TIME(J).LT.EDRYTM) VENTRT=VRMIND
                                                           INH04910
     TGES=(TMIN+TSET)*.5
                                                           10000000
     GO TO 30
                                                           INH04930
  30 CONTINUE
                                                           INH04940
                                                          CINH04950
  CINH04970
     CALL TEMPIN (TGES, VENTRT, WATTSQ, ELPWAR, TSLAB, INDIC, TDB, TDP, TEMPI, INHO4980
    atings
                                                           INHOLOGO
     TI=TEMPI
                                                           13H05000
     IF(VENTRI.LE.VRMIN.AND.TI.GI.TSET) TI=TSET
                                                           INH05010
  11 CONTINUE
                                                           INH05020
     HA=HACP(TDP)
                                                           INH05030
     CALL BROHT (TI, ELPWAR, QS, QLTGT)
                                                           INH05040
```



```
CALL TWBIN(TI .VENTRT, TWBI, QLTOT, HA, TJB)
                                                                     INH05050
     CALL EVPWIR (UNTEVP, VENTRI, TI, TWBI, EVPH20, EVPMUR, 1)
                                                                     TUH05060
 400 CUNTINUE
     HAI=HAIN(QLTGT,TI,VENTRT,UNTEVP,HA)
                                                                      INH05080
C AS AN ASIDE CALCULATE HEAT ADDED TO PUULTRY HOUSE
                                                                    CINHO5081
     CALL EVPWTR (UNTEVP, VENTRT, TI, WBDBHA(TI, HAI), EVPH2C, EVPMUR, 1)
                                                                    INH05090
     CALL ELHEAT(WATTSQ.ELPWAR.ELHT)
     CALL CEILHT (TI, TDB, QCTOT)
                                                                     INH05110
     CALL WALLHT(TI,TDB,QWTOT)
                                                                     INH05120
     CALL FLORHT (TI, TSLAB, INDIC, QFTGT)
                                                                     INH05130
     CAD=OS
              +QLTDT+ELHT+QCTOT+QVTOT+OFTOT
                                                                     INH05140
     IF(J.EQ.1) GO TO 503
                                                                     INH05150
     QADDED(J)=QADDED(J-1)+QAD*DT
                                                                      INH05160
     GC TO 504
                                                                     INHO 5170
 503 CONTINUE
                                                                      INH05180
     QADDED(J)=QAD
                                                                     INH05190
  504 CONTINUE
                                                                     INH05200
 405 CONTINUE
                                                                     INH05210
                                                                     C.T.NH05220
 CINH05240
     TDP1(J)=DPHA(HAI) -459.67
                                                                      INH05250
     HADPI = HADP(TDPI(J)+459.67)
                                                                      INH05260
C HADPI IS THEORETICALLY EQUAL TO HAI BUT IS USED IN LIEU OF HAI TU
                                                                    CINH05261
C MINIMIZE ROUNDING ERRORS IN THE PSYCHEOMETRIC PACKAGE CREATED WHEN
                                                                     CINH05262
C COMPARING VERIFICATION DATA. THE VERIFICATION DATA FOUND THE
                                                                     C TNH05253
C HUMIDITY RATIO COMPARABLE TO HAI DIRECTLY FROM A DEMPOINT TEMPERA-
                                                                     CINH05264
C TURE COMPARABLE TO TOPI.
                                                                    C1NH05265
     HADPO=HADP(TDPO(J-1+K)+459.67)
                                                                      INH05270
     OGCAH-IGGAH=(L)HC
                                                                      INH05280
     WRITE(9,123) IY, MO, ID, TIME(J), HADPI, HADPO
                                                                      INH05290
 123 FJRMAT (313,3X,F5.2,10X,2F10.6)
                                                                      INH05300
     TIDP=TDPI(J)+459.67
                                                                      INH05310
     FLCW(J)=VENTRT
                                                                      INH05320
     TOBI(J)=T1-459.67
                                                                      INH05330
     (9MTCRB) BOUHNTOTION REPORTED
                                                                      INH 05340
     EVAPOT(J)=DH(J)*VENTRT*DT*60./VSDBHA(TI.HAI)
                                                                      INH05350
     JJ=J-1
                                                                      LNH05360
     IF(J.EQ.1)JJ=1
                                                                      INH05370
     (L)TCGAV3+(LL)TTCGV3=(L)TTCGV3
                                                                      INH05380
     F VPMR T= E VPMR T + EVPMIR * OT
                                                                      10405390
     EVPH2T=EVPH2T+EVPH2C#DT
                                                                      TNH05400
     EVPTTI = EVPMRT + EVPH2T
                                                                      INH05410
     OF THE STATE (1.1.) + RSPWTR * OT
                                                                      INH05420
     EVPH2S(J)=EVPH2S(JJ)+EVPH20*DT
                                                                      INH05430
     EVPT(J)=EVPMUR
                                                                      INH05440
     EVAPSM=EVAPSM+EVPTTL
                                                                      INH05450
     EVP SUM (J) = EVPMRT
                                                                      1NH05460
     VELMAS=VENTRI/VSOBHA(TI+HAI)
                                                                      INH05470
     TC# .00 CAM LAVEL MAS * 60. *DT
                                                                      INH05480
     EVPOTT(J)=EVPOTT(JJ)+EVPPOT(J)
                                                                      INH05490
     PCTMCH(J) = AMC(EVPMUR, EXCDMC, EXWTD ) *100.
                                                                      INH05500
     PCTMCT(J)=AMC(EVPMRT.EXCDMC.EXWTSM) #100.
                                                                      INH05510
IF(18UG.E0.0) GU TO 9999
                                                                      INH05530
     DRYRTM=DRYM
                                                                      INH05540
     DRYLIWEDRYN
                                                                      INH05550
     PRINT 990,K,TDB,TDP,TIME(MTIME),MTIME
                                                                      TNH05560
     PRINT 9001
                                                                      INH05570
 9001 FORMAT(9X'DEPSAR', T25, 'DRYRIM', T39, 'DRYSUF', T53, 'HAI ', T67, 'EVPH2INH05580
    AD',14X'EVPH2T',T95,'EVPMUR',T109,'EVPMRT',T123,'EVPTTL',/10X'TEMPIINH05590
    6',T26, 'TGES', T40, 'T1',T54, 'T1N',T68, 'VENTRT', T82, 'VEGESS',196, WINH05600
     2ATSAR', T110, 'QCONST', T123, 'TWBI')
                                                                      INHOS6 10
     PRINT 9000.DRPSAR, DRYRTM,
                                 DRYSUF, HAI, EVPH2G, EVPH2T, EVPHU
                                                                      INH05620
    1R .EVPMRT, EVPTTL, TEMPI, TGES, TI, TIN, VENTRT, VRGESS, WATSAR, QCUNST
                                                                      INH05630
                                                                      INH05640
    D. TWDI
 9000 FORMAT (2X,9E14,3,/,2X,9E14,3)
                                                                      INH05650
     PRINT 9002 DRYRTW
                                                                      INHOSAAO
 9002 FORMAT (6 X. 'DRYRTW= '.E14.3)
                                                                      INH05670
     IF(|BUG.EQ.5) | IBUG=0
                                                                      INH05680
 9999 CONTINUE
                                                                      INH05630
```




```
MTIME=MTIME+1
                                                                       INH05710
   6 CONTINUE
      TIME (J+1)=TIME (J)+DT
                                                                       INH05730
                                                                      CINH05740
C ******GENERATE WEATHER FOR A NEW DAY IF LOOP PASSES
                                                                   ***CINH05750
                                                                     CINH05760
      IF(TIME(J+1).LE.24.) GD TD 4
                                                                       INH05770
      TIME (J+1)=TIME (J+1)-24.
      K=1-J
                                                                       INH05790
      CALL WETHER (NNW, TMINF)
                                                                       INH05800
      IDN(N) = ID
                                                                       INH05810
      BTIMEN(N)=BTIME
                                                                       INH05620
      H7MCN(N)=H7MC
                                                                       INH05830
      MNN(N)=MN
                                                                       INH05840
      MYNINIEMY
                                                                       INH05850
      BR(N)=BRDS
                                                                       1NH05860
      AT (N) = ATMP
                                                                       TNH05870
      AVTD(N)=AVTDBC
                                                                       10405880
      DPF(N)=TDPF
                                                                       1NH05890
      THIN=CRITMPITSET, TDPF
                             +459.67.VRMIN.WATTS0.0.01
                                                                       INH25920
    4 CONTINUE
                                                                       INH05910
    5 COUTINUE
                                                                       INH05920
                                                                      CINH05930
CINH05950
   13 FORMAT (1H1)
                                                                       INH05960
      CALL HEDING
                                                                       10405970
      DO 1 I=1, RUNLGT
                                                                       INHOSGRO
      PRINT 2, TB(I), TP(I), FLOW(I), TD31(I), TDP1(I), EVPT(I), EVPSUM(I) INH05990
     1.PCTMCH(I),PCTMCT(I),TIME(I)
                                                                       1NH26000
    2 FORMAT (1X,E9.3,4E14.3,T67,4E14.5,5X,F5.2)
      WRITE(10,121) IY, MG, ID, TIME(I), EVPDTT(I), EVPSUM(I)
                                                                       INH06020
  121 FORMAT (313,3X,F5.2,F8.2,25X,F8.2)
                                                                       1 NHO6030
      WRITE(8,212) IY, MO, ID, TIME(I), TB(I), TP(I), TDBI(I), TDPI(I), DH(I), FLOINHO6040
     SWIII
                                                                       111406050
  212 FORMAT (313.F5.2.10X.4F6.1.F10.6.F9.0)
                                                                       111106060
    1 COUTINIE
                                                                       INH06070
      PRINT 14.AVTDBC.RANGE.ATMP.MC.ID.IY.TDPF.BRDS
                                                                       INH06080
   14 FURMAT (//1x, ' 4 MINUS SIGN IN COLUMN 8 INDICATES THERE WAS MORE DRYINHOGODO
     SING DURING THAT TIME INCREMENT THAN MANURE MOISTURE PRODUCED 1/
     I' DURING THAT TIME PERIOD.
                                                                       10006110
             //1x, " WEATHER DATA FOR THE DAY: AVERAGE TEMPERATURE", F6.1, INHO6120
     11x, DEGREES F, TEMPERATURE RANGE , FE. 1, 1x, DEGREES F, ATMOSPHERIC INHO6130
     2PRESSURE', F6-1,1X,1X, 'PSI'/1X,12,'/',12,'/',12,18X, 'DEMPGINT TEMPEINHO6140
     3RATURE', F6.1, DEGREES', F', 5X, NUMBER OF EIRDS: ', F6.0)
                                                                       INHOA150
IF(MBUG.EQ.0) GG TC 5000
                                                                       INH06170
      PRINT 13
                                                                       INH06180
      MM= (48/2)/DT
                                                                       LNH06190
      PRINT 4110
                                                                       INH06200
 4110 FORMAT(1X, 'PARTITIONING OF EVAPORATED MOISTURE AND A COMPARISON OF INHO6210
     @ POTENTIAL EVAPORATION OF VENTILATING ALE. 1//)
                                                                       INH06220
      PRINT 4120
                                                                       INH06230
 4120 FORMATITES, 'E V A P O R A T I O N T G T A L', TT, 'EVAPURATION',
                                                                       INH06240
     $T36,16(1H*),T88,14(1H*),T104, 'HEAT ACDED',
     2T22, POTENTIAL ',/T9, DURING',T21, EVAPORATION', T38, FROM',T52, FROINHO6260
     #M',T66, FROM',T80, FROM',T91, VENTILATION'/T11, DI',T22, DURING DIINHO6270
     5',T36,'WATERERS',T49,'RESPERATION',T65,'MANURE',T77,'ALL SOURCES'INHO6280
     *, T92, 'POTENTIAL', T2, 'TIME', T135, ' TO AIR')
      DO 3125 M=1.MM
                                                                       INH06300
      PRINT 4122, TIME(M), EVAPDT(M), EVPPOT (M), EVPH2S (M), OLTOTS (M), EVPSUM(INHO6310
     (M) GEOCAD, (M) TIDANS, (M) TIDANS, (MS
                                                                       INH26320
 4122 FORMAT(1x,F4.1,E12.5,E13.5,1x,6E14.5)
                                                                       15406330
 3125 CONTINUE
                                                                       TNH06340
      PRINT 4130, VARDTA
                                                                       INHO6350
 4130 FORMAT (/T55, HOUSE 7 EVAPORATION ', T70, E12, 5)
                                                                       INHO6360
      PRINT 14, AVTDBC, KANGE, ATMP, MC, ID, IY, TDPF, BRDS
                                                                       INH06370
1BUC 1 VHO6 380
 5000 CEUTINUE
                                                                       INH06390
      EVPRMV (II) = EVPS UM (RUNI GT.)
                                                                       INH06400
      PC(N) = PCTMCT (RUNLGT)
                                                                       INH06410
    3 CONTINUE
                                                                       INH06420
```



INH06430

CALL HEAD

```
DO 2120 M=1.NA
     PRINT 2121. MON (N). MIDN(M). IDN(M). IVN(M). STIMN(M). RTIMEN(M). HTMCN(MINHO6450
 2121 FORMAT(1X, 12, '/', 12, '-', 12, '/', 12, 2F6, 0, T67, F6, 2, T77, F6, 2,
                                                                   INH06480
     PRINT 2119.MMXN(M).MXN(M).MMNN(M).MNN(M).BE(M).AT(M).AVID(M).
                                                                   INH06490
    SUBE (W)
 2119 FORMAT (1H+.T41.12.1-1.12.148.12.1-1.12.T27.F6.0.T34.F6.2.T54.F4.0.INH06510
                                                                   INH06520
     WRITE(11,2132) IYN(M), MON(M), MIDN(M), IDN(M), EVPRMV(M), PC(M),
    DAVID(M), OPF(M)
                                                                   INH06540
 2132 FCRMAT(412,4E12.5)
                                                                   INH06550
 2120 CONTINUE
                                                                   1NH06560
                                                                   INH06570
     END FILE 8
                                                                   TNH06580
     END FILE 9
     END FILE 10
                                                                   10806600
     END FILE 11
     STOP 9999
                                                                   INH06620
                                                                   INH06630
     SUBROUTINE ABLOCK
                                                                   INH06640
 C 1 NHO 6660
                                                                  CINHOAA70
 THIS SUBROUTINE SETS ARRAY VALUES EQUAL TO ZERO OR A TAG VALUE
                                                                  CINH06680
                                                                  C 1NH06690
                                                                  CINH06700
 C I NHO 67 20
Ċ
                                                                  CINH06730
c
                                                                  C1NH06740
               DEFINITION
                                     O F
                                         TERMS
                                                                  C INHO6750
                                                                  CINH06760
                                                                  CINH06770
C
               SEE MAIN PROGRAM FOR ACRONYMS NOT
C
                          LISTED HERE
                                                                  CINH06780
                                                                  C INH06790
c
                                                                  CINH06800
                                                                  CINH06810
  CCMMDN/w8/IDB0(48),IDP0(48),IDB1(48),IIME(48),MIIME,IDP1(48)
                                                                  INH06830
       CCMMCN/WR1/FLOW(48), EVPT(48), EVPSUN(48), PCTMCH(48), PCTMCT(48)INHO6840
     COMMON/81/EVAPOT(48).EVPDTT(48).EVPH2S(48).QLTGTS(48).DPF(48)
                                                                  INH06850
     CCMMON/82/MON( 48), MIDN( 48), IDN( 48), IYN( 48), BTIMN( 48)
                                                                   TUH06860
     CCMMON/B3/aTIMEN( 48).H7MCN( 48).PC( 48).TB(48).TP(48).EVPRNV(48) INHO6870
     COMMON/84/MXN(48), MMXN(48), MNN(48), MMNN(48), BR(48), AT(48), AVTD(48) INHO6880
     DO 24 M=1.48
                                                                   INH06890
     T080(M)=0.
                                                                   TNH06900
     TOPO(M)=0.
                                                                   10406910
     TD81(M)=0.
                                                                   INH06920
     TIME(M)=0.
                                                                   INH06930
     TOPI(M)=0.
                                                                   INH06940
     FLOW(M)=0.
                                                                   INH06950
     EVPT (M) = 0.
                                                                   INH06960
     EVPSUM (M) =0.
                                                                   INH06970
     PCTMCH(M)=0.
                                                                   INH06980
     PCIMCT(M)=0.
                                                                   INHOAGOO
     EVAPOT (M)=0.
                                                                   INH07000
     EVPDIT(M)=0.
                                                                   INH07310
     E VPH25 (M)=0.
                                                                   INH07020
     QLICIS(M)=0.
                                                                   INH07030
     TR
           (M)=0.
                                                                   INH07040
     TP
           (M)=0.
                                                                   INH07050
  24 CONTINUE
                                                                   INH07060
     MITTHE = 1
                                                                   INH07070
     RETURN
                                                                   INH07030
     FND
                                                                   INH07090
```



	FUNCTION ANGLISCOMY OF THE STATE	INH0710
c	FUNCTION AMC(M20RMV,ORIGMC,ORIGMT)	
č		INH0712
č		INH0713
č		INH0714
č		INH0715
Ē		INH0716
c		INH0717
c		INH0718
ċ	**************	INH0719
C		INH0720
С		INH0721
0		INH0722
C		INH0723
0		INH0724
		INH0725
;		INH0726
	*****************	
;		INH0728
		INH0729
		INH0730
		INH0731
	IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM	INH0732
		INH0733
		INH0734
		INH0736
		INH0737
		INH0738
		INH0739
-	***************************************	
•	C CMMON/BUG/MBUG	INH0741
	DRYWT=(1ORIGMC) *DRIGWT	INH0742
	WATRWT=ORIGMC*ORIGWT	INH0743
	WATORD= NATRWT-H2ORMV	INH0744
	WTCOMB=WATDRD+DRYWT	INH0745
	AMC=WATDRD/WTCEMB	INH0746
	IF(DRYWT.GT.OAND.WATDRD.GTO.AND.AMC.GT.O.) GD TO 2	INH0747
	PRINT 3,DRYWT, WATDRO, AMC	INH0748
	3 FORMAT (/1x,130(1Hw)/1x'NEGATIVE VALUE FOR DRY WEIGHT, FINAL	INH0749
	IWATER WEIGHT OR KESULTING MOISTURE CUNTENT. THESE VALUES ARE	INH0750
	2RESPECTIVELY */1X3G21.8/1X*IF WATER IS ADDED H2DREMV SHOULD BE NE	
	3ATIVE*)	INH0752
	IF(MBUG.EQ.0) MBUG=2	INH0753
	PRINT 5	INH0754
	2 CONTINUE	INH0755
	IF(MBUG.EQ.0) GO TO 88	1NH0756
	PRINT 5	INH0757
	5 FGRM4T(/1X,10(1HK), 'AMC',10(1HW))	INHO758
	PRINT 55	INH0759
	55 FORMAT(1HO,10(10HAMC ))	INH0760
	PRINT 1, DRYWT, MATRWT, WATDRD, WTCHMA, AMC, HZCHAV, DRIGHT, GRIGHT CARDINAT (8X, "DRYWT", PX, "MATRWT", 8X, "WATDRD", 7X, "WTCHMS", 8X, "AMC",	
	211x, "H2URMV", 8x, "URIGWT", 8x, "DRIGMC", /1x8E14.3)	INH0762
	38 CONTINUE	INH0764
	IF(MBUG.EQ.2) MBUG=0	INH3765
	RETURN	INH0766
	END	INH0767
		11110101
	SUBROUTINE BROHT (T,DALYT,QS,QL)	1NH0763
	***************************************	
		INH0770
		CINH0771
		C1NH0772
	HEAT OUTPUT FROM CHICKENS FOR VARIOUS TEMPERATURES	CINH0773
ì	AND DAY OR NIGHT ACTIVITY BY TABLE LUCK-UP.	CINH0774
		CINH0775
١		CINH0776
	****************	INHO777
200		61NH0778



```
DEFINITION OF TERMS
                                                                C INH07800
                                                                CINH07810
                                                               CINH07820
              SEE MAIN PROGRAM FOR ACRONYMS NOT
                   LISTED HERE
C ARGL-AN ARRAY OF TEMPERATURES CORRESPONDING TO THE ARRAYS *VLDAY*
                                                               C 10H07870
    AND VLNITE*, DEGREES F
C ARGS-AN ARRAY OF TEMPERATURES CORRESPONDING TO THE ARRAYS #VSDAY# ANDCINHO7890
     *VSNITE*, DEGREES F
                                                               CINH07900
C BRDS-NO. OF BIRDS IN BUILDING
C DALYT-AN INDEX FOR EAY=1, FOR NITE=0
                                                                CINH07920
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
 QL-LATENT HEAT PRODUCTION OF BIRDS, BTU PER HOUR
                                                                CINH07940
C QS-SENSIBLE HEAT PRODUCTION OF BIRDS, BTU PER HOUR
                                                                CINH07950
 T-INSIDE TEMPERATURE, DEGREES R AND F
                                                                C1NH07960
C TABLE-A TABLE LOUKUP FUNCTION SUBROUTINE
                                                                CINH07970
54321 CONTINUE
C VLDAY-AN ARRAY OF DAYTIME LATENT HEAT PRODUCTION VALUES, BTU PER
                                                                CINH07990
     HOUR-BIRD
                                                                CIMPROPOR
 VLNITE-AN ARRAY OF NITETIME LATENT HEAT PRODUCTION VALUES. BTU PER
                                                                CINHOSOLO
    HOUR-BIRD
                                                                CINH08020
 VSDAY-AN ARRAY OF DAY TIME SENSIBLE HEAT PRODUCTION VALUES, BTU PER CINHOBO30
       HOUR-BIRD
                                                                CINHORO40
C VSNITE-AN ARRAY OF NITE TIME SENSIBLE HEAT PRODUCTION VALUES. BTU
                                                                C 11H08050
   PER HOUR-BIRD
                                                                CINHOROSO
C
C WBRD-AVERAGE BIRD WEIGHT. LBS.
                                                                CINH08070
C WT-AVERAGE BIRD WEIGHT, LBS
                                                                CINHO8030
                                                                CINH08090
                                                                CINH08100
DIMENSION ARGS(7), ARGL(8), VSDAY(7), VSNITE(7),
    1 VLDAY(8), VLNITE(8)
                                                                 1MH08130
     EQUIVALENCE (WI.WBRD)
                                                                 INH08140
     C CMMON/BUG/IBUG
                                                                 INHOS150
     COMMON/BIRDS/WERD, BRDS
                                                                 INH08160
     DATA ARGS
                 /26.,34.,47.,56.,64.,84.,94./
                                                                 INHO8170
                      /26.,34.,47.,56.,64.,74.,84.,94./
     DATA ARGL
                                                                INH08150
                      /11.1,8.3,7.3,6.6,6.5,6.3,.2/
/6.9,6.8,6.1,5.3,5.1,3.6,.6/
     DATA VSDAY
                                                                 INH08190
     DATA VSNITE
                                                                 INHO8200
     DATA VLDAY
                        /1.7,2.1,2.3,3.2,3.3,3.4,4.2,5.3/
                                                                INH08210
     DATA VLNITE
                       /1.6.2.0.1.9.2.6.2.2.2.0.3.5.4.7/
                                                                 INH08220
     T=T-459.67
                                                                 INH08230
     IF (DALYT .EQ. O.) GG TG 2
                                                                 INH08240
C DAYTIME HEAT PRODUCTION CALCULATIONS
                                                                C INHO8250
   1 QS=WT*BRDS*TABLI(VSDAY,ARGS,T,7)
                                                                 INH08260
     QL=WT*BRDS*TABLI(VLDAY, ARGL, T, 8)
                                                                 INH08270
     T=T+455.67
                                                                 INH08230
  33 CONTINUE
                                                                 INH08290
     IF(IBUG.E0.0) GD TO 9999
                                                                 LNH08300
     PRINT 6
                                                                 INHOR310
   6 FORMAT (/1x,10(1HV), 'BROHT',10(1HW))
                                                                 INH08320
                                                                 - INHO8330
     PRINT 9080
 9080 FORMAT (1x. 'BROHT' . /9x. 'T' . T25. 'DALYT' . T39. 'QS' . T53. 'CL')
                                                                 INHO8340
     PRINT 9081, T. DALYT, QS, QL
                                                                 INH08350
 9081 FORMAT(2X4E14.2)
                                                                 INH08360
 9999 CONTINUE
                                                                 INH08370
     RETURN
                                                                 CEE30HAI
C NIGHT TIME HEAT PRODUCTION CALCULATIONS
                                                                C 1NH08390
   2 QS=VT*BRDS*TABLI(VSNITE, ARGS, T, 7)
                                                                 INH08400
     GL=WT *BRDS *TABLI(VLNITE, ARGL, T.8)
                                                                 INH08410
     T=T+459.67
                                                                 INH08420
     GO TO 33
                                                                 INH08430
     END
                                                                 INH08440
     SUBROUTINE CEILHT(TIN, TDB, Q)
 CINH08470
                                                                CINH08480
C THIS SUBROUTINE DETERMINES THE BUILDING HEAT LOSS
                                                                C1NH08490
```



```
C THROUGH THE CEILING
                                                      CINH08520
DEFINITION OF TERMS
                                                      C INHO8560
                                                      C1NH08570
            SEE MAIN PROGRAM FOR ACRENYMS NOT
                     LISTED HERE
                                                      CINHOSSON
C ACL -- DEFINED IN CRITMP
                                                      CINH08630
 BLTH-BUILDING LENGTH, FEET
                                                      CINH08640
C HEIT-BUILDING HEIGHT. FEET
                                                      CINH08650
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
C Q--HEAT TRANSFER THROUGH CEILING, BTU PER HOUR
                                                      CINH08670
C RCL--DEFINED IN CRITMP
                                                      C1NH08680
C TOB--DEFINED IN MAIN
                                                      CINH08690
C TIN--DEFINED IN MAIN
                                                      CINH08700
C WIDTH-BUILDING WIDTH, FEET
                                                      CINH08710
                                                      C.1NH08720
c
                                                      CINH06730
                                                      CINH08740
COMMON/BUG/IBUG
                                                       INH08760
    CEMMON/BLDG/BLTH.WIDTH.HEIT
                                                        INHO8770
    ACL=SLTH*HIDTH
                                                        INHO8780
    RCL=23.68
                                                        INH08790
    Q=(TDB-TIN) +ACL/RCL
                                                        INHORBOO
    IF(TIN.LT.519.67) Q=0.
                                                        INH08810
C *** DURING WINTER CEILING HEAT LCSS GOES TO ATTIC & IS RETURNED IN THCINHO8820
    VENTILATING AIR OF MSU HOUSE #7. INSUMMER(TIN>519.67) AIR COMES CINHORB30
     DIRECTLY FROM THE OUTSIDE.
                                                       C1NH08840
    IF(IBUG.EQ.0) GO TO 9999
                                                        TNH08850
    PRINT 7
                                                        INHOSBAO
   7 FORMAT(/1x,10(1HW), 'CEILHT',10(1HW))
    PRINT 9292
                                                        INHORRRO
9090 FORMAT(1X, 'CEILHT'/9X, 'TIN', T25, 'TDB', T39, 'Q', T53, 'ACL', T67, 'RCL', INHO8690
    1T81, BLTH', T95, WIDTH')
                                                       INH08900
    PRINT 9091, TIN, TDB, Q, ACL, RCL, BLTH, WIDTH
                                                        INH08910
9091 FORMAT (2X,8E14.3)
                                                        INH08920
9999 CONTINUE
                                                        1NH08930
    RETURN
                                                       INH08940
    END
                                                        INH08950
                                                       INH08960
    FUNCTION CPA(TDB)
                                                        INH08970
C1NH08990
                                                       CINH09000
C THIS SUBROUTINE FINDS THE APPROPRIATE VALUE FOR THE THERMAL CAPACITY CINHO9010
      OF AIR
                                                      CINH09020
                                                       CIMBOROAD
 CINH09060
                                                      C1NH09070
          DEFINITION OF TERMS
                                                      CINH09080
                                                      CINH09090
             SEE MAIN PROGRAM FOR ACRONYAS NOT
                     LISTED HERE
                                                      CINH09110
                                                      CINH09120
C HTCPA-ARRAY VALUES OF THERMAL CAPACITIES, BTU/LB-F
                                                      CINHOSISO
                                                      CINHOGIAO
C TOB-INPUT DRY BULB TEMPERATURE, DEGREES R
                                                      CINHOS170
C TEMP-ARRAY VALUES OF TEMPERATURE, DEGREES R
                                                      CINH09130
C TF-TEMPERATURE, DEGREES F
                                                      C1NH09190
```



```
****CINH09220
     CCMMON/BUG/18UG
     DIMENSION TF(15)
                                                                111109240
C DATA FOR ROUTINE CPA TAKEN FROM KENTS ME HB 12TH ED P.3-58
 THE INPUT TEMPERATURE IS IN DEGREES RANKINE. FUNCTION *TABLI* IS
     REQUIRED.
                                                                INH09270
     DIMENSION TEMP(15) HTCPA(15)
                                                                INH09280
     DATA TEMP /659.67,759.67,859.67,959.67,1059.67,1159.67,1259.67,1351NH09290
    19.67,1459.67,1959.67,2459.67,2959.67,3459.67,3959.67,4459.67/
                                                                INH09300
     DATA HTCPA /.241,.243,.245,.248,.252,.256,.259,.262,.265,.275,.
                                                              253 INH09310
    1 . . 289 . . 295 . . 300 . . 304/
     00 33 I=1,15
  33 TF(1)=TEMP(1)-459.67
                                                                INH09350
     IF(TDP.GT.671.69) GO TO 1
     CPA= . 2405
                                                                INH09370
     IF(MBUG.NE.1) GO TO 8
                                                                INH09380
     PRINT 55
                                                                INH09390
     PRINT 333, (TF(J), J=1,10), (HTCPA(K), K=1,10), (TF(J), J=11,15), (HTCPA(INH09400
    1K) -K=11-15)
                                                                INH09410
   8 CONTINUE
                                                                INH09420
     RETURN
                                                                 INH09430
    1 CONTINUE
                                                                INH09440
     CPA=TABLI(HTCPA-TEMP-TDB-15)
                                                                INH09450
     IF(MBUG.EQ.O) GC TO 88
                                                                INHOGAGO
     PRINT 55
                                                                INH09470
  55 FORMAT (1H3.10(10HCPA
                             11
                                                                INH09480
     PRINT 333, (TF(J), J=1,10), (HTCPA(K), K=1,10), (TF(J), J=11,15), (HTCPA(1NH09490
    1K1.K=11.151
                                                                1000500
  333 FORMAT (4x'TF', 10F10, 2/1x, 'HTCPA', 10F10, 3/4x, 'TF', 5F10, 2/1x'HTCPA' INH09510
    1.5F10.3)
                                                                INH09520
     PRINT 200, TDB, CPA
                                                                INH09530
  200 FORMAT (1X, TDB, CPA', 2E23.4)
                                                                INH09540
  88 CONTINUE
                                                                INH09550
     RETURN
                                                                 INH09560
     END
                                                                INH09570
     FUNCTION CPW(TOP)
                                                                INH09580
  CINH09600
                                                               CINH05610
C THIS SUBBOUTINE FINDS THE APPROPRIATE VALUE FOR THE THERMAL CAPACITY CINHOS620
  OF VAPOR. DATA FOR CPW TAKEN FROM WELTY, WICK, AND WILSON P.653. THE CINHO9630
C IMPUT TEMPERATURE IS IN DEGREES RANKIN. FUNCTION *TABLI* IS REQUIRED CINHO9640
                                                               C INH09650
c
                                                               CINH09660
  CINH09680
                                                               CINHOS690
c.
            DEFINITION OF TERMS
                                                               CINH09700
                                                               CINH09710
               SEE MAIN PROGRAM FOR ACRONYMS NOT
                                                               CINH09720
                         LISTED HERE
                                                               CINH09730
                                                               CINH09740
C CPW-THERMAL CAPACITY OF WATER VAPOR, BTU/LE-F --- OR DEGREES R
                                                               CINHOSTTO
C HTCPW-ARRAY VALUES OF THERMAL CAPACITIES. ETU/LB-F
                                                               CINHOSTRO
C TABLI-A TABLE LOCKUP FUNCTION SUBROUTINE
                                                               C1NH09790
C TOP-INPUT DEWPOINT TEMPERATURE, DEGREES R
                                                               CINH09300
C TEMPR-ARRAY VALUES OF TEMPERATURE, DEGREES R
                                                               CINH09810
C TF-TEMPERATURE, CEGREES F
                                                               CINH09820
                                                               CINHOGHRO
                                                               CINH09840
CCMMON/BJG/IBUG
                                                                INH09860
     DIMENSION TECLOI
                                                                 INH09870
     DIMENSION TEMPR(10), HTCPW(10)
                                                                 INH09380
     DATA TEMPR /529.67,671.67,709.67,759.67,859.67,959.67,1059.67,1259INH09890
```



```
DATA HTCPW / .448, .493, .483, .476, .472, .477, .483,
                                                                  INH09910
     MBUG= IBUG
     00 33 I=1.10
  33 TF(1)=TEMPR(1)-459.67
                                                                  INH09540
     IF(TDP.GT.529.67) GC TO 1
                                                                  INH09950
     CPH= 448
                                                                  TNHOOGAD
     IF(MBUG.NE.1) GO TO 8
                                                                  INH09970
     PRINT 9
     PRINT 55
                                                                  INH09990
     PRINT 333, (TF(J), J=1,10), (HTCPW(K), K=1,10)
     PRINT 200. TOP. CPW
                                                                  INH10010
   8 CONTINUE
                                                                  INH10020
   9 FORMAT (/1x.10(1HW). CPW .10(1HW))
                                                                  IIIH10030
     RETURN
                                                                  INH10040
   1 CONTINUE
                                                                  1NH10050
     CPW=TABLI(HTCPW,TEMPR,TDP,10)
                                                                  INH10060
     IF(M3UG.EQ.O) GO TO 88
                                                                  INH10070
     PRINT 55
                                                                  INH10030
  55 FORMAT (1HO. 10(10HCPW
                                                                  INH10090
     PRINT 333, (TF(J), J=1,10), (HTCPW(K), K=1,10)
                                                                  INH10100
  333 FORMAT(4X, 'TF', 10F10, 2/1X, 'HTCPA', 10F10, 3)
                                                                  INH10110
     PRINT 200, TUP, CPW
                                                                  INH10120
  200 FORMAT (1X, 'TDP, CPW,', 2E23.4)
                                                                  INH10130
  88 CONTINUE
                                                                  INH10140
     RETURN
                                                                  INH10150
     EMO
                                                                  INH10160
     FUNCTION CRITMP(TSET, TOP, VRMIN, WATTSQ, ELPWAR)
                                                                  TNH10170
  CINH10190
  THIS SUBROUTINE CALCULATES THE MINIMUM OUTSIDE EQUALIBRIUM TEMPER-
                                                                CINH10210
  TURE TO MAINTAIN THE INSIDE TEMPERATURE AT THE SET VALUE.
                                                                 CINH10220
                                                                 C INH1 02 30
                                                                 CINH10243
  *********************************
                                                               **CINH10250
            DEFINITION OF TERMS
                                                                 C INH10280
Č
                                                                 CINH10290
               SEE MAIN PROGRAM FOR ACRONYMS NOT
                                                                 CINH10310
                                                                 CINH10320
  C INH1 0340
C ACL-CEILING SURFACE AREA. SQUARE FEET
                                                                 CINH10350
                                                                 CINH10360
C AWL-EFFECT WALL SURFACE AREA, SO FT
C BLTH-BUILDING LENGTH, FEET
                                                                 CINH10370
C CRITMP-OUTSIDE TEMPERATURE AT WHICH HOUSE GENERATED HEAT IS IN BALANCCINH10380
     FOR THE GIVEN "SET" INSIDE TEMPERATURE, DEGREES R
                                                                 CINH10390
C ELHT- HEAT EQUIVALENT OF ELECTRIC POWER, STU PNR HR
C ELPWAR-AN INDEX FOR LIGHTS, GN=1, OFF=0
                                                                 CINH10410
C HEIT-BUILDING HEIGHT, FEET
                                                                 CINH10420
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
                                                                 CINH10430
  GLTOT-LATENT HEAT PRODUCTION OF BIRDS, BTU PER HOUR
                                                                 CINH10440
C OSTOT-SEE MAIN
                                                                 CINH10450
C RCL-THERMAL RESISTIVITY OF THE CEILING, SQ FT-DEGREES F-HOUR PER BTU CINHIO460
54321 CONTINUE
                                                                  INH10470
C RWL-THERMAL RESISTIVITY OF THE WALL, SO FT-DEGREES F-HOUR PER BTU
                                                                 CINH10430
C TOP-DUTSIDE DEW POINT TEMPERATURE, DEGREES R
                                                                 CINH10490
C TSET-DESIRED INSIDE TEMPERATURE. DEGREES R
                                                                 CINH10500
C UXAREA-THERMAL AREA-RESISTIVITY RATIO FOR BUILDING, BTU PER HOUR-
                                                                 CINH10510
C VRMIN-MINIMUM VENTILATION RATE OF HOUSE, CFM
                                                                 CINH10520
C VS-MINIMUM MASS VENTILATION RATE, LB PER HOUR
                                                                 CINH1 0530
C WATTSQ-ELECTRICAL POWER APPLIED TO BUILDING, WATTS PER SC. FOOT
                                                                 CINH10540
C WIDTH-BUILDING WIDTH, FEET
                                                                 CINH10550
                                                                 CINH10560
                                                                 C1NH10570
```



```
CCMMON/CRT/RCL . RWL . SPN. EXRATE
                                                                  INH10590
     COMMUN/BLOG/BL TH, WIDTH, HE IT
     COMMON / PRESS / PATM
     CALL FI HEAT (WATTSO, FI PWAR, FI HT)
     CALL BROHT (TSET, ELPWAR, GSTCT, QLTOT)
                                                                   INH10660
     VS=(VRMIN/VSEBHA(TSET+HADP(TOP1))*60-
                                                                   INH10650
     ACL = SLTH #WIDTH
     AWL = HEIT+2. * (BLTH+WIDTH/2.)
                                                                   INH1 06 70
C
  *** SINCE END OF ROOM WITH BIRDS NOT EXPOSED DIRECTLY TO DUTSIDE. CINHIO680
  ***
           ASSUME 1/2 HEAT LUSS. ASSUME LOSS THROUGH FLOOR NEGLIBLE. CINH10690
   *** THIS WOULD BE TRUE FOR SHORT TIME PERIODS AS WILL BE THE CASE GINH10700
  HERE THE HEAT LOSS THRU THE CEILING GDES TO THE ATTIC & 15 RETURNED CINH10710
   TO THE SPACE IN THE VENTILATING AIR, THUS ASSUME HEAT LOSS TO
                                                                  CINH10720
  CEILING IS NEGLIBLE.
                                                                  CINH10730
     ACL=0.
                                                                   TEH1 0740
     RCL=23.68
                                                                   INH10750
     RWL=14.11
                                                                   INH10760
     HYAREAMACI /SCI +AWI /RWI
                                                                   TNU10770
     CRITMP=TSET-(OST()T+FIHT)/(CPA(TSET)+VS+CPb(TSET)+VS+HADP(TDP)+
                                                                   INH10780
    1UXAREA1
                                                                   INH10790
     IF(13UG.FG.O) GG TO 9999
                                                                   INH10800
     PRINT 11
                                                                   INH10810
  11 FORMAT (/1x.10(10HCRITMP
                               11
                                                                   IMMIN820
     PRINT 111
                                                                   11410830
  111 FORMAT(T5. 'TSE1'.121. 'TDP'.T34. 'VRMIN'.147. 'WATTSO'.T61. 'ELPKAR'. INH10840
    1779, 'VS', T89, 'OSTGT ', T105, 'ACL'/T5, 'AWL', T21, 'RCL', T34, 'RWL',
    2T47, 'UXAREA', T61, 'CRITMP')
                                                                   10410860
     PRINT 1111.TSET.TDP.VRMIN.WATTSC.ELPWAR.VS.GSTOT .ACL.AWL.RCL.RWL.INH10870
    THEASEN.CRITMP
                                                                   INHIDARD
 1111 FGRMAT(1X, 8E13.3/1X, 5E13.3)
                                                                   TNH1 0890
 9999 CONTINUE
                                                                   INH10900
     RETURN
                                                                   INH10910
     END
                                                                   INH10920
     FUNCTION OPHA(HA)
                                                                   111111020
  C [NH1 0950
                                                                  CINH10960
 THIS SUBROUTINE FINDS THE DEW POINT TEMPERATURE FOR A GIVEN HUMIDITY CINH10970
 WITH UNITS DEGREES RANKINE AND POUNDS OF WATER PER POUND OF DRY AIR. CINH10980
C DATA IS FROM PERRYS CHEM. HB 5TH P.12-7
                                                                  CINH10990
 NEW DATA FOR HRATIC IS CALCULATED FROM LEREW'S MODLEL
                                                                  CINH11000
                                                                  CINH11010
                                                                  CINH11020
 ***********************************
                                                                  C TNH11040
                                                                  CINH11050
            DEFINITION
                                OF TERMS
                                                                 CINH11060
                                                                 C INH11070
                SEE MAIN PROGRAM FOR ACRONYMS NOT
                                                                 CINH11080
                          LISTED HERE
                                                                  C INH11090
                                                                  CINH11100
 C ATMP - ATMCSPHERIC PRESSURE FROM LAST CALL OF SUBROJTINE, PSI
                                                                  C INH11130
C DP-THE DEWPOINT TEMPERATURE. DEGREES F
                                                                  CINH11140
C DPHA-THE DEMPCINT TEMPERATURE, DEGREES, R
                                                                  CINH11150
C HA-THE INPUT HUMIDITY RATIO, LB UF WATER/LB OF AIR
                                                                  CINH11160
C HRATIG-ARRAY OF HUMIDITY RATIOS, LB OF WATER/LB OF DRY AIR
                                                                  CINH11170
C TEMPF-ARRAY OF TEMPERATURES, DEGREES F
                                                                  CINH11180
                                                                  CTUH11190
                                                                  CINH11200
  COMMON/PRESS/PATM
                                                                   INH11220
                                                                   INH11230
     DIMENSION TEMPE( 92), HEATIC( 92)
     DATA HRATIS /
                                                                   INH11240
    1.0007872,.00102,.001315,.001687,.002152,.002733,
                                                                   INH11250
                                          .003454,.003788,.004107,
                                                                 INH11260
    2.00445..004818..005213..005638..006091..006578..0071..007658.
                                                                   INH11270
    3.008256,.038894,.009575,.0103,.01106,.01191,.0128,.01374,.01475, INH11280
```



INH11290

```
5.02919,.03118,.0333,.03556,.03795,.04049,.04319,.04606,.04911,
                                                                  INH11300
    6.05234,.05578,.05944,.06333,.06746,.07185,.07652,.08149,.08678,
                                                                  INH11310
    7.09242,.09341,.1043,.1116,.1189,.1267,.135,.1439,.1534,.1636,
                                                                  INH11320
    8.1745.1862.1989.2125.2271.243.2602.2788.299.3211.3452.
                                                                  INH11330
    9.3716,.4007,.4327,.4682,.5078,.5519,.6016,.6578,.7218,.7953,.8805,INH11340
    Z.9802.1.099.1.241.1.416.1.635.1.917.2.295/
     DATA TEMPE /
                                                                  INH11360
     10.,5.,10.,15.,20.,25.,30.,32.,34.,36.,33.,40.,42.,44.,46.,48.,50.,1NH11370
    252.,54.,56.,58.,60.,62.,64.,66.,68.,70.,72.,74.,76.,78.,80.,82.,
                                                                 INH11380
    384-,86-,88-,90-,92-,94-,96-,98-,100-,102-,104-,106-,106-,110-,112-INH11390
    4,114-,116-,118-,120-,122-,124-,126-,128-,130-,132-,134-,136-,138-,1NH11400
    5140.,142.,144.,146.,148.,150.,152.,154.,156.,158.,160.,162.,164., INH11410
    6166.,168.,170.,172.,174.,176.,178.,180.,182.,184.,186.,188.,190. ,INH1 1420
    7192.,194.,196.,198.,200./
                                                                  INH11430
     DATA ATMP/-1./
                                                                  INH11440
     IF (PATM.EQ.ATMP) GC TO 1
                                                                  INH11450
     DO 2 I=1.92
                                                                  LUH11460
   2 HRATIC(1)=HADP(TEMPF(1)+459.67)
                                                                  INH11470
   1 CONTINUE
                                                                  INH11480
     DP =TABLI(TEMPF.HRATIO.HA.92)
                                                                  INH11490
     DPHA=DP+459.67
                                                                  INH11500
     ATMP=PATM
                                                                  INH11510
     RETURN
                                                                  INH11520
     FND
                                                                  IUH11530
     SUBROUTINE DRYHET (VENTRY, TIN, TDP, QEVAP, ELPWAR, TDB)
 C INHI 1560
                                                                 CINH11570
 THIS SUBROUTINE CALCULATES THE HEAT USED FOR ALL EVAPORATION.
                                                                 CINH11580
                                                                 C INH1 1 590
                                                                 CINH11600
 CINH11620
                                                                 CINH11630
             DEFINITION OF TERMS
                                                                 CINH11640
                                                                 CINH11650
               SEE MAIN PROGRAM FOR ACRONYMS NOT
                         LISTED HERE
                                                                 CINH11670
                                                                 CINH11680
**********
                                                               **CINH11690
                                                                 CINH11700
C BLTH-BUILDING LENGTH. FEET
                                                                 CINH11710
 DP1-DEWPOINT TEMPERATURE BASED ON CALCULATE INSIDE HUMIDITY RATIC.
                                                                 C I NH1 1720
     DEGREES R
                                                                 CINH11730
C DRPSAR-SURFACE AREA OF DROPPINGS, SQ. FEET
                                                                 C INH11740
 EVAPHIC - WATER EVAPORATED FROM WATERS, LBS. PER HOUR
                                                                 CIN411750
C EVPMUR-WATER EVAPERATED FROM MANURE, LBS. PER HO R
                                                                 CINH11760
C HA-THE ASSOLUTE HUMIDITY AT THE OUTSIDE DEV POINT TEMPERATURE, LBS CINH11770
     PER IR.
                                                                 C1NH11780
 HAINI-HUMIDITY RATIO OF INSIDE AIR AS FOUND FOR *CRYHET* CONDITIONS, CINH11790
     LBS OF H20 PER LB OF DA
                                                                 CINH11800
 HEIT-BUILDING HEIGHT, FEET
                                                                 CINH11810
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
                                                                 CINH11820
 PATM-ATMOSPHERIC PRESSURE, PSI
                                                                 CINH11830
 PS-SATURATED VAPOR PRESSURE AT THE DRY BULB TEMPERATURE, PSI
                                                                 C IUH11340
54321 CONTINUE
                                                                  INH11850
C GEVAP-THE HEAT TO EVAPORATE THE WATER FROM MANURE AND WATERERS, BTU
                                                                 CINH11860
 TOP-OUTSIDE DEW POINT TEMPERATURE, DEGREES R
                                                                 CINH11870
 TIN-TEMPERATURE, INSIDE HOUSE, DEGREES RIUSED IN SUBROUTINES!
                                                                 C1NH11880
 TWB-WET BULB TEMPERATURE BASED ON CALCULATED INSIDE HUIDITY RATIO.
                                                                 CINH11890
 DEGREES R
                                                                 CINH11900
 TWBI- INSIDE WETBULB TEMPERATURE, DEGREES R
                                                                 CINH11910
C UNITEVP-TOTAL WATER EVAPORATED IN UNIT TIME, LBS. PER HOUR
C VENTRY-VENTILATION RATE THROUGH HOUSE AT TIME OF CALCULATION, CFM
                                                                 CINH11930
C WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE
                                                                 CINH11940
C WIDTH-BUILDING WIDTH, FEET
                                                                 CINH11950
                                                                 CINH11960
```

C



```
CCMMON/BUG/ IBUG
                                                                  INH11990
     COMMON/BLDG/BLTH, WIDTH, HEIT
     COMMON/E VP/DRPSAR, WATSAR
                                                                  INH12010
     HA=HADP(TDP)
                                                                  INH12030
     CALL BROHT (TIN, ELPWAR, QSTOT, QLTGT)
                                                                  1NH12040
     CALL TWEIN(TIN, VENTRI, TWEI, QLTCT, HA, TDB)
     CALL EVPWTR(UNTEVP, VENTRT, TIN, TWBI, EVPH20, EVPMUR, 1)
     HAINI = HAIN (QLTCT, TIN, VENTRT, UNTEVP, HA)
                                                                   IUH12070
     IF(HAIN1.GT..0007872) GO TO 3
     PRINT 10.HAIN1
                                                                  IMH12090
  10 FORMAT(1x, 15(7HDRYHET )/1x, ABSOLUTE HUMIDITY INSIDE IS: , G21.71NH12100
    1. THE RETURNED VALUE IS: 0.0007872')
                                                                  INH12110
     HAIN1=.0007372
     IF(IBUG.EO.O) IBUG=2
   3 COUTINUE
     DP1=DPHA(HAIN1)
     IF(DP1.LT.TIN) GO TO 2
                                                                  INH12160
     TWB=TIN
     PRINT 9. DP1. TWB
                                                                  INH12180
   9 FORMAT (1X.20(6HDRYHET)/1X. INSIDE DEWPOINT GREATER THAN DRYBULB. INH12190
    10EWPOINT =',G21.7,'WETBULB SET AT:',G21.7)
                                                                   INH12200
     GO TO 1
     (IMB=WE JEHA (TIN, HAINI)
                                                                  INH12230
   1 CONTINUE
                                                                   INH12240
     CALL EVPKTR (UNTEVP, VENTRT, TIN, TWB, EVPH2C, EVPMUR, 1)
                                                                  INH12250
     QEVAP= UNTEVP*HLDB(TIN)*(-1.)
                                                                   INH12260
     IF(IBUS.EQ.0) GD TO 9999
                                                                   TMU12270
     PS=PSDB(TIN)
                                                                   INH12230
     DRY=-9.
                                                                   INH12290
     PRINT 11
                                                                   TNH1 2300
  11 FORMAT(/1X.10(1HW). ORYHET'.10(1HW))
                                                                   INH12310
     PRINT 9030
                                                                   INH12320
9030 FGRMAT (1X' DRYHET'/ 9X' VENTRT' .T25, 'TIN' .T39, 'TDP' .T53, 'DRPSAR' .T67, INH12330
    1'WATSAR'.T31.'EVPMUR'.T95.'EVPH2D'.T109.'DKY '.T123.'QEVAP'./10XINH12340
    2'BLTH'.T26.'HA'.T40,'HAIN1'.T54,'PS'.T68.'UNTEVP'.T82.'DP1 ')
     PRINT 9031 VENTRT TIN TOP DRPSAR WATSAR EVPMUR EVPH20 DRY
                                                                  TNH12360
    1QEVAP, BLTH, HA, HAIN1, PS, UNTEVP, DP1
                                                                   INH12370
9031 FORMAT (2X,9E14.3/2X,6E14.3)
                                                                   INH12380
     IF(IBUG.EQ.2) IBUG=0
                                                                   INH12390
9999 CONTINUE
                                                                   INH12400
     RETURN
                                                                   INH12410
     END
                                                                   INH12420
     SUBROUTINE DRYRAT(VENTKT, TIN, TWB, DRYRTM, DRYRTW, ME)
                                                                  INH1 2430
 C INH12450
C THIS SUBROUTINE CALCULATES THE DRYING RATE USING THE HEAT TRANSFER COCINH12470
C FICIENT
                                                                 C1NH12480
C AS OUTLINED BY PERRYS HANDBOOK PAGE 15-35. PARAMETERS ARECALCULATED CINH12490
A TAG MOR D
                                                                 CINH12500
C IN WELLS THESIS. (PERRYS 4TH ED 1963)
                                                                 CINH12510
                                                                 CINH12520
                                                                 CINH12530
 CINH12550
                                                                 CINH12560
            DEFINITION OF TERMS
                                                                 CINH12570
                                                                 C INH1 2 580
               SEE MAIN PROGRAM FOR ACRONYMS NOT
                                                                 CINH12590
                         LISTED HERE
                                                                 C INH 1 2600
                                                                 C1NH12610
 CINH12630
Ċ
 ALPHA-CONSTANT DETERMINED BY EXPERIMENT FOR DETERMING THE HEAT
                                                                 CINH12640
     TRANSFER COEFICIENT.
                                                                 CINH12650
 BOAREA - AREA OF ONE BIRD IN CROSS SECTION. SQ. FT.
                                                                 CINH12660
C BLTH-BUILDING LENGTH, FEET
                                                                 CINH12670
C HMNIMP-TEMPERATURE AT WHICH *DIFHMN* IS APPROPRIATE, DEGREES C
                                                                 CINH12680
```



```
C CKAREA - APPROX. CROSS SECTIONAL AREA BLOCKED FOR AIR FLOW BY BIRDS. CINHIZ690
     SO FT.
C CRCIMP-TEMPERATURE AT WHICH *DIFCRC* IS APPROPRIATE, DEGREES C.
                                                                          CINH12710
C DC-CHARACTERISTIC DIMENSION OF THE DRYING SURFACE, FEET
C (THE LENGTH OF THE AIR PATH OVER THE DRYING SURFACE)
                                                                          CINH12720
                                                                          CINH12730
54320 CONTINUE
                                                                           INH12740
C DELTAX-DIFFERENCE IN ELEVATION OF WATER SURFACE AND WATERER RIM. FT. CINH12750
C DIFCRC-DIFFUSION COEFFICIENT AS FOUND IN CRC HANDOOK, SQ.CM./SEC CINH12760
C DIFHMN-DIFFUSION COEVFICIENT AS FOUND IN HEAT TRANSFER BY HOLMAN, SQ CINH12770
C DIFSN-DIFFUSION COEFFICIENT, SC CM/SEC.
                                                                         CINH12780
C DRYH-ALTERNATE VALUE FOR *DRYRTM*
                                                                          CINH12790
C DRYRTH-THE DRYING RATE AS CALCULATED, LBS. OF WATER PER HOUR-SQ.FT.
                                                                         CINH12800
       COEFICIENT
C DRYRTH-THE DRYING PATE AS CALCULATED FOR WATER SURFACES, LBS OF WATERCINH12820
     PER HOUR-SQ FT
                                                                          CINH12830
C DRYW-ALTERNATE VALUE FOR *DRYTW*
                                                                          CINH12840
C EXPN-A CONSTANT DETERMINED BY EXPERIMENT FOR DETERMING THE HEAT TRANSCINH12850
C G-MASS VELOCITY, WEIGHT RATE OF FLOW PER CROSSECTIONAL AREA, LBS./HK.CINH12860
         SQ FT
C HEIT-BUILDING HEIGHT, FEET
                                                                          CINH12880
C HT-HEAT TRANSFER COEFICIENT, BTU/HR.-SQ.FT.-F
                                                                          CINH12890
C LAMBDA-LATENT HEAT OF VAPORIZATION FOR WATER AT TEMPERATURE OF MATERICINH12900
C MBUG-CODED FACTOR FOR DESIRED PRINTGUT AS NOTED ELSEWHERE
                                                                         CINH12910
C ME- A CODED INDEX TO SHOW FROM WHITCH SOUNCE *DRYRAT* IS CALLED.2=TWBCINH12920
         1=CTHER
                                                                         C1NH12930
C MOOTH-MASS FLOW RATE OF WATER VAPOR, LBS/HR-SQ. FT.
                                                                          CINH1 2940
C MW-MOLECULAR WEIGHT OF WATER
                                                                          CINH12950
54321 CONTINUE
                                                                           INH12950
C ONELGT-THE ONE-HALF CIRCUMFERENCE OF A 2 CM DROPPING, CM
                                                                         CINH12970
C PAI-THE DIFFERENCE BETWEEN BARAMETRIC PRESSURE AND SATURATED VAPOR
                                                                         C I NH1 2980
      PRESSURE OF THE AIR, PSI
                                                                          CINH12990
C PA2-THE DIFFERENCE BETWEEN BAROMETRIC PRESSURE AND THE VAPOR PRESSURECINH13000
      OF THE AIR, PSI.
                                                                          CINH13010
C PATM-ATMOSPHERIC PRESSURE, PSI
C PI-THE CONSTANT RATIO OF CIRCUMFERNCE TO CLAMETER
                                                                          CINH13030
C RO-UNIVERSAL GAS CONSTANT, LB.FT./LB DEGPEES R
                                                                          CINH13040
C ROWS - NUMBER OF ROWS OF CAGES THRU HOUSE
C TEMRTE-RATE OF CHANGE FOR DIFFUSION WITH TEMPERATURE, SQ CM/SEC. C
                                                                          C I NH1 30 50
                                                                         CINH13060
C TIN-THE TEMPERATURE OF THE DRYING AIR, DEGREES R
                                                                          C INH1 3070
C TS-TEMPERATURE OF MATERIAL BEING DRIED (WELLS P. 70) DEGREES R
                                                                          C1NH13030
C TWB-WET BULB TEMPERATURE OF VENTILATING AND/OR DRYING AIR, DEGREES R CINH13090
C VEL-VELOCITY OF DRYING AIR OVER MATERIAL ON BELT, FT/MIN
                                                                          CINH13100
C VENTRI-THE VENTILATION RATE IN THE HOUSE AT TIME OF CALCULATION.
                                                                         CINH13110
        CFM OUTSIDE AIR
                                                                          CINH13120
C WATWOT-WIDTH OF WATERERS, FEET
                                                                          CINH13130
 WB - WET BULB TEMPERATURE USED TO CALCULATE DRYRTM.
                                                                          F INH13140
C WIDTH-BUILDING WIDTH, FEET
                                                                          CIMHI3150
CCMMON/PRESS/PATM
                                                                           INH13190
      CCMMON/BLDG/BLTH-WIDTH-HEIT
                                                                           INH13200
      CEMMON/DRY/DRYM, DRYW
                                                                           INH13210
      COMMUN/BIRDS/WBRD.BRDS
                                                                           INH13220
      CCMMON/BUG/IBUG
                                                                           INH13230
      REAL LAMBDA.MOOTW
                                                                           INH13240
      WASTUR
                                                                           INH13250
      IF(TWB.LE.TIN) GC TO 2
                                                                           INH13260
      WB=TIN-.91
                                                                           INH1 3270
      WRITE(3.12)
                                                                           INH13280
   12 FURMAT(/1X,10(1HW),')RYRAT',10(1HW))
                                                                           INH13290
      WRITE(3,10) VEL, TIN, WB, DC, G, HT, TS, LAMBDA, DRYRTM, DRYRTM
                                                                           INH13300
      WRITE (3.1) TWB. TIN. WB
                                                                           INH13310
    1 FORMAT(1X, 130(1HW)/1X, 'WET BULB LARGER THAN DRY BULB TEMPERATURE. INH13320
                                                                           INH13330
         TWB=',G21.8,10X,'TIN=',G21.8,10X,'DEGREES RANKINE'/
     21x, 'WET BUL3 RESET TO: ', G21.8)
                                                                           INH13340
    2 CONTINUE
                                                                           INH13350
      PI=355./113.
                                                                           INH13360
      EXPN=.40202222
                                                                           INH13370
      ALPHA= .1222427622
                                                                           INH13380
      GNELGT=PI*2./2.
                                                                           INH13390
      DC=(UNELGT/(2.54*12.))
                                                                           INH1 3400
```



```
TS=WR
                                                                 INH13420
     LAM3DA=FLDB(TS)
                                                                 INH13430
                                                                 INH1 3440
     ROWS=4.
     BDAREA=0.2
                                                                 INH13450
     CKARFA=(BRDS/RChS) *BDARFA
                                                                 INH13460
            ABS(VENTRT)/((HEIT*3LTH)-CKAREA)
                                                                 INH13470
     G=(VEL/VSD3HA(TIN, HAPV(PVD3WB(TIN, WB))) )*60.
                                                                 INH13480
     HT=[ALPHA*(G**EXPN))/(DC**(1.-EXPN))
                                                                 TNU1 3400
     DRYRIM=(HT/LA4BDA)*(TIN-TS)
                                                                 INH13500
C FROM HEAT TRANSFER BY HOLMAN P. 260
                                                                C INH13510
     DIFCRC=.239
                                                                 INH13520
     DIFHMN= .256
                                                                 TMH1 3530
     CRCTMP=8.
                                                                 INH13540
     HANTHE=25.
                                                                 INH13550
     TEMRTE = (DIFHMN-DIFCRC)/(HMNTMP-CRCTMP)
                                                                 INH13560
     DIFSN = (DIFCRC+TEMRTE*((TIN-459.67)-32.)*5./9.)*3600.*1.07639E-3
                                                                 INH13570
     MW=18.
                                                                 TNH1 3530
     RO=1545.
                                                                 INH13590
     DELTAX= 2./12.
                                                                 INH13600
     PA2=PATM-PVDBWS(TIN, WB)
                                                                 INH13610
     PAI =PATM-PSOBITIN)
                                                                 INH13620
     MDGTW=((DIFSN*PATM*MW )/(RG*TIN*DELTAX))*ALGG(PA2/PA1)
                                                                 INH13630
     DRYRTW=MDDTW*144.
                                                                 1 NH 1 3440
     DEVU-DEVETM
                                                                 INH13650
     DRY N= DRYRTW
                                                                 INH13660
     IF(IBUG.EQ.O) GC TO 88
                                                                 INH13670
     PRINT 55
                                                                 INH13680
  55 FORMAT(1HO.10(10HDRYRATE ))
                                                                 INH13690
     WTRYNG, MTRYNG, ADBKA, ST, TH, D, DC, 8W , AIT, LAV. OL TRING
   10 FORMAT(//TX'VEL',T21, 'TIN',T35,' WB ',T48,'DC',T62,'G',T76,'HT',T9INH13710
    10 .'IS'.T104.'LAMBDA'/1X.8E14.4/T7 .'DRYRTM'.T21.'DRYRTW'/2E14.4)INH13720
   38 CONTINUE
                                                                 INH13730
     RETURN
                                                                 INH13740
     END
                                                                 INH13750
     SUBROUTINE DRYSRF (EXSMHS, WATLGT, WATWOT, DRPSAR, WATSAC, DRYSUF)
                                                                 INH13750
  CINH13780
                                                                C TNH1 3700
  THIS SUBSCUTINE FINDS
                                                                C 1NH1 3800
      THE SURFACE AREA OF WATEREES AND MANURE FOR DRYING
                                                                CINH13810
                                                                CINH13820
                                                                CINH13830
  CINH13850
                                                                C1:4H13360
            DEFINITION OF TERMS
                                                                CINH13870
                                                                CINH13880
               SEE MAIN PROGRAM FOR ACRONYMS NOT
                                                                C I NH1 3840
                         LISTED HERE
                                                                CINH13910
  C1NH13930
C DRPNUM-NUMBER OF DROPPINGS OF EXCRETA AS ACCUMULATED THRU THE DAY
                                                                CINH13940
C DRPSAR-SUPFACE AREA OF DROPPINGS. AS ACCUMULATED THRU THE DAY, SQ. FTCINH13950
C DRYSUF-TOTAL SURFACE AREA FOR DRYING, SQ. FEET
                                                                CINH13960
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
                                                                CINH13970
C PLYWIN-THE WIDTH OF THE DROPPING BOARDS. FT.
                                                                CINH13980
C WATLGT-LENGTH OF WATERCHS. FEET
                                                                CINH13990
C WATSAR-SURFACE AREA OF EXPOSED MATER IN HOUSE
                                                  , SQ. FEET.
                                                                C INN14000
C WATKOT-WIDTH OF WATERING TROUGHS. WATER SURFACE. FEET
                                                                C1NH14020
                                                                C INH14030
CEMMON/BUG/IBUG
                                                                 INH14050
     CCMMON/RATE/CRPNUM
                                                                  INH14060
     D RPSAR=DRP NUM*0.0067573
                                                                  INH14070
     PLYATH=10./12.
                                                                  INH14080
     DRPSAR=PLYWTH#WATLGT
                                                                  INH14090
     TOWTAW * TO LITAW = SAZIAW
                                                                  INH14100
```



```
DRYSUF=DRPSAR+WATSAR
                                                                     INH14110
     IF(18UG.EQ.0) GO TO 9999
                                                                     INH14120
     PRINT 13
                                                                     INH14130
  13 FORMAT (/1X, 10(1HW), 'DRY SRF', 10(1HW))
                                                                     THUIATAD
      PRINT 9020
 9020 FORMAT(IX'DRYSRF'/9X'EXSMHS',T25,'WATLGT',T39,'WATWDT',T53,'DRPSARINH14160
     1',T67, 'WATSAR',T81, 'DRYSUF', T95, 'DRPNUM')
     PRINT 9021,
                      EXSMHS, WATLGT, WATWDT, DRPSAR, WATSAR, DRYSUF
                                                                     INH14180
     1 . DR PNU4
                                                                     INH14190
9021 FORMAT (2X,7E14.3)
                                                                     INH14200
 9999 CONTINUE
                                                                     INH14210
     PETHON
                                                                     INH14220
     END
                                                                     INH14230
     SUBROUTINE ELHEAT(WATTSD.ELPWR.ELHT)
                                                                    1NH14240
CINH14260
                                                                   C1NH14270
 THE PURPOSE OF THIS SUBROUTINE IS TO COMPUTE THE HEAT ADDED BY
                                                                   CINH14280
C ELECTRIC LIGHTS. AKWATT IS APPLIED POWER IN THE POULTRY BUILDING.
                                                                   C1NH14290
C WATTSQ IS THE MATTAGE PER SQUARE FOOT. ELPWR IS AN INDEX
C INDICATING POWER IS UN OR OFF. 3413 IS THE WATTAGE TO BTU
                                                                   C 1 NH14310
C COUVERSION FACTOR
                                                                   CINH14320
                                                                    C TNH1 4330
                                                                    CINH14340
 C 1NH1 4360
                                                                    CINH14370
č
             DEFINITION OF TERMS
                                                                   CINH14380
ċ
                                                                   CINH14390
                SEE MAIN PROGRAM FOR ACRONYMS NOT
                                                                   CINH14400
Ċ
                          LISTED HERE
                                                                    C1NH14420
  CINHIA440
C AKWATT-ELECTRIC POWER APPLIED IN THE BUILDING, KILGWATTS
                                                                    CINH14450
C BLTH-BUILDING LENGTH, FEET
                                                                   CINHIAAAA
C ELHT- HEAT EQUIVALENT OF ELECTRIC POWER, BTU PER HR
                                                                   CINH14470
C ELPWR-A!! INDEX INDICATION LIGHTS ARE ON OR OFF
                                                                   C18914440
C HEIT-BUILDING HEIGHT, FEST
                                                                    CTMH14400
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
                                                                   CINH14500
 WATTS 2-ELECTRICAL POWER APPLIED TO BUILDING, WATTS PER SQ. FOOT
                                                                   C1MH14510
54321 CONTINUE
                                                                     INH14520
C WIDTH-BUILDING WIDTH, FEET
                                                                    CINH14530
                                                                    CINH14540
                                                                    C1NH14550
     QUBIVDUS/NCMM3 3
                                                                     INH14570
     CCMMON/BLDG/BLTH.WIDTH.HEIT
     . COCINHICIWATISCASSITAM = TIAWAY
                                                                     INH14590
     ELHT=AKWATT#3413.#ELPWR
     IF(IBUG.EQ.O) GO TO 9999
                                                                     LNH14610
     PRINT 15
  15 FORMAT(/1X.10(1HW). *ELHEAT*.10(1HW))
                                                                     INH14630
     PRINT 9050
                                                                     INH14640
 9050 FOR MAT (2X, 'ELHEAT', /9X, 'WATTSC', T25, 'ELPWR', T39, 'ELHT', T53, '
                                                                     INH14650
    1 AKKATT!)
                                                                     INH14660
     PRINT 9351 .
                       MATTSQ, ELPWR, ELHT, AKMATT
                                                                     INH14670
 9051 FORMAT (9X,4E14.3)
                                                                     INH14680
                                                                     INH14690
 9999 CONTINUE
     RETURN
                                                                     13914700
     END
                                                                     INH14710
      SUBROUTINE EVPKTR (UNTEVP, VENTRT, TIN, THB, EVPH20, EVPMUR, ME)
                                                                     TNH1 47 20
                                                                   CINH14740
                                                                    CINH14750
 THIS SUBROUTINE CALCULATES WATER REMOVED FROM THE WATERERS, THE
                                                                   CINH14760
     MANURE AND THE SUM OF THESE TWG.
                                                                    C1NH14770
     OSTING WATER IS ADDED TO AIR FROM MANURE AND WATERESS(ASSUME NO CINH14780
```



```
C SPILLS HOD REMOVED FROM MANURE IN UNIT TIME
                                                                   C1NH14790
                                                                   C 1 NH1 4800
                                                                   CINHIAGIO
  č
                                                                   C 1 N L 1 4 8 4 0
č
             DEFINITION UF TERMS
                                                                   CINH14850
c
                                                                   CIMHIARA
č
                SEE MAIN PROGRAM FOR ACRENYMS NUT
                                                                   CINH14870
ř
                          LISTED HERE
                                                                   C I II H14880
                                                                   CINH14890
  CTNH14910
C BROTMP-BUCY TEMPERATURE OF A LAYING HEN. DEGREES R
                                                                   CINH14920
C DRPSAR-SURFACE AREA OF DROPPINGS, SQ. FEET
                                                                   CINH14930
 DRYRTM-THE DRYING RATE AS CALCULATED, LBS. OF WATER PER HOUR-SQ.FT.
                                                                  C10H14940
C DRYRTH-THE DRYING RATE AS CALCULATED FOR WATER SURFACES, LBS OF WATERCINH14950
C PER HOUR-SQ FT
                                                                   C1NH14960
C DT-LENGTH OF ITERATION, HOURS
                                                                   C I NH1 / 070
C EVPH20-WATER REMOVED FROM WATERS, LBS PER HOUR
                                                                   CINH14980
C EVPMRT-TOTAL WATER EVAPORATED IN HOUSE FROM MANURE, LBS.
                                                                   CINH14990
C EVPMUR-WATER EVAPORATED FROM MANURE, LBS. PER HO R
                                                                   C INH1 5000
 EVPIST-THE MOISTURE EVAPORATED FROM MANURE AS A RESULT OF ITS INITIALCINHISOLO
      TEMPERATURE BEING GREATER THAN AMBIENT TEMP. . LBS PER HOUR
                                                                   CINH15020
54321 CONTINUE
C EXCONC-THE MOISTURE CONTENT OF MANUKE AS DEFICATED, DECIMAL FRACTION CINHISO40
 EXMISM-WEIGHT OF EXCRETA AS ACCUMULATED THRU THE DAY. LBS
C HLIST-LATENT HEAT OF EVAPORATION ESTIMATION WHILE DRYING MANURE WITH CINHISO60
     INITIAL BODY HEAT, STU/LB
 IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
                                                                   CINH15090
C ME- A CODED INDEX TO SHOW FROM WHICH SOURCE *DRYKAT* IS CALLED.2=TWBICINH15090
        1=CTHER
                                                                   CINH15100
C QIST-THE EXTRA HEAT IN THE MANURE AS A RESULT OF ITS INITIAL
                                                                   CINH15110
 TEMPERATURE BEING GREATER THAN AMBIENT, BTU PER HOUR
                                                                   CINH15120
 SPM- THE SPECIFIC HEAT OF MANURE, BTU/LB-DEGREE F
                                                                   C INH15130
  TIN-TEMPERATURE, INSIDE HOUSE, DEGREES R(USED IN SUBROUTINES)
 THE-WET BULB TEMPERATURE BASED ON CALCULATED INSIDE HUIDITY RATIO.
                                                                   CINH15150
 UNTEVP-TOTAL WATER EVAPORATED IN UNIT TIME, LB . PER HOUR
                                                                   CINH15170
 VENTRY-THE VENTILATION RATE IN THE HOUSE AT TIME OF CALCULATION.
                                                                   CINH15180
        CFM OUTSIDE AIR
                                                                   C 10H15190
  WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE SQ. FT.
                                                                   CINH15200
                                                                   CINH15210
                                                                   CINH15220
  COMMON/CRT/KCL,RWL,SPM,EXRATE
                                                                    INH152+0
     CCMMON/BUG/IBUG
                                                                    IN415250
     CCMMON/C/EXCOMC, EXWID, EXKISM, EVPMRI, DI
                                                                    THU15260
      CEMMON/EVP/DRPSAK, WATSAR
                                                                     INH15270
      CALL DRYRAT(VENTRT ,TIN,TWB,DRYRTM,DRYRTW,ME)
                                                                     TNH 15 280
      BRDTMP=107.1+459.67
                                                                     INH15290
      TO/COLT-9MTCAGI#M94M94DTWX = TICI/OI
                                                                     INH15300
     HLIST=HLD2[[BEDIMP+TIN]/2.]
                                                                     INH15310
      EVP1ST=21ST/HL1ST
                                                                     IMH15320
      EVPHUR=DRYRTM*DRPSAR +EVP1ST
                                                                     INH15330
      RWTRWT=EXWTSM*EXCDMC-EVPMRT
                                                                     INH15340
      IF (KWTRWT# . 9-E VPMUR/DT)1.2.2
                                                                    INH15350
    1 EVPMUR= . 9*RHTRHT/DT
      WRITE(3,3) EVPMUR
                                                                    TUH15370
    3 FORMAT(1X,120(1Hk),5X,'EVPWTR'/1X,'DRYING BELCW CONSTANT RATE WATEINH153d0
     IR REMOVED LIMITED TO: , G21.7)
                                                                    INH15390
      If (IBUG.EQ.O) IBUG=2
                                                                    INH15400
   2 CONTINUE
                                                                    INH15410
C H20 REMOVED FROM WATERS IN UNII TIME
                                                                   CINH15420
     EVPH20=DRYRTW#WATSAP
                                                                    INH15430
C TOTAL H20 EVAPORATED IN UNIT TIME
                                                                    CINH15440
     UNTEVP=EVPMUR+EVPH20
                                                                     INH15450
      IF(IBUG.EQ.0) GC TO 9999
                                                                     INH15460
                                                                     INH15470
      PRINT 16 . DEYRTW
   16 FGFMAT(/1x,10(1HW), EVPWTR ',10(1HW),10x, 'DRYRTW=',E14.4)
                                                                     INH15480
      PRINT 9040
 9040 FORMAT(1X'EVPHTR'/9X'DRYRTM',125, DRPSAR',T39, WATSAR',T53, 'EVPMURINH15500
```



	1',T67,'EVPH2G',T81,'UNTEVP')	INH15510
	PRINT 9041, DRYRTM, DRPSAR, WATSAR, EVPMUR, EVPH20, UNTEVP	INH15520
	9041 FORMAT (2X,6E14.3)	INH15530
	IF(IBUG.EQ.2) IBUG=0	INH15540
	9999 CONTINUE	INH15550
	RETURN	INH15550
	END	INH15570
		1.1112370
	SUBROUTINE EXCRAT (BIRDNO, DF, EXHTSM, EXHTD)	INH15580
C		
C		CINH15600
C		CINH15610
C		CINH15620
C		CINH15630
C		CINH15640
C		CINH15650
C		CINH15660
C		
C		CINH15680
C		C1NH15690
C	DEFINITION OF TERMS	CINH15700
C		CINH15710
C		
		CINH15720
C		CINH15730
C		CINH15740
С	*****************	<b>≠C1NH15750</b>
c		CINH15760
C	BIRDNE- NC. OF BIRDS IN BUILDING	CINH15770
Č		
č		CINH15790
č		CINH15800
C		CINH15810
С		CINH15820
		CINH15830
C		
č	EXWITDY-WEIGHT OF EXCRETA PER DAY, LBS.	CINH15840
	EXWITDY-WEIGHT OF EXCRETA PER DAY, LBS.	
C	EXWIDY-WEIGHT OF EXCRETA PER DAY, LES. 18UG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM	CINH15840 CINH15850
CCC	EXHIDY-WEIGHT OF EXCRETA PER DAY, LBS. 1896-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM	CINH15840 CINH15850 CINH15860
0000	EXATOY-WEIGHT OF EXCRETA PER DAY, LBS. 183G-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM	CINH15840 CINH15850 CINH15860 CINH15870
CCC	EXATOY-HEIGHT OF EXCRETA PER DAY, LES. 184G-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM	CINH15840 CINH15850 CINH15860 CINH15870 ¢CINH15880
0000	EXATOY-HEIGHT OF EXCRETA PER DAY, LES. 1836-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM  CCMMCN/CRT/RCL,RML,SPM,EXRATE	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15880 INH15890
0000	EXATOY-HEIGHT OF EXCRETA PER DAY, LES. 18UG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM  COMMEN/CRT TROLLARM, SPH. EXRATE COMMON/BUG/18UG/18UG	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15880 INH15890 INH15900
0000	EXATOY-HEIGHT OF EXCRETA PER DAY, LES. 18JG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM  CCMMCN/CRT/RCL,RNL,SPM,EXRATE COMMON/SUG/18UG EXATOY-EXATE-SHIRONO	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15880 INH15890 INH15900 INH15910
0000	EXATOY-HEIGHT OF EXCRETA PER DAY, LESS 13UG-AN INTEGER CODE USED FGR DEGUGGING THE PROGRAM  COMMENCET/ROLE, RML, SPM. EXRATE COMMON/ROLE/15UG EXATOY-EXAATE-BEIRONO EXATOY-EXAATE-BEIRONO EXATOY-EXAATE-BEIRONO	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15880 INH15890 INH15910 INH15920
0000	EXATOY-HEIGHT OF EXCRETA PER DAY, LES. 18JG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM  CCMMCN/CRT/RCL,RNL,SPM,EXRATE COMMON/SUG/18UG EXATOY-EXATE-SHIRONO	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15880 INH15890 INH15900 INH15910
0000	EXATOY-HEIGHT OF EXCRETA PER DAY, LESS 13UG-AN INTEGER CODE USED FGR DEGUGGING THE PROGRAM  COMMENCET/ROLE, RML, SPM. EXRATE COMMON/ROLE/15UG EXATOY-EXAATE-BEIRONO EXATOY-EXAATE-BEIRONO EXATOY-EXAATE-BEIRONO	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15880 INH15890 INH15910 INH15920
0000	EXATOY-HEIGHT OF EXCRETA PER DAY, LES. 18UG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM  CCMMCN/CRT/RCL,RML,SPM,EXRATE COMMON/PUG/18UG EXATOY=EXATE=BIRDNO EXATO=EXATOY=EXATE=BIRDNO EXATO=EXATOY=EXATOY=FOR	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15880 INH15890 INH15910 INH15910 INH15920 INH15930
0000	EXATON-HEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FGK DEBUGGING THE PROGRAM  CCMMCN/CRT/RCL, kML, SPM, EXRATE COMMON/SUG/IBUG EXATO-EXATE-BEIRDNO EXATO-EXATO-EXATE-BEIRDNO EXATO-EXATO-EXATO-EXITO IF(18UG, EO. 0) GC TC 9999 EGFTE = 0.69	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15880 INH15890 INH15910 INH15920 INH15920 INH15930 INH15930 INH15943 INH15950
0000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FOR DESUGGING THE PROGRAM  COMMON/SUG/ISUG EXATOY-EXATE-SIRONG EXATOY-EXATE-SIRONG EXATOY-EXATE-SIRONG EXATOY-EXATE-SIRONG EXATOY-EXATE-SIRONG EXATOY-EXATO	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15880 INH15900 INH15910 INH15910 INH15920 INH15940 INH15940 INH15940 INH15950 INH15950
0000	EXATOY-HEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FGK DESUGGING THE PROGRAM  CCMMCN/CRT/RCL,kML,SPM,EXRATE COMMON/SUG/ISUG EXATOY-EXATE-SEIRONO EXATO-EXATOY-EXATE-SEIRON EXATO-EXATOY-EXTOYOF EXTISM-EXATSH-EXATO IF(18UG,EO.0) GG TC 9999 EGFTE = 0.69 PRINT 14 14 FURMATI(1/1) 1011M-1,*EXCRAT*,1011M-)	CINH15840 CINH15850 CINH15870 *CINH15870 *CINH15890 INH15890 INH15910 INH15920 INH15920 INH15940 INH15950 INH15950 INH15970
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FOR DESUGGING THE PROGRAM  CCMMCN/CRT/RCL, RWL, SPP, EXRATE COMMON/SUG/ISUG EXATOYEKRATE-SEIRONO EXATOYEKRATE-SEIRONO EXATOYEKRATE-SIGNED EXTO-EXATOYEC FIT SIGNED SIGNED EXTO-EXATOYEC FIT SIGNED SIGNED EXTO-EXATOYEC FIT SIGNED SIGNED EXTO-EXATOYEC FIT SIGNED SIGNED EXTO-EXATOYEC FIT SIGNED FIT SI	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15870 INH15890 INH15990 INH15910 INH15920 INH15920 INH15950 INH15950 INH15950 INH15950 INH15950 INH15970
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LESS  CCMMCN/CRT/RCL, RHL, SPM, EXRATE  CCMMCN/RD/TRCL, RHL, SPM, EXRATE  CCMMCN/RD/TBUG  EXATOY-EXAATE-BIRONO  EXATOY-EXAATE-BIRONO  EXATOY-EXATOY-OF  EXATSM-EXATSM-EXATD  IFIEBUS, ED. 00 G TO 9999  EGRIE -00.69  FOR THE -00.69  FOR TH	CINH15840 CINH15850 CINH15860 CINH15870 *CINH15880 INH15900 INH15910 INH15910 INH15910 INH15940 INH15950 INH15950 INH15960 INH15960 INH15970 INH15970
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FOR DESUGGING THE PROGRAM  CCMMON/RUG/ISUG EXATOY-EXRATE-BIRDNO EXATOY-EXRATE-BIRDNO EXATOY-EXATOY-OF EXHISH-EXHISH-EXHID IF ISUG-EX-O' GG TU 9999 EGFIE = 02.69 14 FURNATI/IX, 1011HH), "EXCRAT', 1011HH) PRINT 9010 9010 FOR-ANTI(IX/EXCRAT',9X*I-BUDIC',725, "EGRIE',139, "EXHID',753, "EXHID' PRINT 901. BRIDNOW, BORTE-EXHID (EXHID') PRINT 901. BRIDNOW, BORTE-EXHID (EXHID') PRINT 901. BRIDNOW, BORTE-EXHID', EXHID' PRINT 901. BRIDNOW, BORTE-EXHID', EXHID'	CINH15840 CINH15850 CINH15870 CINH15870 CINH15870 INH15900 INH15910 INH15910 INH15930 INH15930 INH15950 INH15950 INH15950 INH15950 INH15950 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  CAMENACAT /ACL, RWL, SPM, EXRATE  COMMONATOR / NOL, RWL, SPM, EXRATE  COMMONATOR / NOL RWL, SPM, EXRATE  EXATOY-EXATTE-BIRONO  EXATOY-EXATOY-OF  EXATSM-EXATOY-OF  EXATSM-EXATSM-EXATO  IF(IEUG, EC. 0) GG TO 9999  EGFIE = 0.49  PRINT 11X, 1011Hb), 'EXCRAT', 10(1Hb) }  9010 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  POIL FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  901 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  901 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  901 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  901 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  901 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')	CINH15840 CINH15850 CINH15870 CINH15880 CINH15880 INH15900 INH15910 INH15920 INH15920 INH15930 INH15930 INH15950 INH15970 INH15970 INH15970 INH15990 INH15990 INH15990 INH15990 INH16010
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FOR DESUGGING THE PROGRAM  CCMMEN/CRT/RCL, RML, SPM, EXRATE COMMON/SUG/ISUG EXATOY-EXRATE-BIRDNO EXATO-EXRATE-BIRDNO EXATO-EXRATE-BIRDNO EXHID-EXRATE-BIRDNO EXHID-EXHID-EXHID IFIISUG-EQ. 01 GC TU 9999 EGATE = 02.69 14 FURNATI/IX, JOIIHHJ, "EXCRAT', 10(1HHJ) PRINT 9010 9010 FOR-ANTI(IX/EXCRAT',9X'=18DDC', 125, "EGRIE',139, "EXHID', T53, "EXHID' PRINT 901. RINDNOW, GGRTE, EXKTD, EXKTDY 9011 FORMAT (2X, 5E14-3) 9999 CCHITUME	CINH15840 CINH15850 CINH15860 CINH15870 CINH15870 INH15900 INH15910 INH15910 INH15930 INH15930 INH15950 INH15950 INH15950 INH15950 INH15950 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  CAMENACAT /ACL, RWL, SPM, EXRATE  COMMONATOR / NOL, RWL, SPM, EXRATE  COMMONATOR / NOL RWL, SPM, EXRATE  EXATOY-EXATTE-BIRONO  EXATOY-EXATOY-OF  EXATSM-EXATOY-OF  EXATSM-EXATSM-EXATO  IF(IEUG, EC. 0) GG TO 9999  EGFIE = 0.49  PRINT 11X, 1011Hb), 'EXCRAT', 10(1Hb) }  9010 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  POIL FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  901 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  901 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  901 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  901 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')  901 FORWAIT (IXF EXCRAT', 9%* IBDDC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXKID')	CINH15840 CINH15850 CINH15870 CINH15870 CINH15870 INH15900 INH15910 INH15910 INH15920 INH15930 INH15950 INH15950 INH15950 INH15970 INH15970 INH15970 INH15990 INH16000 INH16010 INH16010
CCCCC	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FOR DESUGGING THE PROGRAM  CCMMEN/CRT/RCL, RML, SPM, EXRATE COMMON/SUG/ISUG EXATOY-EXRATE-BIRDNO EXATO-EXRATE-BIRDNO EXATO-EXRATE-BIRDNO EXHID-EXRATE-BIRDNO EXHID-EXHID-EXHID IFIISUG-EQ. 01 GC TU 9999 EGATE = 02.69 14 FURNATI/IX, JOIIHHJ, "EXCRAT', 10(1HHJ) PRINT 9010 9010 FOR-ANTI(IX/EXCRAT',9X'=18DDC', 125, "EGRIE',139, "EXHID', T53, "EXHID' PRINT 901. RINDNOW, GGRTE, EXKTD, EXKTDY 9011 FORMAT (2X, 5E14-3) 9999 CCHITUME	CINH15840 CINH15850 CINH15870 CINH15880 CINH15880 INH15900 INH15910 INH15920 INH15920 INH15930 INH15930 INH15950 INH15970 INH15970 INH15970 INH15990 INH15990 INH15990 INH15990 INH16010
00000	EXATOY-WEIGHT DO EXCRETA PER DAY, LES.  313G-AN INTEGER CODE USED FGR DEGUGGING THE PROGRAM  CCMMCh/CRT/RCL,RWL,SPM,EXRATE COMMON/BOST FOR THE PROFILE OF THE PROGRAM  EXATOY-EXATOY-09 EXPONE EXATOY-09 EXPONE EXPO	CINH15840 CINH15850 CINH15860 CINH15880 INH15900 INH15910 INH15920 INH15920 INH15920 INH15940 INH15940 INH15960 INH15960 INH15960 INH15990 INH15990 INH16000 INH16010 INH16010 INH16010 INH16010 INH16030
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LESS  GUMENACRIYACL, RML, SPM, EXRATE  COMMONAUGOTISUS  EXATOY-EXATEBEBIRAND  EXATOY-EXATEBEBIRAND  EXATOY-EXATEBEBIRAND  EXATOY-EXATOY-OF  EXATSM-EXATOY-OF  EXATSM-EXATOH-EXATOR  FIRE -0.69  EGRIE -0.69  FORMATI(1X, JOIIHH), 'EXCRAT', 10IIHH)  PRINT 9010  9010 FORMATI(1X, TEXTRAT', 9X'=18DHCC', 125, 'EGRIE', 139, 'EXMID', T53, 'EXMID'  9011 FORMATI(XY, EXCRAT', 9X'=18DHCC', 125, 'EGRIE', 139, 'EXMID', T53, 'EXMID'  9012 FORMATI(XY, EXCRAT', 9X'=18DHCC', 125, 'EGRIE', 139, 'EXMID', T53, 'EXMID'  9014 FORMATI(XY, EXCRAT', 9X'=18DHCC', 125, 'EGRIE', 139, 'EXMID', T53, 'EXMID', T53, 'EXMID', T53, 'EXMID', EMBLE COMMON EXTRA EXAMINATION EXPLORMED  9015 FORMATI(XY, 5ELFA, 3)  RETURN  ETUDN	CINH15840 CINH15850 CINH15860 CINH15860 *CINH15890 INH15890 INH15910 INH15910 INH15920 INH15920 INH15940 INH15940 INH15960 INH15970 INH15970 INH15970 INH15930 INH16000 INH16010 INH16010 INH16020 INH16020 INH16030 INH16040
00000	EXATDY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FGR DESUGGING THE PROGRAM  CCMMCN/CRT/RCL, RML, SPM, EXRATE COMMON/SUG/ISUG EXATTY-EXARTE-SIRONO PRINT 901 PRI	CINH15840 CINH15850 CINH15870 CINH15870 CINH15870 CINH15870 INH15900 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH16010 INH16010 INH16010 INH16010
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  CCMMCN/CRT/MCL, MAL, SPM, EXRATE CCMMCN/CRT/MCL, MAL, SPM, EXRATE CCMMCN/MCD/IDUC EXATOY-EXATEBEIRONO EXATOY-EXATEBEIRONO EXATOY-EXATOY-OF EXATSM-EXATOY-OF EXATSM-EXATOH-EXATO IFIEUR.GC.01 GC TC 9999 EGFIE =0.69 PRINT 4010 PRINT 4010 PRINT 4010 PRINT 4010 PRINT 4011 HIRDNO, ECREAT', 10(1HH) PRINT 4011 HIRDNO, ECREE, EXATOY, EXATOY, TOOL TOWN TOWN TOWN TOWN TOWN TOWN TOWN TOWN	CINH15840 CINH15850 CINH15870 CINH15870 CINH15870 CINH15870 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH16030 INH16030 INH16030 INH16030 INH16030 INH16030
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  CCMMCN/CRT/MCL, MAL, SPM, EXRATE CCMMCN/CRT/MCL, MAL, SPM, EXRATE CCMMCN/MCD/IDUC EXATOY-EXATEBEIRONO EXATOY-EXATEBEIRONO EXATOY-EXATOY-OF EXATSM-EXATOY-OF EXATSM-EXATOH-EXATO IFIEUR.GC.01 GC TC 9999 EGFIE =0.69 PRINT 4010 PRINT 4010 PRINT 4010 PRINT 4010 PRINT 4011 HIRDNO, ECREAT', 10(1HH) PRINT 4011 HIRDNO, ECREE, EXATOY, EXATOY, TOOL TOWN TOWN TOWN TOWN TOWN TOWN TOWN TOWN	CINH15840 CINH15850 CINH15870 CINH15870 CINH15870 CINH15870 INH15900 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH15910 INH16010 INH16010 INH16010 INH16010
00000	EXATDY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FOR DESUGGING THE PROGRAM  CCMMCN/CRT/RCL, RML, SPM, EXRATE COMMON/SUG/ISUG EXATOYEKRATE-SIRONO PRINT 9010 PRINT 9010 PRINT 9010 PRINT 9011 PRINTONO ECREE, EXATO, EXATOY PRINT 901 PRINTONO ECREE PRINTONO EXAMINATION ECREE PRINTONO EXAMINATION ECREE PRINTON EXAMINATION EXCRETE PRINTON EXAMINATION EXAMINA	CINH15840 CINH15850 CINH15870 CINH15870 CINH15870 CINH15870 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH16030 INH16030 INH16030 INH16030
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FGR DEGUGGING THE PROGRAM  CCMMCA/CRI/RCL.RWL.SPM.EXRATE CMMCA/CRI/RCL.RWL.SPM.EXRATE CMMCA/CRI/RCL.RWL.SPM.EXRATE EXATOY-RCA ADVENTOR EXATO-EXATOY-ROP EXATSM-EXATOY ROP EXATSM-EXATOR 1F1EBUS.EC.0) GG TO 9999 EGFIE =0.69 PRINT 11, 1011Hb), 'EXCRAT', 10(1Hb) J 9010 FGM-AILIY EXCRAT', 9%'=18DICC', 125, 'EGRIE', 139, 'EXMID', 753, 'EXMID' 9011 FGM-AILIY EXCRAT', 9%'=18DICC', 125, 'EGRIE', 139, 'EXMID', 753, 'EXMID' 9011 FGM-AILIY EXCRAT', 9%'=18DICC', 125, 'EGRIE', 139, 'EXMID', 753, 'EXMID' 9011 FGM-AILIY EXCRAT', 9%'=18DICC', 125, 'EGRIE', 139, 'EXMID', 753, 'EXMID', 901 FGM-AILIY EXCRAT', 9%'=18DICC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXMID' 9011 FGM-AILIY EXCRAT', 9%'=18DICC', 125, 'EGRIE', 139, 'EXMID', 753, 'EXMID' 9012 FGM-AILIY EXCRAT', 9%'=18DICC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXMID' 9013 FGM-AILIY EXCRAT', 9%'=18DICC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXMID' 9014 FGM-AILIY EXCRAT', 9%'=18DICC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXMID', 153, 'EXMID', 153, 'EXMID', 154, 'EXCRAT', 154, 'EXMID', 154, 'EXCRAT',	CINH1580 CINH1580 CINH1580 CINH1580 CINH1580 CINH1580 INH1580 INH1580 INH1590 INH1590 INH1590 INH1590 INH1590 INH1590 INH1590 INH1690 INH1600 INH1600 INH1600 INH1600 INH1600 INH1600 CINH1600 CINH1600 CINH1600 CINH1600
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FOR DESUGGING THE PROGRAM  CCMMCN/CRT/RCL, RWL, SPM, EXRATE COMMON/SUG/ISUG EXATOY-EXRATE-SHIRDNO EXATO-EXRATO-EXRID EXATO-EXRATO-EXRID EXPLORE EXATO-EXRID 10 FEB TO 10 GC TO 9999 EGFIE =0.00 PRINT 1 14 FURNATI(/IX, JOILHH), "EXCRAT', 1011HH)) PRINT 9010 9010 FORMAI (IX/EXCRAT'/9X'BIRDIC', T25, "EGRIE', T39, "EXPID', T53, "EXPIDY PRINT 19010 9010 FORMAI (IX/EXCRAT'/9X'BIRDIC', T25, "EGRIE', T39, "EXPID', T53, "EXPIDY PRINT 1901, BIRDION, EGRIE, EXRID, EXRATOY 9011 FORMAI (ZX, 5E14.3) RETURN EHD  SUBROUTINE FICANT (IT, TSLAB, INDIC, 0)	CINH1580 CINH1580 CINH1580 CINH1580 CINH1580 CINH1580 NH1580 NH1590 NH1590 NH1590 NH1590 NH1590 NH1590 NH1590 NH1590 NH1590 NH1590 NH1590 NH1690 NH1690 NH1690 NH1690 CINH1690 CINH1600 CINH1600 CINH1600 CINH1600 CINH1600 CINH1600 CINH1600
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LESS  13UG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM  CCMMCDA/CRT/RCL,RWL,SPM,EXRATE COMMON/BOSTOBUG EXATOY-EXATOY-OF EXATOM-EXATOY-OF EXATOM-EXATOY-OF EXATSM-EXATOY-OF EXATSM-EXATOY-OF EXATSM-EXATOY-OF EXATSM-EXATOY-OF OF RITT 14. 14 FORMATI(IX,101Hh), 'EXCRAT',10(1Hh)') PRINT 301E-EXCRAT', '99': 18DICC', 125, 'EGRIE', 139, 'EXMID', 153, 'EXATOY 901FOMATI(ZX,5E14.3) 9090 CCXTINUE RETURN END  SUBROUTINE FLORMT (I,TSLAB,INDIC,0)  THIS SUBRCUTINE DETERMINES THE BUILDING HEAT LCSS THROUGH THE FLOOK SLAB.	CINH15840 CINH15860 CINH15860 CINH15860 CINH15860 CINH15870 CINH15870 CINH15870 INH15910 INH15910 INH15910 INH15910 INH15910 INH15930 INH15930 INH15930 INH15930 INH15930 INH16930 CINH16930 CINH16930
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LESS  GUMENACRI MCCL, RHL, SPM, EXRATE  COMMONAUGATING  COMMONAUGATING  EXATOY-EXAATE-BIRONO  EXATOY-EXAATE-BIRONO  EXATOY-EXAATE-BIRONO  EXATOY-EXATOY-OF  EMATSH-EXATSH-EXATO  IFFLENG.CO.01 GG TO 9999  EGRIE +0.69  FORMATI(1X, 1011HH), 'EXCRAT', 1011HH)  PRINT 9010  9010 FORMATI(1X, TEXTRAT', 9X'=18DHC', 125, 'EGRIE', 139, 'EXATO', 753, 'EXATOY  PRINT 9011 HIRONO, EGRIE, EXATO, EXATOY  9011 FORMATI(XY, EGRIA', 9X'=18DHC', 725, 'EGRIE', 139, 'EXATO', 753, 'EXATOY  9011 FORMATI(XY, EGRIA', 9X'=18DHC', 125, 'EGRIE', 139, 'EXATO', 753, 'EXATOY  9011 FORMATI(XY, EGRIA', 9X'=18DHC', 125, 'EGRIE', 139, 'EXATO', 753, 'EXATOY  9011 FORMATI(XY, EGRIA', 9X'=18DHC', 125, 'EGRIE', 139, 'EXATO', 753, 'EXATOY  9012 FORMATI(XY, EGRIA', 9X'=18DHC', 125, 'EGRIE', 139, 'EXATO', 753, 'EXATOY  9013 FORMATICAL STATEMENT (XY, 151, 151, 151, 151, 151, 151, 151, 15	CINH15840 CINH15860 CINH15870 CINH15870 CINH15870 CINH15870 CINH15870 CINH15870 CINH15870 CINH15870 CINH15870 CINH15970 CINH15
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FOR DESUGGING THE PROGRAM  CCMMCM/CGT/RCL,RML,SPM,EXRATE COMMCM/CGG/ISUG EXATOY-EXATECHIRAND EXATOY-EXATECHIRAND EXTISM-EXATION-EXATO EXTISM-EXATOH-EXATO IFIEUG-GG-0, GG TC 9999 EGFIE =0.69 PRINT 14 14 FORMATI/IX,101Hm),'EXCRAT',101Hm)) PRINT 9010 FORMATI(IX*IXCAT',9X*6IRDHC',125,'EGRIE',139,'EXPID',753,'EXRTOY PRINT 901 (ZX.5E14-3) PRINT 901 (ZX.5E14-3) PRINT 901 (ZX.5E14-3) SUBROUTINE FLORMT (T,TSLAB,INDIC,0)  THIS SUBROUTINE DETERMINES THE BUILDING HEAT LCSS THROUGH THE FLORM SLAB.	CINH15840 CINH15860 CINH15880 CINH15880 CINH15880 CINH15880 CINH15890 INH15910 INH16010 INH16
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  GUMENACRI MACL MAL, SPM, EXRATE  COMMONATOR DAY  COMMONATOR DAY  COMMONATOR DAY  EXATOY-EXATEBEIRONO  EXATOY-EXATEBEIRONO  EXATOY-EXATOY-OF  EXATSH-EXATOY-OF  EXATSH-EXATOR DAY  FOR THE 40.69  PRINT 40.10  PRINT 40.10  PRINT 40.10  PRINT 40.11  PRINT 40.11  PRINT 40.11  PRINT 40.11  PRINT 40.11  PRINT 40.11  SUBROUTINE FLORAT (T,TSLAB, INDIC, 0)  SUBROUTINE FLORAT (T,TSLAB, INDIC, 0)  THIS SUBROUTINE DETERMINES THE BUILDING HEAT LCSS THROUGH THE FLORK SLAB.	CINH15840 CINH15860 CINH15860 CINH15860 CINH15870 CINH15870 CINH15870 CINH15910 INH15910 CINH16000 CINH16000 CINH16000 CINH16000 CINH16070
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FOR DESUGGING THE PROGRAM  CCMMCN/CRT/RCL, RML, SPM, EXRATE COMMON/SUG/ISUG EXATOY-EXATE-SIRONO EXATOY-EXATE-SIRONO EXATOY-EXATE-SIRONO EXATOY-EXATE-SIRONO EXATOY-EXATOY-EXATO INFORMATI(/IX,)OIGHA), "EXCRAT',10(1HA)) PRINT 901 PRI	CINH15840 CINH15860 CINH15880 CINH15880 CINH15880 CINH15880 CINH15890 INH15910 INH16010 INH16
000000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FOR DESUGGING THE PROGRAM  CCMMCN/CRT/RCL, RML, SPM, EXRATE COMMON/SUG/ISUG EXATOY-EXATE-SIRONO EXATOY-EXATE-SIRONO EXATOY-EXATE-SIRONO EXATOY-EXATE-SIRONO EXATOY-EXATOY-EXATO INFORMATI(/IX,)OIGHA), "EXCRAT',10(1HA)) PRINT 901 PRI	CINH15840 CINH15860 CINH15860 CINH15860 CINH15870 CINH15870 CINH15870 CINH15910 INH15910 CINH16000 CINH16000 CINH16000 CINH16000 CINH16070
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  LBUG-AN INTEGER CODE USED FGR DEBUGGING THE PROGRAM  CAMBOA/CRI /ACL, RWL, SPM, EXRATE COMMON PROBLEM	CINH15840 CINH15860 CINH15880 CINH15880 CINH15880 CINH15870 CINH15870 CINH15870 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH15930 INH16930 INH16930 INH16930 INH16930 INH16930 INH16930 INH16930 INH16930 INH16930 INH16940 CINH16400 CINH164000 CINH164100 CINH164100 CINH164100 CINH164100 CINH164100 CINH164100
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LESS  13UG-AN INTEGER CODE USED FGR DEGUGGING THE PROGRAM  CCAMENACRI FACL, RHL, SPM, EXRATE CCAMENACRI FACL, RHL, SPM, EXCRATI, 10(1HH) FINT 9010 FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMID', 153, 'EXMID' FORMATI (1X, FECKAT', 9X'BIRDIC', 125, 'EGRTE', 139, 'EXMID', 153, 'EXMI	CINH15840 CINH15860 CINH15860 CINH15870 CINH16070 CINH16
00000	EXATOY-WEIGHT OF EXCRETA PER DAY, LES.  13UG-AN INTEGER CODE USED FGR DEGUGING THE PROGRAM  CCAMCA/CRT/RCL.RWL.SPM.EXRATE COMMON/BOSTOROM EXATO-EXATOY-APP EXATO-EXATOY-APP EXATO-EXATOY-APP EXATO-EXATOY-APP EXATO-EXATOY-APP EXATO-EXATOY-APP EXATO-EXATOY-APP EXATO-EXATOY-APP EXATO-EXATOY-APP EXATOR EXATOR EXATOR EXATOR EXATOR PRINT 1/1 x, 1011Hb), 'EXCRAT', 1011Hb) } PRINT 4011. HIRDING.EGRTE.EXATOY PRINT 4011. HIRDING.EGRTE.EX	CINH15840 CINH15860 CINH15860 CINH15860 CINH15860 CINH15870 CINH15870 CINH15890 INH15910 INH15910 INH15910 INH15910 INH15910 INH15930 INH16930 INH16930 INH16930 INH16930 INH16930 INH16930 INH16930 INH16930 CINH16930



C LISTED HERE	C1NH16190
C many many many many many many many many	C INH16200
C **********************	
C BLTH-BUILDING LENGTH, FEET	CINH16220 CINH16230
C CAMU-PRODUCT OF FLOOR UTILIZATION, AREA, SPECIFIC HEAT, AND MASS	CINH16240
C HEIT-BUILDING HEIGHT, FEET	CINH16250
C HTFLO-HEAT TRANSFER PER UNIT FLOUR AREA, BTU PER HOUR-SQ. FT.	C INH16260
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PRUGRAM	CINH16270
54321 CONTINUE	INH16280
C INDIC-AN INDEX TO CHANGE SLAB TEMPERATURE E.G. DAILY NOT EACH	CINH16290
C CALCULATION	CINH16300
C Q-HEAT TRANSFER THROUGH FLOOR, BTU PER HCUR	C INH16310
C T-INSIDE TEMPERATURE, DEGREES R AND F C TSLAB-TEMPERATURE OF FLOOR SLAB, DEGREES R AND F	CINH16320 CINH16330
C UTILIZ-PORTION OF FLOOR NOT COVERED BY MANURE, SQ FT	CINH16340
C WIDTH-CUILDING WIDTH, FEET	CINH16350
C	C INH16360
c	CINH16370
C ************************************	***CINH16380
C CMMON/BUG/ IBU 3	INH16390
COMMON/BLOG/BLTH, WIDTH, HEIT	INH16400
COMMUN/WTHR/AVTOBO, RANGE, ATMP, MO, ID, IY, TDPF, VAROTA	INH16410
T=T-459.67 TSLA3=TSLAb-459.67	INH16420 INH16430
UTILIZ=.25	INH16440
C HEAT FLOW PER SQ FT	CINH16450
HTFL0=1.65*(TSLAB-(T+AVTDBO)/2)	INH16460
C TOTAL HEAT FLOW	CINH16470
Q=HTFLC+ULTH+WIDTH+UTILIZ	INH16480
IF (INDIC .NE. 1) GO TO 2	INH16490
C NEW SLAB TEMPERATURE	CINH16500
C SPECIFIC HEAT=0.156, PERRY P.3-136	C I NH16510 I NH16520
CAMU=UTILIZ*0.156*BLTH*WIDTH*(10./12.)*120. 1 TSLAB=TSLAB5*HTFLU/CAMU	INH16520
INDIC=0	INH16540
2 CONTINUE	INH16550
T=T+459.67	INH16560
TSLAB=TSLAB+459.67	INH16570
IF(I6UG.E0.0) GD TD 9999	INH16580
PRINT 17	INH16590
17 FORMAT(/1X,10(1HW), 'FLORHT',10(1HW))	IN416600
PRINT 9110 9110 FORMAT (1X, FLORHT', /9X, 'T', T25, 'TSLAB', T39, 'INDIC', T53, 'C', T	INH16610
1HTFLO*)	INH16630
PRINT 9111, T, TSLAB, INDIC, C, HTFLC	INH16640
9111 FORMAT (2X2E14.3,114,2E14.3)	INH16650
9999 CONTINUE	INH16660
RETURN	INH16670
END	INH16680
FUNCTION HAIN(CLTOT, TIN, VENTRT, UNTEVP, HA)	INH16690
C ************************************	
C	CINH16710
C THIS SUBROUTINE CALCULATES THE INSIDE ABSOLUTE HUMIDITY	C INH16720 C INH16730
C THIS SURROUTINE CALCULATES THE INSIDE ADSOLUTE HUMISTIT	C INH16740
Č	C1NH16750
C *************************	
c c	CINH16770
C	C I Nh16780
C DEFINITION OF TERMS	CINH16790
C	CINH16800
C SEE MAIN PROGRAM FOR ACRONYMS NOT	CINH16810
C LISTED HERE	C INH16820 C INH16830
C ************************************	
C	C INH16850
C AIRLBI-AN ESTIMATE OF THE MASS RATE OF VENTILATION, LBS OF AIR	CINH16860
C PER MINUTE	CINH16870
C AIRLBY-AIR FLOW RATE, LBS PER MIN	CINH16880



```
C BRDIMP-BODY TEMPERATURE OF A CHICKEN, DEGREES R
C HA-ABSCLUTE HUMIDITY OF INCOMMING AIR, LES PER LB
C HAIEST - AN ESTIMATE OF THE INSIDE ABSCLUTE HUMIDITY, LBS PER LB
                                                                             CINH16890
                                                                             CINH16900
                                                                             CINH16910
C HAIR-ABSOLUTE HUMIDITY OF INSIDE AIR, LBS PER LB CINH16920
C HL-LATENT HEAT OF EVAPORATION AT CHICKIN BUDY TEMPERATURE, BTU PER LBCINH16930
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
C QL-LATENT HEAT FRCM THE HENS, BTU/HR
                                                                             CINHIAGEO
C OLITOT-LATENT HEAT PRODUCTION OF BIRDS. BTU PER HOUR
                                                                             CINHIAGAO
54321 CONTINUE
                                                                              INH16970
C RESPI- AN ESTIMATE OF THE MASS MGISTURE RESPIRATION RATE PER UNIT OF CINH16980
          VENTILATION AIR, LB OF MOISTURE PER LB OF VENTILATED AIR
                                                                             CINH16990
C RESPIR-MOISTURE ADDED TO AIR BY BIRD RESPIRATION, LBS OF WATER PER
                                                                             C1NH17000
      LB OF AIR
                                                                             CINH17010
C TIN-TEMPERATURE. INSIDE HOUSE, DEGREES R(USED IN SUBROUTINES)
                                                                             CINH17020
C UEVPM-UNIT EVAPERATION RATE. LBS OF WATER PER MIN.
                                                                             C INH17030
C UNT-TOTAL WATER EVAPORATED IN UNIT TIME (SAME AS UNTEVP). BL/HR
                                                                             CINH17040
C UNTEVP-TOTAL WATER EVAPORATED IN UNIT TIME, LBS. PER HOUR CINH17050
C VENTAL-THE VENTILATION RATE IN THE HOUSE AT TIME OF CALCULATION.CFM CINH17060
Ċ
                                                                             CINH17070
                                                                             C INH17080
  CCMMON/PRESS/PATH
                                                                              INH17100
      C CMMON/BUG/IBUG
                                                                              INH17110
      AIRLB1=VENTRT/VSDBHA(TIN, HA)
                                                                              INH17120
      UEVPM=UNTEVP/60.
                                                                              INH17130
       BROTMP=107.1+459.67
                                                                              INH17140
      HI = HI DA ( BROTMP )
                                                                              INH17150
      RESPI=(21 TOT/(HI *60.1) /AIRIB1
                                                                               INH17160
      HAIFST=HA+RESP1
                                                                              INH17170
       AIRLBM=VENTRT/VSDBHA(TIN.HAIEST)
                                                                              INH17180
      RESPIR= (QLTCT/(HL*60.))/AIRLBM
                                                                              1NH17190
       HAIN=HA+UEVPM/AIRLBM+RESPIR
                                                                              INH17200
       IF(IBUG.EQ.0) GO TO 9999
                                                                              INH17210
       PRIUT 5
                                                                              INH17220
    5 FORMAT (1X.10(10HHAIN WWWW ) )
                                                                              INH17230
       PRINT 55.TIN.RESPIR.QLTOT.AIRLBM.HAIN.HA.UEVPM.UNTEVP.VENTRT
                                                                              INH17240
   55 FORMAT(7X, 'TIN', T21, 'RESPIR', T35, 'QLTCT', T48, 'AIRLS 4', T62, 'HAIN', INH17250
      1T76, 'HA', T90, 'UEVP', T104, 'UNTEVP', T113, 'VENTRT'/1X9E14.4)
                                                                              INH17260
 9999 CONTINUE
                                                                              INH17270
      DETHON
                                                                              THH1 7280
                                                                              INH17290
      END
      SUBPOUTING HEAD
  CINH17320
                                                                             CINH17330
   THIS SUBROUTINE WRITES THE HEADING FOR A TABLE
                                                                             CINH17340
ċ
                                                                             C1NH17350
                                                                             CINH17360
                                                                             CINH17370
  PRINT 13
                                                                              INH1 7390
   13 FORMAT (1H1)
                                                                              INH17410
   14 FORMAT(1X, 'TABLE 2 COMPARISON OF WEATHER AND POULTRY HOUSE EXPERIMINH17420
      1ENTAL CONDITIONS WITH EXPERIMENTAL AND CALCULATED MANURE MOISTURE INHI7430
      2CONTENT. 1)
                                                                              INH17440
      PRINT 1
                                                                              INH17450
      FRRMAT(/ 9x, 'THEORETICAL MOISTURE CONTENT (WET', INH17460
2 BASIS) OF POULTRY MANURE AFTEK DRYING WITH UNHEATED',/ INH17470
3 9x, 'VENTILATING AIR. THE MANURE IS AS DROPPED IN A CAGE LAYNINHH17480
      4G HOUSE WITH DROPPING BCARDS. 1)
                                                                              INH17500
      PRINT 15
   15 FORMAT(/T35,8(1H-), WEATHER DATA',8(1H-)/T15, 'STAFT', T22, 'END', T28INH17510
      1, 'EIRD', T35, 'AIMP', T42, 'TMAX', T48, 'TMIN', T54, 'TAVE', T60, 'TDP',
                                                                              INH17520
      2765. MCISTURE CONTENT, PERCENT'/T4, 'DATE', T15, 'TIME', T22, 'TIME',
                                                                              INH17530
      3728, 'ND. ', T35, 'PSI', T38, 4(5x, 'F'), T67, 'HGUSE 7 CALCULATED'/)
                                                                              INH17540
      RETURN
                                                                              INH17550
      END
                                                                              INH17560
      SULROUTINE HEDING
                                                                              INH17570
      PRINT 13
                                                                              INH17580
```



```
13 FORMAT (1H1)
                                                                           INH17590
      PRINT 1
                                                                           INH17600
      FORMAT (
                9X, THEORETICAL WATER REMOVAL AND MOISTURE CONTENT (WET INH17610
     2 BASIS) OF PUULTRY MANURE AFTER DRYING WITH UNHEATED: ,/
                                                                           INH17620
          9x, VENTILATING AIR. THE MANURE IS AS DEOPPED IN A CAGE LAYININH17630
     4G HOUSE WITH DRUPPING BUARDS. 1, /9x, INSIDE VALUES ARE THEORETICAL INH17640
     5 EXHAUST AIR*)
     PERRAT (//IX ,T73, MANURE', 198, MANURE'/IX INH17670
1 , OUTSIDE', T16, OUTSIDE', 130, FLD: RATE', T44, INSIDE', T58 INH17680
2 , INSIDE', T73, WATER REMOVED - LSS', 1765, MOISTURE CONTENT - PERCENHHIT690
    2 FORMAT (//1X
            TIME',
                      /1x 'DRY BULB', T16, 'DEW PLINT', T30, 'CFM',
                                                                           INH17700
     1T129. 'HRS' .
                                                                           INH17710
     BT44, DRY BULB', T58, DER PGINT', T72, CRE HOUR', T86, LISTED', INHI7720
CTIOO, AT END', T114, AT END', /1X, DEGREES F', TIO, DEGREES F', INHI7730
DT44, DEGREES F', T58, DEGREES F', T72, CF DRYING', T86, "HOURS CINHI7740
                               T114, 'OF LISTED',/1X, T86, 'DRYING', T100, INH17750
             T100, 'CF ONE',
     F'HOUR', T114, 'HOURS', /4x, '(1)', T20, '(2)', T34, '(3)', T48, '(4)', T62, '(INH17760
     G5)',T74,'(6)',T88,'(7)',T102,'(8)',T115,'(9)',T128,'(10)',/)
                                                                           INH17770
      RETURN
                                                                           INH17780
                                                                           INH17790
      END
      SUBROUTINE HOSTRT( BLTH, WIDTH, HEIT, RWL, RCL, QMECH, NATLGH, WATWDT,
                                                                           INH17800
     -WBFD, BRDS, BRDTHF, EXCOMC, DF, SPM, EXRATE,
                                                                 TMINE.DT. INH17810
     -BTIME.RUNLGT.INDIC.ELPWAR.ISETF.VRMAX.VRMIN.ISLABF)
                                                                           INH17820
CINH17840
C THIS SUBROUTINE PRINTS A TABLE GIVING THE CATE, DESIGN PARAMETERS,
                                                                          CINH17850
      MANAGEMENT CONDITIONS, WEATHER, AND SIMULATION DETAILS FOR THE
                                                                          CINH17860
      SPECIFIC COMPUTER RUN AND DATE.
                                                                          CINH17870
                                                                          CINH17880
  CINH17900
              DEFINITION
                                      OF TERMS
                                                                          CINH17910
                                                                          CINH17920
                  SEE MAIN PROGRAM FOR ACRONYMS NOT
                                                                          CINH17930
                             LISTED HERE
                                                                          C1NH17940
                                                                          C INH1 7950
  COMPON/WTHR/AVTDBO.KANGE.ATMP.MG.ID.IY.TDPF.VARDTA
                                                                           INH17970
      PRINT 1.MC.IC.IY
    1 FORMAT(1H1.1X, DESIGN VALUES USED DURING SIMULATION FOR DATA OF . INH17990
     212, 1/1, 12, 1/1, 12/1
      PRINT 2, BLTH, WIDTH, HEIT, RWL, RCL, QMECH
                                                                            INH18010
    2 FORMAT(/1x, BUILDING: '/5x, LENGTH, FT', T45, F10, 2/5x, WIDTH, FT',
                                                                            INH18020
     %T45,F10.2/5x, CEIL ING HEIGHT, FT ,T45,F10.2/5x, INSULATION-WALLS, INH16030
     *HR-F-SQ FT/STU',T45,F10.2/5X,'INSULATION-CEILING, HR-F-SQ FT/BTU',INH18040
     <T45,F10.2/5x,'LIGHTING HEAT, ETU/HR',T45,F10.2 )
      PRINT 20, WATLCH, MATEUT
                                                                            INHIBOAO
   20 FCRMAT(5x, WATERER LENGTH, FI', T45, F10, 2/5x, WATERER WIDTH, FT', T41NH18070
     $5,F10.2)
                                                                            TN418080
      PRINT 3.BRDS. + ERD. BRDTMF. EXCDMC.DF. SPM. EXRATE
    3 FORMAT(/1X, LAYING HENS: /5X, NUMBER OF HENS', T45, F10.2/5X, 'HEN WEINH18100
     -IGHT, LBS',T45,F10.2/5X,'BODY TEMPERATURE, F',T45,F10.2/5X,
                                                                            TUH18110
     /'EXCRETA MGISTURE CONTENT, %',T45,2PF10.2/5x,'EXCRETA DISTPIBUTIONINH16120
     # FACTOR'.T45.OPF10.2/5X.'SPECIFIC HEAT OF MANURE, BTU/LB-F',
                                                                            INH18130
     ,T45,F10.2/5X, EXCRETA PRODUCTION RATE, LBS/HEN-DAY',T45,F10.2)
                                                                            INH18140
      PRINT 4.TSETF. VRMAX, VRMIN, TSLABF
                                                                            INH18150
    4 FORMAT(/1x, 'VENTILATION: '/5x, 'INSIDE DESIGN(SET) TEMPERATURE, F', TINH18160
                 5x, MAXIMUM VENTILATING RATE, CFM , T45, F10.2/5x, MINIMINH18170
     ,45,F10.2/
     SUM VENTILATING RATE, CFM', T45, F10.2/5X, INITIAL SLAB TEMPERATURE, INH18180
     .F',T45,F10.2)
                                                                            INH18190
      PRINT 5, ATMP, AVTDBC, RANGE, TMINE
                                                                            INH18200
    5 FORMAT (/1x, 'WEATHER: '/5x, 'ATMOSPHERIC PRESSURE, PSI', 145, F10.2/
                                                                            INH18210
     -5x, AVERAGE GUTSIDE TEMPERATUPE, F', T45, F10.2/5x, UUTSIDE TEMPERATINH18220
     TURE RANGE, F', T45, F10.2/5x, 'CRITICAL LUW OUTSIDE TEMPERATURE, F', INH18230
     aT45.F10.2)
                                                                            INH18240
      PRINT &, DT, BTIME, RUNLGT, INDIC, ELPWAR
                                                                            INH18250
    6 FORMAT(/IX, 'SIMULATION DETAILS: '/5X, 'TIME INCREMENT-DT, HOURS',
                                                                            INH18260
     #T45.F10.2/5x. STARTING TIME, CLCCK HCURS .T45.F10.2/5X,
                                                                            In:H18270
     %'LENGTH OF KUN, HOURS', T45, F10.2/5X, 'SLAG INDEX', T45, 18
                                                                     /5X,
                                                                           INH18280
```



r ř

ř

c


```
*'LIGHTING INDEX', T45, F10.2/1H1)
                                                                TNH18290
     PUNCH 11.MO. 10.1Y
                                                                INH18300
  11 FORMAT (
                 'DESIGN VALUES USED DURING SIMULATION FOR DATA OF . INH18310
    012.1/1.12.1/1.12/1
     PUNCH 2, BLTH, WIDTH, HEIT, RWL, ECL, QMECH
     PUNCH 3. BR.DS. WERD . BR.DTMF. EXC.DMC. DF. SPM. EXRATE
     PUNCH 4. TSETF. VRMAX. VRMIN. TSLABF
                                                                INH18350
     PUNCH 5.ATMP.AVTOBO.RANGE.TMINE
     PUNCH 6.DT. STIME. RUNLGT. INDIC. ELPWAR
                                                                 INH18370
     PUNCH 7
   7 FORMAT (38(2H- ), 1 -11)
                                                                111118390
     RETURN
                                                                INH18400
                                                                10818410
     SUBROUTINE TEMBES (WATTSQ, ELPWAR, ST, TAV, TO, TOAVE, TSLAB, INDIC, INH18420
    1 VENTET . TCB . TCP . TI . QNEIT . TIOP)
C INH1 8440
C THIS SUBROUTING CALCULATES THE NET HEAT EXCESS OR SHORTAGE FOR
                                                               CINH18470
C A HEAT BALANCE USED TO ESTIMATE THE INSIDE TEMPERATURE
                                                               C 1NH18480
C IN *TEMPI*
                                                               C1NH18490
                                                               CTNH18500
                                                                CINH18510
CINH18530
                                                               CINH18540
            DEFINITION OF TERMS
                                                               CINH18550
                                                               C I NH1 8560
               SEE MAIN PROGRAM FOR ACRONYMS NOT
                                                               CINH18570
                         LISTED HERE
                                                               CINH18580
                                                                CIMH18590
CINH18610
C ELHT-X HEAT EQUIVALENT OF ELECTRIC POWER. BTU PER HR
                                                               CINH18620
C ELPWAR-AN INDEX FOR LIGHTS, ON=1, OFF=0
                                                               C INH1 8630
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
                                                               C INH18640
C INDIC-AN INDEX TO CHANGE SLAB TEMPERATURE E.G. DAILY RATHER THAN EACHCINH18650
       CALC.
                                                               CTUH18660
C OCTOT-HEAT TRANSFER THROUGH CEILING, BTU PER HOUR
C DEVAP-THE HEAT TO EVAPORATE THE WATER FROM MANURE AND WATERERS. BTU PCINH18680
                                                               CINH18690
C SETOT-HEAT TRANSFER THROUGH FLOOR, BTU PER HOUR
                                                               CIN418700
C OLTOT-LATENT HEAT PRODUCED BY BIEDS, BTU PER HOUR
C QUETT-NET HEAT EXCESS OR DEFICIENCY IN THE LAYING HOUSE, BTU PER HOURCINH18720
C QSTOT-SENSIBLE HEAT PRODUCED BY BIRDS, BTU PER HOUR
54321 CONTINUE
                                                                INH18740
C GVENT-HEAT ADDED TO AND REMOVED WITH VENTILATING AIR, BTU PER HOUR CINH18750
C CHTUT-HEAT TRANSFER THROUGH MALLS, BTU PER HOUR
C ST-ADJUSTED CEILING SOL-AIR TEMPERATURE, DEGREES F
                                                               CINH18760
                                                                CINH18770
C TAV-AVERAGE SOL-AIR TEMPERATURE, DEGREES F
                                                               CINH18780
C TOB-CUTSIDE DRY BULB TEMPERATURE, DEGREES R
                                                               CINH18790
 IDP-OUTSIDE DEW POINT TEMPERATURE, DEGREES R
                                                               CINH18800
C TI-TEMPERATURE INSIDE HOUSE AS CASRIED BY MAIN PROGRAM. DEGREES 6
                                                               C 1NH18810
C TO-OUTSIDE WALL SURFACE TEMPERATURE. DEGREES F
C TOAVE-AVERAGE OUTSIDE TEMPERATURE, DEGREES R AND F
                                                               CINH18830
C TSLAU-TEMPERATURE OF FLOOR SLAB, DEGREES R AND F
                                                                CINH18840
C VEHTRY-THE VENTILATION RATE IN THE HOUSE AT TIME OF CALCULATION, CFM CINH18850
C VS-ESTIMATE OF SPECIFIC VOLUME OF INSIDE AIR, CUBIC FEET PER LB. CINHI8860
C WATTSQ-ELECTRICAL POWER APPLIED TO BUILDING, WATTS PER SQ. FOOT
                                                               CINH18870
                                                                CINH18880
                                                                CINH18890
CCMMON/PRESS/PATM
                                                                 INH18910
     CCMMON/BUG/IBUG
                                                                 INH18920
     CALL ELHEAT (WATTSQ, ELPWAR, ELHT)
                                                                 INHIRGIO
     CALL BROHT (TI, ELPWAR, USTOT, QLTCT)
                                                                INH18940
     CALL CEILHT (TI.TOB.QCTOT)
                                                                 TNH18950
     CALL WALLHT (TI,TOB, QWINT)
                                                                [NH18960
     CALL FLORHT (TI.TSLAB.INDIC.CFTOT)
                                                                INH18970
     CALL DRYHET (VENTRI, TI, TDP, QEVAP, ELPKAR, TDB)
                                                                1NH18980
```



```
THE HEAT PICKED UP BY THE VENTILATING AIR
                                                                  CINH18990
     VS=VSDBHA(TI, HADP(TIDP))
                                                                    INH19000
      QVENT=(VENTRT/VS)*(CPA(TI)+CPh(TIDP)*HADP(TIDP))*(TDB-TI)*60.
                                                                    INH19010
     ONETT=ELHT+QSTOT+QLTOT+QCTUT+QWTOT+QFTOT+QVENI+QEVAP -QLTOT
                                                                    INH19030
  30 CONTINUE
                                          Mary and the state of
      IF(13UG.EQ.0) GO TO 9999
                                                                    INHIONAN
      PRINT 20
                                                                    INH19050
  20 FORMAT(/1X,10(1HW), 'TEMGES',10(1HW))
     PRINT 9120
 9120 FORMAT (1X, 'TEMGES',/T10, 'WATTSQ', T24, 'ELPWAR', T38, 'ST', T52, 'TAV', TNH19080
    1T66, 'TO', T80, 'TOAVE', T94 , 'TSLAB', T108, 'INDIC', /10X, 'VENTRT', T26
                                                                   INH19090
    2, 'TOB', T38, 'TDP', T52,' TI ', T66, 'QNETT', T80 , 'ELHT ', T94, 'QSTOT' INH19100
    3,T108, QLTOT ,/10x, QWTOT ,T24, QFTOT ,T38, QVENT ,T52, QEVAP , INH19110
    4T66 . 'QCTQT')
                                                                    INH19120
     PRINT 9121, WATTSQ. ELPWAR, ST. TAV. TO. TOAVE. TSLAB. INDIC. VENTRT.
                                                                    INH19130
         TDB.TDP.TI.QNETT.ELHT.QSTQT.QLTCT.QWTQT.QFTQT.QVENT.CEVAP.
                                                                    INH19140
    ZOCTOT
                                                                    INH19150
 9121 FGRMAT (2X7E14.3. I14/2X3E14.3/2X5E14.3)
                                                                    INH19160
 9999 CONTINUE
                                                                    INH19170
     RETURN
                                                                    INH19180
     FND
                                                                    INH19190
      SUBROUTINE TEMPIN (TGES, VENTRI, WATTSO, ELPWAR, TSLAB
                                                                    INH19200
     1.INDIC.TOB.TOP.TEMPI.TIDP)
  C TNH19230
                                                                   C INH19240
 THIS SUBROUTINE DETERMINES THE INSIDE TEMPERATURE BY A HEAT BALANCE, CINH19250
                                                                   C 1NH19260
                                                                   CINH19270
  CINH19290
C
            DEFINITION OF TERMS
                                                                   CINH19310
c
                                                                   CINH19320
                SEE MAIN PROGRAM FOR ACRONYMS NOT
                                                                   C I NH1 9330
                          LISTED HERE
                                                                   C [NH19340
                                                                   CINH19350
  CINH1 9370
 DONETT-DIFFERENCE DIFFERENTIAL OF QUETT, BTU/(HR-DEGREE R)
                                                                   CINH19380
C ELPWAR-AN INDEX FOR LIGHTS, ON=1, OFF=0
                                                                   CINH19390
C GES-INPUT VALUE OF TGES
                                                                   C INH19400
C IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM
                                                                   CINH19410
 INDIC-AN INDEX TO CHANGE SLAB TEMPERATURE E.G. DAILY NOT EACH
                                                                  CINH19420
        CALC.
                                                                   CINH19430
 JI-COUNTER USED FOR NEWTONIAN CONVERGENCE
                                                                   CINH19440
54321 CONTINUE
                                                                    INH19450
C ONETTY-NET HEAT FOR FUNCTION MINUS ONE, BTU PER HR.
                                                                   CINH19460
  QUETTN-MET HEAT FOR FUNCTION, BTU PER HR.
                                                                   CINH19470
  QNETTP-NET HEAT FOR FUNCTION PLUS CNE, BTU PER HR.
                                                                   CINH19480
 ST-ADJUSTED CEILING SOL-AIR TEMPERATURE, DEGKEES F
                                                                   CIMH19490
C TAY-AVERAGE SCI-AIR TEMPERATURE, DEGREES F
C TDB-DUTSIDE DRY BULB TEMPERATURE, DEGREES R
                                                                   CINH19500
                                                                   C TNH19510
 TDP-OUTSIDE DEW POINT TEMPERATURE. DEGREES R
                                                                   CINH19523
 TEMPI-THE INSIDE TEMPERATURE OBTAINED BY CONVERGENCE, DEGREES R
                                                                   CINH19530
  TGES-AN INTERMEDIATE GUESS VALUE USED FOR CONVERGENCE. DEGREES R
                                                                   CINH19540
 TO-OUTSIDE WALL SURFACE TEMPERATURE, DEGREES F
                                                                   CINH19550
 TOAVE-AVERAGE OUTSIDE TEMPERATURE, DEGREES K AND F
                                                                   CINH19560
 TP-AN ARRAY OF TEMPERATURES USED FOR NEWTONIAN CONVERGENCE, DEGREES RCINH19570
  TSLAB-TEMPERATURE OF FLOOR SLAB, DEGREES R AND F
                                                                   CINH19580
 VENTRI-THE VENTILATION RATE IN THE HOUSE AT TIME OF CALCULATION, CFM CINH19590
 WATTSQ-ELECTRICAL POWER APPLIED TO BUILDING, WATTS PER SQ. FOOT
                                                                   CINH19630
r
                                                                   CINH19610
                                                                   CINH19620
  DIMENSION TP(10)
                                                                    INHIGAGO
      CEMMON/BUS/I BUG
                                                                    INH19650
      DATA ST, TAV, TOAVE, TO/4*-9./
                                                                    INH19660
      GES=TGES
                                                                    INH19670
C BEGIN NEWTONIAN CONVERGENCE
                                                                   CINH19680
```




DO 500 JT=1,9	INH19690
TP(JT)=TGES-1.	INH19700
CALL TEMGES (WATTSQ, ELPWAR, ST, TAV, TG, TUAVE, TSLAB, INDIC, VENTRT, TO	INH19710
TP(JT)=TGES+1.	INH19730
CALL TEMGES (WATTSQ.ELPWAR, ST. TAV, TO, TJAVE, TSLAB, INDIC, VENTRE, TD	
1TOP, TP(JT), GNE ITP, TIDP)	INH19750
TP(JT)=TGES	INH19760
CALL TEMGES (KATTSQ,ELPWAR,ST,TAV,TC,TDAVE,TSLAB,INDIC,VENTRT,TD	
TTOP, TP (JT), QNE TTN, TIDP)	INH19780
DQNETT=(CNETTP-QNETTM)/2. TP(JT+1)=TP(JT)-CNETTN/DQNETT	INH19790 INH19800
IF(TP(JT+1)-TP(JT).LE.1.) GC TO 502	INH19310
TGES=TP(JT+1)	INH19820
500 CONTINUE	INH19830
PRINT 1500	INH19840
1500 FORMAT (1X'SUBROUTINE TEMPIN ERROR NOT LESS THAN 1 DEGREE F')	INH19850
502 CONTINUE TEMPI=TGES	INH19860
IF(IBUG.EQ.0) GO TO 9999	INH19870 INH19880
1F (TEMPI.GT.120+459.67)1BUG=2	INH19890
PRINT 21	INH19900
21 FGRMAT(/1x,10(1HW), TEMPIN*,10(1HW))	INH19910
PRINT 9130	INH19920
9130 FORMAT (1X, 'TEMPIN', /9X, 'GES', T25, 'VENTRT', T39, 'WATTSQ', T53,'	INH19930
1ELPWAR',167,'ST',181,'TAV',195,'TOAVE',T105,'TSLAB',T123,'INDIC' 2/10x,'TDB',T26,'TDP',T40,'TEMP1',T54,'TP(J1)',T68,'DQNETT',182	INH19950
3, 'GNETIM', T96, 'GNETIP', T110, 'GNETIN')	INH19960
PRINT 9131,GES, VENTRY, WATTSQ, ELPWAR, ST, TAV, TOAVE, TSLAB, INDIC, TDB	INH19970
1 TDP, TE-PI, TP(JT), DQNETT, QNETTM, CNETTP, QNETTN	INH19930
9131 FORMAT (2X8E14.3,114/2X8E14.3)	INH19990
IF(IBUG.EQ.2) IBUG=0 9999 CONTINUE	INH20000 INH20010
RETURN	INH20020
	INH20030
END	
END SUBROUTINE THEIN(TIN, VENTRI, THEIL, CL , HA, TUE)	INH20040 CINH20050
SUBROUTINE THBIN(TIN, VENTRT, THBI, CL , HA, TUB)  C  C  C  C  THIS SUBROUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE C SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSOUTE C HUMIDITY THRU A NEWTONIAN CONVERGENCE.	INH20040  *CINH20050 CINH20060 CINH20070 CINH20080 CINH20090 CINH20100 CINH20110
SUBROUTINE THBIN(TIR, VENTRI, THBI, CL , HA, TUB)  C THIS SUBROUTINE DETERMINES THE RETBULB TEMPERATURE BY EQUATING THE SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSOUTE HUMIDITY THRU A MENTONIAN CONVERGENCE.	INH20040  CINH20050 CINH20060 CINH20070 CINH20080 CINH20090 CINH20110 CINH20110
SUBROUTINE THBIN(TIN, VENTRT, THBI, CL , HA, TUB)  C THIS SUBROUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE C SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSOUTE C HUMIDITY THRU A NEWTONIAN CONVERGENCE.	INH20040  #CINH20050 CINH20060 CINH20070 CINH20080 CINH20190 CINH201100 CINH201100 CINH201100 *CINH201100
C THIS SUBROUTINE DETERMINES THE RETBULB TEMPERATURE BY EQUATING THE SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSOUTE HUMIDITY THRU A NEWTONIAN CONVERGENCE.	INH20040 CINH20050 CINH20060 CINH20070 CINH20080 CINH20090 CINH20110 CINH20110 CINH20110 CINH20110 CINH20120
SUBROUTINE THBIN(TIN, VENTRT, THBI, CL , HA, TUB)  C THIS SUBROUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE C SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSOUTE C HUMIDITY THRU A NEWTONIAN CONVERGENCE.	INH20040  #CINH20050 CINH20060 CINH20070 CINH20080 CINH20190 CINH201100 CINH201100 CINH201100 *CINH201100
SUBROUTINE THEIN(TIN, VERTRI, THEI, CL., HA, TUE)  C THIS SUBPOUTINE DETERMINES THE RETBULB TEMPERATURE BY EQUATING THE C SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSOUTE C HUMIDITY THRU A NEWTONIAN CONVERGENCE.  C C C C C C C C C C C C C C C C C C C	INH20040  *CINH20050 CINH20060 CINH20070 CINH20080 CINH20090 CINH20110
SUBROUTINE THBIN(TIN, VERTRI, THBI, CL , HA, TUB)  C C C THIS SUBROUTINE DETERMINES THE METBULB TEMPERATURE BY EQUATING THE SUM OF AIR VAPON SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSUJTE CHUMIDITY THRU A NEWTONIAN CONVERGENCE.  C D E F I N I I I I O N O F T E R M S  C SEE MAIN PROGRAM FOR ACRONYES NOT	INH20040  *CINH20050 CINH20060 CINH20070 CINH20080 CINH20090 CINH20110 CINH20150 CINH20150 CINH20150 CINH20150 CINH20150 CINH20110
SUBROUTINE THEIN(TIN, VENTRI, THEI, CL., HA, TUB)  C THIS SUBPOUTINE DETERMINES THE RETBULB TEMPERATURE BY EQUATING THE SUM OF ALR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSOLUTE CLUMBUTY THRU A NEWTONIAN CONVERGENCE.  C C C C C C C C C C C C C C C C C C C	INH20040  *CINH20050 CINH20060 CINH20070 CINH20080 CINH20090 CINH20100 CINH20110
SUBROUTINE THBIN(TIN, VENTRI, THBI, CL., HA, TUB)  C C C THIS SUBROUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE COMMON AND AND AND AND AND AND AND AND AND AN	INH20040  *CINH20050 CINH20060 CINH20070 CINH20070 CINH20070 CINH20100 CINH20100 CINH20110 CINH20110 CINH20120 CINH20140 CINH20140 CINH20140 CINH20140 CINH20150 CINH20140 CINH20150 CINH20160 CINH20160 CINH20170
SUBROUTINE THBINITIN, VENTRI, THBI, CL , HA, TUB)  C THIS SUBPOUTINE DETERMINES THE RETBULB TEMPERATURE BY EQUATING THE SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSUJTE CL HUMIDITY THRU A NEWTONIAN CONVERGENCE.  C D E F I N I T I O N O F T E R M S  SEE MAIN PROGRAM FOR ACRONYES NOT LISTED HERE	INH20040  *CINH20050 CINH20060 CINH20070 CINH20070 CINH20070 CINH20100 CINH20110
SUBROUTINE THBINI(TIN, VENTRI, THBI, CL., HA, TUB)  C  C  THIS SUBPOUTINE DETERMINES THE METBULB TEMPERATURE BY EQUATING THE SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSLUTE CHUMIDITY THRU A NEWTONIAN CONVERGENCE.  C  C  C  D  F  I  SEE MAIN PROGRAM FOR ACRONYMS NOT LISTED MERE  C  DFX - DERIVATIVE OF *FX *, (LBS CF H2C/LBS OF AIR)/DEGREE R	INH20040  *CINH20050 CINH20060 CINH20070 CINH20070 CINH20070 CINH20100 CINH20100 CINH20110 CINH20110 CINH20120 CINH20140 CINH20140 CINH20140 CINH20140 CINH20150 CINH20140 CINH20150 CINH20160 CINH20160 CINH20170
SUBROUTINE THBINITIN, VERTRIT, THBI, CL , HA, TUB)  C THIS SUBPOUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE C SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSUJTE C C C C C C C C C C C C C C C C C C C	INH20040  *CINH20050 CINH20060 CINH20070 CINH20080 CINH20080 CINH20190 CINH20110 CINH20120 CINH20210 CINH20220 CINH20220 CINH20220
SUBROUTINE THBIN(TIN, VENTRI, THBI, CL., HA, TUB)  C  THIS SUBPOUTINE DETERMINES THE METBULB TEMPERATURE BY EQUATING THE SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSLUTE HUMIDITY THRU A NEWTONIAN CONVERGENCE.  C  D E F I N I T I O N O F T E R M S  C  SEE MAIN PROGRAM FOR ACRONYMS NOT LISTED HERE  C  DFX - DERIVATIVE OF *FX *, (LBS OF HZC/LBS OF AIR)/DEGREE R  C FKM, FKN, FKM - A FUNCTION OF *VB* EQUAL TO ZERO WITH THE CORRECT  VALUE OF H2CS	INH20040  *CINH20050 CINH20060 CINH20070 CINH20070 CINH20090 CINH20100 CINH20110 CINH20120 CINH20120 CINH20120 CINH20200 CINH20200 CINH20200 CINH20220 CINH20220 CINH20230 CINH20220
SUBROUTINE THBINITIN, VERTRIT, THBI, CL , HA, TUB)  C THIS SUBROUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSUUTE CHUMIDITY THRU A NEWTONIAN CONVERGENCE.  C D E F I N I T I O N O F T E R M S  C SEE MAIN PROGRAM FOR ACRORYES NOT LISTED HERE C LISTED HERE C FXH, FRI, FXP - A FUNCTION OF *VE* EJUAL TG, ZERO WITH THE CGRRECT VALUE OF NOS.	INH20040  *C1NH20050 C1NH20050 C1NH20050 C1NH20010 C1NH20030 C1NH20100 C1NH20100 C1NH20110 C1NH20120 *C1NH20120 C1NH20120 C1NH20120 C1NH20130 C1NH20200
SUBROUTINE THBINITIN, VENTRI, THBI, CL , HA, TUB)  C  C  C  C  C  C  C  C  C  C  C  C  C	INH20040  **C1NH20050 C1NH20050 C1NH20050 C1NH20050 C1NH20030 C1NH20030 C1NH20100 C1NH20100 C1NH20110 C1NH20110 C1NH20110 C1NH20120 C1NH20110 C1NH20140 C1NH20140 C1NH20140 C1NH20150 C1NH20150 C1NH20150 C1NH20150 C1NH20150 C1NH20150 C1NH20200
SUBROUTINE THBIN(TIN, VERTRI, THBI, CL., HA, TUB)  THIS SUBPOUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSOLUTE CLOTH THRU A NEWTONIAN CONVERGENCE.  DEFINITION OF TERMS  SEE MAIN PROGRAM FOR ACRONYS NOT  LISTED HERE  C FXM. FXM. FX PA A FUNCTION OF *VE* EQUAL TO ZERG WITH THE CORRECT CRACK FXM. FXM. FXM. GAS TO THE FXM. FXM. FXM. GAS TO THE CORRECT CRACK WITH THE CORRECT CRACK FXM. FXM. FXM. GAS TO THE FXM. FXM. FXM. FXM. GAS TO THE FXM. FXM. FXM. FXM. GAS TO THE FXM. FXM. FXM. GAS TO THE FXM. FXM. FXM. FXM. GAS TO THE FXM. FXM. FXM. FXM. GAS TO THE FXM. FXM. FXM. FXM. FXM. GAS TO THE FXM. FXM. FXM. FXM. FXM. FXM. FXM. FXM.	INH20040  *C1NH20050 C1NH20050 C1NH20050 C1NH20010 C1NH20030 C1NH20100 C1NH20100 C1NH20110 C1NH20120 *C1NH20120 C1NH20120 C1NH20120 C1NH20130 C1NH20200
SUBROUTINE THBIN(TIN, VENTRI, THBI, CL , HA, TUB)  C THIS SUBROUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE SUM OF ALR VAPOR SOURCES TO THE PSYGRAMMETRICALLY DETERMINED ABSOLUTE CHUMIDITY THRU A NEWTONIAN CONVERGENCE.  C D E F I N I T I O N O F T E R M S  C SEE MAIN PROGRAM FOR ACKCRYMS NOT  LISTED HERE C THE SUBSTITUTIVE OF *FX *, LBS CF H2C/LBS OF AIR//DEGREE R  FXM. FM, FXP — A FUNCTION CF *NS * LUAL TO ZERG WITH THE CORRECT  VALUE OF *ROS  C TWALUE OF *SC * COUSTION AIR, LB OF H2G PER LB OF DA  THE THIS IOE WETBULD TEMPERATURE, DEGREES R  C WELL-HUMIDITY RATIC FOR GUISION AIR, LB OF H2G PER LB OF DA  THE THIS IOE WETBULD TEMPERATURE, DEGREES R  C WELL-THE STREET OF THE CHESUE STREET TO THE CORRECT  C WELL-THE STREET THE CHESUE STREET TO THE PSYCHOLOGY.	INH20040  *CINH20050 CINH20050 CINH20050 CINH20050 CINH20080 CINH20080 CINH20190 CINH20290
SUBROUTINE THBINITIN, VERTRIT, THBI, CL , HA, TUB)  C  C  THIS SUBPOUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE C SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSUJTE HUMIDITY THRU A NEWTONIAN CONVERGENCE.  C  D E F I N I T I O N O F T E R M S  C  SEE MAIN PROGRAM FOR ACRORYMS NOT LISTED HGRE  C  DFX - DERIVATIVE OF *FX *, LLBS CF HZC/LBS OF AIR)/DEGREE R  C FXM, FXM, FXP - A FUNCTION OF *W8 EZUAL TO ZERO WITH THE CORRECT  C TWALUE OF NOSS  H-HUMIDITY RATIC FOR CUTSIDE AIR, LB OF HZC PER LB OF DA  MOGS-A DIGGREE R  MOGS-A DIGGREE ROULD IEMPERATURE, DEGREES R  MOGS-A DIGGREE ROULD IEMPERATURE FOR USE WITH NEWTONIAN CONVERENCE,  MOGS-A DIGGREE ROULD IEMPERATURE FOR USE WITH NEWTONIAN CONVERENCE,  MOGS-A DIGGREE ROULD IEMPERATURE FOR USE WITH NEWTONIAN CONVERENCE,  MOGS-A DIGGREE ROULD IEMPERATURE FOR USE WITH NEWTONIAN CONVERENCE,  MOGS-A DIGGREE ROULD IEMPERATURE FOR USE WITH NEWTONIAN CONVERENCE,  MOGS-B THE TOTAL THE THE TOTAL THE T	INH20040  *C INH20050 C INH20050 C INH20050 C INH20080 C INH20080 C INH20080 C INH201010 C INH20110
SUBROUTINE THBINITIN, VENTRI, THBI, CL , HA, TUB)  C  C  THIS SUBPOUTINE DETERMINES THE METBULB TEMPERATURE BY EQUATING THE SUM OF AIR MAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSUJTE HUMBITY THRU A NEWTONIAN CONVERGENCE.  C  C  D E F I N I T I O N O F T E R M S  SEE MAIN PROGRAM FOR ACRONYKS NOT LISTED HERE  C  DFX - DERIVATIVE OF *FX *, (LBS CF H2C/LBS OF AIR)/DEGREE R  C FXM, FXM, FXP - A FUNCTION OF *WS* EQUAL TO ZERO WITH THE CORRECT VALUE OF MSC.  C H4-HUMBITY MATIC FOR CUISIDE AIR, LB OF H2C PER LB OF DA  TMBI- HISSIE WEIBULB TEMPERATURE, DEGREE R  MOTION DEGREE R  MOSS-A DEGREE R  MOSS-A DEGREE R  MOSS-A DEGREE R  MOSS-FIRST GUESS FOR WB, DEGREES R	INH20040  *CINH20050 CINH20050 CINH20050 CINH20050 CINH20050 CINH20100 CINH20100 CINH20100 CINH20110 CINH20110 CINH20130 CINH20200 CINH2
SUBROUTINE THBINITIN, VERTRIT, THBI, CL., HA, TUB)  C THIS SUBROUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSUUTE CHUMIDITY THRU A NEWTONIAN CONVERGENCE.  C D E F I N I T I O N O F T E R M S  C SEE MAIN PROGRAM FOR ACRORY'S NOT LISTED HERE C LISTED HERE C THIS TO NOT THE CORRECT OF THE REPORT OF THE CORRECT OF THE PROCESS OF AIR NOT CONVERENCE THAT HE CORRECT OF THE PAGE OF THE CORRECT OF THE PROCESS OF AIR NOT CONVERENCE, CONSIDER THE MEDIT OF	INH20040  **CINH20050 CINH20050 CINH20050 CINH20070 CINH20070 CINH20070 CINH20070 CINH20070 CINH20070 CINH20100 CINH20110 CINH20200
SUBROUTINE THBIN(TIN, VENTRI, THBI, CL., HA, TUB)  C  C  THIS SUBPOUTINE DETERMINES THE METBULB TEMPERATURE BY EQUATING THE SUM OF AIR MAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSLUTE HUMIDITY THRU A NEWTONIAN CONVERGENCE.  C  C  D E F I N I T I O N O F T E R M S  C  SEE MAIN PROGRAM FOR ACRCHYMS NOT LISTED HERE  C  DFX - DERIVATIVE OF *FX *, (LBS CF H2C/LBS OF AIR)/DEGREE R  C FKM, FKN, FKP - A FUNCTION OF *WB* EJUAL TO ZERO WITH THE CORRECT  VALUE OF **ROSS  C H4-HUMIDITY MATIC FOR CUTSIDE AIR LB OF H2D FER LB OF DA  T MBI- INISIDE WEIBULB TEMPERATURE, DEGREE R  C MBGS-A DISSES NETBULB TEMPERATURE FOR USE WITH NEWTONIAN CONVERENCE,  C MBGS-I FIRST GUESS FCR WB, DEGREES R	INH20040  *CINH20050 CINH20050 CINH20050 CINH20050 CINH20050 CINH20050 CINH20050 CINH20100 CINH20100 CINH20110 CINH20110 CINH20130 CINH20200 CINH20300 CINH20300 CINH20310 CINH20310 CINH20310 CINH20310 CINH20310 CINH20310 CINH20310 CINH20310 CINH20310
SUBROUTINE THBINITIN, VERTRIT, THBI, CL , HA, TUB)  C THIS SUBROUTINE DETERMINES THE WETBULB TEMPERATURE BY EQUATING THE SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSOLUTE CHUMIDITY THRU A NEWTONIAN CONVERGENCE.  C D E F I N I T I O N O F T E R M S  C SEE MAIN PROGRAM FOR ACRCRYMS NOT LISTED HERE C LISTED HERE C THIS FAP - A FUNCTION OF *VE* CLUB TO JEED WITH THE CORRECT VALUE OF *NOS C TXM, FAM, FAP - A FUNCTION OF *VE* CLUB TO JEED WITH THE CORRECT C TALL THIS TO SUBSTITUTE THE CORRECT OF THE PROGRAM FOR ACCRETING THE PROGRAM FOR ACCRETING THE PROGRAM FOR ACCRETING THE PROGRAM FOR ACCRETING THE PROGRAM FOR ACCRETE WITH THE CORRECT CHAPHURITH FAP - A FUNCTION OF *VE* CLUB TO JEED WITH THE CORRECT OF THE PROGRAM FOR ACCRETING THE PROGRAM FOR ACCRETE THE PROGRAM FOR ACC	INH20040  **CINH20050 CINH20050 CINH20050 CINH20050 CINH20050 CINH20050 CINH20050 CINH20100 CINH20110 CINH20150 CINH20250
SUBROUTINE THBIN(TIN, VENTRI, THBI, CL., HA, TUB)  C  C  THIS SUBPOUTINE DETERMINES THE METBULB TEMPERATURE BY EQUATING THE SUM OF AIR MAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSLUTE HUMIDITY THRU A NEWTONIAN CONVERGENCE.  C  C  D E F I N I T I O N O F T E R M S  C  SEE MAIN PROGRAM FOR ACRCHYMS NOT LISTED HERE  C  DFX - DERIVATIVE OF *FX *, (LBS CF H2C/LBS OF AIR)/DEGREE R  C FKM, FKN, FKP - A FUNCTION OF *WB* EJUAL TO ZERO WITH THE CORRECT  VALUE OF **ROSS  C H4-HUMIDITY MATIC FOR CUTSIDE AIR LB OF H2D FER LB OF DA  T MBI- INISIDE WEIBULB TEMPERATURE, DEGREE R  C MBGS-A DISSES NETBULB TEMPERATURE FOR USE WITH NEWTONIAN CONVERENCE,  C MBGS-I FIRST GUESS FCR WB, DEGREES R	INH20040  *CINH20050 CINH20050 CINH20050 CINH20050 CINH20050 CINH20050 CINH20050 CINH20100 CINH20100 CINH20110 CINH20110 CINH20130 CINH20200 CINH20300 CINH20300 CINH20310 CINH20310 CINH20310 CINH20310 CINH20310 CINH20310 CINH20310 CINH20310 CINH20310
SUBROUTINE THBINITIN, VERTRIT, THBI, CL , HA, TUB)  C THIS SUBPOUTINE DITERMINES THE WETBULB TEMPERATURE BY EQUATING THE C SUM OF AIR VAPOR SOURCES TO THE PSYCHROMETRICALLY DETERMINED ABSUJTE HUMIDITY THRU A NEWTONIAN CONVERGENCE.  C D E F I N I T I O N O F T E R M S  C SEE MAIN PROGRAM FOR AGRORYMS NOT LISTED HERE  C DFX - DERIVATIVE OF *FX *, LLBS OF HZC/LBS OF AIR)/DEGREE R LISTED HERE  C TRYN, FRY, FXP - A FUNCTION OF *WS* EZUAL TO ZERO WITH THE CORRECT C MAY AUGUST OF STORY OF THE CONTROL OF	INH20040  **CIMH20050 CINH20050 CINH20070 CINH20070 CINH20070 CINH20090 CINH20100 CINH20100 CINH20110 CINH



```
IF(TIN-LT-492.) GO TO 492
                                                                    INH20390
     WBGS=KBDBHA(TIN.HADBRH(TIN.D.5))
                                                                    INH20400
 492 CONTINUE
                                                                    INH20410
     WACS 1=WAGS
                                                                    INH20420
     DO 50 I=1.9
                                                                    INH20430
     WB(I)=WBGS+1.
                                                                    INH20440
 400 CONTINUE
                                                                    1NH20450
     CALL EVPWTR (UNT . VENTR T. TIN. WB (I) . EVPH2O. E VPMUR. 2)
                                                                    TNH20460
     FXP=HAIN(QL/2. .TIN. VENTRT. UNT/2. .HA)-HAPV(PVDBWB(TIN. #B([)))
                                                                    INH20470
     WRITT=WRGS-1-
                                                                    INH20480
     CALL EVPATRIUNT
                      . VENTRI, TIN. WB(1).EVPH20.EVPMUR.2)
                                                                     INH20490
     EXM = HAIN(CL/2. TIN. VENTRI. UNI/2. HA) - HAPV(PVDRKS(TIN. WB(I)))
                                                                    INH20500
     WR(I)=WRCS
                                                                     TNH20510
     CALL EVPATRIUNT
                      . VENTET, TIN, WB(I), EVPH20, EVPMUR, 21
                                                                     TNH20520
     FXN=HAIN(QL/2.,TIN,VENTRT,UNT/2.,HA)-HAPV(PVDBhB(TIN,WB(I)))
                                                                     INH20530
     DEX= (EXP-EXM)/2.
                                                                     INH20540
     WRITALL-WRITH-EXMINEY
                                                                     TNH20550
     IF(kB(I+1)-WB(I), LE, 1, AND, WB(I+1)-WB(I), GF, 0, )GO TO 52
                                                                     INH20560
     URCS=ARSILRITATIV
                                                                     TUH20570
  50 CONTINUE
                                                                     INH20580
     PRINT 1500
                                                                     INH20590
 1500 FGRMAT (1X. SUBROUTINE TW3IN ERROR NOT LESS THAN 1 DEGREE F.)
                                                                     INH20600
  52 CONTINUE
                                                                     INH20610
     TWEI-WAGS
                                                                     INH20620
     IF(IBUG.EQ.O) GG TG 9999
                                                                     INH20630
     PRINT 21
                                                                     1 VH2 0640
  21 FORMAT (/1X,10(1HW), TWBIN ',10(1HW))
                                                                     TNH20650
     PRINT 23.TIN. VENTRT. TWBI. WBGS1
                                                                     111120460
  23 FURMAT(9X, 'TIN', T25, 'VENTRT', T39, 'TWBI', T53, 'WBGS1'/2X, 4E14.5)
                                                                     111420670
     PRINT 22 FXP FXP FXN DFX
                                                                     TNH20490
  22 FORMAT(5X, 'FXP', T23,
                              'FXM',T37, 'FXN',T55,'DFX'/2X,4E14.5)
                                                                    INH20690
 9999 CONTINUE
                                                                     TMH20700
     RETURN
                                                                     INH20710
     END
                                                                     TNH20720
     SUBROUTINE VENRAT(WATTSO, ELPWE, TDB ,TIN ,TDP ,DPI,
                                                                    1:3420730
    1AVTDBO.TSLAB.VENTG.INDIC.IND. 2CCNST.VENTR.VRMAX)
                                                                    INH20740
 ċ
                                                                   C INH20760
                                                                   CINH20770
 THIS SUBROUTINE DETERMINES THE VENTILATION RATE BY A HEAT BALANCE.
                                                                   C 1NH20780
                                                                   CINH20740
 C 10H20930
C
             DEFINITION OF TERMS
                                                                   CINH20840
c
                                                                   C.1 UH2 08 50
c
                SEE MAIN PROGRAM FOR ACRENYMS NOT
                                                                   CINH20860
                          LISTED HEEF
                                                                   CINH20870
                                                                   C1NH20880
 CINH20930
C AVSCLT-AVERAGE SOL-AIR TEMPERATURE. DEGREES F
                                                                   C INH20910
C AVIDBO-AVERAGE OUTSIDE TEMPERATURE, DEGREES F
                                                                   C INH20920
 DONET -DIFFERENCE DIFFERENTIAL OF JNET
                                                                   CINH20930
C DPI-INSIDE DEMPGINT TEMPERATURE (SAME AS TIDP), DEGREES R
                                                                   C INH20940
C DRPSAR-SURFACE AREA OF DROPPINGS. SQ. FEET
                                                                   CINH20950
C ELHT- HEAT EQUIVALENT OF ELECTRIC POWER, BTU PER HR
                                                                   CINH20960
 ELPWR-AN INDEX INDICATION LIGHTS ARE ON OR OFF
                                                                   CINH20970
C IND-AN INDICATUR TO BY PASS CONVERGENCE
                                                                   CINH20980
C INDIC-AN INDEX TO CHANGE SLAB TEMPERATURE E.G. DAILY KATHER THAN EACHCINH20990
C JK-COUNTER USED FOR NEWTONIAN CONVERGENCE
C QCUNST-THE SUM OF HEAT BALANCE FACTORS REMAINING CONSTANT DURING CONVCINH21010
     , BTU PER HR.
                                                                   CINH21020
54321 CONTINUE
                                                                     INH21030
C OCTOI-HEAT TRANSFER THROUGH CELLING, BTU PER HOUR
                                                                   C 1NH21040
C OFTUT-HEAT TRANSFER THROUGH FLOOR, BTU PER HOUR
                                                                   CINH21050
C OLIDI-LATENT HEAT PRODUCED by BIRDS. BIU PER HOUR
                                                                   CINH21060
C ONETM-VET HEAT FOR FUNCTION MINUS ONE, BTU PER HR.
                                                                   CINH21070
C ONETN-NET HEAT FOR THE FUNCTION. BTU PER HR.
                                                                   C 171H21080
```



```
C ONETP-NET HEAT FOR FUNCTION PLUS ONE, BTU PER HE.
                                                                           CINH21090
C OSTCT-SENSIBLE HEAT PRODUCED BY BIRCS, BTU PER HOUR
                                                                           CINH21130
C UNTOT-HEAT TRANSFER THROUGH WALLS, BTU PER HOUR
                                                                           CINH21110
C SOLT-ADJUSTED CEILING SOL-AIR TEMPERATURE. DEGREES F
                                                                           C1NH21120
C TOB-DUTSIDE DRY BULB TEMPERATURE, DEGREES R
                                                                           C1EH21130
C TOBO2-GUTSIDE WALL SURFACE TEMPERATURE. DEGREES R
                                                                           C INH21140
C TOP-OUTSIDE DEW POINT TEMPERATURE, DEGREES R
                                                                           CINH21150
C TIN-TEMPERATURE, INSIDE HOUSE, DEGREES R(USED IN SUBROUTINES)
                                                                           CINH21160
C TSLAB-TEMPERATURE OF FLOOR SLAD, DEGREES R AND F
                                                                           CINH21170
C V-THE ERRCR IN VENTILATING RATE AT END OF CONVERGENCE, CFM CINH21180
C VENTG-AN INTERMEDIATE GUESS VALUE FOR VENTILATION RATE (SUBROUTINE VACINH21190
C VENTR-THE VENTILATION RATE IN THE HOUSE AT GIVEN TIME (SUBROUTINE VALCINH21200
  , CFM
                                                                           C INH21210
  VR-AN ARRAY OF VENTILATION PATES USED FOR NEWT. CONVERGENCE. CFM
                                                                           CINH21220
C VRMAX-MAXIMUM VENTILATION RATE OF HOUSE, CFM
                                                                           CINH21230
C WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE
                                                                           CINH21240
C WATTSQ-ELECTRICAL POWER APPLIED TO BUILDING, WATTS PER SQ. FUOT
                                                                           C TNH21250
                                                                           CINH21260
                                                                           CINH21270
DIMENSION VR(22)
                                                                            INH21290
      CCMMON/F VP/DRPSAR . WATSAR
                                                                            INH21300
      COMMON/BUG/IBUG
                                                                            INH21310
      DATA AVSCLT, SOLT, TDB02/3*-9./
                                                                            INH21320
      CALL ELHEAT (WATTSQ,
                                     ELPWR, ELHT)
                                                                            INH21330
      CALL BROHT (TIN ,ELPWR, QSTCT, QLTGT)
                                                                            INH21340
      CALL CEILHT (TIN, TDB, QCTOT)
                                                                            INH21350
      CALL FALLHT (TIN, TEB, OWTET)
      CALL FLORHT (TIN ,TSLAB, INCIC, QFTOT)
                                                                            INH21370
      QCONST=ELHT+QSTGT+QLTOT+QCTGT+QWTGT+QFTGT -QLTGT
                                                                            INH21380
      IF(IND.EC.2) GG TG 2
                                                                            INH21390
C BEGIN NEWTONIAN CONVERGENCE OF VENTILATION RATE
                                                                           CINH21400
      DO 400 JK=1.20
                                                                            INH21410
      VR(JK)=VENTG-.01*VENTG
                                                                            INH21420
      CALL VNTNET (VP(JK). TDB. TDP. TIN. QCONST, QNETM. ELPWAR. DPI)
                                                                            INH21430
      VR(JK)=VENTG +.01*VENTG
                                                                            INH21440
      CALL VNTNET (VR(JK), TDB, TDP, TIN, QCOAST, CNETP, ELPWAR, DPI)
                                                                            INH21450
      VR (JK) = VENTG
                                                                            INH21460
      CALL VNTNET (VR(JK), TDB, TDP, TIN, QCGAST, (NETN, ELPKAR, DPI)
                                                                            INH21470
      DONET= (CNETP-QNETM)/(.02*VENTG)
                                                                            INH21480
      VR(JK+1)=VR(JK)-QNETN/DQNET
                                                                            INh21490
      VENTG=VE (JK+1)
                                                                            TAH 21500
      IF(VR(JK+1)-VR(JK).LE..O1*VRMAX.AND.VE(JK+1)-VR(JK).GE.O.) GU TO
                                                                            1NH21510
                                                                            INH21520
     1 402
  400 CCUTINUS
                                                                            INH21530
      V = VR(JK+1) - VR(JK)
                                                                            1NH21540
      PRINT 1000 .V
                                                                            INH21550
 1000 FORMAT(1X, 'AN ERROR IN SUBROUTINE VENEATE, THE VENTILATION RATE NOTINH21560
     1 LESS THAN .01 X VMAX.V-ERROR='.E14.5)
                                                                            INH21570
      GG TO 20
  402 CONTINUE
                                                                            INH21590
      IF(VENTG.LT.G.) IBUG=2
                                                                            INH21600
      VENTE = ABS(VENTG)
                                                                            INH21610
    2 CONTINUE
                                                                            INH21620
      1F(19UG.EQ.O) GC TU 9999
                                                                            IN421630
   20 CONTINUE
                                                                            INH21640
      PRINT 240, VENTG
                                                                            INH21650
  240 FORMAT(1x, 2(7HVENRAT ), 'VENTG=', G20.9)
                                                                            INH21660
      PRINT 22
                                                                            INH21670
   22 FGRMAT(/1x,10(1Hw), 'VENEAT',10(1Hw))
                                                                            INH21680
      PRINT 9060
                                                                            INH21690
 9060 FORMAT (2x, 'VENRATE', /9x, 'WAITSQ', T25, 'ELPVR', T39, 'TOB', T53, 'TIN', INH21700
     1T67, 'TDP', TS1, 'SOLT', T95, 'AVSGLT', T109, 'TDSG2', T123, 'AVTD86',/
                                                                            INH21710
     210x, 'TSLAE', T26, 'VENTG', T40, 'INDIC', T54, 'GCONST', T68, 'GCONST',
                                                                            INH21720
     3T82, 'VENTR', T9C, 'VMAX', T109, 'DRPSAR', T124, '+ ATSAR'/11X'QNETM', T27 INH21730
     4, 'QNETP', T41, 'CNETN', T55, 'DCNET', T69, 'VR(JK)')
                                                                            INH21740
      PRINT 9061, WATTSC, ELPHK, TDG, TIN, TDP, SQLT, AVSQLT, TDBU2, AVTDBO,
                                                                            INH21750
     ITSLAB, VENTG, INDIC, QCONST, QCONST, VENTR, VRMAX, DRPSAR, WATSAR, QNETM,
                                                                            INH21760
      2UNETP . GNETN . DGNET . VR (JK)
                                                                            INH21770
 9061 FURMAT (2X9514.3/2X2514.3.114.6614.3/2X5614.3)
                                                                            INH21790
      IF(1803.E0.2) IBUG=0
                                                                            INH21790
 9999 CONTINUE
                                                                            INH21800
```




	4 CONTINUE	INH21810
		INH21820
	RETURN	
	END	INH21830
	SUBROUTINE VNTNET (VENTG, TDB, TDP, TIN, QCUNST, QNET, ELPWAR, DPI)	INH21640
C		
C		CINH21860
C		CINH21870
С		CINH21880
С	FOR VENTILATION, CVENT, AND THE	CINH21890
С		CINH21900
С		CINH21910
c		CINH21920
č		CINH21930
		CINH21950
C		CINH21940
С		CINH21950
C		CINH21960
·		
C	DEFINITION OF TERMS	CINH21970
С		CINH21980
č	SEE MAIN PROGRAM FOR ACRONYMS NOT	CINH21990
C	LISTED HERE	CINH22000
c		CINH22010
č		C [NH3 3030
С		CINH22030
С	DPI-INSIDE DEMPCINT TEMPERATURE (SAME AS TIDP), DEGREES R	CINH22040
		CINH22050
С	EVAPH20-WATER EVAPORATED FROM WATERS, LBS. PER HOUR	CINH22060
С	EVPMJR-WATER EVAPORATED FROM MANURE, LBS. PER HOUR	CINH22070
č		C1NH22080
С	CONVERGENCE CALC., BTU PER HR.	CINH22090
C	QEVAP-THE HEAT TO EVAPORATE THE WATER FROM MANURE AND WATERERS, BTU	CINH22100
C		CINH22110
C	ONET-NET HEAT FLOW FROM HEAT BALANCE AND USED FOR CONVERVENCE.	CINH22120
C	IDEALLY ZERO, BIU PER HOUR	CINH22130
		CINH22140
5	4321 CONTINUE	INH22150
C	TOB-OUTSIDE DRY BULB TEMPERATURE, DEGREES R	CINH22160
ć.		
		CINH22170
C	TIN-TEMPERATURE, INSIDE HOUSE, DEGREES RIUSED IN SUBROUTINES)	CINH22180
C		CINH22190
	THE AN ESTIMATE OF THE COLOR FROM THE THE THE ATTENTION AND THE STATE OF THE STATE	CTHILDRAN
C	PER LB	CINH22210
c		
Ċ		C INH22220
c	WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE	C INH22220
000	WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE	CINH22230
c	WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE	
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE	C INH22230 C INH22240
000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE	CINH22230 CINH22240 CINH22250
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE  COMMON/PRESS/PATM	CINH22230 CINH22240 CINH22250 INH22260
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE	CINH22230 CINH22240 CINH22250 INH22260 INH22270
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE  COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM	CINH22230 CINH22240 CINH22250 INH22260
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE  COMMON/PRESS/PATM CHMON/EVP/DRPSAR, WATSAR COMMON/BUS/TSUG	C INH22230 C INH22240 C INH22250 INH22260 INH22270 INH22280
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE  COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/RUF/J BUG VS-VSDBHA(TIN, HADP (DPI))	C INH22230 C INH22240 C INH22250 INH22260 INH22270 INH22280 INH22290
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PAIM COMMON/EVP/ORPSAR HATSAR COMMON/EVP/ORPSAR HATSAR COMMON/EVP/ORPSAR HATSAR OF MONTH WELL AND THE MATSAR OF WATER WATER TO THE MATSAR OF WATER	C INH22230 C INH22240 C INH22250 INH22260 INH22270 INH22280 INH22290 INH22290
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN HOUSE  COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/RUF/J BUG VS-VSDBHA(TIN, HADP (DPI))	C INH22230 C INH22240 C INH22250 INH22260 INH22270 INH22280 INH22290
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM COMMON/RUS/13UG VS-VSDBHA(TIN, HADP(DPI)) OVENT=(VENTC/VS)*(COA(TIN)+CPN(TDP)*HADP(DPI))*(TDB-TIN) *60. CALL DRYHET (VENTC/ IN, TDP, GEVAF, ELPWAR, TDB)	CINH22230 CINH22240 PCINH22250 INH22260 INH22270 INH22280 INH22290 INH22300 INH22310
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESSYPATM COMMONUM PROPERTY OF THE PROP	CINH22230 CINH22240 CINH22250 INH22260 INH22270 INH22280 INH22290 INH22300 INH22310 INH22320
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM COMMON/RUS/13UG VS-VSDBHA(IIN, HADP(DPI)) OVENT=(VENTC/VS)*(COA(TIN)+CPN(TDP)*HADP(DPI))*(TDB-TIN) *60. CALL DRYHET (VENTC, IIN, TDP, QEVAP, ELPWAR, TDB) ONET=GCONST-CUPENT-CUVAP IF(13UG, EC.O.) SO TC 9999	CINH22230 CINH22240 CINH22250 INH22260 INH22270 INH22280 INH22280 INH22290 INH22300 INH22310 INH22330 INH22330
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM COMMON/RUS/13UG VS-VSDBHA(IIN, HADP(DPI)) OVENT=(VENTC/VS)*(COA(TIN)+CPN(TDP)*HADP(DPI))*(TDB-TIN) *60. CALL DRYHET (VENTC, IIN, TDP, QEVAP, ELPWAR, TDB) ONET=GCONST-CUPENT-CUVAP IF(13UG, EC.O.) SO TC 9999	CINH22230 CINH22240 CINH22250 INH22260 INH22270 INH22280 INH22280 INH22290 INH22300 INH22310 INH22330 INH22330
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM INTO COMMON COM	CINH22230 CINH22240 CINH22250 INH22260 INH22270 INH22290 INH22300 INH22310 INH22320 INH22330 INH22330 INH22330 INH223340
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/RUG/130G VS-VSDBHA(TIN, HADP(DPI)) OVENT=(VENTC/VS)*(CPA(TIN)+CPN(TDP)*HADP(DPI))*(TDB-TIN) *60. CALL DRYHET (VENTC, IIN, TDP, QEVAP, ELPWAR, TDB) ONET=CONST-CUPENT-CUVAP IF(130G, EC.0.) SO TO 6999 PATNT 23 23 FORMATI(XIX, 10(11%), *VNITNET*, 10(11M))	CINH22230 CINH22240 FINH22250 INH22270 INH22270 INH22270 INH22280 INH22290 INH22310 INH22310 INH22320 INH22330 INH22330 INH22340 INH22350
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM INTO COMMON COM	CINH22230 CINH22240 CINH22250 INH22260 INH22270 INH22290 INH22300 INH22310 INH22320 INH22330 INH22330 INH22330 INH223340
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/RUG/130G VS-VSDBHA(TIN, HADP(DPI)) OVENT=(VENTC/VS)*(CPA(TIN)+CPN(TDP)*HADP(DPI))*(TDB-TIN) *60. CALL DRYHET (VENTC, IIN, TDP, QEVAP, ELPWAR, TDB) ONET=CONST-CUPENT-CUVAP IF(130G, EC.0.) SO TO 6999 PATNT 23 23 FORMATI(XIX, 10(11%), *VNITNET*, 10(11M))	CINH22230 CINH22240 FINH22250 INH22270 INH22270 INH22270 INH22280 INH22290 INH22310 INH22310 INH22320 INH22330 INH22330 INH22340 INH22350
0000	WATSAR-SURFACE AREA OF EXPOSED WATER 1% MCUSE  COMMON/PRESS/PATM COMMON/EVP/DRPSAR, WATSAR COMMON/EVP/DRPSAR, WATSAR COMMON/EVP/DRPSAR, WATSAR COMMON/EVP/DRPSAR, WATSAR COMMON/EVP/DRPSAR, WATSAR VENUS	CINH22230 CINH22240 CINH22250 INH22250 INH22270 INH22270 INH22290 INH22300 INH22310 INH22320 INH22320 INH22330 INH22340 INH22340 INH22350 INH22350 INH22350 INH22350 INH22370
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM OVERTIFY (PRITCH (PAITIN) + CPW(TDP) + HADP(DPI)) + (TDB-TIN) + 60. CALL-DRET (PAITIN) + (TDR) + (EPWAR, TDB) (FIIDUG-EC.O) SOTIC 9999 PAINT 2 23 FORMATI/IX,10(1Hm), *VNTNET*,10(1Hm)) DPY = -9. EVPRUR=-1. EVPRUP=-1.	C INH2 2230 C INH2 2240 C INH2 2240 C INH2 2250 INH2 2270 INH2 2270 INH2 2290 INH2 2300 INH2 2310 INH2 2310 INH2 2310 INH2 2340 INH2 2340 INH2 2340 INH2 2350 INH2 2350 INH2 2350 INH2 2350 INH2 2350 INH2 2350
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PAIM COMMON/PRESS/PAIM COMMON/PUP / ORPSAR. WATSAR COMMON/PUP / ORPSAR. WATSAR COMMON/PUB / ORPSAR. COMMON/PUB / ORPSAR. VENUE / ORPSAR. VENUE / ORPSAR. CALL DRYHET (VENTC, 71M. TDP, QEVAP, ELPWAR, TDB) QNT-SCOMST-UVENT-COVAP IF(13UG, EO. 0) SO TC 9999 PKIR 2 23 FOWAT IN, 10(1HK), *VNTKET*, 10(1HK)) EVPM.RR-1. EVPM.RR-1. EVPM.RR-1. EVPM.RB-1. EVPM.RD-1. DPHARMALQTIDP)	C INH2 22 30 C INH2 22 40 C INH2 22 50 INH2 22 50 INH2 22 70 INH2 22 90 INH2 23 90 INH2 23 10 INH2 23 10 INH2 23 30 INH2 23 40 INH2 23 40 INH2 23 40 INH2 23 40 INH2 23 50 INH2 23 50
0000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM OVERTIFY (PRITCH (PAITIN) + CPW(TDP) + HADP(DPI)) + (TDB-TIN) + 60. CALL-DRET (PAITIN) + (TDR) + (EPWAR, TDB) (FIIDUG-EC.O) SOTIC 9999 PAINT 2 23 FORMATI/IX,10(1Hm), *VNTNET*,10(1Hm)) DPY = -9. EVPRUR=-1. EVPRUP=-1.	C INH2 2230 C INH2 2240 C INH2 2240 C INH2 2250 INH2 2270 INH2 2270 INH2 2290 INH2 2300 INH2 2310 INH2 2310 INH2 2310 INH2 2340 INH2 2340 INH2 2340 INH2 2350 INH2 2350 INH2 2350 INH2 2350 INH2 2350 INH2 2350
00000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM OVERT=(VENTC/VS)**(CPATTIN)**(PK(TDP)**HADP(DPI))**(TDB-TIN) **60. CALL DXYMET (VENTC, TIN, TDP, CEVAP, ELPWAR, TDB) OWLT=COMST-ECVENT*-ECVAP IFIJOUS-CO.0) SOT TO 999 23 PRESS/PATM COMST-COMENT (JN, VENTRET*, 10(1HM)) DPY = -7. EVPLOS-1. DPHA-HADR(TDP) PRINT 9070	C INH2 23 30 C INH2 240 C INH2 22 40 C INH2 22 50 I INH2 22 70 I INH2 22 70 I INH2 23 90 I INH2 23 10 I INH2 23 10 I INH2 23 10 I INH2 23 10 I INH2 23 50 I INH2 23 50
00000	COMMON/PRESS/PAIM COMMON/PRESS	CINH2230 CINH22240 CINH22250 IIH22250 IIH22270 INH22270 INH2230 IIH2230 IIH2230 IIH2230 IIH22340 IIH22350 IIH22350 IIH22350 IIH22370 IIH22470
00000	WATSAR-SURFACE AREA OF EXPOSED WATER 1% MCUSE  COMMON/PRESS/PATH  COMMON/PRESS/PATH  COMMON/EVP/DAPSAR WATSAR  COMMON/EVP/DAPSAR WATSAR  COMMON/EVP/DAPSAR WATSAR  COMMON/EVP/DAPSAR WATSAR  OFMIT-EVENTC/VSI-EVENTLE/BITTOP,GEVAP,ELPWAR,TDB)  ORLI-ECOMOST-EVENTL-CVAP  PATRIC 260.0) SO TC 9999  PATRIC 260.0 SO TC 999  PA	C INH2 2230 C INH2 2240 C INH2 2250 INH2 2270 INH2 2270 INH2 2270 INH2 2290 INH2 2310 INH2 2310 INH2 2310 INH2 2300 INH2 2300 INH2 2350 INH2 2350 INH2 2350 INH2 2370 INH2 2470 INH2 2470 INH2 2470
00000	WATSAR-SURFACE AREA OF EXPOSED WATER 1% MCUSE  COMMON/PRESS/PATH  COMMON/PRESS/PATH  COMMON/EVP/DAPSAR WATSAR  COMMON/EVP/DAPSAR WATSAR  COMMON/EVP/DAPSAR WATSAR  COMMON/EVP/DAPSAR WATSAR  OFMIT-EVENTC/VSI-EVENTLE/BITTOP,GEVAP,ELPWAR,TDB)  ORLI-ECOMOST-EVENTL-CVAP  PATRIC 260.0) SO TC 9999  PATRIC 260.0 SO TC 999  PA	C INH2 2230 C INH2 2240 C INH2 2250 INH2 2270 INH2 2270 INH2 2270 INH2 2290 INH2 2310 INH2 2310 INH2 2310 INH2 2300 INH2 2300 INH2 2350 INH2 2350 INH2 2350 INH2 2370 INH2 2470 INH2 2470 INH2 2470
00000	COMMON/PRESS/PATM COMMON/PRESS	C INH2 2230 C INH2 2240 E I IH2 2250 I IH2 2260 I IH2 2270 I IH2 2280 I INH2 2290 I IH2 2290 I IH2 2300 I IH2 2310 I IH2 2310 I IH2 2350 I IH2 2450 I IH2 2420 I IH2 2420 I IH2 2430
00000	WATSAR-SURFACE AREA OF EXPOSED WATER 1% MCUSE  COMMON/PRESS/PATH COMMON/EVE/JORPSAR, WATSAR COMMON/EVE/JORPSAR, WATSAR COMMON/EVE/JORPSAR, WATSAR COMMON/EVE/JORPSAR, WATSAR COMMON/EVE/JORPSAR, WATSAR ONE-T-COUNTS-EVERIAL COPAP (FILSUS-CE.O.) SO TE 9999 FILSUS-CE.O.) SO TE 9999 FILSUS-CE.O.) SO TE 9999 FILSUS-CE.O.) SO TE 9999 FILSUS-CE.O.) SO TE 9999 FILSUS-CE.O. SO TE 999 FILSUS-CE.	C INH22230 C INH22240 C INH22250 INH22270 INH22270 INH22270 INH22290 INH22300 INH22310 INH22310 INH22310 INH22340 INH22340 INH22340 INH22340 INH22340 INH22340 INH22340 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH22400 INH22401 INH22401 INH22410
00000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM OVERTO/VES   COMMON/PRESS/PATM ONT-COCONST-EVERTO-CAPT IF (1804, EC.) SO TC 9999 PATRIT 23 23 FORMATI/IX, 1011HW), "WITRET', 1011HW)) DPY =-? EVPMONR=-1. EVPHOON-IX, "WITRET', 1011HW), "DPY? EVPMONR=-1. EVPHOON-IX, "WITRET', 101, "LOCATED, "LOCATED, "LOPY,	C INH2 2230 C INH2 2240 E I IH2 2250 I IH2 2260 I IH2 2270 I IH2 2280 I INH2 2290 I IH2 2290 I IH2 2300 I IH2 2310 I IH2 2310 I IH2 2350 I IH2 2450 I IH2 2420 I IH2 2420 I IH2 2430
00000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM COMMON/PRESS/PATM OVERTO/VES   COMMON/PRESS/PATM ONT-COCONST-EVERTO-CAPT IF (1804, EC.) SO TC 9999 PATRIT 23 23 FORMATI/IX, 1011HW), "WITRET', 1011HW)) DPY =-? EVPMONR=-1. EVPHOON-IX, "WITRET', 1011HW), "DPY? EVPMONR=-1. EVPHOON-IX, "WITRET', 101, "LOCATED, "LOCATED, "LOPY,	CINH22230 CINH22260 INH22260 INH22270 INH22270 INH22270 INH22300 INH22300 INH22310 INH22310 INH22310 INH22310 INH22310 INH22310 INH22350 INH22350 INH22350 INH22360 INH22370 INH22370 INH22370 INH22390 INH22390 INH22390 INH2240 INH2240 INH2240 INH2240 INH2240 INH22430 INH22430 INH22430 INH22430 INH22430 INH22430 INH22430 INH22440 INH22440
00000	WATSAR-SURFACE AREA OF EXPOSED WATER 1% MCUSE  COMMON/PRESS/PAIM COMMON/PRESS/PAIM COMMON/PRESS/PAIM COMMON/PRESS/PAIM COMMON/PRESS/PAIM COMMON/PRESS/PAIM COMMON/PRESS/PAIM COMMON/PRESS/PAIM COMMON/PRESS/PAIM OVERT=CUPTCYSIS*CEQAITIN*CPW(TDP)*HADP(DPI))*(TDB-TIN) *60. CALL DRYHET (VENTC, ITN.TDP, GEVAP, ELPWAR, TDB) ONT=COMENST-UVENT-CCVAP IF(13UG, EO.O) 50 TC 9999 PKINT 22 23 OPMINIALX, 10(1HK), *VNINET*, 10(1HK)) DPIA-HALDPITOP, PRINT 9070 PERMAT (IX, *VNINET*, /9X, *VENTG*, T.25, *TDB*, T.39, *TDP*, T.53, *TIN*, TG 1.00 PK 11, *ORE SAR*, *TBS*, *WATSAR*, T109, **OCONST*, T123, *UNET*, 2007, 100, **OCONST*, T123, *UNET*, 2007,	C INH22230 C INH22240 FC INH22250 INH22270 INH22270 INH22270 INH22290 INH22300 INH22310 INH22310 INH22310 INH22340 INH22340 INH22350 INH22360 INH22360 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH22370 INH2240 INH2240 INH2240 INH2240 INH2240 INH2240 INH2240 INH2240 INH2240 INH2240 INH2240 INH2240 INH2240 INH22440 INH22440 INH22440 INH22440 INH22440 INH22440 INH22440 INH22440 INH22440
00000	WATSAR-SURFACE AREA OF EXPOSED WATER IN MCUSE  COMMON/PRESS/PATM INDIVIDUAL COMP IFIBUGECO.D SO TC 9999 PATMIT 23 23 FORMATI/IX,1011M1, "WITKET',1011HW1) DPY =-9. EVPRUP-1. DPHA-HACP(ID) PRINT 30. 2010 FORMAT (13, "COMPANO", "TAS, "NATSAR", 1109, "COMST', "TAS, "TIN', TO COMPANO", "WITKET', "YX, "VENTG', "T25, "T108, "T39, "T0P', "T53, "TIN', T6 EVPRUP-1. DPIANTACOMINATORY TO SENSOR "T155, "WATSAR", T109, "COMST', "T123, "UNET', T27, "T3, "T54, "EVPRUP, "T54	C INH22230 CINH22240 CINH22250 INH22270 INH22270 INH22270 INH22270 INH22300 INH23300 INH23300 INH23300 INH23300 INH23300 INH23300 INH23300 INH22340 INH22340 INH22340 INH22350 INH22360 INH22360 INH22360 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22400 INH22450 INH22450 INH22450 INH22450 INH22450 INH22450 INH22450 INH22450 INH22450 INH22450
00000	COMMON/PRESS/PAIM OVERTIES/PAIM OVERTIES/PAIM ONT-TOCOMST-CVENT-COAP IFIISUG-E0-0) SD TC 9999 PAINT 23 37 DOWATI/2, 10(1HW), 'VNINET', 10(1HW)) OVERTIES/PAIM OVERTIES/PAIM EVPHZO=-1. DPHIGH-ALDRICH DPHIGH-ALDRICH 1/DRY 'LTSI, 'DRPSAM', 1755, 'MATSAM', 1109, 'COMST', 1123, 'UNET', 2/10X, 'CVENTI, 726, 'HADD', '140, 'CVPMUM, 1754, 'EVPNEO', 1753, 'DRY JSI, 'GUMP' PRITT 9070 STEPRIT 1004  10 DEPTI 1004  10 DEPTI 1005  10 D	C 19H2 22 30 C 19H2 22 40 C 19H2 22 50 I 19H2 22 60 I 19H2 22 60 I 19H2 22 70 I 19H2 22 70 I 19H2 23 70 I 19H2 24 70 I 19H
00000	COMMON/PRESS/PAIM OVERTIES/PAIM OVERTIES/PAIM ONT-TOCOMST-CVENT-COAP IFIISUG-E0-0) SD TC 9999 PAINT 23 37 DOWATI/2, 10(1HW), 'VNINET', 10(1HW)) OVERTIES/PAIM OVERTIES/PAIM EVPHZO=-1. DPHIGH-ALDRICH DPHIGH-ALDRICH 1/DRY 'LTSI, 'DRPSAM', 1755, 'MATSAM', 1109, 'COMST', 1123, 'UNET', 2/10X, 'CVENTI, 726, 'HADD', '140, 'CVPMUM, 1754, 'EVPNEO', 1753, 'DRY JSI, 'GUMP' PRITT 9070 STEPRIT 1004  10 DEPTI 1004  10 DEPTI 1005  10 D	C 19H2 22 30 C 19H2 22 40 C 19H2 22 50 I 19H2 22 60 I 19H2 22 60 I 19H2 22 70 I 19H2 22 70 I 19H2 23 70 I 19H2 24 70 I 19H
00000	WATSAR-SURFACE AREA OF EXPOSED WATER 11: MCUSE  COMMON/PRESS/PATH OVERLY (PRESS/PATH OVERLY (PRESS/PATH OVERLY (PATH) OVERLY (PRESS/PATH OVERLY (PATH) OPT PATH OPT PAT	C 19H2 2230 C 19H2 2240 C 19H2 2250 I 19H2 2250 I 19H2 2270 I 19H2 2270 I 19H2 2300 I 19H2 2310 I 19H2 2410 I 19H2 I 19H2 2410 I 19H2 2410 I 19H2 2410 I 19H2 2410 I 19H2 2410 I 19H2 2410 I 19H2 2410
00000	COMMON/PRESS/PAIM OVERTIES/PAIM OVERTIES/PAIM ONT-TOCOMST-CVENT-COAP IFIISUG-E0-0) SD TC 9999 PAINT 23 37 DOWATI/2, 10(1HW), 'VNINET', 10(1HW)) OVERTIES/PAIM OVERTIES/PAIM EVPHZO=-1. DPHIGH-ALDRICH DPHIGH-ALDRICH 1/DRY 'LTSI, 'DRPSAM', 1755, 'MATSAM', 1109, 'COMST', 1123, 'UNET', 2/10X, 'CVENTI, 726, 'HADD', '140, 'CVPMUM, 1754, 'EVPNEO', 1753, 'DRY JSI, 'GUMP' PRITT 9070 STEPRIT 1004  10 DEPTI 1004  10 DEPTI 1005  10 D	C 19H2 22 30 C 19H2 22 40 C 19H2 22 50 I 19H2 22 60 I 19H2 22 60 I 19H2 22 70 I 19H2 22 70 I 19H2 23 70 I 19H2 24 70 I 19H




	SUBROUTINE WALLHT(1IN.TDB.0)	INH22510
C	***************************************	
C	***************************************	
		CINH22530
C		C1NH22540
C	THIS SUBROUTINE DETERMINES THE BUILDING HEAT LOSS	CINH22550
C	THROUGH THE WALLS	C1NH22560
C	*** SINCE END OF RUGM WITH BIRDS NOT EXPCSED DIRECTLY TO OUTSIDE,	CINH22570
C	*** ASSUME 1/2 HEAT LOSS.	CINH22580
C		C1NH22590
Č		C1NH22600
C	**************	
C		CINH22620
C		CINH22630
C	DEFINITION OF TERMS	CINH22640
C		CINH22650
C	SEE MAIN PROGRAM FOR ACRENYMS NCT	C1NH22660
c	LISTED HERE	CINH22670
	ETSTED HERE	
C		CINH22680
C	*** ** ** ** ** ** * * * * * * * * * * *	
С		CINH22700
	AWLDEFINED IN CRITMP	C1NH22710
C	BLTH-BUILDING LENGTH, FEET	CINH22720
C	HEIT-BUILDING HEIGHT. FEET	CINH22730
5	4321 CONTINUE	INH22740
	IBUG-AN INTEGER CODE USED FOR DEBUGGING THE PROGRAM	CINH22750
č	QHEAT TRANSFER THROUGH WALLS, BTU PER HOUR	CINH22760
С	RWLDEFINED IN CRITMP	CINH22770
C	TDB DEFINED IN MAIN	CINH22780
C	TIN DEFINED IN MAIN	CINH22790
C	WIDTH-BUILDING WIDTH, FEET	CINH22800
č		CINH22810
č		CINH22820
č	***********************************	
C		
	COMMON/BUG/IBUG	INH22840
	C CMMON/BLDG/BLTH, WIDTH, HEIT	INH22850
	AWL=HEIT*2.*(BLTH+WIDTH/2.)	INH22860
	RwL=14.11	INH22870
	Q=(TDB-TIN)*AWL/RWL	INH22880
	IF (IBUG.ED.O) GC TO 9999	INH22890
	PRINT 7	INH22900
	7 FORMAT(/1X,10(1HW), "WALLHT",10(1HW))	I NH2 29 10
	PRINT 9090	INH22920
	9090 FORMAT(1X,'WALLHT'/9X,'TIN',T25,'TDB',T39,'Q',T53,'AHL',T67,'RHL	
	1781, 'HETT', 795, 'BL TH', T109, 'K IDTH')	INH22940
	PRINT 9091, TIN, TDB, C, AWL, RWL, HEIT, BLTH, WIDTH	INH22950
	9091 FORMAT (2X.8E14.3)	INH22960
	9999 CONTINUE	INH22970
	RETURN	INH22980
	END	I NH22990
	ENG.	1:41122990
	SUBROUTINE WETHER (AN, TMINM)	INH23000
C	***************	
C		CINH23020
č		C I NH2 3 0 3 0
č	THIS SUBROUTINE GENERATES A DAILY WEATHER PATTERN, I.E. DRYBULB	CINH23040
č	AND DEMPOINT TEMPERATURES, BASED ON U.S. WEATHER SERVICE DATA (NN=1)	
C	OR ON VARIFICATION DATA (NN=0).	CINH23060
C		CINH23070
С		CINH23030
C	****************	*CINH23390
C		CINH23100
C		CINH23110
č	DEFINITION OF TERMS	C INH23120
Č	SELLINITE OF TERMS	
	CCC WALL DOCCOAN FOR ACCOUNTS NOT	C I NH2 31 30
C	SEE MAIN PROGRAM FOR ACRONYMS NOT	CINH23140
C	LISTED HERE	C INH23150
C		CINH23160
C	**************************************	<b>¢CINH23170</b>
č		CINH23180
č	A-A CONSTANT USED TO CALCULATE THE DAROMETRIC PRESSURE BASED ON THE	
·	A CONSTRUIT OSES TO CALCULATE THE SAROBEINTE PRESSURE BASED ON THE	0 1 MUZ 21 30




```
ELEVATION AND TEMPERATURE.
                                                                       C INH23200
C AB-INTERMEDIATE VALUE USED TO CALCULATE AVERAGE CAILY TEMPERATURE
                                                                       CINH23210
C ATMP-ATMOSHERIC PRESSURE FOR A SPECIFIC DAY, PSI
                                                                      CINH23220
C AVIDBU-AVERAGE OUTSIDE TEMPERATURE, DEGREES F
                                                                       CINH23230
C B-INTERMEDIATE VALUE USED TO CALCULATE MAXIMUM AND MINIMUM DAILY
                                                                       CINH23240
     TEMPERATURE, AND AVERAGE TEMPERATURE
                                                                       CINH23250
C BN-INTERMEDIATE VALUE USED TO CALCULATE MIN. TEMPERATURE FOR THE DAY CINH23260
C BO-DRYBULB TEMPERATURE AS READ FROM CARD INPUT USING DATA GATHERED
                                                                      CINH23270
      FRUM MSL POULTRY HOUSE #7, DEGREES F
C BRDS-NO. OF BIRDS IN BUILDING
                                                                       CINH23290
54321 CONTINUE
                                                                        INH23300
C BTIME-THE TIME OF DAY THE LOOP IS TO BEGIN, HOURS
                                                                       C1NH23310
C BX-INTERMEDIATE VALUE USED TO CALCULATE MAX. TEMPERATURE FOR THE DAY CINH23320
        -AVERAGE OUTSIDE TEMPERATURE, DEGREES C
                                                                       CINH23330
C DT-LENGTH OF ITERATION, HOURS
                                                                       CINH23340
C DTIME-CLOCK TIME FCR DATA GATHERED FROM MSU POULTRY HOUSE #7, HOURS CINH23350
C HTMC-MUISTURE CONTENT OF MANURE AS FOUND FROM EXPERIMENTAL DATA AT
                                                                       CINH23360
         MSU POULTRY FARY BUILDING NO.7, PERCENT
                                                                       C1NH23370
C 12-CODED BOUNDRY FOR BIGINNING OF EACH DISCENTINUITY IN THE
                                                                       CINH23380
      TEMPERATURE FUNCTIONS.
                                                                       CINH23390
C ID-CALENDER CAY, CATE
                                                                       CINH23400
 IDP-AN INDEX TO CHECK DEW POINT TEMPERATURE
                                                                       CINH23410
 IY-CALENDER YEAR, DATE
                                                                       CINH23420
C K-AN INTEGER CODE FOR THE SIZE OF DT
                                                                       C INH23430
C MI-CODED BOUNDRY FOR 1ST DICONTINUITY IN TEMPERATURE EQUATION
                                                                       C1NH23440
C M2-CODED BOUNDRY FOR 2ND DICONTINUITY IN TEMPERATURE EQUATION
                                                                       CINH23450
C M3-CODED BOUNDRY FOR 3RD DICONTINUITY IN TEMPERATURE EQUATION
                                                                       CINH23460
C MN-COUNTER FOR NUMBER OF CUIPUT LINES PER DAY
                                                                       CINH23470
C MO-CALENDER MONTH, CATE
                                                                       C INH2 3480
C MTIME-ELASPED TIME COUNTER DURING RUN, NO. OF DT.S
                                                                       CINH23490
C MX-MAXIMUM GUTSIDE TEMPERATURE FOR THE DAY. DEGREES F
                                                                       CINH23500
C N-ANINTEGER CODE TO REPRESENT ONE-HALF HOUR INTERVALS
C NN-INDICATOR VALUE TO SPECIFY WEATHER DATA IS OR IS NOT VERIFICATION CINH23520
C PATH-ATMOSPHERIC PRESSURE, PSI
                                                                       C1NH23540
C PI-THE CONSTANT RATIO OF CIRCUPFERANCE TO CLAMETER
                                                                       CINH23550
C PC-GEWPOINT TEMPERATURE AS READ FROM CARD INPUT USING DATA GATHERED FCINH23560
      FROM MSL POULTRY HOUSE #7. DEGREES F
                                                                       CINH23570
C RANGE-OUTSIDE DAILY TEMPERATURE RANGE. CREGREES F
                                                                       C I NH2 3580
C RNG2-GNE-HALF RANGE OF DAILY TEMPERATURE. DEGREES F
                                                                       CINH23590
54320 CONTINUE
                                                                        INH23600
C TOBI-INSIDE CRYBULB TEMPERATURE, DEGREES F
                                                                       CINH23610
C TDBD-DUTSIDE DRYBULB TEMPERATURE, DEGREES F
                                                                       CINH23620
C TOPF-DEWPOINT TEMPERATURE AS REPORTED BY U.S. WEATHER SERVICE.
                                                                       C1NH23630
      DEGREES F.
                                                                       C INH23640
C TOPI- INSIDE DEWPOINT TEMPERATURE, DEGREES F
                                                                       C INH2 3650
C TOPG-OUTSIDE DEWPOINT TEMPERATURE, DEGREES F
 TIME-CLOCK TIME, 24-HOUR CLCCK
                                                                       CINH23670
 THINM-MINIMUM TEMPERATURE FOR THE DAY, DEGREES F
                                                                       CINH23680
                                                                       CINH23690
                                                                       CINH23700
CGMMON/BIRDS/WBRD.BRDS
                                                                        INH23720
      CCMMON/BUG/IBUC
      CCMMON/C/EXCDMC.EXVID.EXKISM.EVPMRT.DT
                                                                        INH23740
      CCMMON/CARD/BTIME.HTMC.MX.MN.SDRYTM.EDRYTM
      CEMMON / PRESS / PATM
                                                                        INH23760
      CCMMCN/WR/TDBD(46), TDPD(48), TDBI(48), TIME(48), MTIME, TDP1(48)
                                                                        INH23770
      CCMMON/WTHR/AVTEBG, RANGE, ATMP, MG, ID, IY, TOPF, VARDTA
                                                                        INH23780
      DIMENSION BO(48), PC(48), DTIME(48)
                                                                        INH23790
      REAL MX.MN
                                                                        INH23800
C READ OUTSIDE WEATHER DATA
                                                                       CINH23810
                      MO.ID. IY. ATMP. MX. MN. AVTCBO, TOPF, BRDS, BTIME, H7MC, INH23820
      READ(5,1)
     DV AR OT A , S CR YTM , EDRY TM
                                                                        INH23830
    1 FORMAT(312,F4.2,4F2.0,F4.0,F2.0,F4.2,F6.2,2F4.2)
                                                                        INH23840
      IF(NN.EQ.0) GO TO 100
                                                                        INH23850
  THE REGRESSION EQUATION FOR DEMPCINT IS Y=6.4663+0.800368*DB
                                                                       CINH23860
       BASED ON VARIFICATION DATA OF 8/12,13, & 20/74 AND 1/667/75
                                                                       CINH23870
      PI=355./113.
                                                                        INH23880
      K = 1
                                                                        INH23890
      IF(DT.EQ..5) K=2
                                                                        INH23900
      M1=6*K
                                                                        INH23910
```



```
M2=15*K
                                                                             INH23920
      M3=24+K
      12=1
                                                                             INH23940
      IDP=0
                                                                             INH23950
      IF (TOPF. EQ. O.) TOPF=MN
                                                                             INH23960
      IF (AVIDBO. EQ. 0.) AVIDBO= (MN+MX)/2.
                                                                             INH23970
      IF(ATMP.NE.O.) GO TO 13
                                                                             INH23980
      CD= (5./9.) * (AVTDBO-32.)
                                                                           INH23990
C 27070. IS THE
                     ELEVATION OF E. LANSING , MI IN CM
      A=27070./(1600000.*(1.+.004*CD))
      ATMP=14.696*(1.-A)/(1.+A)
                                                                             INH24020
   13 CONTINUE
                                                                             INH24030
      RANGE=MX-MN
                                                                             INH24040
      PATM=ATMP
                                                                             INH24050
C CALCULATE CRY BULB TEMPS FOR THE CAY (PHILLIPS P. 6)
                                                                           CINH24060
      RNG2=RANGE/2.
                                                                             INH24070
      TMINM= AVTOBO-RNG2
                                                                             INH24080
      IF(TOPF.LT.TMINM) GG TO 7
                                                                             TNH24090
      IDP = 1
                                                                             1NH24100
                                                                             INH24110
    7 CONTINUE
      DO 8 I=12.M1
                                                                             1NH24120
      N=2*1/K
                                                                             1MH24130
      TCBO(1)=TMINM+RNG2*(1.+COS(((FLCAT(N)+18.)/30.)*PI))
                                                                             INH24140
      TOPO(1)=6.47+.8*TDBO(1)
                                                                             INH24150
    8 CONTINUE
                                                                             INH24160
      I 2= M1 + 1
                                                                             INH24170
      DO 9 I=12.M2
                                                                             INH24180
      N=2*1/K
                                                                             INH24190
      TDBD(I)=IM[NM+RNG2*(1.-COS(((FLOAT(N)-12.)/18.)*PI))
                                                                             INH24200
      TOPC(I)=6.47+.8*TDBG(I)
                                                                             INH24210
    9 CONTINUE
                                                                             INH24220
      I2=M2+1
                                                                             1NH24230
      00 10 I=12.M3
                                                                             INH24240
      N=2 + 1 / K
                                                                             INH24250
      TDBO(1)=TMINM+RNG2+(1.+CGS(((FLGAT(N)-30.)/30.)*P1))
                                                                             TEH24260
      TDPO(1)=6.47+.8*TDBO(1)
                                                                             INH24270
   10 CONTINUE
                                                                             INH24280
                                                                            CINH24290
c
    WEATHER DETERMINED FROM HOUSE 7 DATA
                                                                            CINH24300
č
                                                                            CINH24310
  100 CONTINUE
                                                                             INH24320
      IF (NN. GT.O) GD TO 777
                                                                             INH24330
      PATM=ATMP
                                                                             INH24340
      N=0
                                                                             INH24350
      3 X= 0.
                                                                             INH24360
      BN=100.
                                                                             INH24370
      AB=C.
                                                                             INH24380
      DO 710 J=1,24
                                                                             INH24390
      READ(5,760) DTIME(J), BO(J), PO(J), TOBI(J), TOPI(J)
                                                                             INH24400
  760 FORMAT (12X, F5.2, 10X, 4F6.2)
                                                                             INH24410
  710 CONTINUE
                                                                             INH24420
      DO 770 K=1.24
                                                                             INH24430
      4=K
                                                                             INH24440
      TD50(K)=80(K)
                                                                             INH24450
      TDPG(K)=PG(K)
                                                                             INH24460
                                                                             INH24470
      TOPG(K+24)=HADP(PG(K)+459.67)
      IF(K.GT.O) GC TO 745
                                                                             INH24480
      M = (FLOAT(K) / 2.0 +.5)
                                                                             INH24490
      IF (M.NE.N) GC TO 750
                                                                             INH24500
      TIME(M)=FLGAT(M)
                                                                             INH24510
      IF(TIME(M).LT.DTIME(1)) GO TO 610
                                                                             INH24520
       IF(TIME(M).GT.CTIME(48)) GO TO 620
                                                                             INH24530
       TOBO(M)=TABLI(BC,DTIME,TIME(M),48)
                                                                             INH24540
                                                                             INH24550
      TOPO(M)=TABLI(PC,OTIME,TIME(M),43)
  745 CONTINUE
                                                                             INH24560
  750 CCNTINUE
                                                                             INH24570
      B=BO(K)
                                                                             INH24580
      IF(B.GT.EX) EX=B
                                                                             INH24590
       IF (B.LT.BN) BN=B
                                                                             INH24600
                                                                             INH24610
      AB=AB+B
      N = 4
                                                                             INH24620
  770 CCNTINUE
                                                                             INH24630
```




	AVIDBC=AB/48.	INH24640
	RANGE=BX=BN	INH24650
777	CONTINUE	1NH24660
	NN=NN+1	INH24670
	IF(IDP.EQ.0) GO TO 12	INH24680
	PRINT 26	INH24690
	PRINT 6.TCPF.TMINM	INH24700
6	FORMAT(1x, DEWPOINT TEMPERATURE GREATER THAN MINIMUM TEMPERATURE	
	LOR THE DAY. DEWPOINT INPUT AS ';G21.7/1X, 'BUT RESET AS SHOWN')	
	GO TO 27	INH24730
1.2	CENTINUE	INH24740
	IF(DT.E05.DR.DT.EQ.1.) GU TO 99	INH24750
	PRINT 26	INH24760
9.0	PRINT 900.DT	INH24770
	FORMAT(1X. OT NOT EQUAL .5 OR 1. NOTE VALUES FOR TOBO BELOW. RET	
	RNED VALUE FOR DT 15:1.G20.5)	INH24790
,	GO TO 27	INH24800
00	CONTINUE	INH24810
44	IF (IBUG.EO.O) GD TO 9999	INH24810
	PRINT 26	INH24830
26	FCRMAT(/1X+10(1Hh))+8(10H WETHER )+10(1HW))	INH24840
	CONTINUE	1NH24850
21	PRINT 9000.MTIME.IZ.K.MI.MZ.M3. AVIDSG.RANGE.TDPF.RNGZ.TMINM	INH24860
0000	FORMAT(1X, "MTIME", 15X, "12", 18X, "K", 19X, "K1", 18X, "M2", 16X, "M3"/	INH24860
	A 1X'AVTOBE',14X, RANGE',15X, TOPF',16X, RNG2 ',15X, TMINN'/	INH24870
	11X, 12, 5(120)/1X, E11, 4, 4E20, 4)	INH24880
,	PAINT SOC5.SDRYTM.EDRYTM	INH24890
0005	FORMAT (/1x. ORYER START AND END TIME - WINTER MONTHS . 2F10.2/)	INH24910
9000	PRINT 9010 . MO. ID. IY	INH24910
0010	FORMAT (/1X, CATE', 12, '/', 12, '/', 12)	INH24920
9010	PRINT 9090 TOBO	I NH24940
0000	FORMAT (1H0.10(10HWETHER )./1X' TDBG(J)'./8(6E20.4/))	INH24950
9093	PRINT 9091, TDP0	INH24950
0001	FGRMAT (1X*TDPG(J)*/1X.8(6E20.4/))	INH24980
9091	PRINT 9092 .TDHI	INH24970
0003	FORMAT (1X'TDB1(J)'/1X.8(6E20.4/))	INH24990
9092	PRINT 9093. IDPI	INH25000
00.33	FORMAT (1X'TOPI(J)'/1X.8(6E20.4/))	INH25010
9093	PRINT 9054-TIME	1NH25010
0001	FCRMAT (1X*TIME(.))*/1X+8(6F20-4/))	INH25020
	CONTINUE	INH25040
4444		
	RETURN	INH25050
613	TDBO(M)=BC(K)	INH25060
	TDPG(M)=PG(K)	INH25070
	GU TD 750	INH25080
620	TDBU(M)=8C(48)	INH25090
	TOPG(F)=P0(48)	INH25100
	GG TO 750 END	INH25110 INH25120



## APPENDIX B

EXAMPLES OF INTERMEDIATE COMPARISON GRAPHS



## APPENDIX B

## EXAMPLES OF INTERMEDIATE COMPARISON GRAPHS




Figure B.1. An example of a comparison graph used for evaluation during verification of the simulation model with the measured data. This graph showed that the incoming air dry-bulb temperature as used in the model was in fact equal to that of the collected data.






Figure B.2. An example of a comparison graph used for evaluation during verification of the simulation model with the measured data. This graph showed that the incoming air dewpoint temperature as used in the model was in fact equal to that of the collected data.






Figure B.3. An example of a comparison graph used for evaluation during verification of the simulation model with the measured data. This graph showed that the incoming air humidity ratio was in fact equal to that of the







Figure B.4. An example of a comparison graph used for evaluation during verification of the simulation model with the measured data. This graph showed that the outgoing air dry-bulb temperature as calculated by the simulation model follows very closely to the measured value.






Figure B.5. An example of a comparison graph used for evaluation during the verification of the simulation model with measured data. This graph showed that the outgoing air dewpoint temperature as calculated by the simulation model follows very closely to the measured value.






Figure B.6. An example of a comparison graph used for evaluation during the verification of the simulation model with measured data. This graph showed that the humidity ratio of the outgoing air as calculated by the simulation model follows very closely to the measured value.







Figure B.7. An example of a comparison graph used for evaluation during the verification of the simulation model with measured data. This graph showed that incoming air and outgoing air humidity ratio difference was greater for the measured data than as calculated by the simulation model for all but two hours of the day.







Figure B.8. An example of a comparison graph used for evaluation during the verification of the simulation model with measured data. This graph showed that the air flow through the poultry house as calculated by the simulation model follows very closely to the measured value.






Figure B.9. An example of a comparison graph used for evaluation during the verification of the simulation model with measured data. This graph showed that the evaporation from the poultry house during one hour as calculated by the simulation model followed the same trend as that which was calculated from measured data. The two curves result from curvilinear regression calculations based on the two separate sets of data.



#### APPENDIX C

# VERIFICATION MANAGEMENT FACTOR, DESIGN, AND INPUT VALUES



#### APPENDIX C

## VERIFICATION MANAGEMENT FACTOR, DESIGN, AND INPUT VALUES

Table C.1. Management factor, design, and input values as used for verifying the model with data collected August 12, 1974.

BUILDING: LENGTH, FT WIDTH, FT CEILING HEIGHT, FT INSULATION-WALLS, HR-F-SQ FT/BTU INSULATION-CEILING, HR-F-SQ FT/BTU LIGHTING HEAT, BTU/HR	92.25 38.00 8.25 14.11 23.68 3242.35
LAYING HENS:  NUMBER OF HENS  HEN WEIGHT, LBS  BODY TEMPERATURE, F  EXCRETA MOISTURE CONTENT, %  EXCRETA DISTRIBUTION FACTOR  SPECIFIC HEAT OF MANURE, BTU/LB-F  EXCRETA PRODUCTION RATE, LBS/HEN-DAY	5239.00 4.25 107.10 80.00 0.04 0.87 0.27
VENTILATION: INSIDE DESIGN(SET) TEMPERATURE, F MAXIMUM VENTILATING RATE, CFM MINIMUM VENTILATING RATE, CFM INITIAL SLAB TEMPERATURE, F	56.00 20421.34 5406.01 42.89
WEATHER: ATMOSPHERIC PRESSURE, PSI AVERAGE OUTSIDE TEMPERATURE, F OUTSIDE TEMPERATURE RANGE, F CRITICAL LOW OUTSIDE TEMPERATURE, F	14.28 37.89 25.18 36.29
SIMULATION DETAILS: TIME INCREMENT-DT, HOURS STARTING TIME, CLOCK HOURS LENGTH OF RUN, HOURS SLAB INDEX LIGHTING INDEX	1.00 0.0 24.00 1



Table C.2. Management factor, design, and input values as used for verifying the model with data collected August 13, 1974.

BUILDING:  LENGTH, FT  WIDTH, FT  CEILING HEIGHT, FT  INSULATION-WALLS, HR-F-SQ FT/BTU INSULATION-CEILING, HR-F-SQ FT/BTU LIGHTING HEAT, BTU/HR	92.25 38.00 8.25 14.11 23.68 3242.35
LAYING HENS:  NUMBER OF HENS  HEN WEIGHT, LBS  BODY TEMPERATURE, F  EXCRETA MOISTURE CONTENT, %  EXCRETA DISTRIBUTION FACTOR  SPECIFIC HEAT OF MANURE, BTU/LB-F  EXCRETA PRODUCTION RATE, LBS/HEN-DAY	5237.00 4.25 107.10 80.00 0.04 0.87 0.27
VENTILATION: INSIDE DESIGN(SET) TEMPERATURE, F MAXIMUM VENTILATING RATE, CFM MINIMUM VENTILATING RATE, CFM INITIAL SLAB TEMPERATURE, F	56.00 20421.34 5406.01 43.02
WEATHER: ATMOSPHERIC PRESSURE, PSI AVERAGE OUTSIDE TEMPERATURE, F OUTSIDE TEMPERATURE RANGE, F CRITICAL LOW OUTSIDE TEMPERATURE, F	14.29 38.02 18.12 36.32
SIMULATION DETAILS: TIME INCREMENT-DT, HOURS STARTING TIME, CLOCK HOURS LENGTH OF RUN, HOURS SLAB INDEX LIGHTING INDEX	1.00 0.0 24.00 1



Table C.3. Management factor, design, and input values as used for verifying the model with data collected August 20, 1974.

BUILDING:  LENGTH, FT  WIDTH, FT  CEILING HEIGHT, FT  INSULATION-WALLS, HR-F-SQ FT/BTU  INSULATION-CEILING, HR-F-SQ FT/BTU  LIGHTING HEAT, BTU/HR	92.25 38.00 8.25 14.11 23.68 3242.35
LAYING HENS:  NUMBER OF HENS  HEN WEIGHT, LBS  BODY TEMPERATURE, F  EXCRETA MOISTURE CONTENT, %  EXCRETA DISTRIBUTION FACTOR  SPECIFIC HEAT OF MANURE, BTU/LB-F  EXCRETA PRODUCTION RATE, LBS/HEN-DAY	5222.00 4.25 107.10 80.00 0.04 0.87 0.27
MIXING TENTIER TO THE TENTIER THE TENTIER TO THE TE	56.00 20421.34 5406.01 43.58
WEATHER: ATMOSPHERIC PRESSURE, PSI AVERAGE OUTSIDE TEMPERATURE, F OUTSIDE TEMPERATURE RANGE, F CRITICAL LOW OUTSIDE TEMPERATURE, F	14.34 38.58 31.85 36.44
SIMULATION DETAILS: TIME INCREMENT-DT, HOURS STARTING TIME, CLOCK HOURS LENGTH OF RUN, HOURS SLAB INDEX LIGHTING INDEX	1.00 0.0 24.00 1





Table C.4. Management factor, design, and input values as used for verifying the model with data collected January 6, 1975.

BUILDING: LENGTH, FT WIDTH, FT CEILING HEIGHT, FT INSULATION-WALLS, HR-F-SQ FT/BTU INSULATION-CEILING, HR-F-SQ FT/BTU LIGHTING HEAT, BTU/HR	92.25 38.00 8.25 14.11 23.68 3242.35
LAYING HENS:  NUMBER OF HENS HEN WEIGHT, LBS BODY TEMPERATURE, F EXCRETA MOISTURE CONTENT, % EXCRETA DISTRIBUTION FACTOR SPECIFIC HEAT OF MANURE, BTU/LB-F EXCRETA PRODUCTION RATE, LBS/HEN-DAY	4944.00 4.25 107.10 80.00 0.04 0.87 0.27
VENTILATION: INSIDE DESIGN(SET) TEMPERATURE, F MAXIMUM VENTILATING RATE, CFM MINIMUM VENTILATING RATE, CFM INITIAL SLAB TEMPERATURE, F	56.00 20421.34 6706.75 23.45
WEATHER: AIMOSPHERIC PRESSURE, PSI AVERAGE OUTSIDE TEMPERATURE, F OUTSIDE TEMPERATURE RANGE, F CRITICAL LOW OUTSIDE TEMPERATURE, F	14.23 18.45 10.37 40.85
SIMULATION DETAILS: TIME INCREMENT-DT, HOURS STARTING TIME, CLOCK HOURS LENGTH OF RUN, HOURS SLAB INDEX LIGHTING INDEX	1.00 0.0 24.00 1



Table C.5. Management factor, design, and input values as used for verifying the model with data collected January 7, 1975.

BUILDING: LENGTH, FT WIDTH, FT CEILING HEIGHT, FT INSULATION-WALLS, HR-F-SQ FT/BTU INSULATION-CEILING, HR-F-SQ FT/BTU LIGHTING HEAT, BTU/HR	92.25 38.00 8.25 14.11 23.68 3242.35
LRYING HENS:  NUMBER OF HENS HEN WEIGHT, LBS BODY TEMPERATURE, F EXCRETA MOISTURE CONTENT, % EXCRETA DISTRIBUTION FACTOR SPECIFIC HEAT OF MANURE, BTU/LB-F EXCRETA PRODUCTION RATE, LBS/HEN-DAY	4942.00 4.25 107.10 80.00 0.04 0.87 0.27
VENTILATION: INSIDE DESIGN(SET) TEMPERATURE, F MAXIMUM VENTILATING RATE, CFM MINIMUM VENTILATING RATE, CFM INITIAL SLAB TEMPERATURE, F	56.00 20421.34 6613.67 23.48
WEATHER: ATMOSPHERIC PRESSURE, PSI AVERAGE OUTSIDE TEMPERATURE, F OUTSIDE TEMPERATURE RANGE, F CRITICAL LOW OUTSIDE TEMPERATURE, F	14.25 18.48 12.42 40.67
SIMULATION DETAILS:  TIME INCREMENT-DT, HOURS STARTING TIME, CLOCK HOURS LENGTH OF RUN, HOURS SLAB INDEX LIGHTING INDEX	1.00 0.0 24.00 1



LIST OF REFERENCES



### LIST OF REFERENCES

- ASHRAE <u>Guide</u> and <u>Data Book</u>, 1965. American Society of Heating, Refrigerating and Air-Conditioning Engineers, New York, N.Y. 880 pp.
- Bakker-Arkema, F. W., and L. E. Lerew, 1972. A psychrometric package. Mimeo: Agricultural Engineering Department, Michigan State University, East Lansing, Michigan.
- Bressler, G. O., and E. L. Bergman, 1971. Solving the poultry manure problem economically through dehydration. Proceedings International Symposium on Livestock Wastes, Ohio State University. ASAE Publication PROC-270: 81-84.
- Davis, E. G., I. L. Field, and J. H. Brown, 1972. Combustion disposed of manure wastes and utilization of the residue. United States Department of the Interior, Bureau of Mines, Solid Wastes Research Program Technical Progress Report 46.
- Dixon, J. E., J. B. Gerrish, T. S. Chang, C. J. Flegal, C. C. Sheppard, and H. C. Zindel, 1976a. Poultry environment system model for drying manure. ASAE paper 76-4039, ASAE, St. Joseph. MI 49085.
- Dixon, J. E., G. D. Wells, and M. L. Esmay, 1976b. Convective heat transfer coefficient for poultry manure. ASAE paper 76-4511, ASAE. St. Joseph. MI 49085.
- Dixon, J. E., G. D. Wells, and M. L. Esmay, 1978. Convective heat transfer coefficient for poultry excreta. Transactions of the ASAE 21(3):534-536.
- Erickson, A. E., J. M. Tiedje, B. G. Ellis, and C. M. Hanson, 1971. A barriered landscape water renovation system for removing phosphate and nitrogen from liquid feedlot waste. Proceedings International Symposium on Livestock Wastes, Ohio State University. ASAE Publication PROC-271: 232-234.
- Esmay, M. L., 1969. <u>Principles of Animal Environment</u>. AVI Publishing Co., Westport, Conn. 325 pp.
- Esmay, M. L., C. J. Flegal, J. B. Gerrish, J. E. Dixon, C. C. Sheppard, H. C. Zindel, and T. S. Chang, 1975a. Poultry manure dehydration by air-drying and machine in a caged-layer house handling system. Research Report No. 269, Agricultural Experiment Station, Michigan State University, East Lansing, pp. 2-14.



- Esmay, M. L., C. J. Flegal, J. B. Gerrish, J. E. Dixon, C. C. Sheppard, H. C. Zindel, and T. S. Chang, 1975b. In-house handling and dehydration of poultry manure from caged-layer operations: A project review. Proceedings Third International Symposium on Livestock Waste, University of Illinois, ASAE Publication PROC-275: 468-473, 477.
- Flegal, C. J., M. L. Esmay, J. B. Gerrish, J. E. Dixon, C. C. Sheppard, H. C. Zindel, and T. S. Chang, 1974. A complete system for collecting, handling, air-drying and machine dehydration of poultry manure in a caged-layer production unit. Cornell Agricultural Waste Management Conference Proceedings, Rochester, New York, March 25-27, pp. 122-131.
- Forsht, R. Gar, C. R. Burbee, and W. M. Crosswhite, 1974. Recycling poultry waste as a feed: Will it pay? Agricultural Economic Report 254. Economic Research Service, United States Department of Agriculture, Washington, D.C. 5lpp.
- Gerrish, J. B., J. E. Dixon, M. L. Esmay, G. H. Quebe, C. J. Flegal, C. C. Sheppard, and H. C. Zindel, 1973. Engineering aspects of handling and dehydrating poultry excreta: A progress report. ASAE Paper 73-4560. ASAE, St. Joseph, MI 49085.
- Holman, J. P., 1963. <u>Heat Transfer</u>. McGraw-Hill Book Company, Inc., New York, N.Y. 289 pp.
- Hummel, J. W., and G. B. Willson, 1975. High-rate mechanized composting of dairy manure. Proceedings Third International Symposium on Livestock Wastes, University of Illinois, ASAE Publication PROC-275: 481-484.
- Lampman, C. E., J. E. Dixon, C. F. Petersen, and R. E. Black, 1967. Environmental control for poultry housing. Idaho Agricultural Experiment Station Bulletin 456, University of Idaho, Moscow, Idaho. 27 pp.
- Llewellyn, R. W., 1965. Fordyn--An Industrial Dynamics Simulator. Privately published by R. W. Llewellyn, Box 5353, Raleigh, North Carolina. 150 pp.
- Longhouse, A. D., H. Ota, and W. Ashby, 1960. Heat and moisture design data for poultry housing. Agricultural Engineering 41: 567-576.
- Ludington, D. C., 1963. Dehydration and incineration of poultry manure. Proceedings National Symposium on Poultry Waste Management. May 13-15.



- Miner, J. R., and R. J. Smith, 1975. Livestock Waste Management with Pollution Control. Northcentral Regional Research Publication 222, Midwest Plan Service, Ames, Towa, June. 89 pp.
- Oheimb, Rainer A. von, and A. D. Longhouse, 1974. Partial drying of poultry manure using in-house air. West Virginia University Agricultural Experiment Station Bulletin 633T, Morgantown. 16np.
- Ota, H., and E. H. McNally, 1961. Poultry respiration calorimetric studies of laying hens--single comb white leghorns, Rhode Island reds, and New Hampshire X Cornish Cross. United States Department of Agriculture ARS 42-43. 34 pp.
- Perry, Robert H., and Cecil H. Chilton, 1963. <u>Chemical Engineers'</u>
  <u>Handbook</u>. 4th edition. McGraw-Hill Book Company, New York.
  1663 pp.
- Perry, Robert H., and Cecil H. Chilton, 1973. <u>Chemical Engineers'</u> <u>Handbook</u>. 5th edition. McGraw-Hill Book Company, New York. 1962 pp.
- Phillips, R. E., 1970. A systems analysis of summer environment for laying hens. Unpublished Ph.D. thesis, Agricultural Engineering Department, Michigan State University, East Lansing, Michigan.
- Sheppard, C. C., C. J. Flegal, M. L. Esmay, J. B. Gerrish, J. E. Dixon, H. C. Zindel, and T. S. Chang, 1974. A complete system for collecting, handling, air-drying and machine dehydration of poultry manure in a caged-layer production unit. XV World's Poultry Congress, New Orleans, LA., June.
- Singley, M. E., Martin Decker, and S. J. Toth, 1975. Composting of swine waste. Proceedings Third International Symposium on Livestock Wastes, University of Illinois, ASAE Publication PROC-275: 492-496.
- Smith, E. S., Meyer Salkover, and H. K. Justice, 1947. <u>Unified Calculus</u>. John Wiley and Sons, New York. 534 pp.
- Sobel, A. T., 1972. Undercage drying of laying hen manure. Proceedings of the 1972 Cornell Agricultural Waste Management Conference, pp. 187-200.
- Structures and Environment Handbook, 1975. Midwest Plan Service, MWPS 1, Ames, Iowa. 412 pp.
- Surbrook, T. C., 1969. Evaluation of an animal excreta dryer. Unpublished MS Thesis, Agricultural Engineering Department, Michigan State University, East Lansing, Michigan.



- Surbrook, T. C., C. C. Sheppard, J. W. Boyd, H. C. Zindel, and C. J. Flegal, 1971. Drying poultry waste. Proceedings International Symposium on Livestock Wastes, Ohio State University. ASAE Publication PROC-271, pp. 192-194.
- Weast, Robert C., 1970. <u>Handbook of Chemistry and Physics</u>. 51st edition. Chemical Rubber Company, Cleveland, Ohio.
- Wells, Grant DeWitt, 1972. Simulation of in-house drying of chicken excreta. Unpublished Ph.D. Thesis, Department of Agricultural Engineering, Michigan State University. East Lansing, Michigan.
- U.S. Department of Commerce, 1968. Climatic Atlas of the United States. Environmental Science Services Administration, Environmental Data Service, Asheville, North Carolina.
- U.S. Department of Commerce, 1977a. Local Climatological Datamonthly summary for Lansing, Michigan. National Weather Service, National Oceanic and Atmospheric Administration, National Climatic Center, Asheville, North Carolina.
- U.S. Department of Commerce, 1977b. Monthly Weather Data. National Weather Service, National Oceanic and Atmospheric Administration, National Climatic Center, Asheville, North Carolina.
- Zindel, H. C., T. S. Chang, C. J. Flegal, D. Polin, C. C. Sheppard, B. A. Stout, J. E. Dixon, M. L. Esmay, and J. B. Gerrish, 1977. Poultry excreta dehydration and utilization: System development and demonstration. U.S. Environmental Protection Agency, Environmental Research Laboratory, Athens, Georgia, Report EPA-600/2-77-221.

