

REDUCTION OF THE NUMBER OF INDEPENDENT
VARIABLES AND OPTIMIZATION IN
SWIRLING FLUID FLOW

Thesis for the Degree of Ph. D.
MICHIGAN STATE UNIVERSITY
MICHAEL JEROME BRINK
1971



This is to certify that the

thesis entitled

REDUCTION OF THE NUMBER OF INDEPENDENT
VARIABLES AND OPTIMIZATION IN SWIRLING FLUID FLOW

presented by

Michael Jerome Brink

has been accepted towards fulfillment
of the requirements for

Ph.D. degree in Mechanical Engineering

M. Z. v. Bryan Block
Major professor


Date May 12, 1971

JUN 08 1995

~~7L 8413440~~

1.811 4









ABSTRACT

REDUCTION OF THE NUMBER OF INDEPENDENT VARIABLES AND OPTIMIZATION IN SWIRLING FLUID FLOW

By

Michael Jerome Brink

The major objective of this investigation is to determine solutions to the system of fundamental equations governing inviscid, incompressible swirling flow in (R, θ, Z) space by using group theory to reduce the number of independent variables and obtaining the solutions for the resulting system of ordinary differential equations.

Transformations obtained by the application of continuous one-parameter group theory are applied to the fundamental system of non-dimensional equations for conservation of mass, conservation of momentum, and conservation of energy. The number of independent variables is reduced from three to two to one using the absolute invariants determined for each transformation group. The resulting system of nonlinear ordinary differential equations is then solved numerically by Hamming's modified predictor-corrector technique. The one-dimensional solutions are transformed back to the three-dimensional space using the transformations obtained from the application of the continuous one-parameter group theory.

Computer curves are presented for both the one-dimensional and the transformed three-dimensional solutions to the conservation of mass and conservation of momentum equations. Two continuous one-parameter transformation groups and their invariants which were discovered and then utilized to accomplish the reduction in the number of



Michael Jerome Brink

independent variables for cylindrical polar coordinates are also presented.

A Mayer type optimization problem is solved using the one-dimensional representations for conservation of energy and the swirl parameter to optimize the one-dimensional representation for pressure. The one-dimensional optimization results are transformed back to the three-dimensional space using the transformations obtained from the application of the continuous one-parameter group theory.

Computer curves are presented for the optimization results in both the one-dimensional and the three-dimensional space.



REDUCTION OF THE NUMBER OF INDEPENDENT VARIABLES
AND OPTIMIZATION IN SWIRLING FLUID FLOW

By

Michael Jerome Brink

A THESIS

Submitted to
Michigan State University
in partial fulfillment of the requirements
for the degree of

DOCTOR OF PHILOSOPHY

Department of Mechanical Engineering

1971



PLEASE NOTE:

Some Pages have indistinct
print. Filmed as received.

UNIVERSITY MICROFILMS

670259

To Marylyn, David, Bridjette, and Cynthia -
for infinite patience and understanding

guic

val

Ter

gui

as

ty

ACKNOWLEDGMENTS

The author wishes to express his sincere appreciation to his guidance committee chairman, Professor M. Z. v. Krzywoblocki, for his valuable guidance during the period of graduate study and research.

He also wishes to thank Professors C. R. St. Clair, Jr., Terry Triffet, Robert Wasserman, and C. P. Wells for serving on his guidance committee.

Thankful acknowledgment is extended to Mr. W. Arntson for his assistance in computer programming and Mrs. J. Harris for her excellent typing.



TABLE OF CONTENTS

	Page
LIST OF TABLES	vi
LIST OF FIGURES.	vii
NOMENCLATURE	ix
I. FUNDAMENTALS	1
1.1 Introduction.	1
1.2 Scope of This Investigation	2
1.3 Group Theory.	3
1.4 Optimization Techniques	11
II. MATHEMATICAL SWIRLING FLOW MODEL	15
2.1 Type of Fluid Flow and Coordinate System.	15
2.2 Fundamental Equations	16
2.3 Boundary Conditions and Swirl Parameter	19
2.4 Non-Dimensional Equations	21
III. REDUCTION OF THE NUMBER OF INDEPENDENT VARIABLES	24
3.1 Three to Two Reduction in the Number of Independent Variables	24
3.2 Two to One Reduction in the Number of Independent Variables	44
3.3 Summary	60
IV. SOLUTIONS FOR THE CASE $\xi = -1$	62
4.1 One-Dimensional Solutions of the Ordinary Differential Equations	62
4.2 Three-Dimensional Pressure and Velocity Curves.	68
4.3 Summary and Recommendations for Further Research.	70
V. OPTIMAL SOLUTIONS.	76
5.1 Application of Optimization Techniques in X Space.	76
5.2 Three-Dimensional Optimal Pressure and Velocity Curves	82
5.3 Summary	85
BIBLIOGRAPHY	88



TABLE OF CONTENTS

	Page
APPENDICES	
APPENDIX A: NUMERICAL DATA FOR THE SOLUTIONS TO THE SYSTEM OF ORDINARY DIFFERENTIAL EQUATIONS.	92
APPENDIX B: CALCOMP PLOTTER ROUTINE.	113
APPENDIX C: LEAST SQUARES POLYNOMIAL CURVE FITTING PROGRAM.	122
APPENDIX D: PRESSURE AND VELOCITY PROGRAMS AND NUMERICAL DATA	141
APPENDIX E: PROGRAMS AND NUMERICAL DATA FOR OPTIMUM FUNCTIONS.	145

Table

A.1 Numerical
of Ordinates

C.1 Curve F

C.2 Curve F

D.1 Sample

E.1 Numerical

E.2 Numerical
and Tables

LIST OF TABLES

ble	Page
.1 Numerical Data for Solutions to the System of Ordinary Differential Equations.	108
.1 Curve Fitting Data for the Interval $0.10000 \leq X \leq 0.46531$. . .	129
.2 Curve Fitting Data for the Interval $0.46531 \leq X \leq 1.0000$	135
.1 Sample Data Pressure and Velocity Functions	144
.1 Numerical Data for Optimum One-Dimensional Functions. . . .	148
.2 Numerical Data for Optimum Pressure and Tangential Velocity	154

Figure

2.1 Cylind

2.2 Veloc

3.1 (R,

3.2 (R,

3.3 (R,

3.4 (R,
Mass

3.5 (R,
Berr

3.6 (R,
Par

3.7 (n_1

3.8 (n_1

3.9 (n_1

3.10 (n_1

3.11 (n_1
and

4.1 One

4.2 Pre

4.3 Ra

4.4 Ta

4.5 Ax

4.6 Re

LIST OF FIGURES

Figure	Page
2.1 Cylindrical Polar Coordinates	17
2.2 Velocity Components	18
3.1 $(R, \theta, Z) \rightarrow (\eta_1, \eta_2)$ Reduction R-Momentum Equation (2.4.7). .	39
3.2 $(R, \theta, Z) \rightarrow (\eta_1, \eta_2)$ Reduction θ -Momentum Equation (2.4.8). .	40
3.3 $(R, \theta, Z) \rightarrow (\eta_1, \eta_2)$ Reduction Z-Momentum Equation (2.4.9). .	41
3.4 $(R, \theta, Z) \rightarrow (\eta_1, \eta_2)$ Reduction Conservation of Mass Equation (2.4.10).	42
3.5 $(R, \theta, Z) \rightarrow (\eta_1, \eta_2)$ Reduction Bernoulli Equation (2.4.11)	43
3.6 $(R, \theta, Z) \rightarrow (\eta_1, \eta_2)$ Reduction Swirl Parameter Equation (2.4.11)	43
3.7 $(\eta_1, \eta_2) \rightarrow (X)$ Reduction Equation (3.1.66).	54
3.8 $(\eta_1, \eta_2) \rightarrow (X)$ Reduction Equation (3.1.72).	55
3.9 $(\eta_1, \eta_2) \rightarrow (X)$ Reduction Equation (3.1.77).	57
3.10 $(\eta_1, \eta_2) \rightarrow (X)$ Reduction Equation (3.1.82).	58
3.11 $(\eta_1, \eta_2) \rightarrow (X)$ Reduction Equation (3.1.83) and Equation (3.1.84)	59
4.1 One-Dimensional Functions	67
4.2 Pressure Curves	72
4.3 Radial Velocity Curves.	73
4.4 Tangential Velocity Curves.	74
4.5 Axial Velocity Curves	75
4.6 Real Space Functions.	76

Figure

5.1 G_2 Cu

5.2 G_4 Cu

5.3 Optim

5.4 Veloc

Figure	Page
5.1 G_2 Curves S Parameter	83
5.2 G_4 Curves S Parameter	84
5.3 Optimum Pressure Curves	86
5.4 Velocity Curves for Optimum Pressure.	87

p - Pr

r, s, z - Ph

u, v, w - Ve

ρ - De

q - Ve

e - In

Q - T

h - B

λ_j - L

K - A

ϕ_j - F

τ_1 - S

τ_2 - T

S -

z_0 -

v_0 -

R =

Z =

U -

V -

W -

P -

NOMENCLATURE

p - Pressure

θ, z - Physical coordinates, independent variables

v, w - Velocity components

ρ - Density

q - Velocity

e - Internal energy and base of the natural logarithm system

Q - Total energy change

h - Bernoulli constant

λ_j - Lagrange multipliers

K - Augmented function

ϕ_j - Functional forms of optimal constraint equations

π_1 - Swirl aspect ratio = r^2/z^2

π_2 - Tangential energy fraction = $v^2/(h/\rho)$

S - Swirl parameter = $\pi_1 \pi_2$

z_0 - Axial swirl length

v_0 - Tangential velocity at the outer swirl radius

R - Dimensionless independent variable = r/z_0

Z - Dimensionless independent variable = z/z_0

U - Dimensionless radial velocity component = u/v_0

V - Dimensionless tangential velocity component = v/v_0

W - Dimensionless axial velocity component = w/v_0

P - Dimensionless static pressure = $p/(\rho v_0^2)$

H - Dime

t_1 - Cons

a - Grou

A_1 - One

ϕ - Dif

t^i - Arg

η_1 - Ind

f_i - Abs

ζ - Gro

a - Gro

F_1 - Tw
co

F_2 - Tw
co

F_3 - Tw
co

F_4 - Tw

k - Co

γ_1 - Co

c - G

B_1 - O

X - I

σ - G

- H - Dimensionless Bernoulli constant = $h/(\rho v_0^2)$
- Γ_1 - Constants
- a - Group parameter
- A_1 - One-parameter group
- Φ - Differential form of k-th order in m independent variables
- Γ_1^i - Arguments of the k-th order differential form
- η_1 - Independent variables, absolute invariants of A_1
- Γ_1^f - Absolute invariants of A_1
- ξ - Group constant = t_2/t_1
- α - Group constant = t_4/t_2
- Γ_1^r - Two-dimensional representation for the radial velocity component
- Γ_2^t - Two-dimensional representation for the tangential velocity component
- Γ_3^a - Two-dimensional representation for the axial velocity component
- Γ_4^p - Two-dimensional representation for static pressure
- k - Constant
- Γ_i - Constants
- c - Group parameter
- Γ_1 - One-parameter group
- χ - Independent variable, absolute invariant of B_1
- γ - Group constant = γ_1/k

g_1 - Abs

G_1 - On
cor

G_2 - On
co

G_3 - On
co

G_4 - Or

L^2 - Co

' - De
vi

- g_1 - Absolute invariants of B_1
- G_1 - One-dimensional representation for the radial velocity component
- G_2 - One-dimensional representation for the tangential velocity component
- G_3 - One-dimensional representation for the axial velocity component
- G_4 - One-dimensional representation for static pressure
- L^2 - Constant = $G_1^2 + G_3^2 = G^2$
- $'$ - Denotes differentiation with respect to the independent variable

1.1 Introduction

Swi
engineers si
cently, it s
ed in Wheele
"black hole"

Ge
which the t
that the fl
occur in Hi
and rotatin

T
in the gene
ferential
lytical te
were compe
components
ble [6, 11
were assum

to the fu
are obtai

I. FUNDAMENTALS

1. Introduction

Swirling fluid flows have been of interest to scientists and engineers since 1797 when Venturi studied the free vortex. Most recently, it seems that swirling flow may appear in the motion encountered in Wheeler's theory of gravitational collapse [51] and the so-called "black hole" in space.

Generally, swirling flow may be categorized as any flow in which the tangential velocity component has a finite magnitude such that the fluid has a macroscopic rotary motion. Typical flow examples occur in Hilsch tubes, vortex amplifiers, tornados, large fuel tanks, and rotating fluid machinery.

The system of fundamental equations describing swirling flow in the general case includes three-dimensional, nonlinear partial differential equations which are not amenable to solution by standard analytical techniques. Therefore, investigators of swirling type flows are compelled to make various simplifying assumptions. All velocity components were assumed to be functions of only one independent variable [6, 11, 14, 15, 16, 30, 36, 47] or particular velocity components were assumed to have only certain special forms [13, 29, 35].

In this work, the major objective is to determine solutions of the fundamental equations governing swirling flow. The solutions are obtained by accomplishing a reduction in the number of independent

variables util
ing ordinary

The
one-parameter
differential
transformed
dependent va
differential

1.2 Scope

Th
dimensional
of momentum

C
reduce the
comply th
groups are
duction by
tion. The
linear. H
termine th

dimension
strained

dimension
dimension
the appl

ables utilizing one-parameter group theory and solving the result-ordinary differential equations.

The minor objective of this work is to discover two sets of parameter transformation groups such that the system of partial differential equations for the model in three independent variables is transformed into a system of partial differential equations in two independent variables which is then transformed into a system of ordinary differential equations.

Scope of this Investigation

The fundamental fluid flow model is posed using the three-dimensional system of equations for conservation of mass, conservation of momentum, and conservation of energy.

One-parameter group theory is applied twice in succession to reduce the number of independent variables from three to one. To accomplish this reduction, two sets of one-parameter transformation groups are discovered since the one-parameter group theory allows a reduction by one in the number of independent variables per transformation. The resulting system of ordinary differential equations is nonlinear. Hamming's predictor-corrector numerical method is used to determine the solutions to this system of equations.

Calculus of variations techniques are applied to the one-dimensional system of equations to determine an optimum solution constrained by a transformed swirl parameter.

The one-dimensional solutions are then transformed from one-dimensional space to two-dimensional space and next to three-dimensional space using the two sets of transformations discovered by application of the continuous one-parameter group theory.

1.3 Group Theory

The
a particular
particular of

1. Closure.

2. Associat.

3. Left Ide

4. Left In

5. Commute

Not all gr
fifth axiom

[24]. The
transforms

Group Theory

The axioms [2, 18] which a set of elements must follow under particular operation are stated below. A star (*) symbol denotes the particular operation between two elements.

Closure. If a and b are two elements of the set, then $a*b = c$ is also a unique element of the set.

Associativity. When three or more elements are formally manipulated using the defined operation, the order of manipulation makes no difference. Hence,

$$(a*b)*c = a*(b*c).$$

Left Identity. Among the elements there is an identity element, denoted by I , with the property of leaving the elements unchanged after formal manipulation with the defined operation. Therefore, $I*a = a$.

Left Inverse. Each element, a , in the group has a left inverse a^{-1} such that $a^{-1}*a = I$.

Commutativity. When two or more elements are formally manipulated using the defined operation, the order of manipulation may be reversed. Hence, $a*b = b*a$.

All groups satisfy the fifth axiom. Those groups that satisfy the axiom are known as Abelian or commutative.

Continuous one-parameter groups are multiplicative groups

The groups of interest in this work are continuous one-parameter formation groups. The defined operation for multiplicative

transformation

tions. Hence

A set of tra

tion of tran

values a^{-1} ar

such that A

and

Having defi

cept is now

1. Closure

2. Associ

3. Left I

sformation groups is the successive application of the transformations. Hence a point x is taken into a point X as follows:

$$X = A_{a^2} X^1 = A_{a^2} (A_{a^1} x) \equiv A_{a^2} A_{a^1} x,$$

where a^2 and a^1 are parameters.

A set of transformations is said to be closed under the defined operation of transformation multiplication if, given any set of parametric values a^1 and a^2 , a set of parametric values a^3 can always be found such that A_{a^3} is a unique member of the set of given transformations

$$A_{a^1} A_{a^2} = A_{a^3}.$$

When defined the operation for closure, the transformation group concept is now formulated in terms of the group axioms.

Closure. $A_{a^1} A_{a^2} = A_{a^3} \quad (1.3.1)$

Associativity. $A_{a^1} (A_{a^2} A_{a^3}) x = (A_{a^1} A_{a^2}) A_{a^3} x \quad (1.3.2)$

Left Identity. A transformation I exists such that

$$I A_{a^1} x = A_{a^1} I x = A_{a^1} x \quad (1.3.3)$$

Any transformation which leaves a point unaltered is defined as an identity transformation.

4. Left Inverse

Def

Q is unaltered

A , i.e.

$Q(x^1, \dots$

then the fun

De

$Q_{\alpha\mu}(x, y)$,

following de

$$\left| \begin{array}{c} \frac{\partial Q_1}{\partial x^1} \\ \cdot \\ \cdot \\ \cdot \\ \frac{\partial Q_1}{\partial y^1} \end{array} \right|$$

Following t

now restric

of the form

A_1 :

Left Inverse. An inverse transformation $A_{a^1}^{-1}$ belonging to the set exists such that

$$A_{a^1}^{-1} A_{a^1} x = I x = x. \quad (1.3.4)$$

Definition 1.3.1 - If a numerically valued (scalar) function unaltered by an r -parameter continuous group of transformations, i.e.

$$(x^1, \dots, x^m, y^1, \dots, y^n) = Q(\bar{x}^1, \dots, \bar{x}^m, \bar{y}^1, \dots, \bar{y}^n), \quad (1.3.5)$$

the function $Q(x, y)$ is called an absolute invariant of A_r .

Definition 1.3.2 - The $m+n$ functions, $Q_1(x, y), \dots, Q_{m+n}(x, y)$, are said to be functionally independent if and only if the following determinant is non-vanishing.

$$\begin{vmatrix} \frac{\partial Q_1}{\partial x^1} & \dots & \frac{\partial Q_{m+n}}{\partial x^1} \\ \vdots & & \vdots \\ \frac{\partial Q_1}{\partial y^j} & \dots & \frac{\partial Q_{m+n}}{\partial y^j} \end{vmatrix} \neq 0 \quad (i = 1, \dots, m; j = 1, \dots, n) \quad (1.3.6)$$

Following the approach developed by A.J.A. Morgan [44], attention is restricted to a one-parameter continuous group of transformations of the form:

$$\begin{aligned} \bar{x}^i &= f^i(x^1, \dots, x^m; a) & (i = 1, \dots, m; m \geq 2) \\ \bar{y}^j &= f^j(y^1, \dots, y^n; a) & (j = 1, \dots, n; n \geq 1) \end{aligned} \quad (1.3.7)$$

where a is a

form a subg

and the dep

tions. The

up to any r

stives of t

(1.3.7), th

one-paramet

known as e

solute inv

solute inv

$$S_1(y^1)$$

and it is

and

where R

where a is a numerical parameter. The transformations

$$\bar{x}^i = f^i(x^1, \dots, x^m; a) \quad (1.3.8)$$

form a subgroup S_{A_1} of A_1 . The x^i and the y^j denote the independent and the dependent variables of a system of partial differential equations. The y^j are considered to be differentiable functions of the x^i to any required order. If the transformations of the partial derivatives of the y^j with respect to the x^i are appended to those of (1.3.7), the resulting set of transformations also forms a continuous parameter group, A_1^k . New groups constructed in this manner are known as enlargements of the group A_1 .

The group A_1 (1.3.7) has $m+n-1$ functionally independent absolute invariants

$$\eta_1(x^1, \dots, x^m), \dots, \eta_{m-1}(x^1, \dots, x^m) \quad (1.3.9)$$

$$g_1(y^1, \dots, y^n, x^1, \dots, x^m), \dots, g_n(y^1, \dots, y^n, x^1, \dots, x^m) \quad (1.3.10)$$

It is possible to choose them such that the Jacobian

$$\frac{\partial(g_1, \dots, g_n)}{\partial(y^1, \dots, y^n)} \neq 0 \quad (1.3.11)$$

$$R \left[\frac{\partial(\eta_1, \dots, \eta_{m-1})}{\partial(x^1, \dots, x^m)} \right] = m-1 \quad (1.3.12)$$

where R denotes the rank of the indicated Jacobian matrix.

Th
tions of the

where the
in (1.3.10)

y^j , implic
to be exact
defined as
 $\bar{x}^1, \dots, \bar{x}^j$

z

The condi
lent condi

The $n_1, \dots$
the subg
(1.3.15)
absolute
ally in

The y^j and $\bar{y}^j$ are considered to be implicitly defined as functions of the x^i and $\bar{x}^i$ by the equations

$$z_j(x^1, \dots, x^m) = g_j(y^1, \dots, y^n, x^1, \dots, x^m) \quad (1.3.13)$$

$$\bar{z}_j(\bar{x}^1, \dots, \bar{x}^m) = g_j(\bar{y}^1, \dots, \bar{y}^n, \bar{x}^1, \dots, \bar{x}^m) \quad (1.3.14)$$

where the g_j are the absolute invariants of the group (1.3.7) indicated (1.3.10).

Theorem 1.3.1 - A necessary and sufficient condition for the z_j , implicitly defined as functions of $x^1, \dots, x^m$ by equation (1.3.13), to be exactly the same functions of $x^1, \dots, x^m$ as the $\bar{y}^j$, implicitly defined as functions of $\bar{x}^1, \dots, \bar{x}^m$ by equation (1.3.14), are of the form $z_j = \bar{z}_j$, $\dots, \bar{x}^m$ is that

$$z_j(x^1, \dots, x^m) = \bar{z}_j(\bar{x}^1, \dots, \bar{x}^m) = z_j(\bar{x}^1, \dots, \bar{x}^m). \quad (1.3.15)$$

The condition given by equation (1.3.15) can be replaced by the equivalent condition

$$z_j(x^1, \dots, x^m) = F_j(\eta_1, \dots, \eta_{m-1}). \quad (1.3.16)$$

where $\eta_1, \dots, \eta_{m-1}$ are functionally independent absolute invariants of the subgroup S_{A_1} of the group (1.3.7). The equivalence of equations (1.3.15) and (1.3.16) is seen from the group theory statement that any absolute invariant of a group is expressible in terms of the functionally independent absolute invariants.

De

ential equat

same function

solutions of

M

differentia

essary to c

form,

S.

By equation

properties

expressed

point $(x^1,$

n independ

whose arg

are consi

ments of

Definition 1.3.3 - Solutions of a system of partial differential equations which have the property that the y^j are exactly the functions of the x^i as the $\bar{y}^j$ are of the $\bar{x}^i$ are called invariant solutions of a system of partial differential equations.

When considering invariant solutions of systems of partial differential equations, Theorem 1.3.1 demonstrates that it is only necessary to consider equations (1.3.13) or (1.3.14) to be given in the form,

$$g_j(y^1, \dots, y^n, x^1, \dots, x^m) = F_j(\eta_1, \dots, \eta_{m-1}). \quad (1.3.17)$$

equation (1.3.11) and the assumed continuity and differentiability properties of the functions F_j and g_j , it follows that the y^j can be expressed as functions of the F_j and x^i in some neighborhood of the point $(x^1, \dots, x^m)$.

$$y^j = y^j(F_1, \dots, F_n, x^1, \dots, x^m) \quad (1.3.18)$$

Definition 1.3.4 - A differential form of the k-th order in independent variables is a function of the form

$$\phi(x^1, \dots, x^m, y^1, \dots, y^n, \dots, \frac{\partial^k y^1}{\partial (x^1)^k}, \dots, \frac{\partial^k y^n}{\partial (x^m)^k}) \quad (1.3.19)$$

whose arguments include derivatives of the y^j up to order k. The y^j are considered to be functions of the x^i . For convenience, the p arguments of the differential form will be designated by $z^1, \dots, z^p$.

De

variant under
of the group

$\phi(\lambda)$

where ϕ is
 M is some f

D
ally invari
nation of

where ϕ is
and M is s

variant u
of the gr

where ϕ

tial equ
group of
forms ϕ

Definition 1.3.5 - A differential form ϕ is conformally invariant under a one-parameter group A_1 , if, under the transformations of the group, it satisfies the relation

$$\phi(\bar{z}^1, \dots, \bar{z}^p) = M(z^1, \dots, z^p; a) \phi(z^1, \dots, z^p) \quad (1.3.20)$$

ϕ is exactly the same function of the z 's as it is of the $\bar{z}$'s and some function of the z 's and the parameter a .

Definition 1.3.6 - A differential form ϕ is constant conformally invariant under a one-parameter group A_1 , if, under the transformations of the group, it satisfies the relation

$$\phi(\bar{z}^1, \dots, \bar{z}^p) = M(a) \phi(z^1, \dots, z^p) \quad (1.3.21)$$

ϕ is exactly the same function of the z 's as it is of the $\bar{z}$'s and is some function of the parameter a .

Definition 1.3.7 - A differential form ϕ is absolutely invariant under a one-parameter group A_1 , if, under the transformations of the group, it satisfies the relation

$$\phi(\bar{z}^1, \dots, \bar{z}^p) = \phi(z^1, \dots, z^p) \quad (1.3.22)$$

ϕ is exactly the same function of the z 's as it is of the $\bar{z}$'s.

Definition 1.3.8 - A system of k -th order partial differential equations $\phi_j = 0$ is invariant under a continuous one-parameter group of transformations A_1 if each of the k -th order differential ϕ_j is conformally invariant under the transformations of A_1^k . The

group A_n^k is t

cussed previo

Let

$$\phi_j(x^1,$$

be a system

$n(x^2)$ indepe

$x^1, \dots, x^n$

ant under ti

Th

in the syst

invariant u

variant sol

of a system

$$B_j(\eta$$

which is a

independent

the $m-1$ ab

those of e

independen

be reduced

up A_1^k is the k -th enlargement of the group A_1 which has been discussed previously.

Let

$$\phi_j(x^1, \dots, x^m, y^1, \dots, y^n, \dots, \frac{\partial^k y^1}{\partial (x^1)^k}, \dots, \frac{\partial^k y^n}{\partial (x^m)^k}) = 0 \quad (1.3.23)$$

a system of partial differential equations of the k -th order in n independent variables $x^1, \dots, x^m$ and $n(\geq 1)$ dependent variables $y^1, \dots, y^n$ where each of the differential forms is conformally invariant under the k -th enlargement of the group A_1 .

Theorem 1.3.2 - If each of the differential forms $\phi_1, \dots, \phi_n$ of the system of partial differential equations (1.3.23) is conformally invariant under the k -th enlargement of the group (1.3.7), then the invariant solutions of (1.3.23) can be expressed in terms of the solutions of the system of the form

$$B_j(\eta_1, \dots, \eta_{m-1}, F_1, \dots, F_n, \dots, \frac{\partial^k F_1}{\partial \eta_1^k}, \dots, \frac{\partial^k F_n}{\partial \eta_{m-1}^k}) = 0 \quad (1.3.24)$$

is a system of k -th order partial differential equations in $m-1$ independent variables $\eta_1, \dots, \eta_{m-1}$. In equation (1.3.24), the η 's are $m-1$ absolute invariants of the group S_{A_1} and the functions F_j are solutions of equation (1.3.17).

Theorem 1.3.2 gives the conditions under which the number of independent variables in a system of partial differential equations can be reduced by one in the process of obtaining invariant solutions.

1.4 Optimiz

The
standard technique
[41]. The c
minima of f
mined. Hence
the assembly
or a surface

A
below.

In equation
and $y'_k = \frac{dy_k}{dx}$
functions

for which

(1.4.2) se

which inv
freedom o
tween the
It is ass
ing end

Optimization Techniques

The optimization techniques used in this work are the standard techniques from the calculus of variations as presented by Miele

The calculus of variations is concerned with the maxima and minima of functional expressions where entire functions must be determined. Hence, the unknown of the calculus of variations problem is the assembly of an infinite set of points which identify either a curve or a surface, depending upon the nature of the problem.

A functional form to be optimized may be defined as shown

$$\Omega \equiv [\tau(x, y_k)]_i^f + \int_{x_i}^{x_f} \sigma(x, y_k, y_k') dx \quad (1.4.1)$$

Equation (1.4.1), subscripts i and f denote initial and final points

$y_k' \equiv \frac{dy_k}{dx}$. The form Ω is optimized by finding that special set of functions

$$y_k(x) \quad k = 1, \dots, n \quad (1.4.2)$$

such that it is either a maximum or a minimum. The class of functions which satisfy the constraints

$$\phi_j(x, y_k, y_k') = 0 \quad j = 1, \dots, p < n \quad (1.4.3)$$

involve $\pi = n - p$ degrees of freedom. The number of degrees of freedom of a differential system is defined to be the difference between the number of dependent variables and the number of equations. It is assumed that the functions $y_k(x)$ are consistent with the following conditions.

u_p

u_p

The problem

Bolza problem

Th

roducing a

and by form

function.

It is known

satisfy not

which are

The differ

and the Du

knowns. T

tions yiel

simultane

$$\omega_{\mu}(x_i, y_{ki}) = 0 \quad \mu = 1, \dots, q \quad (1.4.4)$$

$$\omega_{\mu}(x_f, y_{kf}) = 0 \quad \mu = q + 1, \dots, s \leq 2n+2 \quad (1.4.5)$$

blem as formulated in the preceding paragraph is known as the problem.

The Bolza problem can be treated simply and elegantly by introducing a set of variable Lagrange multipliers

$$\lambda_j(x) \quad j = 1, \dots, p \quad (1.4.6)$$

Forming the following expression which is known as the augmented

1.

$$K = \sigma + \sum_{j=1}^p \lambda_j \phi_j \quad (1.4.7)$$

known that the optimal arc (the special curve optimizing Ω) must not only equations (1.4.3) but also the following equations be known as the Euler-Lagrange equations.

$$\frac{d}{dx} \left(\frac{\partial K}{\partial y_k} \right) - \frac{\partial K}{\partial y_k} = 0 \quad k = 1, \dots, n \quad (1.4.8)$$

ifferential system composed of the constraining equations (1.4.3), Euler-Lagrange equations (1.4.8) includes $n+p$ equations and un-

Therefore, the solution of this system of differential equations yields the n dependent variables and the p Lagrange multipliers successively.

There are $2n+2$ boundary conditions to which equations (1.4.3)

and (1.4.8)
the bounda
plied by t
condition.

The trans
systems o
and (1.4.

investiga
The Legen
The Leger

For a re

first ca
zero; th
number o
second c
integra
known a
are val

and (1.4.8) are subjected. Equations (1.4.4) and (1.4.5) supply s of the boundary conditions and $2n+2-s$ of the boundary conditions are supplied by the following condition which is known as the transversality condition.

$$\left[d\tau + \left(K - \sum_{k=1}^n \frac{\partial K}{\partial y'_k} y'_k \right) dx + \sum_{k=1}^n \frac{\partial K}{\partial y'_k} dy_k \right]_i^f = 0 \quad (1.4.9)$$

The transversality condition is to be satisfied identically for all systems of infinitesimal displacements consistent with equations (1.4.4) and (1.4.5).

After an optimal arc has been determined, it is necessary to investigate whether the functional Ω attains a maximum or minimum value. The Legendre-Clebsch necessary condition is used to determine this. The Legendre-Clebsch condition for a relative minimum is

$$\sum_{k=1}^n \sum_{j=1}^n \frac{\partial^2 K}{\partial y'_k \partial y'_j} \delta y'_k \delta y'_j \geq 0. \quad (1.4.10)$$

For a relative maximum, the inequality (1.4.10) is reversed.

There are two particular cases of the Bolza problem. The first case is when the integrand of equation (1.4.1) is identically zero; that is, when $\sigma \equiv 0$. This case is known as a Mayer problem. The number of end conditions s is less than $2n+2$ for a Mayer problem. The second case is when the functional to be optimized appears entirely in integral form; that is, when $\tau \equiv 0$ in equation (1.4.1). This case is known as a Lagrange problem. Equations (1.4.8), (1.4.9), and (1.4.10) are valid for both of these particular cases.

Th
to this work
the reader
excellent r

This section reviews only the optimization relations relevant to this work. For a comprehensive treatment on calculus of variations, the reader is referred to the literature on calculus of variations. One excellent reference on calculus of variations is Akhiezer [1].

2.1 Type c

since the

The follow

Therefore

compressi

choice of

coordinat

tions sho

II. MATHEMATICAL SWIRLING FLOW MODEL

Type of Fluid Flow and Coordinate System

In swirling flow, the fluid has a macroscopic rotary motion and the velocity has a tangential component of finite magnitude. The following assumptions are made for this type of flow:

- (1) Viscous effects are negligible.
- (2) The dependent variables are not functions of time
($\frac{\partial}{\partial t} = 0$).
- (3) The fluid is incompressible ($\rho = \text{const.}$).
- (4) Gravitational and electromagnetic body force effects are negligible.
- (5) The flow is isentropic.

Therefore, the class of flows of interest are inviscid, isentropic, incompressible flows.

Since the fluid has a macroscopic rotary motion, the natural set of coordinates is a cylindrical polar coordinate system. These coordinates are related to cartesian coordinates by the familiar relations shown as equations (2.1.1), (2.1.2), and (2.1.3).

$$r^2 = x^2 + y^2 \quad (2.1.1)$$

$$\tan \theta = y/x \quad (2.1.2)$$

$$z = z \quad (2.1.5)$$

In Figure 2.

a basic syst

has a unique

$0 \leq \tau$.

T

will be wri

The velocit

Figure 2.2

2.2 Funda

in Section

servation

in fluid c

tion of n

u

Figure 2.1, the cylindrical polar coordinates are shown referred to a Cartesian system of coordinates. Any point not on the z-axis has a unique representation (r, θ, z) with the restrictions $r \geq 0$ and $0 \leq \theta < 2\pi$.

The vector form for velocity in cylindrical polar coordinates can be written as shown by equation (2.1.4).

$$\vec{q} = u \hat{e}_r + v \hat{e}_\theta + w \hat{e}_z \quad (2.1.4)$$

Velocity components at a point in (r, θ, z) space are shown in Figure 2.2.

Fundamental Equations

The equations governing the types of swirling flow described in Section 2.1 are based on the basic laws of conservation of mass, conservation of momentum, and conservation of energy.

The conservation of mass is given by the continuity equation for fluid dynamics.

$$\frac{\partial u}{\partial r} + \frac{u}{r} + \frac{1}{r} \frac{\partial v}{\partial \theta} + \frac{\partial w}{\partial z} = 0 \quad \begin{array}{l} \text{Conservation of Mass} \\ \text{(Continuity Equation)} \end{array} \quad (2.2.1)$$

For inviscid, isentropic, incompressible flows, the conservation of momentum is given by the three Euler equations.

$$u \frac{\partial u}{\partial r} + \frac{v}{r} \frac{\partial u}{\partial \theta} + w \frac{\partial u}{\partial z} - \frac{v^2}{r} = -\frac{1}{\rho} \frac{\partial p}{\partial r} \quad \begin{array}{l} \text{r-Momentum} \\ \end{array} \quad (2.2.2)$$




FIGURE 2.1 CYLINDRICAL POLAR COORDINATES






FIGURE 2.2 VELOCITY COMPONENTS

u

u

The Rule

equation

thermody

may be

Q is th

to the

work, i

tations

assumpt

are (2

conser

2.3

radiu

varia

$r = r$

$$u \frac{\partial v}{\partial r} + \frac{v}{r} \frac{\partial v}{\partial \theta} + w \frac{\partial v}{\partial z} + \frac{uv}{r} = - \frac{1}{\rho r} \frac{\partial p}{\partial \theta} \quad \theta\text{-Momentum} \quad (2.2.3)$$

$$u \frac{\partial w}{\partial r} + \frac{v}{r} \frac{\partial w}{\partial \theta} + w \frac{\partial w}{\partial z} = - \frac{1}{\rho} \frac{\partial p}{\partial z} \quad z\text{-Momentum} \quad (2.2.4)$$

The Euler equations are non-linear, first order, partial differential equations.

The conservation of energy is expressed by the first law of thermodynamics. For the assumed model, the first law of thermodynamics may be written as the familiar steady flow energy equation.

$$Q = \Delta(e + p/\rho + \frac{1}{2}q^2 + gz) \quad (2.2.5)$$


is the total energy change or difference between the heat energy added to the system and the shaft work done by the system. Assuming no shaft work, isentropic flow, no temperature variations, and negligible gravitational body forces, the quantities Q , e , and gz all vanish. For the assumptions mentioned, equation (2.2.5) reduces to Bernoulli's equation:

$$h = p + \frac{1}{2}\rho q^2 = \text{constant}. \quad (2.2.6)$$

The fundamental governing equations for this investigation are (2.2.1) - conservation of mass; (2.2.2), (2.2.3), and (2.2.4) - conservation of momentum; and (2.2.6) - conservation of energy.

3 Boundary Conditions and Swirl Parameter

The boundary conditions are all specified at the outside swirl radius, r_0 , for any θ and any z . The specific values of the dependent variables will be denoted as shown in the following equations. At $r = r_0$,



$$u = u_0 \quad (2.3.1)$$

$$v = v_0 \quad (2.3.2)$$

$$w = w_0 \quad (2.3.3)$$

$$p = p_0. \quad (2.3.4)$$

four independent variables have specific values at the outside swirl
us and these values are the boundary conditions for this investiga-

The swirl parameter is defined to be the product of a geomet-
similarity ratio known as the swirl aspect ratio and a kinematic
similarity ratio known as the tangential energy fraction.

$$S \equiv \Pi_1 \Pi_2 \quad \text{Swirl Parameter} \quad (2.3.1)$$


$$\Pi_1 \equiv r^2/z^2 \quad \text{Swirl Aspect Ratio} \quad (2.3.2)$$

$$\Pi_2 \equiv \frac{v^2}{h/\rho} \quad \text{Tangential Energy Fraction} \quad (2.3.3)$$

stituting equations (2.3.2) and (2.3.3) into equation (2.3.1), the
parameter equation becomes

$$S = \frac{r^2}{z^2} \frac{v^2}{h/\rho}. \quad (2.3.4)$$

quantity h in equation (2.3.4) is determined from Bernoulli's equa-
(2.2.6).



Non-Dimensional Equations

For greater generality and convenience, all variables are dimensionless. A reference length, z_0 , which is the axial length of the swirl, reduces the radial and axial lengths into dimensionless coordinates. Similarly, the velocity components and static pressure are made dimensionless by comparing them to the tangential velocity, v_0 , and the tangential dynamic pressure, ρv_0^2 . The dimensionless variables are defined as follows:

$$R \equiv r/z_0 \quad (2.4.1)$$

$$Z \equiv z/z_0 \quad (2.4.2)$$

$$U \equiv u/v_0 \quad (2.4.3)$$

$$V \equiv v/v_0 \quad (2.4.4)$$

$$W \equiv w/v_0 \quad (2.4.5)$$

$$P \equiv p/\rho v_0^2. \quad (2.4.6)$$

Application of the dimensionless variables to equation (2.2.2) yields the following intermediate result.

$$U v_0^2 \frac{\partial U}{z_0 \partial R} + \frac{V v_0^2}{R z_0} \frac{\partial U}{\partial \theta} + W v_0^2 \frac{\partial U}{z_0 \partial Z} - \frac{v_0^2}{z_0} \frac{V^2}{R} = - \frac{1}{\rho} \rho v_0^2 \frac{\partial P}{z_0 \partial R}$$

result reduces to

$$U \frac{\partial U}{\partial R} + \frac{V}{R} \frac{\partial U}{\partial \theta} + W \frac{\partial U}{\partial Z} - \frac{V^2}{R} = - \frac{\partial P}{\partial R}. \quad \text{R-Momentum} \quad (2.4.7)$$



Similar applications of the dimensionless variables to equations (2.2.3), (2.2.4), (2.2.1), and (2.2.6) yield the following set of non-dimensional equations:

$$U \frac{\partial V}{\partial R} + \frac{V}{R} \frac{\partial V}{\partial \theta} + W \frac{\partial V}{\partial Z} + \frac{UV}{R} = - \frac{1}{R} \frac{\partial P}{\partial \theta} \quad \theta \text{-Momentum} \quad (2.4.8)$$

$$U \frac{\partial W}{\partial R} + \frac{V}{R} \frac{\partial W}{\partial \theta} + W \frac{\partial W}{\partial Z} = - \frac{\partial P}{\partial Z} \quad Z\text{-Momentum} \quad (2.4.9)$$

$$\frac{\partial U}{\partial R} + \frac{U}{R} + \frac{1}{R} \frac{\partial V}{\partial \theta} + \frac{\partial W}{\partial Z} = 0 \quad \text{Conservation of Mass} \quad (2.4.10)$$

$$H = P + 1/2(U^2 + V^2 + W^2) \quad \text{Bernoulli Equation.} \quad (2.4.11)$$

The quantity H in equation (2.4.11) is defined to be

$$H \equiv h/\rho v_o^2. \quad (2.4.12)$$

The dimensionless boundary conditions at $R = R_o$ are:

$$U = U_o \quad (2.4.13)$$


$$V = V_o = 1 \quad (2.4.14)$$

$$W = W_o \quad (2.4.15)$$


$$P = P_o. \quad (2.4.16)$$

When converted to dimensionless variables, the swirl parameter (2.3.4) becomes

$$S = \frac{R^2}{Z^2} \frac{V^2}{H}. \quad (2.4.17)$$



Equations (2.4.7), (2.4.8), (2.4.9), (2.4.10), and (2.4.11) are the non-dimensional forms of the fundamental governing equations for this work.



III. REDUCTION OF THE NUMBER OF INDEPENDENT VARIABLES

In this chapter, the ideas outlined in section 1.3 are applied to the non-dimensional model equations given in section 2.4. The number of independent variables is reduced from three to two and then from two to one.


3.1 Three to Two Reduction in the Number of Independent Variables

The three independent variables (R, θ, Z) are reduced to the two independent variables (η_1, η_2) . The new independent variables (η_1, η_2) are functionally independent absolute invariants of a subgroup of the one-parameter continuous group of transformations, A_1 . The one-parameter continuous group of transformations, A_1 , will subsequently be referred to as the group A_1 .

The group A_1 is chosen as shown below:

$$\begin{aligned}
 \bar{R} &= e^{at_1} R & \bar{U} &= e^{at_4} U & \bar{P} &= e^{at_7} P \\
 A_1: \quad \bar{\theta} &= \theta + at_2 & \bar{V} &= e^{at_5} V & & (3.1.1) \\
 \bar{Z} &= e^{at_3} Z & \bar{W} &= e^{at_6} W
 \end{aligned}$$

where $t_1, t_2, t_3, t_4, t_5, t_6$, and t_7 are constants and a is the group parameter. The group labeled as (3.1.1) has the general form specified by equation (1.3.7). The transformed independent variables are functions of the parameter a and the previous independent variables.



ilarly, the transformed dependent variables are functions of the parameter a and the previous dependent variables. There is no unique method for specifying groups such as (3.1.1) and the form for θ is that proposed by Hall [24, pg. 93]. By specifying θ as shown, the author discovered that the group A_1 would satisfy all the required conditions to affect a reduction by one in the number of independent variables for the system of equations given in section 2.4.

The group A_1 (3.1.1) must satisfy the four group axioms given in equations (1.3.1), (1.3.2), (1.3.3), and (1.3.4). To demonstrate the satisfaction of the group axioms, only the transformations on R and θ are considered. All the remaining transformations are similar to the transformation on R and if the R transformation satisfies the group axioms, so will the remaining transformations.

The closure axiom, equation (1.3.1), is applied using the symbol A_{a1} to denote a particular transformation utilizing the parameter

$$A_{a1} A_{a2} R = A_{a1} (e^{a^2 t_1} R) = A_{a1} \bar{R} = e^{a^1 t_1} \bar{R} = \quad (3.1.2)$$

$$e^{a^1 t_1} e^{a^2 t_1} R = e^{(a^1 + a^2) t_1} R = e^{a^3 t_1} R \equiv A_{a3} R$$

$$A_{a1}^1 A_{a2}^1 \theta = A_{a1}^1 (\theta + a^2 t_2) = A_{a1}^1 \bar{\theta} = \bar{\theta} + a^1 t_2 = \quad (3.1.3)$$

$$\theta + a^2 t_2 + a^1 t_2 = \theta + (a^1 + a^2) t_2 = \theta + a^3 t_2 \equiv A_{a3}^1 \theta$$

$$\text{Where} \quad a^1 + a^2 \equiv a^3. \quad (3.1.4)$$

closure axiom is satisfied since A_{a^3} and $A_{a^3}^1$ have been shown to be group members of the set of given transformations.

Equation (1.3.2), the associativity axiom, is applied where a^1 denotes a particular transformation utilizing the parameter a^1 .

$$A_{a^1}(A_{a^2} A_{a^3}) R = A_{a^1} e^{(a^2 + a^3)t_1} R = e^{a^1 t_1} e^{(a^2 + a^3)t_1} R = e^{[a^1 + (a^2 + a^3)]t_1} R \quad (3.1.5)$$

$$(A_{a^1} A_{a^2}) A_{a^3} R = A_{a^1} A_{a^2} e^{a^3 t_1} R = e^{(a^1 + a^2)t_1} e^{a^3 t_1} R = e^{[(a^1 + a^2) + a^3]t_1} R \quad (3.1.6)$$

Since equation (3.1.5) equals (3.1.6), the associativity axiom is satisfied for the type of transformation employed on R .


$$(A_{a^2}^1 A_{a^3}^1) \theta = A_{a^1}^1 (\theta + (a^2 + a^3)t_2) = \theta + [a^1 + (a^2 + a^3)]t_2 \quad (3.1.7)$$

$$A_{a^1}^1 A_{a^2}^1 A_{a^3}^1 \theta = A_{a^1}^1 A_{a^2}^1 (\theta + a^3 t_2) = \theta + [(a^1 + a^2) + a^3]t_2 \quad (3.1.8)$$

Equation (3.1.7) equals equation (3.1.8) which demonstrates that the associativity axiom is satisfied also for the type of transformation employed on θ .

Any transformation which leaves a point unaltered is by definition an identity transformation. For the group A_1 , it is seen by inspection that this definition is satisfied when the parameter a equals 0. The left identity axiom, equation (1.3.3), is satisfied when

$$a = 0. \quad (3.1.9)$$



= 0,

$$\bar{R} = e^{at_1} R = R \quad (3.1.10)$$

$$\bar{\theta} = \theta + at_2 = \theta. \quad (3.1.11)$$

For the types of transformations employed on R and θ , it is by inspection that the inverse transformation is obtained by allowing the parameter a to be negative. Therefore, the left inverse axiom, equation (1.3.4), is satisfied when

$$a = -a. \quad (3.1.12)$$

example,


$$A_a^{-1} A_a R = e^{-at_1} e^{at_1} R = IR = R \quad (3.1.13)$$

$$A_a^{-1} \theta = A_a^{-1} (\theta + at_2) = A_a^{-1} \bar{\theta} = \bar{\theta} - at_2 = \theta + at_2 - at_2 = \theta. \quad (3.1.14)$$

Group A_1 (3.1.1) satisfies the four group axioms for closure, associativity, left identity, and left inverse.

Theorem 1.3.2 gives the conditions under which the number of independent variables in a system of partial differential equations can be reduced by one in the process of obtaining invariant solutions. The k -dimensional equations given in section 2.4 must be conformally invariant under the k -th enlargement of the group A_1 (3.1.1). Conformal invariance is defined by Definition 1.3.5 and given in equation form by equation (1.3.20). For convenience, equation (1.3.20) for conformal invariance is displayed in this section.

$$\Phi(\bar{z}^1, \dots, \bar{z}^p) = M(\bar{z}^1, \dots, z^p; a) \Phi(z^1, \dots, z^p) \quad (1.3.20)$$



By conformal invariance, the group A_1 (3.1.1) is formally substituted into an equation and the mathematical manipulations indicated in equation (1.3.20) are performed. The resulting form must then be the equation (1.3.20) for the equation to be conformally invariant.

The group A_1 (3.1.1) is formally substituted into equation the R-Momentum equation.

$$\begin{aligned} \bar{U} \frac{\partial \bar{U}}{\partial \bar{R}} + \frac{\bar{V}}{\bar{R}} \frac{\partial \bar{U}}{\partial \bar{\theta}} + \bar{W} \frac{\partial \bar{U}}{\partial \bar{Z}} - \frac{\bar{V}^2}{\bar{R}} + \frac{\partial \bar{P}}{\partial \bar{R}} &= e^{a(2t_4-t_1)} U \frac{\partial U}{\partial R} \\ (t_4+t_5-t_1) \frac{V}{R} \frac{\partial U}{\partial \theta} + e^{a(t_6+t_4-t_3)} W \frac{\partial U}{\partial Z} - e^{a(2t_5-t_1)} \frac{V^2}{R} \\ &+ e^{a(t_7-t_1)} \frac{\partial P}{\partial R} \end{aligned} \quad (3.1.15)$$


Exponential terms in equation (3.1.15) must equal each other to obtain necessary form for conformal invariance as indicated by equation (1.3.20). Equating the exponential terms, the following results are obtained:

$$t_1 = t_4 + t_5 - t_1 = t_6 + t_4 - t_3 = 2t_5 - t_1 = t_7 - t_1, \quad (3.1.16)$$

$$t_4 = t_5, t_4 = t_6 + t_1 - t_3, t_7 = 2t_4. \quad (3.1.17)$$

From equation (3.1.15) that the function M of equation (1.3.20) is only a function of the parameter a . By Definition 1.3.6, the differential form represented by equation (3.1.15) is constant conformally invariant.

The group A_1 (3.1.1) is formally substituted into equation the θ -Momentum equation.



$$\begin{aligned}
\bar{U} \frac{\partial \bar{V}}{\partial \bar{R}} + \frac{\bar{V}}{\bar{R}} \frac{\partial \bar{V}}{\partial \bar{\theta}} + \bar{W} \frac{\partial \bar{V}}{\partial \bar{Z}} + \frac{\bar{U}\bar{V}}{\bar{R}} + \frac{1}{\bar{R}} \frac{\partial \bar{P}}{\partial \bar{\theta}} &= e^{a(t_4+t_5-t_1)} U \frac{\partial V}{\partial R} \\
e^{a(2t_5-t_1)} \frac{V}{R} \frac{\partial V}{\partial \theta} + e^{a(t_6+t_5-t_3)} W \frac{\partial V}{\partial Z} + e^{a(t_4+t_5-t_1)} \frac{UV}{R} \\
+ e^{a(t_7-t_1)} \frac{1}{R} \frac{\partial P}{\partial \theta} & \quad (3.1.18)
\end{aligned}$$

ponential terms in equation (3.1.18) must equal each other to obtain the necessary form for conformal invariance as indicated by equation (3.1.20). Equating the exponential terms, the following results are obtained:


$$t_4 + t_5 - t_1 = 2t_5 - t_1 = t_6 + t_5 - t_3 = t_7 - t_1, \quad (3.1.19)$$

$$t_4 = t_5, t_5 = t_6 + t_1 - t_3, t_7 = 2t_4. \quad (3.1.20)$$

Comparison of equations (1.3.20) and (3.1.18) indicates that the function of equation (1.3.20) is only a function of the parameter a . By equation 1.3.6, the differential form represented by equation (3.1.18) is invariant conformally invariant.

The group A_1 (3.1.1) is formally substituted into equation (3.1.18), the Z-Momentum equation.

$$\begin{aligned}
\bar{U} \frac{\partial \bar{W}}{\partial \bar{R}} + \frac{\bar{V}}{\bar{R}} \frac{\partial \bar{W}}{\partial \bar{\theta}} + \bar{W} \frac{\partial \bar{W}}{\partial \bar{Z}} + \frac{\partial \bar{P}}{\partial \bar{Z}} &= e^{a(t_4+t_6-t_1)} U \frac{\partial W}{\partial R} \\
+ e^{a(t_5+t_6-t_1)} \frac{V}{R} \frac{\partial W}{\partial \theta} + e^{a(2t_6-t_3)} W \frac{\partial W}{\partial Z} \\
+ e^{a(t_7-t_3)} \frac{\partial P}{\partial Z} & \quad (3.1.21)
\end{aligned}$$



obtain the necessary form for conformal invariance as indicated by equation (1.3.20), the exponential terms in equation (3.1.21) must equal each other. The following results are obtained by equating the exponential terms:

$$t_4 + t_6 - t_1 = t_5 + t_6 - t_1 = 2t_6 - t_3 = t_7 - t_3, \quad (3.1.22)$$

$$t_4 = t_5, \quad 2t_6 = t_7. \quad (3.1.23)$$

Comparison of equations (3.1.17), (3.1.20), and (3.1.23) yields the result,

$$t_4 = t_5 = t_6. \quad (3.1.24)$$


From equations (3.1.22) and (3.1.24), it follows that

$$t_1 = t_3. \quad (3.1.25)$$

Comparison of equations (1.3.20) and (3.1.21) indicates that the function M in equation (1.3.20) is only a function of the parameter a . Therefore, the differential form represented by equation (3.1.21) is constant conformally invariant according to Definition 1.3.6.

The group A_1 (3.1.1) is formally substituted into equation (4.10), the Conservation of Mass equation.

$$\begin{aligned} \frac{\partial \bar{U}}{\partial R} + \frac{\bar{U}}{R} + \frac{1}{R} \frac{\partial \bar{V}}{\partial \theta} + \frac{\partial \bar{W}}{\partial Z} &= e^{a(t_4-t_1)} \frac{\partial U}{\partial R} + e^{a(t_4-t_1)} \frac{U}{R} \\ &+ e^{a(t_5-t_1)} \frac{1}{R} \frac{\partial V}{\partial \theta} + e^{a(t_6-t_3)} \frac{\partial W}{\partial Z} \end{aligned} \quad (3.1.26)$$



the exponential terms in equation (3.1.26) must equal each other to obtain the necessary form for conformal invariance as indicated by equation (1.3.20). Equating the exponential terms, the following results are obtained:

$$t_4 = t_5, t_5 = t_6 + t_1 - t_3, t_4 = t_5 = t_6. \quad (3.1.27)$$

Equations (3.1.27) agree with the results obtained from the previous conformal invariance verifications. Again, by comparison of equations (1.3.20) and (3.1.26), the function M in equation (1.3.20) is seen to be only a function of the parameter a . Therefore, the differential form represented by equation (3.1.26) is constant conformally invariant according to Definition 1.3.6.


The group A_1 (3.1.1) is formally substituted into equation (1.4.11), the Bernoulli equation:

$$H - \bar{P} - 1/2 (\bar{U}^2 + \bar{V}^2 + \bar{W}^2) = H - e^{at_7} P - 1/2 (e^{a2t_4} U^2 + e^{a2t_5} V^2 + e^{a2t_6} W^2). \quad (3.1.28)$$

For conformal invariance, the exponential terms in equation (3.1.28) must equal each other as indicated by equation (1.3.20). The results of equating the exponential terms are shown below:

$$t_7 = 2t_4, t_4 = t_5 = t_6. \quad (3.1.29)$$

Equations (3.1.29) agree with the results obtained previously. Comparison of equations (3.1.28) and (1.3.20) indicates that the function M in equation (1.3.20) is a function only of the parameter a . By Definition 1.3.6, the differential form represented by equation (3.1.28) is



constant conformally invariant.

By inspection, it is seen that equation (2.4.17) for the Swirl Parameter is constant conformally invariant under the group A_1 (3.1.1).


Since the equations (2.4.7), (2.4.8), (2.4.9), (2.4.10), (2.4.11), and (2.4.17) are all constant conformally invariant under the k -th enlargement of the group A_1 (3.1.1), Theorem 1.3.2 states that the number of independent variables for the system of equations mentioned above can be reduced by one in the process of obtaining invariant solutions.

Using the results (3.1.17), (3.1.24), and (3.1.25) obtained from the conformal invariance verifications, the group A_1 (3.1.1) is modified as shown below:

$$\begin{aligned}
 \bar{R} &= e^{at_1} R & \bar{U} &= e^{at_4} U & \bar{P} &= e^{2at_4} P \\
 A_1: \quad \bar{\theta} &= \theta + at_2 & \bar{V} &= e^{at_4} V & & (3.1.30) \\
 \bar{Z} &= e^{at_1} Z & \bar{W} &= e^{at_4} W
 \end{aligned}$$

where t_1 , t_2 , and t_4 are constants and a is the group parameter.

The group A_1 (3.1.30) has $m+n-1 = 6$ functionally independent absolute invariants. Equation (1.3.9) gives the form for $m-1 = 2$ of the absolute invariants and equation (1.3.10) gives the form for the remaining $n = 4$ absolute invariants. Definition 1.3.1 and equation 1.3.5 give the definition and general form for an absolutely invariant form. The manner in which absolute invariants are selected is not well defined. The functions η_1 and η_2 are chosen as follows:



$$\eta_1 = e^{-\theta} R^p \quad (3.1.31)$$

$$\eta_2 = e^{-\theta} Z^b. \quad (3.1.32)$$

For the functions in equations (3.1.31) and (3.1.32) to be absolute invariants, the following relations must hold:

$$\eta_1(\bar{\theta}, \bar{R}) = \eta_1(\theta, R) \quad (3.1.33)$$

$$\eta_2(\bar{\theta}, \bar{Z}) = \eta_2(\theta, Z). \quad (3.1.34)$$

The values of the exponents p and b of equations (3.1.31) and (3.1.32) must be determined such that equations (3.1.33) and (3.1.34) are true. The required transformations from the group A_1 (3.1.30) are utilized in the following equations to determine p and b :

$$\eta_1 = e^{-\bar{\theta}} \bar{R}^p = e^{-(\theta+at_2)} e^{pat_1} R^p = e^{a(pt_1-t_2)} e^{-\theta} R^p$$

$$p = t_2/t_1 \quad (3.1.35)$$


$$\eta_2 = e^{-\bar{\theta}} \bar{Z}^b = e^{-(\theta+at_2)} e^{bat_1} Z^b = e^{a(bt_1-t_2)} e^{-\theta} Z^b$$

$$b = t_2/t_1 \quad (3.1.36)$$

Equations (3.1.35) and (3.1.36) are substituted into equations (3.1.31) and (3.1.32):

$$\eta_1 = e^{-\theta} R^{t_2/t_1} \quad (3.1.37)$$

$$\eta_2 = e^{-\theta} Z^{t_2/t_1}. \quad (3.1.38)$$



functions f_1, f_2, f_3 , and f_4 are chosen to resemble η_1 and η_2 :

$$f_1 = Ue^{-\delta_1 \theta}, f_2 = Ve^{-\delta_2 \theta}, f_3 = We^{-\delta_3 \theta}, f_4 = Pe^{-\delta_4 \theta}. \quad (3.1.39)$$

the functions in equations (3.1.39) to be absolute invariants, the following relations must hold:

$$f_1(\bar{U}, \bar{\theta}) = f_1(U, \theta), f_2(\bar{V}, \bar{\theta}) = f_2(V, \theta), \quad (3.1.40)$$

$$f_3(\bar{W}, \bar{\theta}) = f_3(W, \theta), f_4(\bar{P}, \bar{\theta}) = f_4(P, \theta). \quad (3.1.41)$$

values of the exponents $\delta_1, \delta_2, \delta_3$, and δ_4 of equations (3.1.39) be determined such that equations (3.1.40) and (3.1.41) are true. required transformations from the group A_1 (3.1.30) are utilized in following equations to determine the exponents $\delta_1, \delta_2, \delta_3$, and δ_4 :

$$f_1 = \bar{U}e^{-\delta_1 \bar{\theta}} = e^{at_4} Ue^{-\delta_1(\theta+at_2)} = e^{a(t_4-\delta_1 t_2)} Ue^{-\delta_1 \theta}$$

$$\delta_1 = t_4/t_2 \quad (3.1.42)$$

$$f_2 = \bar{V}e^{-\delta_2 \bar{\theta}} = e^{at_4} Ve^{-\delta_2(\theta+at_2)} = e^{a(t_4-\delta_2 t_2)} Ve^{-\delta_2 \theta}$$

$$\delta_2 = t_4/t_2 \quad (3.1.43)$$

$$f_3 = \bar{W}e^{-\delta_3 \bar{\theta}} = e^{at_4} We^{-\delta_3(\theta+at_2)} = e^{a(t_4-\delta_3 t_2)} We^{-\delta_3 \theta}$$

$$\delta_3 = t_4/t_2 \quad (3.1.44)$$

$$f_4 = \bar{P}e^{-\delta_4 \bar{\theta}} = e^{2at_4} Pe^{-\delta_4(\theta+at_2)} = e^{a(2t_4-\delta_4 t_2)} Pe^{-\delta_4 \theta}$$

$$\delta_4 = 2t_4/t_2. \quad (3.1.45)$$

The values of the δ_i 's are substituted into equations (3.1.39) to obtain the following results:

$$f_1 = Ue^{-t_4/t_2^\theta}, f_2 = Ve^{-t_4/t_2^\theta}, f_3 = We^{-t_4/t_2^\theta}, f_4 = Pe^{-2t_4/t_2^\theta}. \quad (3.1.46)$$


The condition given by equation (1.3.11) must be satisfied by the chosen functions f_1, f_2, f_3 , and f_4 .

$$J = \frac{\partial(f_1, f_2, f_3, f_4)}{\partial(U, V, W, P)} \neq 0 \quad (3.1.47)$$

$$J = \begin{vmatrix} \frac{\partial f_1}{\partial U} & \frac{\partial f_1}{\partial V} & \frac{\partial f_1}{\partial W} & \frac{\partial f_1}{\partial P} \\ \frac{\partial f_2}{\partial U} & \frac{\partial f_2}{\partial V} & \frac{\partial f_2}{\partial W} & \frac{\partial f_2}{\partial P} \\ \frac{\partial f_3}{\partial U} & \frac{\partial f_3}{\partial V} & \frac{\partial f_3}{\partial W} & \frac{\partial f_3}{\partial P} \\ \frac{\partial f_4}{\partial U} & \frac{\partial f_4}{\partial V} & \frac{\partial f_4}{\partial W} & \frac{\partial f_4}{\partial P} \end{vmatrix} \quad (3.1.48)$$

Using equations (3.1.46), equation (3.1.48) becomes:

$$J = \begin{vmatrix} e^{-t_4/t_2^\theta} & 0 & 0 & 0 \\ 0 & e^{-t_4/t_2^\theta} & 0 & 0 \\ 0 & 0 & e^{-t_4/t_2^\theta} & 0 \\ 0 & 0 & 0 & e^{-2t_4/t_2^\theta} \end{vmatrix}.$$



The Jacobian determinant J is non-vanishing for the chosen functions f_1, f_2, f_3 , and f_4 . Therefore, the condition (3.1.47) is satisfied.

The condition given by equation (1.3.12) must be satisfied by the functions η_1 and η_2 .

$$R \left[\frac{\partial(\eta_1, \eta_2)}{\partial(R, \theta, Z)} \right] = m-1 = 2 \quad (3.1.49)$$

The rank of the indicated matrix must equal 2. Expanding the matrix given in equation (3.1.49) gives the following result:


$$\begin{bmatrix} \frac{\partial \eta_1}{\partial R} & \frac{\partial \eta_1}{\partial \theta} & \frac{\partial \eta_1}{\partial Z} \\ \frac{\partial \eta_2}{\partial R} & \frac{\partial \eta_2}{\partial \theta} & \frac{\partial \eta_2}{\partial Z} \end{bmatrix} \equiv M. \quad (3.1.50)$$

Using equations (3.1.37) and (3.1.38), equation (3.1.50) becomes:

$$\begin{bmatrix} \frac{\xi}{R} \eta_1 & -\eta_1 & 0 \\ 0 & -\eta_2 & \frac{\xi}{Z} \eta_2 \end{bmatrix} = M, \quad (3.1.51)$$

$$\text{where } \xi \equiv t_2/t_1. \quad (3.1.52)$$

Since M is a 2×3 matrix and the row rank equals the column rank for a matrix, 2 is the maximum rank that M in (3.1.51) can have. Both rows of M in (3.1.51) are linearly independent and hence, M has rank of 2. The condition indicated by equation (3.1.49) is satisfied for the chosen functions η_1 and η_2 .



It has been demonstrated that equations (3.1.37), (3.1.38), (3.1.46) represent the functionally independent absolute invariants of the group A_1 (3.1.30).

Application of equation (1.3.17) to the invariants of the group A_1 (3.1.30) yields the following result:

$$f_j(U, V, W, P, R, \theta, Z) = F_j(\eta_1, \eta_2) \quad j = 1, 2, 3, 4. \quad (3.1.53)$$

Equations (3.1.46) are rearranged using the symbolic equation (3.1.53):

$$U = e^{\alpha\theta} F_1(\eta_1, \eta_2), \quad V = e^{\alpha\theta} F_2(\eta_1, \eta_2), \quad (3.1.54)$$

$$W = e^{\alpha\theta} F_3(\eta_1, \eta_2), \quad P = e^{2\alpha\theta} F_4(\eta_1, \eta_2), \quad (3.1.55)$$

$$\text{where } \alpha \equiv t_4/t_2. \quad (3.1.56)$$

For convenience, equations (3.1.44) and (3.1.45) and the partial derivatives of these equations are listed together.


$$\eta_1 = e^{-\theta} R^\xi \quad (3.1.57)$$

$$\eta_2 = e^{-\theta} Z^\xi \quad (3.1.58)$$


$$\frac{\partial \eta_1}{\partial Z} = 0 \quad \frac{\partial \eta_2}{\partial R} = 0$$

$$\frac{\partial \eta_1}{\partial \theta} = -\eta_1 \quad \frac{\partial \eta_2}{\partial \theta} = -\eta_2 \quad (3.1.59)$$

$$\frac{\partial \eta_1}{\partial R} = \frac{\xi}{R} \eta_1 \quad \frac{\partial \eta_2}{\partial Z} = \frac{\xi}{Z} \eta_2$$



The relations (3.1.54) through (3.1.59) are now used to reduce the number of independent variables in the system of equations given in section 2.4. The three independent variables (R, θ, Z) are reduced to the two independent variables (η_1, η_2) in equations (2.4.7), (2.4.8), (2.4.9), (2.4.10), (2.4.11), and (2.4.17). Figures 3.1 through 3.6 illustrate the transformation details and give the final result for each of these equations. Note that the final result displayed in each figure is obtained by summing all the transformed terms given in the figure.



$$\frac{\partial}{\partial R} = e^{-F_1} \left(\frac{1}{\partial \eta_1} \frac{\partial}{\partial R} + \frac{1}{\partial \eta_2} \frac{\partial}{\partial R} \right) = e^{-F_1} \frac{\partial}{\partial R} \quad (3.1.60)$$

$$\frac{V}{R} \frac{\partial U}{\partial \theta} = \frac{e^{2\alpha\theta}}{R} \frac{F_2}{\partial \theta} \left(\frac{\partial F_1}{\partial \theta} + \alpha F_1 \right) = \frac{e^{2\alpha\theta}}{R} \left(\frac{\partial F_1}{\partial \eta_1} \frac{\partial \eta_1}{\partial \theta} + \frac{\partial F_1}{\partial \eta_2} \frac{\partial \eta_2}{\partial \theta} + \alpha F_1 \right) = \frac{e^{2\alpha\theta}}{R} \left(F_2 \left(-\eta_1 \frac{\partial F_1}{\partial \eta_1} - \eta_2 \frac{\partial F_1}{\partial \eta_2} \right) + \alpha F_1 F_2 \right) \quad (3.1.61)$$

$$W \frac{\partial U}{\partial Z} = e^{2\alpha\theta} F_3 \frac{\partial F_1}{\partial Z} = e^{2\alpha\theta} F_3 \left(\frac{\partial F_1}{\partial \eta_1} \frac{\partial \eta_1}{\partial Z} + \frac{\partial F_1}{\partial \eta_2} \frac{\partial \eta_2}{\partial Z} \right) = e^{2\alpha\theta} F_3 \xi \eta_2 \frac{\partial F_1}{\partial \eta_2} \quad (3.1.62)$$

$$-V^2 = -e^{2\alpha\theta} \frac{F_2^2}{R} \quad (3.1.63)$$


39


$$-\frac{\partial P}{\partial R} = -e^{2\alpha\theta} \frac{\partial F_4}{\partial R} = -e^{2\alpha\theta} \left(\frac{\partial F_4}{\partial \eta_1} \frac{\partial \eta_1}{\partial R} + \frac{\partial F_4}{\partial \eta_2} \frac{\partial \eta_2}{\partial R} \right) = -e^{2\alpha\theta} \xi \eta_1 \frac{\partial F_4}{\partial \eta_1} \quad (3.1.64)$$

$$\frac{R}{Z} = \left(\frac{\eta_1}{\eta_2} \right)^{1/\xi} \quad \begin{array}{l} \text{(From equations} \\ \text{(3.1.57) and (3.1.58).)} \end{array} \quad (3.1.65)$$

$$\left(\xi F_1 - F_2 \right) \eta_1 \frac{\partial F_1}{\partial \eta_1} + \left(\xi F_3 \left(\frac{1}{\eta_2} \right) - F_2 \right) \eta_2 \frac{\partial F_1}{\partial \eta_2} - F_2^2 + \alpha F_1 F_2 = \xi \eta_1 \frac{\partial F_4}{\partial \eta_1} \quad (3.1.66)$$

FIGURE 3.1 $(R, \theta, Z) \rightarrow (\eta_1, \eta_2)$ REDUCTION R-MOMENTUM EQUATION (2.4.7)





$$(3.1.73)$$

$$\frac{\partial}{\partial R} = e^{-1} \left(\frac{\partial}{\partial R} + \frac{1}{\partial \eta_1} \frac{\partial}{\partial R} + \frac{1}{\partial \eta_2} \frac{\partial}{\partial R} \right) = e^{-1} \left(\frac{\partial}{\partial R} + \frac{1}{\partial \eta_1} \frac{\partial}{\partial R} + \frac{1}{\partial \eta_2} \frac{\partial}{\partial R} \right)$$

$$\frac{V}{R} \frac{\partial W}{\partial \theta} = \frac{e^{2\alpha\theta}}{R} \left(F_2 \frac{\partial F_3}{\partial \theta} + \alpha F_2 F_3 \right) = \frac{e^{2\alpha\theta}}{R} \left(F_2 \left(\frac{\partial F_3}{\partial \theta} + \frac{\partial F_3}{\partial \eta_1} \frac{\partial \eta_1}{\partial \theta} \right) + \alpha F_2 F_3 \right) = \frac{e^{2\alpha\theta}}{R} \left(F_2 \left(-\eta_1 \frac{\partial F_3}{\partial \eta_1} - \eta_2 \frac{\partial F_3}{\partial \eta_2} \right) + \alpha F_2 F_3 \right) + \alpha F_2 F_3$$

$$(3.1.74)$$

$$W \frac{\partial W}{\partial Z} = e^{2\alpha\theta} F_3 \frac{\partial F_3}{\partial Z} = e^{2\alpha\theta} F_3 \left(\frac{\partial F_3}{\partial \eta_1} \frac{\partial \eta_1}{\partial Z} + \frac{\partial F_3}{\partial \eta_2} \frac{\partial \eta_2}{\partial Z} \right) = e^{2\alpha\theta} F_3 \left(\frac{\partial F_3}{\partial \eta_1} \frac{\partial \eta_1}{\partial Z} + \frac{\partial F_3}{\partial \eta_2} \frac{\partial \eta_2}{\partial Z} \right)$$

$$(3.1.75)$$

$$41$$

$$-\frac{\partial P}{\partial Z} = -e^{2\alpha\theta} \frac{\partial F_4}{\partial Z} = -e^{2\alpha\theta} \left(\frac{\partial F_4}{\partial \eta_1} \frac{\partial \eta_1}{\partial Z} + \frac{\partial F_4}{\partial \eta_2} \frac{\partial \eta_2}{\partial Z} \right) = -e^{2\alpha\theta} \left(\frac{\partial F_4}{\partial \eta_1} \frac{\partial \eta_1}{\partial Z} + \frac{\partial F_4}{\partial \eta_2} \frac{\partial \eta_2}{\partial Z} \right)$$

$$(3.1.76)$$

$$\left(\xi F_1 - F_2 \right) \eta_1 \frac{\partial F_3}{\partial \eta_1} + \left(\xi F_3 \left(\frac{1}{\eta_2} \right) - F_2 \right) \eta_2 \frac{\partial F_3}{\partial \eta_2} + \alpha F_2 F_3 = \xi \left(\frac{1}{\eta_2} \right) \eta_2 \frac{\partial F_4}{\partial \eta_2}$$

$$(3.1.77)$$

FIGURE 3.3 (R, θ, Z) → (η₁, η₂) REDUCTION Z-MOMENTUM EQUATION (2.4.9)



(3.1.78)

$$\frac{\partial R}{\partial \theta} = \frac{\partial R}{\partial \eta_1} \frac{\partial R}{\partial \eta_2} + \frac{\partial R}{\partial \eta_1} \frac{\partial R}{\partial \eta_2} = \frac{1}{R} \frac{\partial R}{\partial \eta_1}$$

$$\frac{U}{R} = \frac{e^{\alpha \theta}}{R} F_1 \quad (3.1.79)$$

$$\frac{1}{R} \frac{\partial V}{\partial \theta} = \frac{e^{\alpha \theta}}{R} \left(\frac{\partial F_2}{\partial \theta} + \alpha F_2 \right) = \frac{e^{\alpha \theta}}{R} \left(-\eta_1 \frac{\partial F_2}{\partial \eta_1} - \eta_2 \frac{\partial F_2}{\partial \eta_2} + \alpha F_2 \right) \quad (3.1.80)$$

 $\frac{1}{R}$

$$\frac{\partial W}{\partial Z} = e^{\alpha \theta} \frac{\partial F_3}{\partial Z} = e^{\alpha \theta} \left(\frac{\partial F_3}{\partial \eta_1} \frac{\partial \eta_1}{\partial Z} + \frac{\partial F_3}{\partial \eta_2} \frac{\partial \eta_2}{\partial Z} \right) = e^{\alpha \theta} \frac{1}{Z} \eta_2 \frac{\partial F_3}{\partial \eta_2} \quad (3.1.81)$$

$$\xi \eta_1 \frac{\partial F_1}{\partial \eta_1} + F_1 + \alpha F_2 - \eta_1 \frac{\partial F_2}{\partial \eta_1} - \eta_2 \frac{\partial F_2}{\partial \eta_2} + \xi \left(\frac{1}{\eta_2} \right)^{1/\xi} \eta_2 \frac{\partial F_3}{\partial \eta_2} = 0 \quad (3.1.82)$$

FIGURE 3.4 (R, θ, Z) → (η₁, η₂) REDUCTION CONSERVATION OF MASS EQUATION (2.4.10)



$$H = e^{2\alpha\theta} (F_4 + 1/2(F_1^2 + F_2^2 + F_3^2))$$


(3.1.83)

FIGURE 3.5 $(R, \theta, Z) \rightarrow (\eta_1, \eta_2)$ REDUCTION BERNOULLI EQUATION (2.4.11)

$$S = \left(\frac{\eta_1}{\eta_2}\right)^{2/\xi} e^{2\alpha\theta} F_2^2/H$$

(3.1.84)

FIGURE 3.6 $(R, \theta, Z) \rightarrow (\eta_1, \eta_2)$ REDUCTION SWIRL PARAMETER EQUATION (2.4.17)



A three-to-two reduction in the number of independent variables has been accomplished for the system of equations given in section 3.1. The new system of equations for the fluid flow model in (η_1, η_2) consists of equations (3.1.66), (3.1.72), (3.1.77), (3.1.82), (3.1.83), and (3.1.84)


Two to One Reduction in the Number of Independent Variables

The two independent variables (η_1, η_2) are reduced to the one independent variable (X) . The new independent variable (X) is a functionally independent absolute invariant of a subgroup of the one-parameter continuous group of transformations, B_1 . The one-parameter continuous group of transformations, B_1 , will subsequently be referred to as the group B_1 .

Taking advantage of the experience gained from choosing the group A_1 (3.1.1), the group B_1 is chosen as shown:

$$\begin{aligned}
 B_1: \quad \bar{\eta}_1 &= c^k \eta_1 & \bar{F}_2 &= c^{\gamma_1} F_2 \\
 \bar{\eta}_2 &= c^k \eta_2 & \bar{F}_3 &= c^{\gamma_1} F_3 \\
 \bar{F}_1 &= c^{\gamma_1} F_1 & \bar{F}_4 &= c^{2\gamma_1} F_4
 \end{aligned} \tag{3.2.1}$$

k and γ_1 are constants and c is the group parameter. The group defined as (3.2.1) has the general form specified by equation (1.3.7). The transformed independent variables are functions of the parameter c and the previous independent variables. Similarly, the transformed dependent variables are functions of the parameter c and the previous dependent variables.




The group B_1 (3.2.1) must satisfy the four group axioms given in equations (1.3.1), (1.3.2), (1.3.3), and (1.3.4). The form of the transformations in group B_1 (3.2.1) is the same as the form for the R transformation in group A_1 (3.1.1). Since the R transformation in A_1 (3.1.1) satisfies all the group axioms, it follows that the transformations in the group B_1 (3.2.1) satisfy all the group axioms.

The conditions under which the number of independent variables in a system of partial differential equations can be reduced by the process of obtaining invariant solutions are given by theorem 1.3.2. The two-dimensional equations (3.1.66), (3.1.72), (3.1.77), (3.1.82), (3.1.83), and (3.1.84) must be conformally invariant under the k-th enlargement of the group B_1 (3.2.1). Conformal invariance is defined by Definition 1.3.5 and given in equation form by equation (1.3.20). To verify conformal invariance, the group B_1 (3.2.1) is formally substituted into an equation and the mathematical operations indicated by the equation are performed. The resulting equation must then be the same as equation (1.3.20) for the equation to be conformally invariant.

The group B_1 (3.2.1) is formally substituted into equation (3.1.84), the two-dimensional representation of the R-Momentum equation.

$$\begin{aligned}
 & (\bar{F}_2 - F_2) \bar{\eta}_1 \frac{\partial \bar{F}_1}{\partial \bar{\eta}_1} + (\xi \bar{F}_3 (\frac{\bar{\eta}_1}{\bar{\eta}_2})^{1/\xi} - \bar{F}_2) \bar{\eta}_2 \frac{\partial \bar{F}_1}{\partial \bar{\eta}_2} - \bar{F}_2^2 + \alpha \bar{F}_1 \bar{F}_2 \\
 & \frac{\partial \bar{F}_4}{\partial \bar{\eta}_1} = c^{2\gamma_1} (\xi F_1 - F_2) \eta_1 \frac{\partial F_1}{\partial \eta_1} + c^{2\gamma_1} (\xi F_3 (\frac{\eta_1}{\eta_2})^{1/\xi} - F_2) \eta_2 \frac{\partial F_1}{\partial \eta_2} \\
 & - c^{2\gamma_1} F_2^2 + c^{2\gamma_1} \alpha F_1 F_2 - c^{2\gamma_1} \xi \eta_1 \frac{\partial F_4}{\partial \eta_1} \quad (3.2.2)
 \end{aligned}$$



is evident from equation (3.2.2) that the function M of equation (20) is only a function of the parameter c . By Definition 1.3.6, differential form represented by equation (3.2.2) is constant canonically invariant.

The group B_1 (3.2.1) is formally substituted into equation (72), the two-dimensional representation of the θ -Momentum equation.

$$\begin{aligned}
 & (\bar{F}_1 - \bar{F}_2) \bar{\eta}_1 \frac{\partial \bar{F}_2}{\partial \bar{\eta}_1} + (\xi \bar{F}_3 (\frac{\bar{\eta}_1}{\bar{\eta}_2})^{1/\xi} - \bar{F}_2) \bar{\eta}_2 \frac{\partial \bar{F}_2}{\partial \bar{\eta}_2} + \bar{F}_1 \bar{F}_2 + \alpha \bar{F}_2^2 \\
 & - \bar{\eta}_1 \frac{\partial \bar{F}_4}{\partial \bar{\eta}_1} - \bar{\eta}_2 \frac{\partial \bar{F}_4}{\partial \bar{\eta}_2} + 2\alpha \bar{F}_4 = c^{2Y_1} (\xi F_1 - F_2) \eta_1 \frac{\partial F_2}{\partial \eta_1} \\
 & + c^{2Y_1} (\xi F_3 (\frac{\eta_1}{\eta_2})^{1/\xi} - F_2) \eta_2 \frac{\partial F_2}{\partial \eta_2} + c^{2Y_1} F_1 F_2 + c^{2Y_1} \alpha F_2^2 \\
 & - c^{2Y_1} \eta_1 \frac{\partial F_4}{\partial \eta_1} - c^{2Y_1} \eta_2 \frac{\partial F_4}{\partial \eta_2} + c^{2Y_1} 2\alpha F_4 \quad (3.2.3)
 \end{aligned}$$

equation (3.2.3), it is evident that the function M of equation (20) is only a function of the parameter c . By definition 1.3.6, differential form represented by equation (3.2.3) is constant canonically invariant.

The group B_1 (3.2.1) is formally substituted into equation (77), the two-dimensional representation of the Z -Momentum equation.




$$\begin{aligned}
& (\xi \bar{F}_1 - \bar{F}_2) \bar{n}_1 \frac{\partial \bar{F}_3}{\partial \bar{n}_1} + (\xi \bar{F}_3 (\frac{\bar{n}_1}{\bar{n}_2})^{1/\xi} - \bar{F}_2) \bar{n}_2 \frac{\partial \bar{F}_3}{\partial \bar{n}_2} + \alpha \bar{F}_2 \bar{F}_3 \\
& (\frac{\bar{n}_1}{\bar{n}_2})^{1/\xi} \bar{n}_2 \frac{\partial \bar{F}_4}{\partial \bar{n}_2} = c^{2Y_1} (\xi F_1 - F_2) \eta_1 \frac{\partial F_3}{\partial \eta_1} + c^{2Y_1} (\xi F_3 (\frac{\eta_1}{\eta_2})^{1/\xi} - F_2) \eta_2 \frac{\partial F_3}{\partial \eta_2} \\
& + c^{2Y_1} \alpha F_2 F_3 - c^{2Y_1} \xi (\frac{\eta_1}{\eta_2})^{1/\xi} \eta_2 \frac{\partial F_4}{\partial \eta_2} \quad (3.2.4)
\end{aligned}$$

Comparison of equations (1.3.20) and (3.2.4) indicates that the function M in equation (1.3.20) is only a function of the parameter c . Therefore, the differential form represented by equation (3.2.4) is constant conformally invariant according to Definition 1.3.6.

The group B_1 (3.2.1) is formally substituted into equation (1.3.2), the two-dimensional representation of the Conservation of energy equation.

$$\begin{aligned}
& \xi \bar{n}_1 \frac{\partial \bar{F}_1}{\partial \bar{n}_1} + \bar{F}_1 + \alpha \bar{F}_2 - \bar{n}_1 \frac{\partial \bar{F}_2}{\partial \bar{n}_1} - \bar{n}_2 \frac{\partial \bar{F}_2}{\partial \bar{n}_2} + \xi (\frac{\bar{n}_1}{\bar{n}_2})^{1/\xi} \bar{n}_2 \frac{\partial \bar{F}_3}{\partial \bar{n}_2} \\
& = c^{Y_1} \xi \eta_1 \frac{\partial F_1}{\partial \eta_1} + c^{Y_1} F_1 + c^{Y_1} \alpha F_2 - c^{Y_1} \eta_1 \frac{\partial F_2}{\partial \eta_1} - c^{Y_1} \eta_2 \frac{\partial F_2}{\partial \eta_2} \\
& + c^{Y_1} \xi (\frac{\eta_1}{\eta_2})^{1/\xi} \eta_2 \frac{\partial F_3}{\partial \eta_2} \quad (3.2.5)
\end{aligned}$$

It is evident from equation (3.2.5) that the function M of equation (1.3.20) is only a function of the parameter c . By Definition 1.3.6, the differential form represented by equation (3.2.5) is constant conformally invariant.



The group B_1 (3.2.1) is formally substituted into equation (3.1.83), the two-dimensional representation of the Bernoulli equation.

$$H - e^{2\alpha\theta}(\bar{F}_4 + 1/2(\bar{F}_1^2 + \bar{F}_2^2 + \bar{F}_3^2)) = H - e^{2\alpha\theta}(c^{2Y_1}\bar{F}_4 + 1/2(c^{2Y_1}\bar{F}_1^2 + c^{2Y_1}\bar{F}_2^2 + c^{2Y_1}\bar{F}_3^2)) \quad (3.2.6)$$


Comparison of equations (1.3.20) and (3.2.6) indicates that the function M of equation (1.3.20) is only a function of the parameter c . The differential form represented by equation (3.2.6) is constant conformally invariant according to Definition 1.3.6.

The group B_1 (3.2.1) is formally substituted into equation (3.1.84), the two-dimensional representation of the Swirl Parameter equation.

$$S - \left(\frac{\bar{\eta}_1}{\bar{\eta}_2}\right)^{2/\xi} e^{2\alpha\theta} \bar{F}_2^2/H = S - c^{2Y_1} \left(\frac{\eta_1}{\eta_2}\right)^{2/\xi} e^{2\alpha\theta} F_2^2/H \quad (3.2.7)$$

From equation (3.2.7), it is seen that the function M of equation (1.3.20) is a function of only the parameter c . By Definition 1.3.6, equation (3.2.7) is constant conformally invariant.

The group B_1 (3.2.1) has $m+n-1 = 5$ functionally independent absolute invariants. Equation (1.3.9) gives the form for $m-1 = 1$ of the absolute invariants and equation (1.3.10) gives the form for the remaining $n = 4$ absolute invariants. Definition 1.3.1 and equation (1.3.5) give the definition and general form for an absolutely invariant form. As previously mentioned, the manner in which absolute



invariants are selected is not well defined. The function X is chosen as shown below:

$$X = \frac{\eta_1}{\eta_2} . \quad (3.2.8)$$

This choice is suggested by the appearance of this ratio in equations (3.1.66), (3.1.72), (3.1.77), (3.1.82), and (3.1.84). For the function X to be an absolute invariant, the following relation must hold:

$$X(\bar{\eta}_1, \bar{\eta}_2) = X(\eta_1, \eta_2). \quad (3.2.9)$$

The specific condition for the absolute invariance of X is determined by substituting equation (3.2.8) into relation (3.2.9):

$$\frac{\bar{\eta}_1}{\bar{\eta}_2} = \frac{\eta_1}{\eta_2} . \quad (3.2.10)$$

Using relations from group B_1 (3.2.1) for η_1 and η_2 , it is evident that equation (3.2.10) is satisfied and that X is an absolute invariant.


The functions g_1, g_2, g_3 , and g_4 are chosen as shown:

$$g_1 = F_1 \eta_1^{-\sigma}, \quad g_2 = F_2 \eta_1^{-\sigma}, \quad g_3 = F_3 \eta_1^{-\sigma}, \quad g_4 = F_4 \eta_1^{-2\sigma}. \quad (3.2.11)$$

For the functions in equations (3.2.11) to be absolute invariants, the following relations must hold:

$$g_1(\bar{F}_1, \bar{\eta}_1) = g_1(F_1, \eta_1), \quad g_2(\bar{F}_2, \bar{\eta}_1) = g_2(F_2, \eta_1) \quad (3.2.12)$$

$$g_3(\bar{F}_3, \bar{\eta}_1) = g_3(F_3, \eta_1), \quad g_4(\bar{F}_4, \bar{\eta}_1) = g_4(F_4, \eta_1). \quad (3.2.13)$$



The value of the exponent σ in equations (3.2.11) must be determined such that symbolic equations (3.2.12) and (3.2.13) are true. The required transformations from the group B_1 (3.2.1) are utilized in the following equations to determine σ :

$$\begin{aligned} g_1 &= \bar{F}_1 \bar{\eta}_1^{-\sigma} = c^{\gamma_1 F_1} (c^{k \eta_1})^{-\sigma} = c^{\gamma_1 - \sigma k}_{F_1 \eta_1}^{-\sigma}, \\ g_2 &= \bar{F}_2 \bar{\eta}_1^{-\sigma} = c^{\gamma_1 F_2} (c^{k \eta_1})^{-\sigma} = c^{\gamma_1 - \sigma k}_{F_2 \eta_1}^{-\sigma}, \\ g_3 &= \bar{F}_3 \bar{\eta}_1^{-\sigma} = c^{\gamma_1 F_3} (c^{k \eta_1})^{-\sigma} = c^{\gamma_1 - \sigma k}_{F_3 \eta_1}^{-\sigma}, \\ g_4 &= \bar{F}_4 \bar{\eta}_1^{-2\sigma} = c^{2\gamma_1 F_4} (c^{k \eta_1})^{-2\sigma} = c^{2(\gamma_1 - \sigma k)}_{F_4 \eta_1}^{-2\sigma}. \end{aligned} \quad (3.2.14)$$


From the set of equations (3.2.14), it is evident that the g_i will be absolutely invariant if

$$\sigma = \gamma_1 / k. \quad (3.2.15)$$

The condition given by equation (1.3.11) must be satisfied by the chosen functions g_1, g_2, g_3 , and g_4 .

$$J = \frac{\partial(g_1, g_2, g_3, g_4)}{\partial(F_1, F_2, F_3, F_4)} \neq 0 \quad (3.2.16)$$

$$J = \begin{vmatrix} \frac{\partial g_1}{\partial F_1} & \frac{\partial g_1}{\partial F_2} & \frac{\partial g_1}{\partial F_3} & \frac{\partial g_1}{\partial F_4} \\ \frac{\partial g_2}{\partial F_1} & \frac{\partial g_2}{\partial F_2} & \frac{\partial g_2}{\partial F_3} & \frac{\partial g_2}{\partial F_4} \\ \frac{\partial g_3}{\partial F_1} & \frac{\partial g_3}{\partial F_2} & \frac{\partial g_3}{\partial F_3} & \frac{\partial g_3}{\partial F_4} \\ \frac{\partial g_4}{\partial F_1} & \frac{\partial g_4}{\partial F_2} & \frac{\partial g_4}{\partial F_3} & \frac{\partial g_4}{\partial F_4} \end{vmatrix} \quad (3.2.17)$$



Using equations (3.2.11), equation (3.2.17) becomes:

$$J = \begin{vmatrix} \eta_1^{-\sigma} & 0 & 0 & 0 \\ 0 & \eta_1^{-\sigma} & 0 & 0 \\ 0 & 0 & \eta_1^{-\sigma} & 0 \\ 0 & 0 & 0 & \eta_1^{-2\sigma} \end{vmatrix}.$$

The Jacobian determinant J is non-vanishing for the chosen functions g_1, g_2, g_3 , and g_4 . Therefore, the condition (3.2.16) is satisfied.

The function X must satisfy the condition given by equation (1.3.12).

$$R \left[\frac{\partial(X)}{\partial(\eta_1, \eta_2)} \right] = m-1 = 1 \quad (3.2.18)$$

The rank of the indicated matrix must equal 1. Expanding the matrix given in equation (3.2.18) gives the following result:

$$\begin{bmatrix} \frac{\partial X}{\partial \eta_1} & \frac{\partial X}{\partial \eta_2} \end{bmatrix} \equiv M. \quad (3.2.19)$$

Using equation (3.2.8), equation (3.2.19) becomes,

$$\begin{bmatrix} \frac{1}{\eta_2} & -\frac{\eta_1}{\eta_2^2} \end{bmatrix} = M. \quad (3.2.20)$$



Since M is a 1×2 matrix and the row rank equals the column rank for a matrix, 1 is the maximum rank that M in (3.2.20) can have. The columns of M in (3.2.20) are not linearly independent (one is a multiple of the other) and hence, M has rank of 1. The condition indicated by equation (3.2.18) is satisfied for the chosen function X .

It has been demonstrated that equations (3.2.8) and (3.2.11) represent the functionally independent absolute invariants of the group (3.2.1).

Application of equation (1.3.17) to the invariants of the group B_1 (3.2.1) yields the following result:

$$g_j(F_1, F_2, F_3, F_4, \eta_1, \eta_2) = G_j(X) \quad j = 1, 2, 3, 4. \quad (3.2.21)$$

Equations (3.2.11) are rearranged using the symbolic equation (3.2.21) to obtain the following general form for the F_i :

$$F_i = \eta_1^{\kappa\sigma} G_i(X) \quad \begin{array}{l} i = 1, 2, 3, 4 \\ \kappa = \begin{cases} 1 & i \neq 4 \\ 2 & i = 4 \end{cases} \end{array} \quad (3.2.22)$$


For convenience, equation (3.2.8) and the partial derivatives of the function X are listed together.

$$X = \eta_1 / \eta_2 \quad (3.2.23)$$

$$\frac{\partial X}{\partial \eta_1} = \frac{1}{\eta_2} \quad \frac{\partial X}{\partial \eta_2} = \frac{-\eta_1}{\eta_2^2} \quad (3.2.24)$$

The relations (3.2.22) through (3.2.24) are now used to reduce the number of independent variables in the system of equations given in

tion 3.1. The two independent variables (η_1, η_2) are reduced to the independent variable (X) in equations (3.1.66), (3.1.72), (3.1.77), (3.1.82), (3.1.83), and (3.1.84). Figures 3.7 through 3.11 illustrate transformation details and give the final result for each of these equations. Note that the final result displayed in each figure is obtained by summing all the transformed terms given in the figure.



$$-F_{21} \frac{\partial F_1}{\partial \eta_1} = -\eta_1^\sigma G_2 \eta_1 (\eta_1^\sigma \frac{\partial G_1}{\partial \eta_1} + G_1 \frac{\partial \eta_1}{\partial \eta_1}) = -\eta_1^{2\sigma} (XG_{21} G_1' + \sigma G_1 G_1') \quad (3.2.26)$$

$$-F_{22} \eta_2 \frac{\partial F_1}{\partial \eta_2} = -\eta_1^\sigma G_2 \eta_2 \eta_1^\sigma \frac{\partial G_1}{\partial \eta_2} \quad \frac{\partial G_1}{\partial \eta_2} = \frac{dG_1}{dX} \frac{\partial X}{\partial \eta_2} = -\frac{X}{\eta_2} G_1' \quad -F_{22} \eta_2 \frac{\partial F_1}{\partial \eta_2} = \eta_1^{2\sigma} XG_{12} G_2 \quad (3.2.27)$$

$$\xi \left(\frac{\eta_1}{\eta_2} \right)^{1/\xi} \eta_2^F \frac{\partial F_1}{\partial \eta_2} = \xi(X)^{1/\xi} \eta_2^F \eta_1^\sigma G_1 \frac{\partial G_1}{\partial \eta_2} = -\xi X^{1+1/\xi} \eta_1^{2\sigma} G_1 G_1' \quad (3.2.28)$$


$$-F_2^2 = -\eta_1^{2\sigma} G_2^2 \quad (3.2.29)$$

$$-\xi \eta_1 \frac{\partial F_4}{\partial \eta_1} = -\xi \eta_1 (\eta_1^{2\sigma} \frac{\partial G_4}{\partial \eta_1} + G_4 \frac{\partial \eta_1}{\partial \eta_1}) = -\xi \eta_1^{2\sigma} (XG_{41} G_4' + 2\sigma G_4) \quad (3.2.30)$$

$$-\alpha F_{12} = -\alpha \eta_1^{2\sigma} G_1 G_2 \quad (3.2.31)$$

$$\xi XG_{11} G_1' + \xi \sigma G_1^2 - \sigma G_1 G_2 - \xi X^{1+1/\xi} G_1 G_3' - G_2^2 + \sigma G_1 G_2 = -\xi XG_{41} G_4' - 2\xi \sigma G_4 \quad (3.2.32)$$

FIGURE 3.7 $(\eta_1, \eta_2) \rightarrow (X)$ REDUCTION EQUATION (3.1.66)



(3.2.33)

$$1 + \frac{1}{\partial \eta_1} \cdot 1 + 2 \frac{\partial \eta_1}{\partial \eta_1} \cdot \omega_1^2 + \omega_1^2 \cdot \omega_1^2$$

$$-F_2 \eta_1 \frac{\partial F_2}{\partial \eta_1} = -\eta_1^{\sigma} G_1 \eta_1^{\sigma} \frac{\partial G_2}{\partial \eta_1} + G_2 \frac{\partial \eta_1^{\sigma}}{\partial \eta_1} = -\eta_1^{2\sigma} G_2 (X G_2' + \sigma G_2) \quad (3.2.34)$$

$$-F_2 \eta_2 \frac{\partial F_2}{\partial \eta_2} = -\eta_1^{2\sigma} G_1 \eta_2 \frac{\partial G_2}{\partial \eta_2} = \eta_1^{2\sigma} X G_2 G_2' \quad (3.2.35)$$

55

$$\xi \left(\frac{\eta_1}{\eta_2} \right)^{\eta_1 / \xi} F_3 \eta_2 \frac{\partial F_2}{\partial \eta_2} = -\xi(X)^{1/\xi} \eta_1^{2\sigma} X G_3 G_2' \quad (3.2.36)$$

$$F_1 F_2 = \eta_1^{2\sigma} G_1 G_2 \quad (3.2.37)$$

$$\alpha F_2^2 = \alpha \eta_1^{2\sigma} G_2^2 \quad (3.2.38)$$

FIGURE 3.8 $(\eta_1, \eta_2) \rightarrow (X)$ REDUCTION EQUATION (3.1.72)

$$\eta_1 \frac{\partial}{\partial \eta_1} - \eta_1 (\eta_1 \frac{\partial}{\partial \eta_1} + G_4 \frac{\partial}{\partial \eta_1}) = \eta_1 (XG_4' + 2\sigma G_4)$$

(3.2.39)

$$\eta_2 \frac{\partial F_4}{\partial \eta_2} = \eta_2 \eta_1 \frac{\partial G_4}{\partial \eta_2} = -\eta_1 XG_4'$$

(3.2.40)

$$-2\alpha F_4 = -2\alpha \eta_1 G_4$$


(3.2.41)

56

$$\xi XG_1'G_2' + (\xi\sigma + 1) G_1 G_2 + (\alpha - \sigma) G_2^2 - \xi X^{1+1}/\xi G_3 G_2' = 2(\sigma - \alpha) G_4$$

(3.2.42)

FIGURE 3.8 (CONT'D.)



$$\xi F_1 \eta_1 \frac{\partial F_3}{\partial \eta_1} = \xi \eta_1^\sigma G_1 \eta_1 \frac{\partial}{\partial \eta_1} (n_1^\sigma G_3) \quad (3.2.43)$$

$$\xi F_1 \eta_1 \frac{\partial F_3}{\partial \eta_1} = \xi \eta_1^{2\sigma} (X G_1 G_3' + \sigma G_1 G_3)$$

$$-F_2 \eta_1 \frac{\partial F_3}{\partial \eta_1} = -\eta_1^\sigma G_2 \eta_1 \frac{\partial}{\partial \eta_1} (n_1^\sigma G_3) = -\eta_1^{2\sigma} (X G_2 G_3' + \sigma G_2 G_3) \quad (3.2.44)$$

$$-F_2 \eta_2 \frac{\partial F_3}{\partial \eta_2} = -\eta_1^{2\sigma} G_2 \eta_2 \frac{\partial G_3}{\partial \eta_2} = \eta_1^{2\sigma} X G_2 G_3' \quad (3.2.45)$$


$$F_3 \xi \left(\frac{\eta_1}{\eta_2} \right)^{1/\epsilon} \frac{\partial F_3}{\partial \eta_2} = \eta_1^{2\sigma} G_3 X^{1/\epsilon} \eta_2 \frac{\partial G_3}{\partial \eta_2} = -\xi \eta_1^{2\sigma} X^{1+1/\epsilon} G_3 G_3' \quad (3.2.46)$$

$$\alpha F_2 F_3 = \alpha \eta_1^{2\sigma} G_2 G_3 \quad (3.2.47)$$

$$-\xi \left(\frac{\eta_1}{\eta_2} \right)^{1/\epsilon} \eta_2 \frac{\partial F_4}{\partial \eta_2} = -\xi X^{1/\epsilon} \eta_2^{2\sigma} \eta_1 \frac{\partial G_4}{\partial \eta_2} = -\frac{X}{\eta_2} G_4' = -\frac{\eta_1^{1/\epsilon}}{\xi \left(\frac{\eta_1}{\eta_2} \right)^{1/\epsilon} \eta_2} \frac{\partial F_4}{\partial \eta_2} = \xi X^{1+1/\epsilon} \eta_1^{2\sigma} G_4' \quad (3.2.48)$$

$$\xi X G_1 G_3' + \xi \sigma G_1 G_3 + (\alpha - \sigma) G_2 G_3 = \xi X^{1+1/\epsilon} G_3 G_3' = \xi X^{1+1/\epsilon} G_4' \quad (3.2.49)$$

FIGURE 3.9 $(\eta_1, \eta_2) \rightarrow (X)$ REDUCTION EQUATION (3.1.77)



(3.2.50)

$$1 \frac{\partial}{\partial \eta_1} \left(\eta_1^{1+\epsilon} \right) = 1 + \eta_1 \frac{\partial}{\partial \eta_1} = \epsilon \eta_1 (\sigma \epsilon_1 + \lambda \epsilon_1)$$

$$F_1 = \eta_1^\sigma G_1 \quad (3.2.51)$$

$$-\eta_1 \frac{\partial F_2}{\partial \eta_1} = -\eta_1 \left(\eta_1^\sigma \frac{\partial G_2}{\partial \eta_1} + \sigma G_2 \eta_1^{\sigma-1} \right) = -\eta_1^\sigma (XG_2' + \sigma G_2) \quad (3.2.52)$$

$$-\eta_2 \frac{\partial F_2}{\partial \eta_2} = -\eta_2 \left(\eta_1^\sigma \frac{\partial G_2}{\partial \eta_2} \right) = \eta_1^\sigma XG_2' \quad (3.2.53)$$


58

$$\alpha F_2 = \alpha \eta_1^\sigma G_2 \quad (3.2.54)$$

$$\xi \left(\frac{\eta_1}{\eta_2} \right)^{1/\epsilon} \eta_2 \frac{\partial F_3}{\partial \eta_2} = \xi X^{1/\epsilon} \eta_2^\sigma \eta_1^\sigma \frac{\partial G_3}{\partial \eta_2} = -\xi X^{1+1/\epsilon} \eta_1^\sigma G_3' \quad (3.2.55)$$

$$(1 + \xi \sigma) G_1 + (\alpha - \sigma) G_2 + \xi X G_1' - \xi X^{1+1/\epsilon} G_3' = 0 \quad (3.2.56)$$

FIGURE 3.10 $(\eta_1, \eta_2) \rightarrow (X)$ REDUCTION EQUATION (3.1.82)



$$G_4 = \frac{H}{e^{2\alpha\theta} \eta_1^{2\sigma}} - 1/2(G_1^2 + G_2^2 + G_3^2)$$


(3.2.57)

59

$$S = X^{2/\xi} e^{2\alpha\theta} \eta_1^{2\sigma} G_2^2/H$$

(3.2.58)

FIGURE 3.11 $(\eta_1, \eta_2) \rightarrow (X)$ REDUCTION EQUATION (3.1.83) AND EQUATION (3.1.84)



To obtain a complete reduction to one independent variable in equations (3.2.57) and (3.2.58), the constants α and σ must vanish.

Let $\alpha = \sigma = 0$, equations (3.2.32), (3.2.42), (3.2.49), (3.2.56), (3.2.57), and (3.2.58) then become:

$$\xi X G_1 G_1' - \xi X^{1+1/\xi} G_3 G_1' - G_2^2 = -\xi X G_4' \quad (3.2.59)$$

$$\xi X G_1 G_2' + G_1 G_2 - \xi X^{1+1/\xi} G_3 G_2' = 0 \quad (3.2.60)$$

$$\xi X G_1 G_3' - \xi X^{1+1/\xi} G_3 G_3' = \xi X^{1+1/\xi} G_4' \quad (3.2.61)$$

$$G_1 + \xi X G_1' - \xi X^{1+1/\xi} G_3' = 0 \quad (3.2.62)$$


$$G_4 = H - 1/2(G_1^2 + G_2^2 + G_3^2) \quad (3.2.63)$$

$$S = X^2/\xi G_2^2/H. \quad (3.2.64)$$

A two to one reduction in the number of independent variables has been accomplished for the system of equations given in section 3.1. Equations (3.2.59) through (3.2.64) comprise the new system of equations for the fluid flow model in (X) space.

3.3 Summary

The partial differential equations of the fluid flow model in (R, θ , Z) space have been transformed into partial differential equations in (η_1, η_2) space by the application of the continuous one-parameter transformation group A_1 (3.1.30). Subsequently, the partial differential equations of the fluid flow model in (η_1, η_2) space have



been transformed into ordinary differential equations in (X) space by the application of the continuous one-parameter transformation group B_1 (3.2.1).



IV. SOLUTIONS FOR THE CASE $\xi = -1$

4.1 One-Dimensional Solutions of the Ordinary Differential Equations

The group constant ξ which is defined by equation (3.1.52) appears as an exponent in the transformation equations (3.1.57) and (3.1.58). ξ may be chosen to be positive, negative, or zero. The effect of each of these choices is readily determined after substitution of equations (3.1.57) and (3.1.58) into equation (3.2.8). For each choice, the variable X is influenced as shown:

$$\xi > 0, X = (R/Z)^\xi; \quad \xi < 0, X = (Z/R)^{|\xi|}; \quad \xi = 0, X = 1.$$

For the choice $\xi = 0$, X becomes a constant and is not a variable and the system of ordinary differential equations (3.2.59) through (3.2.62) becomes meaningless.

For an example in this investigation, ξ is chosen to be negative. By inspection, it is noted that for $\xi = -1$:

1. The system of ordinary differential equations is simplified.
2. The velocity components will be proportional to $1/R$ in (R, θ, Z) space and the pressure will be proportional to $1/R^2$ in (R, θ, Z) space.
3. The system of ordinary differential equations on page 60 is greatly simplified as the exponential term $1 + 1/\xi$ vanishes.



The system of ordinary differential equations consisting of equations (3.2.59), (3.2.60), (3.2.61), and (3.2.62) simplifies to the following system of ordinary differential equations:

$$-XG_1 G_1' + G_3 G_1' - G_2^2 = XG_4' \quad (4.1.1)$$

$$-XG_1 G_2' + G_1 G_2 + G_3 G_2' = 0 \quad (4.1.2)$$

$$-XG_1 G_3' + G_3 G_3' = -G_4' \quad (4.1.3)$$

$$-XG_1' + G_1 + G_3' = 0 \quad (4.1.4)$$

where $G_1' \equiv dG_1/dX$. Since this system of ordinary differential equations is non-linear, a numerical analysis approach is required to determine its solutions.


Hamming's modified predictor-corrector numerical method is utilized to obtain solutions for the system consisting of equations (4.1.1), (4.1.2), (4.1.3), and (4.1.4). The method employs the following numerical calculations:

$$\text{Predictor: } P_{j+1} = G_{j-3} + \frac{4h}{3}(2G_j' - G_{j-1}' + 2G_{j-2}')$$

$$\text{Modifier: } M_{j+1} = P_{j+1} - \frac{112}{121}(P_j - C_j)$$

$$\text{Corrector: } C_{j+1} = \frac{1}{8}(9G_j - G_{j-2} + 3h(M_{j+1}' + 2G_j' - G_{j-1}'))$$

$$\text{Final Value: } G_{j+1} = C_{j+1} + \frac{9}{121}(P_{j+1} - C_{j+1})$$



If the results are known at the equidistant points X_{j-3} , X_{j-2} , X_{j-1} , and X_j ; the results at point $X_{j+1} = X_j + h$ (where h is the step size) can be computed using the numerical equations given above. Hamming's predictor-corrector method is not self starting; that is, the functional values at a single previous point are not enough to get the functional values ahead. To obtain the starting values, a special Runge-Kutta procedure followed by one iteration step is added to the predictor-corrector method.


It may be demonstrated that the convergence criterion given by Wilf [52, pg. 98] for Hamming's modified predictor-corrector method requires that the step size be chosen such that $h < 8/(3|F/\partial M_{j+1}|)$ where $F(X_{j+1}, M_{j+1}) = M'_{j+1}$. For an extensive discussion on Hamming's modified predictor-corrector method, the reader is referred to Carnahan [9, pp. 381-392] or Wilf [52, pp. 96-108].

Appendix A contains the computer printout of the IBM scientific subroutine DHCPG, a double precision arithmetic routine utilizing Hamming's method, which was used in this work to solve the system of non-linear ordinary differential equations. The numerical computations were performed by an IBM 360 computer and the numerical results are displayed in Table A.1.

After rearrangement, equations (4.1.1), (4.1.2), (4.1.3), and (4.1.4) become:

$$G_4' = C/E \quad (4.1.5)$$

$$G_3' = G_4'/A \quad (4.1.6)$$



$$G_2' = (G_1 G_2)/A \quad (4.1.7)$$

$$G_1' = (G_1 + G_3')/X \quad (4.1.8)$$

where $A \equiv XG_1 - G_3$, $C \equiv -(AG_1)/X$, and $E \equiv X + 1/X$.

The boundary conditions (2.4.13), (2.4.14), (2.4.15), and (2.4.16) are constants and transform to X space unaltered. The values for the boundary conditions are selected as shown:

$$U_O \rightarrow F_{1*} \rightarrow G_{1*} = 1.0, \quad V_O \rightarrow F_{2*} \rightarrow G_{2*} = 1.0, \quad (4.1.9)$$


$$W_O \rightarrow F_{3*} \rightarrow G_{3*} = 1.0, \quad P_O \rightarrow F_{4*} \rightarrow G_{4*} = 0.5.$$

In X space, $G_{j*} \equiv G_j(X_*)$ where $j = 1, 2, 3, 4$.

The boundary point X_* is the left limit of the X interval $(X_* \leq X \leq X_2)$. Using the result obtained from substituting equations (3.1.57) and (3.1.58) into equation (3.2.8), X_* is defined to transform as indicated by the following equation:

$$X_* \equiv \frac{\eta_{1*}}{\eta_2} = \frac{e^{-\theta} R_O^{-1}}{e^{-\theta} Z^{-1}} = \frac{Z}{R_O}. \quad (4.1.10)$$

For the selected boundary conditions, the numerical solutions to equations (4.1.1), (4.1.2), (4.1.3), and (4.1.4) are plotted for the interval $0.1 \leq X \leq 1.0$ in Figure 4.1. The output from the computer program using the DHCPG subroutine was stored as the input to a subroutine which controls a Calcomp plotter from which the plots were produced. Appendix B contains a printout for the Calcomp plotter routine.




At the point $X = 0.46531$ in Figure 4.1, the solution functions G_1 , G_2 , and G_3 all have a discontinuous derivative. G_4 (the one-dimensional representation for pressure) reaches its maximum value and G_2 (the one-dimensional representation for the tangential velocity component) reaches its minimum value. Therefore, the point $X = 0.46531$ is designated as the "tangential quasi-stagnation point" for this flow.

The solutions G_1 , G_2 , G_3 , and G_4 were determined by simultaneously solving the one-dimensional representations for conservation of momentum and conservation of mass. To verify these results, the one-dimensional representation for conservation of energy, equation (3.2.63), is used to determine the Bernoulli constant H at each point X . From equation (3.2.63), it is seen that the equation for H is:

$$H = G_4 + 1/2 \sum_{i=1}^3 G_i^2. \quad (4.1.11)$$

The value of H is fixed by the selected boundary conditions and for this case, $H = 2$. Data values for H were computed at each point X using equation (4.1.11) and the solutions G_1 , G_2 , G_3 , and G_4 . From the data values listed in Table A.1, the maximum percent deviation of H from the value $H = 2$ is determined to be 0.28%. This maximum percent deviation occurs at only one point. Most of the percent deviations for H are in the range from 0.00% to 0.09% and hence, equation (3.2.63) is satisfied.

Polynomial expressions for the solutions G_1 , G_2 , G_3 , and G_4 were determined using a Gaussian least squares method known as Polfit. A Polfit computer printout is included in Appendix C. The polynomial expressions for the interval $0.1 \leq X \leq 0.46531$ are:



ONE DIMENSIONAL FUNCTIONS
 G1 SQUARE, G2 CIRCLE, G3 TRIANGLE, G4 PLUS





FIGURE 4.1 ONE-DIMENSIONAL FUNCTIONS



$$G_1 = 0.88531 + 1.1040X + 0.44657X^2 \quad (4.1.12)$$

$$G_2 = 1.4366 - 9.5497X + 82.897X^2 - 383.95X^3 \\ + 829.38X^4 - 691.74X^5 \quad (4.1.13)$$

$$G_3 = 1.0909 - 0.91970X + 0.13199X^2 \quad (4.1.14)$$

$$G_4 = 0.40740 + 1.0314X - 1.0941X^2. \quad (4.1.15)$$

The polynomial expressions for the interval $0.46531 \leq X \leq 1.0$ are:

$$G_1 = 1.5338 - 0.29709X + 0.43202X^2 \quad (4.1.16)$$

$$G_2 = -36.184 + 241.04X - 636.39X^2 + 838.23X^3 \\ - 546.94X^4 + 141.25X^5 \quad (4.1.17)$$

$$G_3 = 1.4350 - 1.7466X + 0.30862X^2 \quad (4.1.18)$$

$$G_4 = 0.31091 + 1.5504X - 1.7556X^2 \quad (4.1.19)$$

4.2 Three-Dimensional Pressure and Velocity Curves

Application of equations (3.1.54), (3.1.55), (3.1.57), (3.1.58), (3.2.8), and (3.2.22) to this case results in the following transformation equations:

$$X = \eta_1/\eta_2 = Z/R \quad (4.2.1)$$



$$G_1(X) = F_1(\eta_1, \eta_2) = U(R, \theta, Z), \quad (4.2.2)$$

$$G_2(X) = F_3(\eta_1, \eta_2) = V(R, \theta, Z),$$

$$G_3(X) = F_3(\eta_1, \eta_2) = W(R, \theta, Z), \quad (4.2.3)$$

$$G_4(X) = F_4(\eta_1, \eta_2) = P(R, \theta, Z).$$

The three-dimensional equations for pressure and velocity components are obtained by substituting the transformation relations (4.2.1), (4.2.2), and (4.2.3) into equations (4.1.12) through (4.1.19). For the interval $0.1 \leq Z/R \leq 0.46531$, the polynomial expressions become:

$$U = 0.88531 + 1.1040(Z/R) + 0.44657(Z/R)^2 \quad (4.2.4)$$

$$V = 1.4366 - 9.5497(Z/R) + 82.897(Z/R)^2 - 383.95(Z/R)^3 \\ + 829.38(Z/R)^4 - 691.74(Z/R)^5 \quad (4.2.5)$$


$$W = 1.0909 - 0.91970(Z/R) + 0.13199(Z/R)^2 \quad (4.2.6)$$

$$P = 0.40740 + 1.0314(Z/R) - 1.0941(Z/R)^2. \quad (4.2.7)$$

For the interval $0.46531 \leq Z/R \leq 1.0$, the polynomial expressions become:

$$U = 1.5338 - 0.29709(Z/R) + 0.432.02(Z/R)^2 \quad (4.2.8)$$

$$V = -36.184 + 241.04(Z/R) - 636.39(Z/R)^2 + 838.23(Z/R)^3 \\ - 546.94(Z/R)^4 + 141.25(Z/R)^5 \quad (4.2.9)$$



$$W = 1.4350 - 1.7466(Z/R) + 0.30862(Z/R)^2 \quad (4.2.10)$$

$$P = 0.31091 + 1.5504(Z/R) - 1.7556(Z/R)^2. \quad (4.2.11)$$


The absence of the θ coordinate in the transformed equations for U , V , W , and P signifies that for this case an axially symmetric flow is obtained.

The U , V , W , and P curves are plotted as functions of R using Z as a parameter. For Z as a parameter, the plot intervals become: $0.0Z \leq R \leq 2.1491Z$ and $2.1491Z \leq R \leq 10Z$. The Calcomp plotter routine is given input data from the author's subroutines PC05E1 and PC05E2 which calculate data points from the polynomial expressions for pressure and the velocity components. Appendix D contains the PC05E1 and PC05E2 subroutine programs and a sample of the computed data for these curves.

Figures 4.2, 4.3, 4.4, and 4.5 display the curves for pressure, radial velocity, tangential velocity, and axial velocity, respectively. For the parametric values $Z = 0.1$, $Z = 0.4$, and $Z = 0.7$, the corresponding tangential quasi-stagnation point locations are $R = 0.21491$, $R = 0.85964$, and $R = 1.5044$. In each set of curves except the set for axial velocity, the location of the tangential quasi-stagnation point is pronounced by an abrupt slope change for a particular curve. Figure 4.6 displays the real space functions U , V , W , and P on a single diagram for the parametric value $Z = 0.7$.

3 Summary and Recommendations for Further Research


Numerical solutions to the non-linear ordinary system of differential equations have been obtained for selected boundary conditions on the group constant $\xi = -1$. These solutions are plotted in Figure



4.1. Polynomial expressions were determined for each of these solutions and the polynomial expressions were transformed from the one-dimensional (X) space back to the three-dimensional (R, θ , Z) space. The three-dimensional polynomial solutions for pressure and the velocity components are plotted in Figures 4.2, 4.3, 4.4 and 4.5.

Solutions to the case $\xi = -1$ for boundary conditions other than those reported on in this chapter were investigated by the author. However, the investigations were not completed as the computer expense was prohibitive. The author's bill for computer time on this investigation is \$2,765.47. During this investigation, funds for computer time were generously provided by the Process Engineering Department of General Motors Institute, Flint, Michigan.

Many interesting areas for further research are exposed by this work. The author suggests that profitable results could be obtained from investigation into the case $\xi = -1$ in this work, transformations for a system of equations in spherical coordinates, and transformations for a system of equations including derivative boundary conditions.







FIGURE 4.2 PRESSURE CURVES







FIGURE 4.3 RADIAL VELOCITY CURVES



TANGENTIAL VELOCITY (V)
Z=.1 SQUARE, Z=.4 CIRCLE, Z=.7 TRIANGLE





FIGURE 4.4 TANGENTIAL VELOCITY CURVES







FIGURE 4.5 AXIAL VELOCITY CURVES







FIGURE 4.6 REAL SPACE FUNCTIONS



V. OPTIMAL SOLUTIONS

1. Application of Optimization Techniques in X Space

The mathematical optimization model employs the one-dimensional representations for the conservation of energy (equation 3.2.63)) and the swirl parameter (equation (3.2.64)). For the case $\alpha = -1$, these equations become:

$$G_4 = H - 1/2(G_2^2 + G^2) \text{ where } G^2 \equiv G_1^2 + G_3^2 \quad (5.1.1)$$

$$S = G_2^2/(HX^2). \quad (5.1.2)$$

The optimization problem is posed to discover those functions G_2 and G that will optimize the function G_4 subject to the restriction imposed by the swirl parameter S .


Let

$$\phi_1 = G_4 - H + 1/2(G_2^2 + G^2) = 0 \quad (5.1.3)$$

$$\text{and } \phi_2 = G_2^2 - SHX^2 = 0. \quad (5.1.4)$$

The augmented function for this case is written as:

$$\Phi = \lambda_1 \phi_1 + \lambda_2 \phi_2 = \lambda_1 G_4 - \lambda_1 H + \frac{\lambda_1}{2}(G_2^2 + G^2) + \lambda_2 G_2^2 - \lambda_2 SHX^2. \quad (5.1.5)$$



Comparison of equation (5.1.5) to equation (1.4.7) demonstrates that this problem is formulated as a classical Mayer type problem (refer to section 1.4).

Following the proposition given in reference [41, pg. 33] for solving problems not involving derivatives of the dependent variables, a change of dependent variables is introduced.

$$\text{Let } \alpha' = G_4, \beta' = G_2, \text{ and } \gamma' = G. \quad (5.1.6)$$


Substitution of equations (5.1.6) into equations (5.1.3), (5.1.4), and (5.1.5) yields the following expressions for the constraint equations and the augmented function:

$$\phi_1 = \alpha' - H + 1/2(\beta'^2 + \gamma'^2) = 0 \quad (5.1.7)$$

$$\phi_2 = \beta'^2 - SHX^2 = 0 \quad (5.1.8)$$

$$K = \lambda_1 \alpha' - \lambda_1 H + \frac{\lambda_1}{2}(\beta'^2 + \gamma'^2) + \lambda_2 \beta'^2 - \lambda_2 SHX^2. \quad (5.1.9)$$

A single degree of freedom exists for this problem as there are three dependent variables (α, β, γ) and two constraint equations (5.1.7) and (5.1.8). Hence, one optimum requirement can be imposed on α . The following end conditions are specified for this problem: $x_1, x_f, \alpha_f, \gamma_1$, and γ_f . Now the optimum problem is specifically formulated as follows: In the class of functions $\alpha(X), \beta(X)$, and $\gamma(X)$ which are consistent with the constraint equations (5.1.7) and (5.1.8) and the specified end conditions, find that special set which minimizes the difference $\Delta\tau = \tau_f - \tau_1$, where $\tau = \alpha$. Note that for α_f specified, minimizing the difference $\Delta\tau$ corresponds to maximizing α_1 .



Applying equation (1.4.8), one Euler-Lagrange equation is obtained for each dependent variable.

$$\frac{d}{dX} \left(\frac{\partial K}{\partial \alpha'} \right) - \frac{\partial K}{\partial \alpha} = 0 \quad (5.1.10)$$

$$\frac{d}{dX} \left(\frac{\partial K}{\partial \beta'} \right) - \frac{\partial K}{\partial \beta} = 0 \quad (5.1.11)$$

$$\frac{d}{dX} \left(\frac{\partial K}{\partial \gamma'} \right) - \frac{\partial K}{\partial \gamma} = 0 \quad (5.1.12)$$

Substitution of equation (5.1.9) into equations (5.1.10), (5.1.11), and (5.1.12) leads to the following results:

$$\lambda_1' = 0 \text{ or } \lambda_1 = \text{constant} \quad (5.1.13)$$

$$(\lambda_1 + 2\lambda_2) \beta'' + (\lambda_1' + 2\lambda_2') \beta' = 0 \quad (5.1.14)$$


$$\lambda_1 \gamma'' + \lambda_1' \gamma' = 0. \quad (5.1.15)$$

Substitution of equation (5.1.13) into equation (5.1.15) leads to the following result:

$$\gamma' = \frac{L}{\lambda_1} \quad \text{where } L \text{ is an integration constant.} \quad (5.1.16)$$

Since λ_1 is a constant, an obvious solution to equation (5.1.14) is obtained by choosing λ_2 to be a constant. Let

$$\lambda_2 = \text{constant} = -\frac{\lambda_1}{2}. \quad (5.1.17)$$



The value of λ_1 is determined by applying equation (1.4.9), the transversality condition. The specific transversality condition for this problem becomes:

$$\begin{aligned} d\alpha - (\lambda_1 (H + \frac{\beta^2}{2} + \frac{\gamma^2}{2}) + \lambda_2 (\beta'^2 + SHX^2)) dX + \lambda_1 d\alpha + (\lambda_1 + 2\lambda_2) \beta' d\beta \\ + \lambda_1 \gamma' d\gamma \Big|_1^f = 0. \end{aligned} \quad (5.1.18)$$

Equation (5.1.18) is to be satisfied identically and for the specified end conditions this then requires that:

$$\lambda_{1f} = -1. \quad (5.1.19)$$

From equation (5.1.13),

$$\int_1^f d\lambda_1 = 0.$$

Therefore,


$$\lambda_{1f} = \lambda_{1i} = \lambda_1 \text{ and } \lambda_1 = -1. \quad (5.1.20)$$

Thus, from the application of the Euler-Lagrange equations and the transversality condition; λ_1 , λ_2 , and γ' have been determined.

If expression (1.4.10), the Legendre-Clebsch necessary condition, is negative, the optimum obtained is a maximum. For this case, expression (1.4.10) becomes:

$$K_{y_k y_j} \delta y_k' \delta y_j' < 0 \quad (5.1.21)$$

where repeated indicial subscripts indicate summation.



By inspection of the form of the augmented function, equation (5.1.9), it is seen that

$$K_{y_k y_j} = 0 \quad \text{for } j \neq k. \quad (5.1.22)$$

Utilizing equation (5.1.22), the specific expression for expression (5.1.21) becomes:

$$K_{\alpha' \alpha'} (\delta \alpha')^2 + K_{\beta' \beta'} (\delta \beta')^2 + K_{\gamma' \gamma'} (\delta \gamma')^2 < 0. \quad (5.1.23)$$

From equation (5.1.9), the following relations are determined:

$$K_{\alpha' \alpha'} = 0, \quad K_{\beta' \beta'} = \lambda_1 + 2\lambda_2, \quad K_{\gamma' \gamma'} = \lambda_1. \quad (5.1.24)$$

Upon substitution of equations (5.1.24), expression (5.1.23) becomes:


$$(\lambda_1 + 2\lambda_2) (\delta \beta')^2 + \lambda_1 (\delta \gamma')^2 < 0. \quad (5.1.25)$$

From equations (5.1.17) and (5.1.20) it is indeed evident that expression (5.1.25) holds and hence a maximum is obtained for this case.

The optimum expression for G_h is obtained by substituting equations (5.1.6), (5.1.8), (5.1.16), and (5.1.20) into equation (5.1.7).

$$G_h = H - 1/2(SHX^2 + L^2) \quad (5.1.26)$$

Equation (5.1.26) represents the optimum G_h when the sum $G^2 = G_1^2 + G_3^2 = G_2^2$ is a constant and G_2 is governed by the swirl parameter S as given by equation (5.1.2). G_h attains its maximum value at $X = X_1$.



Since G_4 is the one-dimensional representation for pressure, it is restricted to positive values. This restriction on G_4 places the following restriction on the swirl parameter:


$$S < 2 - L^2/H. \quad (5.1.27)$$

From Table A.1, the values $H = 2.0000$ and $L^2 = 2.6951$ are selected since they occur at the point where the function G_4 is a maximum as determined by the solution of the system of ordinary differential equations in Chapter IV. For the selected values of H and L^2 , equation (5.1.27) requires that $S < 0.6525$.

Computing the maximum G_4 at $X = X_1 = 0.1$ using equation (5.1.26) with the above-mentioned values for H and L^2 , the computed maximum G_4 for $S = 0.25$ is found to be within 0.02% of the maximum value given in Table A.1. For $S = 0.65$, the computed maximum value of G_4 is found to be within 0.63% of the maximum value given in Table A.1. Therefore, the maximum G_4 value determined by equation (5.1.26) compares favorably with the maximum G_4 value determined by the solution of the system of ordinary differential equations in Chapter IV.

Figures 5.1 and 5.2 illustrate the G_2 and G_4 curves generated from equations (5.1.2) and (5.1.26) using S as a parameter. The S values chosen are $S = 0.25$, $S = 0.45$, $S = 0.55$, and $S = 0.65$. The maximum value of G_4 occurs at the left end of the X interval where G_2 is at a minimum.

The curves were plotted by a Calcomp plotter which is controlled by the output data from an IBM 360 computer. The computer facility used during this investigation is located at General Motors



Institute, Flint, Michigan. Appendix E contains the program for computing the data for these curves and the actual curve data.

5.2 Three-Dimensional Optimal Pressure and Velocity Curves

The three-dimensional equations for optimum pressure and tangential velocity are obtained by substituting the transformation relations (4.2.1), (4.2.2), and (4.2.3) into equations (5.1.26) and (5.1.2):

$$P = H - 1/2(SH(Z/R)^2 + L^2), \quad (5.2.1)$$


$$V = [SH]^{1/2} Z/R. \quad (5.2.2)$$


Equation (5.2.1) represents the optimum pressure and equation (5.2.2) represents the tangential velocity for optimum pressure.


The optimum P and V curves are plotted as functions of R using Z as a parameter and S = 0.65. For Z as a parameter, the plot interval becomes: $Z \leq R \leq 10Z$. The maximum value of P occurs at the right end of the R interval where $R = 10Z$. At $R = 10Z$, V is a minimum. Therefore, the maximum pressure occurs at the point where the tangential velocity is a minimum. This same result is obtained in Chapter IV for the transformed equations of the solutions to the system of ordinary differential equations.


These curves were also plotted by a Calcomp plotter. The computing program and the actual computed data are contained in Appendix E.


Figures 5.3 and 5.4 display the curves for optimum pressure and tangential velocity, respectively. For the parametric values



FIGURE 5.1 G₂ CURVES S PARAMETER



FIGURE 5.2 G_4 CURVES S PARAMETER



$Z = 0.1$, $Z = 0.4$, and $Z = 0.7$, the corresponding maximum pressure locations are $R = 1$, $R = 4$, and $R = 7$. Hence, the maximum pressure value occurs at the right-end point for each pressure curve in Figure 5.3. Similarly, the minimum value of the tangential velocity occurs at the right-end point for each velocity curve in Figure 5.4.

5.3 Summary

A one-dimensional optimal expression for G_4 has been determined for the case where the G_2 expression is governed by the swirl parameter and the expression G^2 is required to be a constant. Optimal curves for G_2 and G_4 are plotted in Figures 5.1 and 5.2. The expressions for G_2 and G_4 were transformed from the one-dimensional (X) space back to the three-dimensional (R, θ, Z) space omitting the passage to the two-dimensional (η_1, η_2) space. The three-dimensional expressions for optimal pressure and tangential velocity are plotted in Figures 5.3 and 5.4.





FIGURE 5.3 OPTIMUM PRESSURE CURVES







FIGURE 5.4 VELOCITY CURVES FOR OPTIMUM PRESSURE



BIBLIOGRAPHY

BIBLIOGRAPHY


1. Akhiezer, Naum I., The Calculus of Variations, Blaisdell Publishing Co., New York, 1962.
2. Alexandroff, P. S., Einführung in Die Gruppentheorie, Deutscher Verlag der Wissenschaften, Berlin, 1954.
3. Batchelor, G. K., "On Steady Laminar Flow with Closed Streamlines at Large Reynolds Number", *Journal of Fluid Mechanics*, Vol. 12, Part 2, pp. 177-190, 1956.
4. Beckett, Royce and Hurt, James, Numerical Calculations and Algorithms, McGraw-Hill Book Co., New York, 1967.
5. Benjamin, T. B., "Significance of the Vortex Breakdown Phenomenon", *Transactions of the ASME*, pp. 518-524, June 1965.
6. Bichara, R. T., and Orner, P. A., "Analysis and Modeling of the Vortex Amplifier", ASME Publication, 69-FLCS-20, 1969.
7. Birkhoff, Garrett, Hydrodynamics, Second Edition, Princeton University Press, Princeton, 1960.
8. Bookston, J. M. and McKeachie, D. D., "Notes on the Numerical Solution of Differential Equations", General Motors Corporation Research Laboratories Report GMR 161, July 1958.
9. Carnahan, Brice, Luther, H. A., and Wilkes, James O., Applied Numerical Methods, John Wiley & Sons, Inc., New York, 1969.
10. Chow, Chuen-Yen, "Swirling Flow in Tubes of Nonuniform Cross-Sections", *Journal of Fluid Mechanics*, Vol. 38, Part 4, pp. 843-854, October 1969.
11. Deissler, Robert G. and Perlmutter, Morris, "An Analysis of the Energy Separation in Laminar and Turbulent Compressible Vortex Flows", *Proceedings Heat Transfer and Fluid Mechanics Institute*, 1958.
12. Dickson, L. E., "Differential Equations from the Group Standpoint", *Annals of Mathematics*, Second Series, Vol. 25, No. 4, pp. 287-378, June 1924.
13. Donaldson, Coleman duP. and Sullivan, Roger D., "Behavior of Solutions of the Navier-Stokes Equations for a Complete Class of Three Dimensional Viscous Vortices", 1960 *Proceedings of the Heat Transfer and Fluid Mechanics Institute*, Stanford University Press, pp. 16-30.

14. Dussourd, J. L., and Schivley, G. P., "An Analytical and Experimental Study of a Vortex Pump", ASME Publication, 70-FE-32, 1970.
15. Eckert, E. R. G., and Hartnett, J. P., "Experimental Study of the Velocity and Temperature Distribution in a High Velocity Vortex Type Flow", University of Minnesota Heat Transfer Laboratory Technical Report No. 6, September 1955.
16. Einstein, Hans Albert and Li, Huon, "Steady Vortex Flow in a Real Fluid", Heat Transfer and Fluid Mechanics Proceedings, Stanford University Press, 1951.
17. Ewing, George M., Calculus of Variations with Applications, W. W. Norton & Co., New York, 1969.
18. Frame, J. S., "Matrix Theory and Linear Algebra with Applications", Lecture notes - Michigan State University, East Lansing, Michigan, 1968.
19. Gartshore, I. S., "Recent Work in Swirling Incompressible Flow", National Research Council of Canada Aeronautical Report LR-343, June, 1962.
20. Greenspan, Donald, "Numerical Studies of Prototype Cavity Flow Problems", The Computer Journal, Vol. 12, No. 1, pp. 89-94, February 1969.
21. Greenspan, Donald, "Numerical Studies of Viscous, Incompressible Flow for Arbitrary Reynolds Number", University of Wisconsin Computer Sciences Technical Report No. 11, January 1968.
22. Greenspan, Donald, "Numerical Studies of Two Dimensional, Steady State Navier-Stokes Equations for Arbitrary Reynold's Number", University of Wisconsin Computer Sciences Technical Report No. 9, October 1967.
23. Greenspan, H. P., The Theory of Rotating Fluids, Cambridge University Press, London, 1968
24. Hall, G. G., Applied Group Theory, American Elsevier Publishing Co., New York, 1967.
25. Hansen, Arthur G., Similarity Analysis of Boundary Value Problems in Engineering, Prentice-Hall, Inc., Englewood Cliffs, New Jersey, 1964.
26. Hildebrand, Francis B., Finite Difference Equations and Simulations, Prentice-Hall, Inc., Englewood Cliffs, New Jersey, 1968.
27. Hilsch, R., "The Use of the Expansion of Gases in a Centrifugal Field as Cooling Process", The Review of Scientific Instruments, Vol. 18, No. 2, pp. 108-113, February 1947.

28. Kawaguti, M., "Numerical Solutions of the Navier-Stokes Equations for the Flow in a Two Dimensional Cavity", Journal of the Physical Society of Japan, Vol. 16, pp. 2307-2318, April 1961.
29. Kolf, R. C., "Vortex Flow from Horizontal Thin-Plate Orifices", Ph.D. Thesis, University of Wisconsin, Madison, Wisconsin, 1956.
30. Kwok, C. C. K., "A Theoretical Study of Vortex Flow in a Thin Cylindrical Chamber", Bendix Technical Journal, Vol. 1, No. 4, 1969.
31. Lamb, Sir Horace, Hydrodynamics, Sixth Edition, Dover Publications, New York, 1932.
32. Ledermann, Walter, Introduction to the Theory of Finite Groups, Interscience Publishers, Inc., New York, 1957.
33. Leitmann, George, Optimization Techniques, Academic Press, New York, 1962.
34. Lomont, J. S., Applications of Finite Groups, Academic Press, New York, 1961.
35. Lugt, Hans J. and Schwiderski, Ernst W., "Birth and Decay of Vortices", Physics of Fluids, Vol. 9, No. 5, pp. 851-859, May 1966.
36. Mack, Leslie M., "The Compressible, Viscous, Heat-Conducting Vortex", Cal. Tech. Jet Propulsion Laboratory Progress Report No. 20-382, 1959.
37. Maker, Paul, and Mayer, Endre A., "Control Characteristics of Vortex Valves", Proceedings of the Fluid Amplification Symposium, Vol. II, U. S. Army Material Command, pp. 61-83, May 1964.
38. Mayer, Endre A., "Large-Signal Vortex Valve Analysis", Advances in Fluidics, Proceedings of the 1967 ASME Fluidics Symposium, ASME Publication, pp. 233-249, May 1967.
39. Mellor, G. L., Chapple, P. J., and Stokes, V. K., "On the Flow Between a Rotating and a Stationary Disk", Journal of Fluid Mechanics, Vol. 31, Part 1, pp. 95-112, January 1968.
40. Michal, A. D., "Differential Invariants and Invariant Partial Differential Equations in Normed Linear Spaces", Proceedings of the National Academy of Sciences, Vol. 37, No. 9, pp. 623-627, September 1952.
41. Miele, Angelo, Theory of Optimum Aerodynamic Shapes, Academic Press, New York, 1965.
42. Milne, William Edmund, Numerical Solution of Differential Equations, John Wiley & Sons, Inc., New York, 1953.

43. Milne-Thomson, L. M., Theoretical Hydrodynamics, Fourth Edition, The Macmillan Co., New York, 1966.
44. Morgan, A. J. A., "The Reduction by One of the Number of Independent Variables in Some Systems of Partial Differential Equations", Quarterly Journal of Mathematics, Oxford Second Series, Vol. 3, No. 12, pp. 250-259, December 1952.
45. Olmsted, John M. H., Advanced Calculus, Appleton-Century-Crofts, Inc., New York, 1961.
46. Pearson, Carl E., "A Computational Method for Viscous Flow Problems", Journal of Fluid Mechanics, Vol. 21, Part 4, pp. 611-622, 1965.
47. Pengelley, C. Desmond, "Flow in a Viscous Vortex", Journal of Applied Physics, Vol. 28, No. 1, pp. 86-92, January 1957.
48. Protter, Murray H. and Morrey, Charles B., Modern Mathematical Analysis, Addison-Wesley Publishing Co., Reading, Mass., 1964.
49. Springer, E. Kent, and Patterson, F. M., "Experimental Investigation of Critical Submergence for Vortexing in a Vertical Cylindrical Tank", ASME Publication, 69-FE-49, 1969.
50. Torda, T. P., and Agarwal, Urmila, "Numerical Investigation of Unsteady Laminar Incompressible Boundary Layer Flows with Cylindrical Symmetry", ASME Publication, 69-FE-47, 1969.
51. Wheeler, John A., and Ruffini, Remo, "Introducing the Black Hole", Physics Today, Vol. 24, No. 1, January 1971.
52. Wilf, Herbert S. and Ralston, Anthony, Mathematical Methods for Digital Computers, John Wiley & Sons, Inc., New York, 1960.

APPENDICES



APPENDIX A


APPENDIX A

NUMERICAL DATA FOR THE SOLUTIONS TO THE SYSTEM OF ORDINARY DIFFERENTIAL EQUATIONS

A computer program utilizing Hamming's modified predictor-corrector method for numerically solving a general system of ordinary differential equations is presented in this appendix. This program is written in Fortran IV language and includes a file save such that the computed output data can be stored and used as input data to the subroutine which controls a Calcomp plotter. The IBM scientific subroutine DHCPG mentioned in Chapter IV is included in this particular program.

Table A.1 presents the numerical data for the solutions to the system of non-linear ordinary differential equations given in Chapter IV. In addition to values for G_1 , G_2 , G_3 , and G_4 , values for H , S , L^2 , and π_2 are listed. The values of these functions at each value of X are displayed in the order shown in the following 2×5 matrix:


$$X \text{ value} \begin{bmatrix} G_1 & G_2 & G_3 & G_4 & H \\ S & L^2 & \pi_2 & - & - \end{bmatrix}.$$



```

/1D PC05,BRINK,PC05,DIFFERENTIAL EQUATIONS
/JOB GO
/FILE DISK=13,NREC=960,PTPTPT),VOL=RAXFL1,DISP=(OLD,KEEP)
/JOB GO,TIME=10
/FTC LIST
C      COMMON IYY,ITER8T,IPLOT,IIONCE,IJTIME,ITIME
C      THIS PROGRAM REPLACES THE BASIC DIFFEQ
C      DOUBLE PRECISION OPT
C      DOUBLE PRECISION X
C      DIMENSION PRMT(5),Y(23),DERV(20),AUX(16,20)
C      DIMENSION YTEMP(20)
C      IONCE=0
C      LJTIME=240
C      J1=0
C      PRMT(4)=.02
C      READ(5)ITER8T,IPLOT,IYY
C      READ(5)NDIM,NN,PRMT(3),PRMT(1),PRMT(2),OPT
C      WRITE(6,160)
C      160 FORMAT('1',
C      WRITE(6,800)NDIM
C      800 FORMAT(' NO OF DIFFERENTIAL EQUATIONS', 7X,13)
C      WRITE(6,810)NN
C      810 FORMAT(' VARIABLE(=0) OR FIXED(=1) STEP SIZE',13)
C      WRITE(6,820)PRMT(3)
C      820 FORMAT(' INITIAL STEP SIZE',6X,F15.5)
C      WRITE(6,830)PRMT(1),PRMT(2)
C      830 FORMAT(' INITIAL AND FINAL VALUES OF X',2F15.5)
C      WRITE(6,840)OPT
C      840 FORMAT(' PRINT OUT INTERVAL',5X,F15.5///)
C      Y(1)=1.
C      Y(2)=1.
C      Y(3)=1.
C      Y(4)=.5
C      DO 8310 I=1,NDIM
C      8310 YTEMP(I)=Y(I)
C      IF(NN)90,80,90
C      90 DO 100 I=1,NDIM


```



```

100 DERY(I)=0.
    GO TO 120
    80 DO 110 I=1,NDIM
    110 DERY(I)=1./NDIM
    120 CALL HPCG(PRMT,Y,DERY,NDIM,IHLF,AUX,OPT,J1,X)
        IF (IONCE-1)8300,8090,8300
8090 IONCE=2
    PRMT(2)=X
    IJTIME=ITIME/300+240
    IF (NN)190,180,190
    190 DO 1000 I=1,NDIM
    1000 DERY(I)=0.
    GO TO 1200
    180 DO 1100 I=1,NDIM
    1100 DERY(I)=1./NDIM
    1200 CONTINUE
    DO 8120 I=1,NDIM
    8120 Y(I)=YTEMP(I)
    CALL HPCG(PRMT,Y,DERY,NDIM,IHLF,AUX,OPT,J1,X)
    8300 X=99999.
    CALL OUTP(X,Y,DERY,IHLF,NDIM,PRMT,OPT,J1)
    IF (IHLF-31)130,200,210
    200 WRITE(6,220)
    220 FORMAT(' MORE THAN 30 BISECTIONS OF THE INITIAL INCREMENT ARE * /
    1'NECESSARY TO GET SATISFACTORY ACCURACY')
    GO TO 130
    210 WRITE(6,230)
    230 FORMAT(' INITIAL INCREMENT IS EQUAL TO 0 OR HAS WRONG SIGN * )
    130 STOP
    END
/BAP
ELAPSE START 0
      USING *,15
      STM 14,12,12(13)
      L 2,0(1)
      L 3,X*268*
      L 4,40(3)


```

```

      ST      4,0(2)
      LM      14,12,12(13)
      BCR     15,14
      END
/FTC LIST
      SUBROUTINE FCT(X,Y,D)
      COMMON IYY,ITERBT, IPLOT,IONCE,IJTIME,ITIME
      DOUBLE PRECISION X
      DIMENSION Y(11),D(1)
      DIMENSION ZZ(4)
      A=X*Y(1)-Y(3)
      C=-(A*Y(11))/X-Y(2)**2
      E=X+1./X
      D(4)=C/E
      D(3)=D(4)/A
      D(2)=(Y(11)*Y(2))/A
      D(1)=(Y(1)+D(3))/X
      Y(5)=Y(4)+(Y(1)**2+Y(2)**2+Y(3)**2+Y(3)**2)/2.
      Y(6)=(Y(2)**2)/(Y(5)*X**2)
      Y(7)=Y(1)**2+Y(3)**2
      Y(8)=(Y(2)**2)/Y(5)
      IF(Y(21)-1)9111,9112,9111
9112  IJ=0
      KKK=KKK+1
      NOZ=Y(22)
      IN=Y(23)
      DO 9113 IJJI=IN,1YY,NOZ
      INOZ=IJJI+NOZ-1
      IJ=IJ+1
      Z=ZZ(IJ)
9113  WRITE(7,9114)(X,Y(1),Z,KKK,I,I=IJJI,INOZ)
9114  FORMAT(6X,'GO TO',E13.6,',',E13.6,',',E13.6,22X,I3,I2)
      RETURN
9111  CONTINUE
      RETURN
      END
      SUBROUTINE OUTP(X,Y,DERV,IHLF,NDIM,PRMT,OPT,IJ1)


```



```

COMMON IYY,ITERBT,IPLOT,IONCE,IJTIME,ITIME
DIMENSION Y(1),DERY(1),PRMT(1)
DIMENSION ICT(20),JCT(20),YMAX(20),YYMIN(20)
DIMENSION NY(20),YSAVE(100,20),YSCALE(20)
DIMENSION DSAVE(20),YMAX(20),YYMN(20)
DIMENSION YSTOP(20)
DOUBLE PRECISION OPT
IF(X-PRMT(1))5.84,5
84 PP=PRMT(1)
  IJJ=0
  KKKC=0
  IF(NDIM-IYY)93,93,94
93 IYMAX=IYY
  GO TO 96
94 IYMAX=NDIM
96 XX=X
  DO 850 I=1,NDIM
    ICT(I)=1
    JCT(I)=1
850 DSAVE(I)=DERY(I)
  DO 730 I=1,IYMAX
    YMX(I)=-1.E75
    YYMN(I)=1.E75
    YMAX(I)=-1.E75
730 YYMIN(I)=1.E75
  IF(1PLOT)333,333,71
71 IF(IONCE-2)8100,726,8100
8100 INPTS=40
  IF(ITERBT)726,726,8101
8101 WRITE(6,725)
725 FORMAT(' HOW MANY PTS DO YOU WISH TO PLOT?')
  READ(9)INPTS
  IF(INPTS-20)851,726,726
851 INPTS=20
726 XSTEP=(PRMT(2)-PRMT(1))/INPTS
  XPLOT=PRMT(1)
  ICORT=0.


```



```

333 IF(IONCE-2)8110,5,8110
8110 WRITE(6,140)
140 FORMAT(/'3H NO,14X,1HX,9X,4HY(1),9X,4HY(2),9X,4HY(3),9X,4HY(4)')
READ(5)IPUNCH,NOZ,IN
Y(22)=NOZ
Y(23)=IN
READ(5)IONEY,XSTART
5 CONTINUE
IF(X-99999.)3099,3091,3099
3099 IF(X-XSTART)3091,3091,3092
3092 IF(DERY(IONEY))3091,3093,3093
3093 IONONE=IONONE+1
IF(IONONE-2)3096,3091,3091
3096 DO 3095 II=1,IYMAX
3095 Y(II)=YSTOP(II)
X=XXXXXX
PRMT(5)=1.
RETURN
3091 DO 3094 II=1,IYMAX
3094 YSTOP(II)=Y(II)
IF(IJJJ-5)9222,223,9224
9222 IJJJ=IJJJ+1
GO TO 222
223 SIJJ=(PRMT(2)-PRMT(1))/PRMT(3)
IIJ=SIJJ/1000.+1.
GO TO 9223
9224 KKKC=KKKC+1
IF(KKKC-11)224,9223,224
9223 IJJJ=IJJJ+1
KKKC=0
222 CONTINUE
WRITE(3)X,(Y(1),I=1,IYMAX)
224 CONTINUE
IF(IPLOT)540,540,740
740 CONTINUE
IF(X-99999.)540,550,540
550 WRITE(6,551)


```



```

551 FORMAT(////)
    IYMX=IYMAX+1
    WRITE(3)(Y(I),I=1,IYMX)
    CALL PLOT(YSAVE,ICOTT,YMAX,YMIN,PRMT(1),XSTEP)
    RETURN
540 IF(X-99999.)541,35,541
35 X=XXXXYY
    GO TO 38
541 DO 900 I=1,IYMAX
    IF(Y(I)-YMAX(I))920,920,910
    910 YMAX(I)=Y(I)
    920 IF(Y(I)-YMIN(I))930,900,900
    930 YMIN(I)=Y(I)
    900 CONTINUE
    DO 600 I=1,NDIM
    IF(DSAVE(I))602,332,601
    332 IF(X-PRMT(1))335,600,335
    335 IF(DERY(I))600,334,600
    334 JCT(I)=JCT(I)+1
    ICT(I)=ICT(I)+1
    GO TO 600
    601 IF(DERY(I))603,603,600
    603 XY=ABS(YMX(I)/100.)
    IF(XY)6000,6010,6010
    6000 XY=.01
    6010 IF(ABS(Y(I)-YMX(I))-XY)604,604,605
    604 ICT(I)=ICT(I)+1
    IF(Y(I)-YMX(I))600,600,608
    605 ICT(I)=1
    608 YMX(I)=Y(I)
    GO TO 600
    602 IF(DERY(I))600,610,610
    610 XY=ABS(YMN(I)/100.)
    IF(XY)6020,6030,6030
    6020 XY=.01
    6030 IF(ABS(Y(I)-YMN(I))-XY)611,611,612
    611 JCT(I)=JCT(I)+1


```

```

IF(Y(I)-YYMN(I))613,600,600
612 JCT(I)=1
613 YYMN(I)=Y(I)
600 CONTINUE
DO 800 I=1,NDIM
800 DSAVE(I)=DERY(I)
720 CONTINUE
IF(IPLTOT)6,6,8
8 IF(ABS(XPLOT-X)-(X-XX)/2+.0001)500,510,510
510 IF(X-XPLOT)6,500,500
500 XPLOT=XPLOT+XSTEP
51 ICOTT=ICOTT+1
YSAVE(ICOTT,1)=X
DO 53 I=1,IYMAX
53 YSAVE(ICOTT,I+1)=Y(I)
6 IF(X-PRMT(2))8041,85,8041
8041 CONTINUE
87 IF(X-PP)20,85,85
85 PP=PP+OPT
10 J1=J1+1
IF(IIONCE)20,62,20
62 WRITE(6,50)J1,X,(Y(I),I=1,IYY)
50 FORMAT(14,E14.5,4E13.5/(18X,4E13.5))
IF(IIPUNCH-1)20,8223,20
8223 Y(21)=1.
CALL FCT(X,Y,D)
Y(21)=0.
20 XX=X
IF(IPLTOT)8000,8000,34
34 CALL ELAPSE(ITIME)
2081 IF(IIONCE-2)2081,2080,2080
2090 IF(JTIME-1)2090,2091,2080
2091 IF(ITIME-1200)2080,3010,3010
2091 IF(ITIME-2400)2080,3010,3010
3010 JTIME=JTIME+1
IF(JTIME-1)3011,3011,3012

```




```

3011 XTIME=(X-PRMT(1))*60.+PRMT(1)
GO TO 3013
3012 XTIME=(X-PRMT(1))*30.+PRMT(1)
3013 IF(XTIME-PRMT(2))3020,2080,2080
3020 XSTEP=(XTIME-PRMT(1))/INPTS
2080 CONTINUE
IF(ETIME/300-IJTIME)8000,8000,36
36 WRITE(6,37)
37 FORMAT(' ', 4 MINUTES EXECUTION TIME HAS BEEN USED',/
1. BRANCH TO PLOT ROUTINE BEING MADE',)
38 WRITE(6,746)X
746 FORMAT(' FINAL X =',E15.7,/)
IYMX=IYMAX+1
WRITE(3)(Y(I),I=1,IYMX)
WRITE(6,747)
747 FORMAT(' Y CURRENT VALUE MIN MAX')
DO 748 I=1,IYMAX
748 WRITE(6,749)I,Y(I),YYMIN(I),YYMAX(I)
749 FORMAT(15,3E15.7)
PRMT(5)=1.
8000 XXXYYY=X
RETURN
END
SUBROUTINE HPCG(PRMT,Y,DERY,NDIM,IHLF,AUX,OPT,J1,X)
COMMON IYY,ITERBT,IPLDT,IUNCE,IJTIME,IJTIME

DIMENSION PRMT(1),Y(1),DERY(1),AUX(16,1)
DOUBLE PRECISION OPT
DOUBLE PRECISION X
N=1
IHLF=0
X=PRMT(1)
H=PRMT(3)
PRMT(5)=0.
DO 1 I=1,NDIM
AUX(16,I)=0.

```


C C



```

      AUX(15,I)=DERY(I)
1  AUX(1,I)=Y(I)
   IF(H*(PRMT(2)-X))3,2,4
C
C  ERROR RETURNS
2  IHLF=32
   GO TO 4
3  IHLF=33
C
C  COMPUTATION OF DERY FOR STARTING VALUES
4  CALL FCT(X,Y,DERY)
C
C  RECORDING OF STARTING VALUES
CALL OUTPIX,Y,DERY,IHLF,NDIM,PRMT,OPT,J1)
   IF(PRMT(5))6,5,6
5  IF(IHLF)7,7,6
6  RETURN
7  DO 8 I=1,NDIM
8  AUX(8,I)=DERY(I)
C
C  COMPUTATION OF AUX(2,I)
   ISW=1
   GO TO 100
C
9  X=X+H
   DO 10 I=1,NDIM
10  AUX(2,I)=Y(I)
C
C  INCREMENT H IS TESTED BY MEANS OF BISECTION
11  IHLF=IHLF+1
   X=X-H
   DO 12 I=1,NDIM
12  AUX(4,I)=AUX(2,I)
   H=.5*H
   N=1
   ISW=2
   GO TO 100

```



```

C      13 X=X+H
        CALL FCT(X,Y,DERV)
        N=2
        DO 14 I=1,NDIM
          AUX(2,I)=Y(I)
        14 AUX(9,I)=DERV(I)
          ISW=3
          GO TO 100


C      C      COMPUTATION OF TEST VALUE DELT
        15 DELT=0.
        DO 16 I=1,NDIM
          DELT=DELT+AUX(15,I)*ABS(Y(I)-AUX(4,I))
        16 DELT=-0.6666667*DELT
          IF(DELT-PRMT(4))19,19,17
        17 IF(IHLF-30)11,18,18

C      C      NO SATISFACTORY ACCURACY AFTER 10 BISECTIONS. ERROR MESSAGE.
        18 IHLF=31
          X=X+H
          GO TO 4

C      C      THERE IS SATISFACTORY ACCURACY AFTER LESS THAN 11 BISECTIONS.
        19 X=X+H
          CALL FCT(X,Y,DERV)
          DO 20 I=1,NDIM
            AUX(3,I)=Y(I)
          20 AUX(10,I)=DERV(I)
            N=3
            ISW=4
            GO TO 100

C      21 N=1
          X=X+H
          CALL FCT(X,Y,DERV)
          X=PRMT(1)


```

```

DO 22 I=1,NDIM
  AUX(11,I)=DERY(I)
22 Y(I)=AUX(1,I)+H*(.375*AUX(8,I)+.7916667*AUX(9,I)
  1-.2083333*AUX(10,I)+.0416667*DERY(I))
23 X=X+H
  N=N+1
  CALL FCT(X,Y,DERY)
  CALL OUTP(X,Y,DERY,IHLF,NDIM,PRMT,OPT,J1)
  IF(PRMT(5))6,24,6
24 IF(N-4)25,200,200
25 DO 26 I=1,NDIM
  AUX(N,I)=Y(I)
26 AUX(N+7,I)=DERY(I)
  IF(N-3)27,29,200
C
27 DO 28 I=1,NDIM
  DELT=AUX(9,I)+AUX(9,I)
  DELT=DELT+DELT
28 Y(I)=AUX(1,I)+.3333333*H*(AUX(8,I)+DELT+AUX(10,I))
  GO TO 23
C
29 DO 30 I=1,NDIM
  DELT=AUX(9,I)+AUX(10,I)
  DELT=DELT+DELT+DELT
30 Y(I)=AUX(1,I)+.375*H*(AUX(8,I)+DELT+AUX(11,I))
  GO TO 23
C
C THE FOLLOWING PART OF SUBROUTINE HPCG COMPUTES BY MEANS OF
C RUNGE-KUTTA METHOD STARTING VALUES FOR THE NOT SELF-STARTING
C PREDICTOR-CORRECTOR METHOD.
100 DO 101 I=1,NDIM
  Z=H*AUX(N+7,I)
  AUX(5,I)=Z
101 Y(I)=AUX(N,I)+.4*Z
C Z IS AN AUXILIARY STORAGE LOCATION
C
Z=X+.4*H


```



```

CALL FCT(Z,Y,DERY)
DO 102 I=1,NDIM
Z=H*DERY(I)
AUX(6,I)=Z
102 Y(I)=AUX(N,I)+.2969776*AUX(5,I)+.1587596*Z
C
Z=X+.4557372*H
CALL FCT(Z,Y,DERY)
DO 103 I=1,NDIM
Z=H*DERY(I)
AUX(7,I)=Z
103 Y(I)=AUX(N,I)+.2181004*AUX(5,I)-3.050965*AUX(6,I)+3.832865*Z
C
Z=X+H
CALL FCT(Z,Y,DERY)
DO 104 I=1,NDIM
104 OY(I)=AUX(N,I)+.1747603*AUX(5,I)-.5514807*AUX(6,I)
+1.205536*AUX(7,I)+.1711848*H*DERY(I)
GO TO (9,13,15,21),ISW
C
POSSIBLE BREAK-POINT FOR LINKAGE
C
C
C
STARTING VALUES ARE COMPUTED.
C
NOW START HAMMINGS MODIFIED PREDICTOR-CORRECTOR METHOD.
200 ISTEP=3
201 IF(N-8)204,202,204
C
N=8 CAUSES THE ROWS OF AUX TO CHANGE THEIR STORAGE LOCATIONS
202 DO 203 N=2,7
DO 203 I=1,NDIM
AUX(N-1,I)=AUX(N,I)
203 AUX(N+6,I)=AUX(N+7,I)
N=7
C
C
N LESS THAN 8 CAUSES N+1 TO GET N
204 N=N+1
C


```



```

C      COMPUTATION OF NEXT VECTOR Y
DO 205 I=1,NDIM
  AUX(N-1,I)=Y(I)
205  AUX(N+6,I)=DERY(I)
  X=X+H
206  ISTEP=ISTEP+1
  DO 207 I=1,NDIM
    ODELTA=AUX(N-4,I)+1.333333*H*(AUX(N+6,I)+AUX(N+6,I)-AUX(N+5,I)+
      1AUX(N+4,I)+AUX(N+4,I))
    Y(I)=DELTA-.9256198*AUX(16,I)
207  AUX(16,I)=DELTA
  PREDICTOR IS NOW GENERATED IN ROW 16 OF AUX, MODIFIED PREDICTOR
  IS GENERATED IN Y. DELTA MEANS AN AUXILIARY STORAGE.
C
C      CALL FCT(X,Y,DERY)
C      DERIVATIVE OF MODIFIED PREDICTOR IS GENERATED IN DERY
C
DO 208 I=1,NDIM
  ODELTA=.125*(9.*AUX(N-1,I)-AUX(N-3,I)+3.*H*(DERY(I)+AUX(N+6,I)+
    1AUX(N+6,I)-AUX(N+5,I)))
  AUX(16,I)=AUX(16,I)-DELTA
208  Y(I)=DELTA+.07438017*AUX(16,I)
C
C      TEST WHETHER H MUST BE HALVED OR DOUBLED
  DELTA=0.
DO 209 I=1,NDIM
  DELTA=DELTA+AUX(15,I)*ABS(AUX(16,I))
209  IF(DELTA-PRMT(4))210,222,222
C
C      H MUST NOT BE HALVED. THAT MEANS Y(I) ARE GOOD.
210  CALL FCT(X,Y,DERY)
  CALL OUTP(X,Y,DERY,IHLF,NDIM,PRMT,OPT,J1)
  IF(PRMT(5))212,211,212
211  IF(IHLF-31)213,212,212
212  RETURN
213  IF(H*(X-PRMT(2)))214,1212,1212
214  IF(DABS(X-PRMT(2))-1.*ABS(H))1212,215,215


```



```

1212 H=PRMT(2)-X
      IF (H)201,212,201
215  IF (DELT-.10*PRMT(4))216,216,201
C
C
C
      H COULD BE DOUBLED IF ALL NECESSARY PRECEEDING VALUES ARE
      AVAILABLE
216  IF (H-.1)217,217,201
217  IF (N-7)201,218,218
218  IF (1STEP-4)201,219,219
219  IMOD=1STEP/2
      IF (1STEP-IMOD-IMOD)201,220,201
220  H=H+H
      IHLF=IHLF-1
      ISTEP=0
      DO 221 I=1,NDIM
        AUX(N-1,I)=AUX(N-2,I)
        AUX(N-2,I)=AUX(N-4,I)
        AUX(N-3,I)=AUX(N-6,I)
        AUX(N+6,I)=AUX(N+5,I)
        AUX(N+5,I)=AUX(N+3,I)
        AUX(N+4,I)=AUX(N+1,I)
        DELT=AUX(N+6,I)+AUX(N+5,I)
        DELT=DELT+DELT
2210AUX(16,I)=8.962963*(Y(I)-AUX(N-3,I))-3.361111*H*(DERY(I)+DELT
      1+AUX(N+4,I))
      GO TO 201
C
C
C
      H MUST BE HALVED
222  IHLF=IHLF+1
      IF (IHLF-30)223,223,210
223  H=.5*H
      ISTEP=0
      DO 224 I=1,NDIM
        OY(I)=.00390625*(80.*AUX(N-1,I)+135.*AUX(N-2,I)+40.*AUX(N-3,I)+
        1AUX(N-4,I))-1171875*(AUX(N+6,I)-6.*AUX(N+5,I)-AUX(N+4,I))*H

```

```

    O AUX(N-4,I) = .00390625*(12.*AUX(N-1,I)+135.*AUX(N-2,I)+
1108.*AUX(N-3,I)+AUX(N-4,I))- .0234375*(AUX(N+6,I)+18.*AUX(N+5,I))-
29.*AUX(N+4,I))*H
    AUX(N-3,I) = AUX(N-2,I)
224  AUX(N+4,I) = AUX(N+5,I)
    X = X-H
    DELT = X-(H+H)
    CALL FCT(DELT,Y,DERY)
    DO 225 I=1,NDIM
    AUX(N-2,I) = Y(I)
    AUX(N+5,I) = DERY(I)
225  Y(I) = AUX(N-4,I)
    DELT = DELT-(H+H)
    CALL FCT(DELT,Y,DERY)
    DO 226 I=1,NDIM
    DELT = AUX(N+5,I)+AUX(N+4,I)
    DELT = DELT+DELT+DELT
    O AUX(16,I) = 8.962963*(AUX(N-1,I)-Y(I))-3.361111*H*(AUX(N+6,I)+DELT
1+DERY(I))
226  AUX(N+3,I) = DERY(I)
    GO TO 206
    END

```




TABLE A-1 NUMERICAL DATA FOR SOLUTIONS TO THE SYSTEM OF ORDINARY DIFFERENTIAL EQUATIONS

NO	X	Y(1)	Y(2)	Y(3)	Y(4)	Y(5)
1	0.10000E 00	0.10000E 01	0.10000E 01	0.10000E 01	0.50000E 00	0.20000E 01
2	0.10500E 00	0.50000E 02	0.20000E 01	0.50000E 00	0.50394E 00	0.20000E 01
3	0.11000E 00	0.10060E 01	0.99441E 00	0.99560E 00	0.50783E 00	0.20000E 01
4	0.11500E 00	0.44846E 02	0.20033E 01	0.49443E 00	0.51167E 00	0.20000E 01
5	0.12000E 00	0.10120E 01	0.98876E 00	0.99120E 00	0.51547E 00	0.20000E 01
6	0.12500E 00	0.40394E 02	0.20067E 01	0.48882E 00	0.51922E 00	0.20000E 01
7	0.13000E 00	0.10181E 01	0.98304E 00	0.98681E 00	0.52292E 00	0.20000E 01
8	0.14000E 00	0.36536E 02	0.20103E 01	0.48318E 00	0.53019E 00	0.20000E 01
9	0.15000E 00	0.10242E 01	0.97725E 00	0.98242E 00	0.53725E 00	0.20000E 01
10	0.16000E 00	0.33160E 02	0.20140E 01	0.47751E 00	0.54413E 00	0.20000E 01
11	0.17000E 00	0.10302E 01	0.97139E 00	0.97803E 00	0.55080E 00	0.20000E 01
12	0.18000E 00	0.30193E 02	0.20179E 01	0.47180E 00	0.56355E 00	0.20000E 01
13	0.19000E 00	0.10364E 01	0.96547E 00	0.97364E 00	0.57548E 00	0.20000E 01
14	0.20000E 00	0.27578E 02	0.20220E 01	0.46606E 00	0.58637E 00	0.20000E 01
15	0.21000E 00	0.10487E 01	0.95339E 00	0.96487E 00	0.59682E 00	0.20000E 01
16	0.22000E 00	0.23188E 02	0.20307E 01	0.45448E 00	0.61471E 00	0.20000E 01
17	0.23000E 00	0.10610E 01	0.94102E 00	0.95612E 00	0.20000E 01	0.20000E 01
18	0.24000E 00	0.19678E 02	0.20400E 01	0.44276E 00	0.20000E 01	0.20000E 01
19	0.25000E 00	0.10735E 01	0.92833E 00	0.94738E 00	0.20000E 01	0.20000E 01
20	0.26000E 00	0.16832E 02	0.20499E 01	0.43090E 00	0.20000E 01	0.20000E 01
21	0.27000E 00	0.10861E 01	0.91532E 00	0.93865E 00	0.20000E 01	0.20000E 01
22	0.28000E 00	0.14499E 02	0.20606E 01	0.41890E 00	0.20000E 01	0.20000E 01
23	0.29000E 00	0.11114E 01	0.88824E 00	0.92124E 00	0.20000E 01	0.20000E 01
24	0.30000E 00	0.10928E 02	0.20839E 01	0.39449E 00	0.20000E 01	0.20000E 01
25	0.31000E 00	0.11371E 01	0.85965E 00	0.90390E 00	0.20000E 01	0.20000E 01
26	0.32000E 00	0.83788E 01	0.21100E 01	0.36951E 00	0.20000E 01	0.20000E 01
27	0.33000E 00	0.11031E 01	0.82939E 00	0.88662E 00	0.20000E 01	0.20000E 01
28	0.34000E 00	0.65019E 01	0.21389E 01	0.34395E 00	0.20000E 01	0.20000E 01
29	0.35000E 00	0.11895E 01	0.79725E 00	0.86942E 00	0.20000E 01	0.20000E 01
30	0.36000E 00	0.50849E 01	0.21707E 01	0.31791E 00	0.20000E 01	0.20000E 01
31	0.37000E 00	0.12431E 01	0.72629E 00	0.83527E 00	0.20000E 01	0.20000E 01
32	0.38000E 00	0.31362E 01	0.22431E 01	0.26375E 00	0.20000E 01	0.20000E 01




TABLE A.1 (CONT'D.)

17	0.33000E 00	0.12981E 01	0.64385E 00	0.80148E 00	0.62905E 00	0.20000E 01
18	0.37000E 00	0.19033E 01	0.23273E 01	0.20727E 00	0.63975E 00	0.20000E 01
19	0.41000E 00	0.13542E 01	0.54460E 00	0.76809E 00	0.64674E 00	0.19999E 01
20	0.45000E 00	0.10832E 01	0.24238E 01	0.14830E 00	0.64992E 00	0.20007E 01
21	0.45500E 00	0.14116E 01	0.41622E 00	0.73517E 00	0.65003E 00	0.20046E 01
22	0.46000E 00	0.51533E 00	0.25331E 01	0.86626E-01	0.65012E 00	0.20047E 01
23	0.46500E 00	0.14725E 01	0.19415E 00	0.70384E 00	0.65013E 00	0.19986E 01
24	0.46531E 00	0.93040E-01	0.26638E 01	0.18841E-01	0.65012E 00	0.19982E 01
25	0.46562E 00	0.14824E 01	0.14255E 00	0.70096E 00	0.65012E 00	0.19986E 01
26	0.46594E 00	0.48961E-01	0.26888E 01	0.10136E-01	0.65012E 00	0.19986E 01
27	0.46625E 00	0.14885E 01	0.93135E-01	0.69633E 00	0.65012E 00	0.19986E 01
28	0.46656E 00	0.20448E-01	0.27006E 01	0.43268E-02	0.65012E 00	0.19986E 01
29	0.46687E 00	0.14934E 01	0.53592E-01	0.69115E 00	0.65012E 00	0.19986E 01
30	0.46750E 00	0.66230E-02	0.27080E 01	0.14321E-02	0.65012E 00	0.19986E 01
31	0.46812E 00	0.14900E 01	0.47948E-01	0.68910E 00	0.65012E 00	0.19986E 01
32	0.46875E 00	0.53122E-02	0.26951E 01	0.11502E-02	0.65012E 00	0.19986E 01
33	0.46937E 00	0.14900E 01	0.50620E-01	0.68864E 00	0.65012E 00	0.19986E 01
		0.59134E-02	0.26944E 01	0.12821E-02	0.65012E 00	0.19986E 01
		0.14899E 01	0.52570E-01	0.68811E 00	0.65012E 00	0.19986E 01
		0.63709E-02	0.26933E 01	0.13831E-02	0.65012E 00	0.19986E 01
		0.14901E 01	0.57925E-01	0.68776E 00	0.65012E 00	0.19986E 01
		0.77227E-02	0.26935E 01	0.16788E-02	0.65012E 00	0.19986E 01
		0.14902E 01	0.61595E-01	0.68732E 00	0.65012E 00	0.19986E 01
		0.87206E-02	0.26931E 01	0.18983E-02	0.65012E 00	0.19986E 01
		0.14903E 01	0.65260E-01	0.68690E 00	0.65012E 00	0.19986E 01
		0.97758E-02	0.26928E 01	0.21308E-02	0.65012E 00	0.19986E 01
		0.14900E 01	0.77124E-01	0.68582E 00	0.65012E 00	0.19986E 01
		0.13619E-01	0.26904E 01	0.29766E-02	0.65012E 00	0.19986E 01
		0.14901E 01	0.83619E-01	0.68492E 00	0.65012E 00	0.19986E 01
		0.15967E-01	0.26894E 01	0.34991E-02	0.65012E 00	0.19986E 01
		0.14901E 01	0.89673E-01	0.68402E 00	0.65012E 00	0.19986E 01
		0.18314E-01	0.26884E 01	0.40240E-02	0.65012E 00	0.19986E 01
		0.14902E 01	0.94929E-01	0.68314E 00	0.65012E 00	0.19986E 01
		0.20469E-01	0.26875E 01	0.45096E-02	0.65012E 00	0.19986E 01




TABLE A.1 (CONT'D.)

34	0.47662E 00	0.14905E 01	0.10404E 00	0.68140E 00	0.65003E 00	0.19984E 01
35	0.47187E 00	0.24455E-01	0.26859E 01	0.54165E-02	0.64999E 00	0.19984E 01
36	0.47312E 00	0.14907E 01	0.11286E 00	0.67963E 00	0.64995E 00	0.19984E 01
37	0.47437E 00	0.28624E-01	0.26841E 01	0.63736E-02	0.64990E 00	0.19984E 01
38	0.47687E 00	0.14909E 01	0.12145E 00	0.67784E 00	0.64977E 00	0.19985E 01
39	0.47937E 00	0.32976E-01	0.26821E 01	0.73816E-02	0.64962E 00	0.19985E 01
40	0.48187E 00	0.14910E 01	0.12948E 00	0.67605E 00	0.64945E 00	0.19985E 01
41	0.48437E 00	0.37282E-01	0.26802E 01	0.83995E-02	0.64924E 00	0.19985E 01
42	0.48937E 00	0.14916E 01	0.14251E 00	0.67258E 00	0.64875E 00	0.19982E 01
43	0.49437E 00	0.44686E-01	0.26771E 01	0.10162E-01	0.64816E 00	0.19982E 01
44	0.49937E 00	0.14919E 01	0.15575E 00	0.66903E 00	0.64747E 00	0.19982E 01
45	0.50437E 00	0.52823E-01	0.26735E 01	0.12139E-01	0.64667E 00	0.19982E 01
46	0.51437E 00	0.14923E 01	0.16780E 00	0.66195E 00	0.64476E 00	0.19982E 01
47	0.52437E 00	0.60678E-01	0.26699E 01	0.14090E-01	0.64244E 00	0.19982E 01
48	0.53437E 00	0.14927E 01	0.17920E 00	0.66195E 00	0.63971E 00	0.19982E 01
49	0.54437E 00	0.68489E-01	0.26664E 01	0.16069E-01	0.63658E 00	0.19982E 01
50	0.56437E 00	0.14933E 01	0.20092E 00	0.65476E 00	0.62913E 00	0.19982E 01
		0.84357E-01	0.26586E 01	0.20202E-01		
		0.14941E 01	0.21991E 00	0.64769E 00		
		0.99020E-01	0.26518E 01	0.24201E-01		
		0.14949E 01	0.23728E 00	0.64064E 00		
		0.11299E 00	0.26452E 01	0.28176E-01		
		0.14958E 01	0.25342E 00	0.63361E 00		
		0.12634E 00	0.26389E 01	0.32140E-01		
		0.14976E 01	0.28332E 00	0.61953E 00		
		0.15183E 00	0.26266E 01	0.40173E-01		
		0.14995E 01	0.31013E 00	0.60956E 00		
		0.17506E 00	0.26153E 01	0.48136E-01		
		0.15016E 01	0.33492E 00	0.59163E 00		
		0.19659E 00	0.26047E 01	0.56138E-01		
		0.15037E 01	0.35799E 00	0.57777E 00		
		0.21643E 00	0.25950E 01	0.64136E-01		
		0.15085E 01	0.39979E 00	0.55028E 00		
		0.25112E 00	0.25784E 01	0.79987E-01		




TABLE A.1 (CONT'D.)

51	0.58437E 00	0.15136E 01	0.43809E 00	0.52296E 00	0.62008E 00	0.19982E 01
52	0.60437E 00	0.28126E 00	0.25643E 01	0.96049E-01	0.60948E 00	0.19982E 01
53	0.62437E 00	0.15190E 01	0.47341E 00	0.49589E 00	0.59733E 00	0.19982E 01
54	0.66437E 00	0.30706E 00	0.25333E 01	0.11216E 00	0.56848E 00	0.19980E 01
55	0.70437E 00	0.15249E 01	0.50643E 00	0.46905E 00	0.53379E 00	0.19979E 01
56	0.74437E 00	0.32923E 00	0.25452E 01	0.12835E 00	0.49343E 00	0.19979E 01
57	0.78437E 00	0.15376E 01	0.56710E 00	0.41602E 00	0.44756E 00	0.19979E 01
58	0.86437E 00	0.36467E 00	0.25373E 01	0.16097E 00	0.33974E 00	0.19974E 01
59	0.9437E 00	0.15519E 01	0.62235E 00	0.36401E 00	0.21119E 00	0.19973E 01
60	0.95133E 00	0.39075E 00	0.25409E 01	0.19387E 00	0.20016E 00	0.19982E 01
61	0.95828E 00	0.15676E 01	0.67350E 00	0.31300E 00	0.18774E 00	0.19983E 01
62	0.96523E 00	0.40975E 00	0.25553E 01	0.22704E 00	0.17672E 00	0.19982E 01
63	0.97219E 00	0.15846E 01	0.72151E 00	0.26296E 00	0.16425E 00	0.19981E 01
64	0.98609E 00	0.42351E 00	0.25801E 01	0.26056E 00	0.14256E 00	0.19995E 01
65	0.10000E 01	0.16220E 01	0.81063E 00	0.16556E 00	0.11680E 00	0.19992E 01
66	0.10000E 01	0.44032E 00	0.26582E 01	0.32899E 00	0.11576E 00	0.19993E 01
67	0.10000E 01	0.16639E 01	0.89268E 00	0.72077E-01		
		0.44737E 00	0.27737E 01	0.39898E 00		
		0.16680E 01	0.8992E 00	0.63766E-01		
		0.44782E 00	0.27863E 01	0.40529E 00		
		0.16720E 01	0.90697E 00	0.5612E-01		
		0.44826E 00	0.27986E 01	0.41164E 00		
		0.16755E 01	0.91292E 00	0.48681E-01		
		0.44767E 00	0.28095E 01	0.41708E 00		
		0.16793E 01	0.91964E 00	0.40860E-01		
		0.44784E 00	0.28219E 01	0.42328E 00		
		0.16868E 01	0.93162E 00	0.26939E-01		
		0.44640E 00	0.28459E 01	0.43407E 00		
		0.16947E 01	0.94480E 00	0.11529E-01		
		0.44649E 00	0.28723E 01	0.44649E 00		
		0.16950E 01	0.94522E 00	0.11034E-01		
		0.44689E 00	0.28731E 01	0.44689E 00		
		0.16951E 01	0.94534E 00	0.10897E-01		
		0.44700E 00	0.28734E 01	0.44700E 00		






TABLE A.1 (CONT'D.)

68	0.10000E 01	0.16947E 01	0.94477E 00	0.11562E-01	0.11686E 00	0.19992E 01
		0.44646E 00	0.28722E 01	0.44646E 00		
69	0.10000E 01	0.16947E 01	0.94472E 00	0.11620E-01	0.11695E 00	0.19992E 01
		0.44642E 00	0.28721E 01	0.44642E 00		



APPENDIX B




APPENDIX B

CALCOMP PLOTTER ROUTINE

A special library subroutine named L9MIKE was used to control the Calcomp plotter which plotted all the curves displayed in this thesis. This subroutine allows the user to title curves, title axes, select scale lengths, plot parametric curves where the plot interval is a function on the parameter, specify the order and number (up to 20) of variables to be plotted per diagram, and identify each curve by at least 10 identification marks (squares, circles, triangles, etc.). The input data for the L9MIKE subroutine is taken from a stored file and all data points in the file are plotted, but only 10 or 11 identification points are marked on each curve. The L9MIKE subroutine is written in Fortran IV language.


This appendix presents the computer printout listing of the L9MIKE subroutine used for controlling the Calcomp plotter.



```

/JOB GO,TIME=10      L9MIKE CALCOMP PLOTTER ROUTINE
/FILE DISK=(3,PTPTPT),VOL=RAXFL1,DISP=(OLD,KEEP)
/FILE DISK=(2,NREC=960,OFFWAL),VOL=RAXFL1,DISP=(NEW,DELETE)
/FILE DISK=(1,NREC=960,TEMPRY),VOL=RAXFL1,DISP=(NEW,DELETE)
  READ(5)NVAR
  NVAR=NVAR+1
  CALL PLOTTT(NVAR)
  STOP
END
SUBROUTINE PLOTTT(NVAR)
  DIMENSION IBUF(1000),NYY(21),YY(150),X(2002),NAME(15),
  1X(10),Y(10),NN(4),Z(5),XXMI(21),XXMA(21)
  DIMENSION NNAME(15)
  DIMENSION NMME(8)
  ICOMP='P400'
  CALL STARTK(ICOMP,99,1,2)
  CALL PLOTS(IBUF,1000)
  NX=1
  READ(5)IG0ZZ,KKKK
  IF(IG0ZZ-5)1207,1205,1207
1205 READ(5)NZ
  DO 1650 I=1,NZ
1650 READ(5)Z(I)
  READ(5)IFST,IINC,A1,B1
  IJK=0
  NVRR=NVAR-1
  DO 1210 IJ=IFST,NVRR,IINC
  IJK=IJK+1
  IKJ=IJ+IINC-1
  DO 1210 IJSY=IJ,IKJ
  XXMI(IJSY)=Z(IJK)*A1
  XXMA(IJSY)=Z(IJK)*B1
1210 CONTINUE
1207 CONTINUE
  READ(5)ISCLE
  IF(ISCLE-1)9031,9032,9031
9032 READ(5)XLN,VLN


```



```

9031 CONTINUE
2 IF(ISCLE-1)914,914,913
913 READ(5)NXX
914 READ(5)NY
  ITWO=1
  DO 10 I=1,NY
10 READ(5)NYY(I)
  READ(5,5)(NNAME(I),I=1,15)
  READ(5,5)(NAME(I),I=1,15)
  READ(5,5)(NNME(I),I=1,8)
5  FORMAT(15A4)
  AMAX=-1.E68
  AMIN=1.E68
  AAMAX=-1.E68
  AAMIN=1.E68
  INTEQ=0
  KONE=KONE+1
  CALL PLOT(3.,-15.,-3)
  CALL PLOT(0.,.5,-3)
  JJJ=NYY(I)
  REWIND 3
  I=0
333 I=I+1
  READ(3)(YY(J),J=1,NVAR)
  IF(YY(I)-99999.)334,335,334
334 IF(IGOZZ-5)1230,1610,1230
1610 IF(ISCLE-1)1820,1820,1810
1810 X10=YY(NXX+1)
  GO TO 1830
1820 X10=YY(NX)
1830 IF(X10-AAMAX)1850,1850,1840
1840 AAMAX=X10
1850 IF(X10-AAMIN)1860,1870,1870
1860 AAMIN=X10
1870 CONTINUE
  IF(YY(I)-XXMI(JJJ)+.0001)1215,1220,1220
1215 I=I-1


```



```

GO TO 819
1220 IF(YY(1)-XXMA(JJJ))1230,1230,1225
1225 I=I-1
GO TO 819
1230 Y(I)=YY(JJJ+1)
IF(ISCLE-1)20,20,912
912 X(I)=YY(NXX+1)
GO TO 799
20 X(I)=YY(NX)
799 IF(ISCLE-1)333,819,333
819 DO 821 I=2,NVAR
DO 851 IJ=1,NY
NNY=NY(IJ)
IF(IGZZ-5)1936,9221,1936
9221 CONTINUE
IF(YY(1)-XXMA(NNY))1934,1934,821
1934 IF(YY(1)-XXMI(NNY)+.0001)821,1936,1936
1936 CONTINUE
IF(I1-1-NYY(IJ))851,852,851
852 IF(AMAX-YY(I1))822,823,823
822 AMAX=YY(I1)
823 IF(AMIN-YY(I1))851,851,824
824 AMIN=YY(I1)
GO TO 821
851 CONTINUE
821 CONTINUE
1935 IF(ITWO-2)333,1265,333
335 NOB=I-1
IINN=NOB/10
IF(IINN)8112,8112,8113
8112 IINN=1
8113 CONTINUE
IF(ISCLE-1)826,798,826
798 YY(1)=AMIN
YY(2)=AMAX
CALL SCALE(YY,YLN,2,1)
Y(NOB+1)=YY(3)


```



```

Y(NOB+2)=YY(4)
GO TO 827
      826 CALL SCALE(Y, YLN, NOB, 1)
      827 IF(IGDZ-5)1890,1880,1890
1880 YY(1)=AAMIN
      YY(2)=AAMAX
      CALL SCALE(YY, XLN, 2, 1)
      X(NOB+1)=YY(3)
      X(NOB+2)=YY(4)
      GO TO 1900
      1890 CALL SCALE(X, XLN, NOB, 1)
1900 CONTINUE
      XXX1=X(NOB+1)
      XXX2=X(NOB+2)
      YYY1=Y(NOB+1)
      YYY2=Y(NOB+2)
      CALL AXIS(0., 0., VNAME, -60, XLN, 0., X(NOB+1), X(NOB+2))
      CALL AXIS(0., 0., NNME(1), 32, YLN, 90., Y(NOB+1), Y(NOB+2))
      CALL LINE(X, Y, NOB, 1, IINN, INTEQ)
      CALL LINE(X(NOB), Y(NOB), 1, 1, 1, INTEQ)
      IDC8= ' '
      XX=-.5
      YW=4.
      YYY=0.
      XXX=0.
      IBCD='VAR '
      AA=NY(1)
      CALL SYMBOL(.5, YLN, .14, NAME, 0., 60)
      IF(KKKK-1)2010,2020,2010
2020 READ(5,5)(NAME(I), I=1, 15)
      CALL SYMBOL(.5, YLN, .25, .14, NAME, 0., 60)
2010 CONTINUE
      IF(1SCLE-2)1014,1013,1014
1013 AB=NX
      CALL SYMBOL(4., .5, .14, IBCD, 0., 4)
      CALL NUMBER(999., 999., .14, AB, 0., -1)
1014 CONTINUE


```

```

CALL SYMBOL(XX,YM,.14,IBCD,90.,4)
CALL NUMBER(999.,999.,.14,AA,90.,-1)
CALL SYMBOL(999.,999.,.14,IDCB,90.,3)
CALL SYMBOL(999.,999.,.14,INTEQ,90.,-1)
IF(NY-1)9382,9882,9382
9382 CONTINUE
AMAX=-1.E68
AMIN=1.E68
DO 50 JJ=2,NY
XX=XX-1.
JJ=NY(JJ)+1
REWIND 3
INTEQ=INTEQ+1
AA=JJJ-1
CALL SYMBOL(XX,YM,.14,IBCD,90.,4)
CALL NUMBER(999.,999.,.14,AA,90.,-1)
CALL SYMBOL(999.,999.,.14,IDCB,90.,3)
CALL SYMBOL(999.,999.,.14,INTEQ,90.,-1)
ITWO=2
NOB=0
1265 NOB=NOB+1
READ(3)(YY(J),J=1,NVAR)
IF(YY(1)-9999.)1300,1320,1300
1300 IF(IG0Z2-5)1275,1630,1275
1630 IF(YY(1)-XXMI(JJJ-1)+.0001)1255,1260,1260
1255 NOB=NOB-1
GO TO 819
1260 IF(YY(1)-XXMA(JJJ-1))1275,1275,1270
1270 NOB=NOB-1
GO TO 819
1275 Y(NOB)=YY(JJJ)
IF(ISCLE-1)1280,1280,1285
1285 X(NOB)=YY(NXX+1)
IF(ISCLE-1)1265,1310,1265
1280 X(NOB)=YY(NX)
IF(ISCLE-1)1265,819,1265
1310 GO TO 819


```



```

1320 NOB=NOB-1
      X(NOB+1)=XXXX1
      Y(NOB+2)=XXXX2
      Y(NOB+1)=YYYY1
      Y(NOB+2)=YYY2
      IINN=NOB/10
      IF(IINN)1240,1240,1250
1240 IINN=1
1250 CONTINUE
      YYY=YYY-1.
      XXX=XXX+1.
      IF(ISCLE-1)829,50,829
829  CALL PLOT( YYY,0.,-3)
      CALL SCALE(Y,VLN,NOB,1)
      CALL AXIS(0,0.,NN(1),6,XLN,90.,Y(NOB+1),Y(NOB+2))
      CALL PLOT(XXX,0.,-3)
50   CALL LINE(X,Y,NOB,1,IINN,INTEQ)
      CALL LINE(X(NOB),Y(NOB),1,1,1,INTEQ)
9882 CONTINUE
      CALL PLOT(16.,0.,-3)
      READ(5)ISCLE
      REWIND 3
      IF(ISCLE-4)2,70,70
70   CALL ENDIT
      CALL PLOTTR(2)
      RETURN
      END
      SUBROUTINE PLOTTR(IDS)
      DIMENSION ISPOOL(31), IC(10), IOUT(118), IH(6), IGET(8)
      REWIND IDS
      IC(1)=20987968
      IC(2)=37765184
      IC(3)=71319616
      IC(4)=138428480
      IC(5)=272646208
      IC(6)=339755072
      IC(7)=406863936


```



```

IC(8)=541081664
IC(9)=608190528
IC(10)=675299392
IDOL1=1530937408
IH(1)=-489171242
IH(2)=-750729019
IH(3)=-1044068903
IH(4)=1088013763
IH(5)=-690371520
IH(6)=-909847069
LIM=8
IBLK=31
READ (IDS) ISPOOL
IHOLD=ISPOOL(7)
DO 1 I=1,6
  IF (ISPOOL(1)-IH(I)) 14,1,14
1 CONTINUE
  NREC=ISPOOL(8)/(256*256)
  IF (NREC) 14,14,2
2 ISPOOL(8)=ISPOOL(8)-256*256*NREC
  INAME=ISPOOL(8)/256
  ISPOOL(8)=ISPOOL(8)-256*INAME
  M=1
  N=1
  I=9
  GO TO 4
3 I=1
  N=2
  DO 11 J=2,NREC
    READ (IDS) ISPOOL
    DO 10 K=1,IBLK
      CALL TESTU (ISPOOL(K), IGET(1))
      I1=IGET(1)
19 IF (I1) 14,14,5
      5 IF (I1-10) 6,6,14
      6 IOUT(M)=IC(I1)


```




```

15 M=M+1
   IF (M-118) 9,9,7
   7 WRITE (6,100) IDOL1,IDOL1,IOUT
     M=1
     9 CONTINUE
    10 CONTINUE
    GO TO (3,11),N
    11 CONTINUE
    DO 12 I=M,118
    12 IOUT(1)=IC(2)
    WRITE (6,100) IDOL1,IDOL1,IOUT
    13 STOP
    14 WRITE (6,200)
      STOP
    100 FORMAT (120A1)
    200 FORMAT (' DATA SET HAS AN INVALID HEADER OR ID')
      END
/BAP
TESTED START 0
      USING *,15
      STM 14,12,12(13)
      L 10,0(1)
      L 7,0(10)
      L 9,4(1)
      LA 11,8
      SR 6,6
      SLDL 6,4
      ST 6,0(9)
      LA 9,4(9)
      BCT 11,A
      LM 14,12,12(13)
      BCR 15,14
      END
/ DATA
/END

```

APPENDIX C



APPENDIX C

LEAST SQUARES POLYNOMIAL CURVE FITTING PROGRAM


A computer program utilizing the method of least squares for determining a polynomial approximation of tabular data is presented in this appendix. The program is written in Fortran IV language and the least squares portion is a part of a library of standard scientific subroutines. The program is named PC05MB and it will fit 2 through 100 points with a polynomial of degree 1 through 11. For this program, the standard error of estimate is defined as:

$$\text{Standard error of estimate} = \left[\frac{\sum_{i=1}^m (G^i - G_{\text{est.}}^i)^2}{m - (n+1)} \right]^{1/2}$$

In the equation for the standard error of estimate, m represents the total number of observations and n represents the degree of the approximating polynomial.

Table C.1 displays the polynomial coefficients and the curve fitting data for the functions G_1 , G_2 , G_3 , and G_4 in the interval $0.10000 \leq X \leq 0.46531$.


Table C.2 displays the polynomial coefficients and the curve fitting data for the functions G_1 , G_2 , G_3 , and G_4 in the interval $0.46531 \leq X \leq 1.0000$.



```

/JOB GO      PC05MB LEAST SQUARES POLYNOMIAL FIT
/FILE DISK=(3,KEEPIT),VOL=RAXFLL,DISP=(OLD,KEEP)
        DIMENSION YYY(20)
        DIMENSION A(15),B(15),S(15),G(15),U(15)
        DIMENSION Q(1600),P(1600),X(1600),Y(1600),C(1600)
        WRITE(6,1)
      1 FORMAT(' WHAT ARE THE N AND NDM OF THE DATA')
        READ(9)N,NDIM
        IXXX=N
      790 WRITE(6,2)
      2 FORMAT(' WHICH G VARIABLE DO YOU WISH TO USE?')
        READ(9)KK
        Z=0
        O=1
        K=12
        N=N+1
        IF(N-11)55,55,576
      55 CONTINUE
      70 T7=Z
        T8=Z
        W7=Z
        I=1
      54 CONTINUE
        READ(3)X(I),(YYY(J),J=1,NDIM)
        IF(X(I)-99999)60,311,60
      60 CONTINUE
        Y(I)=YYY(KK)
        T7=W7+X(I)
        T7=T7+Y(I)
        T8=T8+Y(I)**2
        I=I+1
        GO TO 54
      311 M=I-1
        T9=(M*T8-T7**2)/(M**2-M)
        IF(NNN-1)740,730,740
      740 CONTINUE
        WRITE(6,316)


```



```

316 FORMAT(/, L E A S T - S Q U A R E S P O L Y N O M I A L S',/)
WRITE(6,320)M
320 FORMAT('      NUMBER OF POINTS =',I12)
AMEAN=W7/M
WRITE(6,322)AMEAN
322 FORMAT('      MEAN VALUE OF X =',E12.5)
YMEAN=T7/M
WRITE(6,324)YMEAN
324 FORMAT('      MEAN VALUE OF Y =',E12.5)
STDE=SQR(T19)
WRITE(6,326)STDE
326 FORMAT('      STD ERROR OF G =',E12.5)
WRITE(6,330)
330 FORMAT(/, NOTE. . . CODE FOR 'WHAT NEXT?', IS',/,9X,
1'0 = STOP PROGRAM',/,9X,1'1 = COEFFICIENTS ONLY',/,9X,
2'2 = ENTIRE SUMMARY',/,9X,3'3 = FIT NEXT HIGHER DEGREE',/)
730 CONTINUE
DO 352 I=1,M
P(I)=Z
Q(I)=0
352 CONTINUE
DO 362 I=1,I1
A(I)=Z
B(I)=Z
S(I)=Z
362 CONTINUE
E1=Z
F1=Z
W1=W
N4=K
I=1
K1=2
IF(N)378,380,378
378 K1=N4
380 W=Z
DO 386 L=1,M
W=W+Y(L)*Q(L)


```

```

386 CONTINUE
S(I)=W/W1
IF(I-N4)392,428,428
392 EI=Z
DO 398 L=1,M
EI=E1+X(L)*Q(L)*Q(L)
398 CONTINUE
EI=E1/W1
A(I+1)=EI
W=Z
DO 416 L=1,M
V=(X(L)-EI)*Q(L)-F1*P(L)
P(L)=Q(L)
Q(L)=V
W=W+V*V
416 CONTINUE
F1=W/W1
B(I+2)=F1
W1=W
I=I+1
GO TO 380
428 DO 432 L=2,11
G(L)=Z
432 CONTINUE
G(I)=0
DO 464 J=1,N
S1=Z
DO 448 L=1,N
IF(L-1)444,446,444
444 G(L)=G(L)-A(L)*G(L-1)-B(L)*G(L-2)
446 S1=S1+S(L)*G(L)
448 CONTINUE
U(J)=S1
L=N
DO 460 I2=2,N
G(L)=G(L-1)
L=L-1


```



```

460 CONTINUE
462 G(1)=Z
464 CONTINUE
T=Z
DO 488 L=1,M
  C(L)=Z
  J=N
DO 482 I2=1,N
  C(L)=C(L)*X(L)+U(J)
  J=J-1
482 CONTINUE
  T3=Y(L)-C(L)
  T=T+T3**2
488 CONTINUE
492 T5=0
  IF(M-N)496,492,496
  GO TO 498
496 T5=T/(M-N)
498 Q7=1-(T5/T9)
  NN=N-1
  WRITE(6,502)NN,Q7
502 FORMAT(/,' POLYFIT OF DEGREE',I3,' INDEX OF DETERM =',F10.4,
  1//,'WHAT NEXT ')
  READ(9)IR
512 IF(IR)514,628,514
514 IF(IR-3)516,564,516
516 WRITE(6,517)
517 FORMAT(/,' IX, TERM',4X,' COEFFICIENT',/)
520 DO 526 J=1,N
  I2=J-1
  WRITE(6,524)I2,U(J)
524 FORMAT(115,E15.5)
526 CONTINUE
  READ(5,829)
829 FORMAT('
  WRITE(6,829)
  IF(IR-1)531,558,531
  )

```



```

531 WRITE(6,530)
530 FORMAT(/'6X','X-ACTUAL',6X,'G-ACTUAL',8X,'G-CALC',7X,'DIFF',8X,
1,'PCT-DIFF',/)
DO 550 L=1,M
Q8=Y(L)-C(L)
IF(C(L))544,548,544
548 WRITE(6,540)X(L),Y(L),C(L),Q8
540 FORMAT(4E15.6,4X,'INFINITE')
GO TO 550
544 CL=100.*Q8/C(L)
547 WRITE(6,547)X(L),Y(L),C(L),Q8,CL
547 FORMAT(5E14.6)
550 CONTINUE
ST5=SQRT(IT5)
WRITE(6,554)ST5
554 FORMAT(/' ' STD ERROR OF ESTIMATE FOR G =' ,F10.4/)
IF(K-N)558,628,558
558 WRITE(6,560)
560 FORMAT(' WHAT NEXT?')
READ(9)IR
GO TO 512
564 N=N+1
IF(M-N)616,568,568
568 GO TO 428
570 WRITE(6,572)
572 FORMAT('PROGRAM SIZE LIMIT IS 100 DATA POINTS.')
```




```

GO TO 628
576 WRITE(6,578)
578 FORMAT('ELEVENTH DEGREE IS THE LIMIT')
```



```

GO TO 628
616 NN=N-1
WRITE(6,618)NN
618 FORMAT(' TOO FEW POINTS FOR FITTING DEGREE',I3)
GO TO 628
628 WRITE(6,710)
710 FORMAT(' TYPE 1 IF ANOTHER RUN IS DESIRED')
READ(9)ITONES
```



```
N=IXXX  
REWIND 3  
NNN=1  
IF (IONES-1) 720, 790, 720  
720 STOP  
END  
/DATA  
/END
```





TABLE C-1 CURVE FITTING DATA FOR THE INTERVAL $0.10000 \leq X \leq 0.46531$

G1 ONE-DIMENSIONAL REPRESENTATION FOR RADIAL VELOCITY

TERM	COEFFICIENT	X-ACTUAL	G-ACTUAL	G-CALC	DIFF	PCT-DIFF
0	0.88531E 00	0.10000E 01	0.100017E 01	-0.170708E-03	-0.170679E-01	
1	0.11040E 01	0.100601E 01	0.100615E 01	-0.142097E-03	-0.141229E-01	
2	0.44657E 00	0.101203E 01	0.101215E 01	-0.114441E-03	-0.113067E-01	
		0.101808E 01	0.101817E 01	-0.858307E-04	-0.842989E-02	
		0.102416E 01	0.102422E 01	-6.00815E-04	-5.86610E-02	
		0.103025E 01	0.103028E 01	-3.33786E-04	-3.32375E-02	
		0.103636E 01	0.103637E 01	-8.58307E-05	-8.28185E-03	
		0.104246E 01	0.104262E 01	-1.60543E-04	-3.81973E-02	
		0.104856E 01	0.104862E 01	-6.48770E-04	-8.00008E-02	
		0.105466E 01	0.105469E 01	-3.126839E-03	-0.118168E-01	
		0.106076E 01	0.106095E 01	-1.63078E-03	-0.150180E-01	
		0.106686E 01	0.106689E 01	-2.24113E-03	-0.201689E-01	
		0.107296E 01	0.107337E 01	-4.00543E-04	-0.230693E-01	
		0.107906E 01	0.107910E 01	-2.62260E-03	-0.237015E-01	
		0.108516E 01	0.108589E 01	-7.275612E-03	-0.217326E-01	
		0.109126E 01	0.109118E 01	-8.258446E-03	-0.217326E-01	
		0.109736E 01	0.109721E 01	-1.19209E-03	-0.959033E-02	
		0.110346E 01	0.110302E 01	-0.119209E-03	-0.959033E-02	
		0.110956E 01	0.110925E 01	-0.192642E-03	-0.148386E-01	
		0.111566E 01	0.111549E 01	-0.710487E-03	-0.524379E-01	
		0.112176E 01	0.112130E 01	-0.141335E-02	-0.100024E 00	
		0.112786E 01	0.112725E 01	-0.209808E-04	-0.142482E-02	
		0.113396E 01	0.113364E 01	-0.233364E-02	-0.157672E 00	

TABLE C.1 (CONT'D.)

0.460000E 00 0.148851E 01 0.148763E 01 0.837871E-03 0.596837E-01
 0.465000E 00 0.149344E 01 0.14921E 01 -0.177574E-02 -0.118762E 00

STD ERROR OF ESTIMATE FOR G = 0.0008

G2 ONE-DIMENSIONAL REPRESENTATION FOR TANGENTIAL VELOCITY

TERM	COEFFICIENT
0	0.14366E 01
1	-0.55497E 01
2	0.82897E 02
3	-0.38395E 03
4	0.82938E 03
5	-0.69174E 03

X-ACTUAL	G-ACTUAL	G-CALC	DIFF	PCT-DIFF
0.100000E 00	0.100000E 01	0.100270E 01	-0.270081E-02	-0.269353E 00
0.105000E 00	0.994412E 00	0.995365E 00	-0.952661E-03	-0.957097E-01
0.110000E 00	0.988759E 00	0.988469E 00	0.289798E-03	0.293178E-01
0.115000E 00	0.983039E 00	0.981934E 00	0.110513E-02	0.112546E 00
0.120000E 00	0.977251E 00	0.975686E 00	0.156546E-02	0.160447E 00
0.125000E 00	0.971394E 00	0.969657E 00	0.173712E-02	0.179148E 00
0.130000E 00	0.965466E 00	0.963787E 00	0.167972E-02	0.174283E 00
0.140000E 00	0.953393E 00	0.952306E 00	0.108695E-02	0.114139E 00
0.150000E 00	0.941019E 00	0.940871E 00	0.147939E-03	0.157236E-01




TABLE C.1 (CONT'D.)

0.16000E 00	0.928332E 00	0.929190E 00	-0.858247E-03	-0.923651E-01
0.17000E 00	0.915317E 00	0.917046E 00	-0.172901E-02	-0.188541E 00
0.18000E 00	0.888241E 00	0.890827E 00	-0.258547E-02	-0.290233E 00
0.19000E 00	0.859655E 00	0.861656E 00	-0.200075E-02	-0.232198E 00
0.20000E 00	0.829392E 00	0.829637E 00	-0.244737E-03	-0.294992E-01
0.21000E 00	0.797253E 00	0.795271E 00	0.198203E-02	0.249227E 00
0.22000E 00	0.726288E 00	0.721877E 00	0.441188E-02	0.611168E 00
0.23000E 00	0.643846E 00	0.643291E 00	0.554621E-03	0.862162E-01
0.24000E 00	0.544596E 00	0.550659E 00	-0.606215E-02	-0.110089E 01
0.25000E 00	0.416225E 00	0.415973E 00	0.252247E-03	0.606402E-01
0.26000E 00	0.194148E 00	0.185334E 00	0.106146E-01	0.578348E 01
0.27000E 00	0.142546E 00	0.143481E 00	-0.935674E-03	-0.652123E 00
0.28000E 00	0.931352E-01	0.100297E 00	-0.716174E-02	-0.714053E 01
0.29000E 00	0.535923E-01	0.537481E-01	-0.155836E-03	-0.289938E 00

STD ERROR OF ESTIMATE FOR G = 0.0039




TABLE C.1 (CONT'D.)

G3 ONE-DIMENSIONAL REPRESENTATION FOR AXIAL VELOCITY

TERM	COEFFICIENT	X-ACTUAL	G-ACTUAL	G-CALC	DIFF	PCI-DIFF
0	0.10999E 01	0.10000E 01	0.10000E 01	0.10000E 01	-0.287056E-03	-0.286974E-01
1	-0.91970E 00	0.99560E 00	0.99560E 00	0.99560E 00	-0.223279E-03	-0.224215E-01
2	0.13199E 00	0.99120E 00	0.99120E 00	0.991367E 00	-0.163674E-03	-0.165100E-01
		0.986809E 00	0.986917E 00	0.986917E 00	-0.108302E-03	-0.109737E-01
		0.982417E 00	0.982474E 00	0.982474E 00	-0.571609E-04	-0.581805E-02
		0.978027E 00	0.978037E 00	0.978037E 00	-0.100732E-04	-0.102994E-02
		0.973640E 00	0.973607E 00	0.973607E 00	0.329614E-04	0.338349E-02
		0.964874E 00	0.964766E 00	0.964766E 00	0.108242E-03	0.112195E-01
		0.956121E 00	0.955952E 00	0.955952E 00	0.169098E-03	0.176890E-01
		0.947381E 00	0.947164E 00	0.947164E 00	0.216544E-03	0.228623E-01
		0.938654E 00	0.938403E 00	0.938403E 00	0.251114E-03	0.267598E-01
		0.921244E 00	0.920899E 00	0.920899E 00	0.285089E-03	0.309557E-01
		0.903898E 00	0.903621E 00	0.903621E 00	0.277400E-03	0.306587E-01
		0.886622E 00	0.886388E 00	0.886388E 00	0.233769E-03	0.263733E-01
		0.869421E 00	0.869261E 00	0.869261E 00	0.159800E-03	0.183834E-01
		0.853267E 00	0.853324E 00	0.853324E 00	-0.572205E-04	-0.685009E-02
		0.801477E 00	0.801809E 00	0.801809E 00	-0.331938E-03	-0.41387E-01
		0.768092E 00	0.768717E 00	0.768717E 00	-0.625014E-03	-0.813062E-01
		0.735170E 00	0.736047E 00	0.736047E 00	-0.876963E-03	-0.119145E 00
		0.703835E 00	0.703799E 00	0.703799E 00	0.363588E-04	0.516608E-02
		0.700963E 00	0.699798E 00	0.699798E 00	0.116533E-02	0.166524E 00




TABLE C.1 (CONT'D.)

0.460000E 00 0.696333E 00 0.695803E 00 0.530660E-03 0.762659E-01
 0.465000E 00 0.691151E 00 0.691815E 00 -0.663817E-03 -0.959329E-01

STD ERROR OF ESTIMATE FOR G = 0.0004

GA ONE-DIMENSIONAL REPRESENTATION FOR PRESSURE

TERM COEFFICIENT

0 0.40740E 00
 1 0.10314E 01
 2 -0.10941E 01

X-ACTUAL	G-ACTUAL	G-CALC	DIFF	PCT-DIFF
0.100000E 00	0.500000E 00	0.499600E 00	0.400126E-03	0.800893E-01
0.105000E 00	0.503937E 00	0.503635E 00	0.301898E-03	0.599437E-01
0.110000E 00	0.507828E 00	0.507616E 00	0.212133E-03	0.417900E-01
0.115000E 00	0.511673E 00	0.511542E 00	0.130534E-03	0.255178E-01
0.120000E 00	0.515470E 00	0.515414E 00	0.565648E-04	0.109746E-01
0.125000E 00	0.519221E 00	0.519231E 00	-0.995398E-05	-0.191706E-02
0.130000E 00	0.522923E 00	0.522993E 00	-0.692010E-04	-0.132317E-01
0.135000E 00	0.526185E 00	0.526353E 00	-0.167310E-03	-0.315470E-01
0.140000E 00	0.530185E 00	0.530353E 00	-0.240147E-03	-0.46791E-01
0.145000E 00	0.534253E 00	0.534416E 00	-0.289857E-03	-0.532419E-01
0.150000E 00	0.544126E 00	0.544119E 00	0.751119E-05	0.578721E-01
0.155000E 00	0.550800E 00	0.550800E 00	0.000000E 00	0.000000E 00
0.160000E 00	0.563547E 00	0.563870E 00	-0.332057E-03	-0.572929E-01
0.165000E 00	0.575475E 00	0.575745E 00	-0.270069E-03	-0.469077E-01




TABLE C.1 (CONT'D.)

0.230000E 00	0.586570E 00	0.586745E 00	-0.175416E-03	-0.298965E-01
0.250000E 00	0.596816E 00	0.596870E 00	-0.541806E-04	-0.307746E-02
0.290000E 00	0.614707E 00	0.614493E 00	0.213504E-03	0.347447E-01
0.330000E 00	0.629047E 00	0.628616E 00	0.431240E-03	0.686814E-01
0.370000E 00	0.639749E 00	0.639237E 00	0.512242E-03	0.801334E-01
0.410000E 00	0.646739E 00	0.646357E 00	0.381649E-03	0.590461E-01
0.450000E 00	0.649924E 00	0.649976E 00	-0.526309E-04	-0.809735E-02
0.455000E 00	0.650032E 00	0.650182E 00	-0.150859E-03	-0.232026E-01
0.460000E 00	0.650120E 00	0.650334E 00	-0.214458E-03	-0.329765E-01
0.465000E 00	0.650137E 00	0.650431E 00	-0.293434E-03	-0.451137E-01

STD ERROR OF ESTIMATE FOR G = 0.0003




TABLE C.2 CURVE FITTING DATA FOR THE INTERVAL 0.46531<X<1.0000

G1 ONE-DIMENSIONAL REPRESENTATION FOR RADIAL VELOCITY

TERM	COEFFICIENT	X-ACTUAL	G-ACTUAL	G-CALC	DIFF	PCT-DIFF
0	0.15338E 01	0.149004E 01	0.148913E 01	0.913620E-03	0.613526E-01	
1	-0.29709E 00	0.149063E 01	0.148967E 01	0.965118E-03	0.647876E-01	
2	0.43202E 00	0.149105E 01	0.149022E 01	0.831604E-03	0.558440E-01	
		0.149158E 01	0.149080E 01	0.778198E-03	0.522000E-01	
		0.149214E 01	0.149140E 01	0.739098E-03	0.495372E-01	
		0.149267E 01	0.149202E 01	0.641823E-03	0.430169E-01	
		0.149324E 01	0.149267E 01	0.573158E-03	0.383983E-01	
		0.149350E 01	0.149402E 01	-0.522614E-03	-0.349804E-01	
		0.149456E 01	0.149546E 01	-0.901222E-03	-0.602640E-01	
		0.149591E 01	0.149698E 01	-0.107670E-02	-0.719246E-01	
		0.149747E 01	0.149859E 01	-0.112724E-02	-0.752200E-01	
		0.150102E 01	0.150208E 01	-0.105572E-02	-0.702839E-01	
		0.150485E 01	0.150590E 01	-0.104944E-02	-0.696620E-01	
		0.150905E 01	0.151008E 01	-0.102806E-02	-0.680801E-01	
		0.151367E 01	0.151459E 01	-0.923137E-03	-0.609508E-01	
		0.152442E 01	0.152467E 01	-0.246048E-03	-0.161378E-01	
		0.153632E 01	0.153612E 01	0.196457E-03	0.127891E-01	
		0.154973E 01	0.154896E 01	0.763893E-03	0.493164E-01	
		0.156445E 01	0.156318E 01	0.126648E-02	0.810192E-01	
		0.159709E 01	0.159577E 01	0.131130E-02	0.821733E-01	
		0.163463E 01	0.163389E 01	0.732422E-03	0.448267E-01	




TABLE C.2 (CONT'D.)

0.951484E 00	0.164308E 01	0.164227E 01	0.811623E-03	0.493598E-01
0.967656E 00	0.165142E 01	0.165088E 01	0.546455E-03	0.331009E-01
0.983828E 00	0.165956E 01	0.165971E 01	-0.149727E-03	-0.902128E-02
0.100000E 01	0.166809E 01	0.166876E 01	-0.667372E-03	-0.400040E-01
0.100000E 01	0.166837E 01	0.166876E 01	-0.389099E-03	-0.233166E-01
0.100000E 01	0.166845E 01	0.166876E 01	-0.314713E-03	-0.188590E-01
0.100000E 01	0.166808E 01	0.166876E 01	-0.685692E-03	-0.410898E-01
0.100000E 01	0.166804E 01	0.166876E 01	-0.719070E-03	-0.430900E-01

STD ERROR OF ESTIMATE FOR G = 0.0009

G2 ONE-DIMENSIONAL REPRESENTATION FOR TANGENTIAL VELOCITY

TERM	COEFFICIENT	G-CALC	DIFF	PCT-DIFF
0	-0.36184E 02	0.772400E-01	-0.292921E-01	-0.379234E 02
1	0.24104E 03	0.106171E 00	0.114977E-03	0.108295E 00
2	-0.63639E 03	0.133530E 00	0.784856E-02	0.587777E 01
3	0.83823E 03	0.159332E 00	0.111511E-01	0.699866E 01
4	-0.54694E 03	0.183701E 00	0.102249E-01	0.556609E 01
5	0.14125E 03	0.206635E 00	0.892752E-02	0.432044E 01
X-ACTUAL	G-ACTUAL			
0.465312E 00	0.479479E-01			
0.470312E 00	0.106286E 00			
0.475312E 00	0.141378E 00			
0.480312E 00	0.170483E 00			
0.485312E 00	0.193925E 00			
0.490312E 00	0.215562E 00			




TABLE C.2 (CONT'D.)

0.495312E 00	0.235846E 00	0.228363E 00	0.668252E-02	0.292627E 01
0.505312E 00	0.271852E 00	0.268158E 00	0.369370E-02	0.137743E 01
0.515312E 00	0.303545E 00	0.303665E 00	-0.119984E-03	-0.395120E-01
0.525312E 00	0.331882E 00	0.335373E 00	-0.349081E-02	-0.104087E 01
0.535312E 00	0.357847E 00	0.363937E 00	-0.609070E-02	-0.167356E 01
0.545312E 00	0.404325E 00	0.413040E 00	-0.871551E-02	-0.211009E 01
0.555312E 00	0.446494E 00	0.454086E 00	-0.759202E-02	-0.167193E 01
0.565312E 00	0.483214E 00	0.489456E 00	-0.424224E-02	-0.866725E 00
0.575312E 00	0.521174E 00	0.521332E 00	-0.157356E-03	-0.301835E-01
0.585312E 00	0.568157E 00	0.588185E 00	0.597239E-02	0.102339E 01
0.595312E 00	0.645593E 00	0.637848E 00	0.774491E-02	0.121422E 01
0.605312E 00	0.708313E 00	0.696426E 00	0.388664E-02	0.558083E 00
0.615312E 00	0.751559E 00	0.743030E 00	-0.274372E-02	-0.363743E 00
0.625312E 00	0.846603E 00	0.857346E 00	-0.107429E-01	-0.125384E 01
0.635312E 00	0.933529E 00	0.933289E 00	0.240147E-03	0.257313E-01
0.645312E 00	0.954668E 00	0.947662E 00	0.300568E-02	0.317168E 00
0.655312E 00	0.967415E 00	0.963150E 00	0.426485E-02	0.442800E 00
0.665312E 00	0.983073E 00	0.980560E 00	-0.251234E-02	-0.256214E 00
0.675312E 00	0.998268E 00	0.100145E 01	-0.218183E-02	-0.217867E 00
0.685312E 00	0.999801E 00	0.100145E 01	-0.164884E-02	-0.164846E 00
0.695312E 00	0.999942E 00	0.100145E 01	-0.150752E-02	-0.150534E 00
0.705312E 00	0.999237E 00	0.100145E 01	-0.221252E-02	-0.220932E 00
0.715312E 00	0.999174E 00	0.100145E 01	-0.227559E-02	-0.227229E 00

STD ERROR OF ESTIMATE FOR G = 0.0088




TABLE C.2 (CONT'D.)

G3 ONE-DIMENSIONAL REPRESENTATION FOR AXIAL VELOCITY

TERM	COEFFICIENT	X-ACTUAL	G-ACTUAL	G-CALC	DIFF	PCT-DIFF
0	0.14358E 01	0.689105E 00	0.689145E 00	-0.407696E-04	-0.591596E-02	
1	-0.17466E 01	0.681928E 00	0.681856E 00	0.717640E-04	0.105248E-01	
2	0.30862E 00	0.674674E 00	0.674583E 00	0.908375E-04	0.134657E-01	
		0.667468E 00	0.667325E 00	0.143349E-03	0.214812E-01	
		0.660281E 00	0.660082E 00	0.199800E-03	0.301598E-01	
		0.653075E 00	0.652855E 00	0.219882E-03	0.336800E-01	
		0.645894E 00	0.645643E 00	0.250876E-03	0.388568E-01	
		0.631077E 00	0.631265E 00	-0.187933E-03	-0.297709E-01	
		0.616679E 00	0.616950E 00	-0.270128E-03	-0.437845E-01	
		0.602428E 00	0.602696E 00	-0.267088E-03	-0.443156E-01	
		0.588290E 00	0.588503E 00	-0.213563E-03	-0.362893E-01	
		0.568165E 00	0.568344E 00	-0.138700E-03	-0.247544E-01	
		0.532268E 00	0.532351E 00	-0.833273E-04	-0.156527E-01	
		0.504590E 00	0.504645E 00	-0.554323E-04	-0.109844E-01	
		0.477169E 00	0.477186E 00	-0.174642E-04	-0.365982E-02	
		0.423108E 00	0.423019E 00	0.976920E-04	0.230945E-01	
		0.369946E 00	0.369821E 00	0.125408E-03	0.339105E-01	
		0.317819E 00	0.317618E 00	0.200808E-03	0.632230E-01	
		0.266677E 00	0.266484E 00	0.272870E-03	0.102427E 00	
		0.166948E 00	0.166939E 00	0.971556E-05	0.581983E-02	
		0.713677E-01	0.714236E-01	-0.548959E-04	-0.768607E-01	




TABLE C.2 (CONT'D.)

0.951484E 00	0.523065E-01	0.525951E-01	-0.288595E-03	-0.548709E 00
0.967636E 00	0.334678E-01	0.339279E-01	-0.460166E-03	-0.135631E 01
0.983828E 00	0.157426E-01	0.154219E-01	0.320721E-03	0.207965E 01
0.100000E 01	-0.263558E-02	-0.292110E-02	0.282528E-03	-0.967194E 01
0.100000E 01	-0.324369E-02	-0.292110E-02	-0.322583E-03	0.110432E 02
0.100000E 01	-0.340454E-02	-0.292110E-02	-0.483434E-03	0.165497E 02
0.100000E 01	-0.260535E-02	-0.292110E-02	0.315750E-03	-0.108093E 02
0.100000E 01	-0.253397E-02	-0.292206E-02	0.388088E-03	-0.132813E 02

STD ERROR OF ESTIMATE FOR G = 0.0003

G4 ONE-DIMENSIONAL REPRESENTATION FOR PRESSURE

TERM COEFFICIENT

0 0.31091E 00
 1 0.15504E 01
 2 -0.17556E 01

X-ACTUAL	G-ACTUAL	G-CALC	DIFF	PCT-DIFF
0.465312E 00	0.650129E 00	0.652227E 00	-0.209773E-02	-0.321625E 00
0.470312E 00	0.650045E 00	0.651766E 00	-0.172091E-02	-0.264037E 00
0.475312E 00	0.649853E 00	0.651217E 00	-0.136465E-02	-0.209553E 00
0.480312E 00	0.649554E 00	0.650581E 00	-0.102729E-02	-0.157903E 00
0.485312E 00	0.649149E 00	0.649857E 00	-0.708163E-03	-0.108972E 00
0.490312E 00	0.648634E 00	0.649045E 00	-0.411034E-03	-0.633289E-01
0.495312E 00	0.648015E 00	0.648146E 00	-0.130951E-03	-0.202040E-01
0.500312E 00	0.646397E 00	0.646083E 00	0.314116E-03	0.486186E-01






TABLE C.2 (CONT'D.)

0.51312E 00	0.64440E 00	0.64366E 00	0.73242E-03	0.11378E 00
0.52312E 00	0.64202E 00	0.64095E 00	0.10973E-02	0.17122E 00
0.53312E 00	0.63919E 00	0.63778E 00	0.14064E-02	0.22026E 00
0.54312E 00	0.63235E 00	0.63084E 00	0.18474E-02	0.29301E 00
0.55312E 00	0.62387E 00	0.62181E 00	0.20638E-02	0.33190E 00
0.56312E 00	0.61381E 00	0.61172E 00	0.20952E-02	0.34256E 00
0.57312E 00	0.60219E 00	0.60022E 00	0.19687E-02	0.32802E 00
0.58312E 00	0.57433E 00	0.57301E 00	0.13220E-02	0.23072E 00
0.59312E 00	0.54047E 00	0.54018E 00	0.29254E-03	0.54155E-01
0.60312E 00	0.50087E 00	0.50173E 00	-0.86385E-03	-0.17217E 00
0.61312E 00	0.45568E 00	0.45767E 00	-0.19923E-02	-0.43319E 00
0.62312E 00	0.43888E 00	0.43888E 00	-0.38064E-02	-0.10792E 01
0.63312E 00	0.22055E 00	0.22524E 00	-0.31884E-02	-0.14155E 01
0.64312E 00	0.19512E 00	0.19674E 00	-0.16253E-02	-0.82611E 00
0.65312E 00	0.16266E 00	0.16733E 00	-0.10696E-02	-0.63941E 00
0.66312E 00	0.13781E 00	0.13704E 00	-0.80686E-03	0.58933E 00
0.67312E 00	0.10739E 00	0.10756E 00	0.16340E-02	0.15497E 01
0.68312E 00	0.10639E 00	0.10756E 00	0.64849E-03	0.60889E 00
0.69312E 00	0.10613E 00	0.10756E 00	0.37622E-03	0.35574E 00
0.70312E 00	0.10749E 00	0.10756E 00	0.16932E-02	0.16011E 01
0.71312E 00	0.10756E 00	0.10755E 00	0.18112E-02	0.17126E 01

STD ERROR OF ESTIMATE FOR G = 0.0017



APPENDIX D



APPENDIX D


PRESSURE AND VELOCITY PROGRAMS AND NUMERICAL DATA

This appendix presents the computer program utilizing the subroutines PC05E1 and PC05E2 to calculate the pressure and velocity component data for the polynomial equations given in Chapter IV.

Table D.1 displays some sample data for these functions at each R value in the order shown in the following 3X5 matrix:

$$\text{R value} \begin{bmatrix} \text{U}_{.1} & \text{V}_{.1} & \text{W}_{.1} & \text{P}_{.1} & \text{H}_{.1} \\ \text{U}_{.4} & \text{V}_{.4} & \text{W}_{.4} & \text{P}_{.4} & \text{H}_{.4} \\ \text{U}_{.7} & \text{V}_{.7} & \text{W}_{.7} & \text{P}_{.7} & \text{H}_{.7} \end{bmatrix} .$$


The subscripts indicate the value of the Z parameter used to calculate each of the functions U, V, W, P, and H. Only a single page sample of the data is included in this appendix as it would take 76 pages to display it all.



```

/ID PC05,BRINK,PC05,VELOCITY AND PRESSURE Z-PARAMETER
/JO8 GO
/FILE DISK=(3,PTIPT1),VOL=RAXFL1,DISP=(OLD,KEEP)
DIMENSION Y(21),ZZ(10)
J1=0
WRITE(6,9015)
9015 FORMAT(/3H NO,14X,1HX,9X,4HY(1),9X,4HY(2),9X,4HY(3),9X,
14HY(4))
READ(5)XMIN,XMAX,XSTEP,NYYY
X=XMIN
1 CONTINUE
ZZ(1)=.1
ZZ(2)=.4
ZZ(3)=.7
IJK=0
DO 10 I=1,11,5
IJK=IJK+1
Z=ZZ(IJK)
IF(IZ-.1) 11,4,11
11 IF(Z-.4) 2,5,2
2 IF(Z-.7) 3,6,3
3 CONTINUE
4 IF(X-.21491) 7,7,8
5 IF(X-.85964) 7,7,8
6 IF(X-1.5044) 7,7,8
7 Y(1)=1.5338-.29709*(Z/X)+.43202*(Z/X)**2
Y(1+1)=-36.184+241.04*(Z/X)-636.39*(Z/X)**2+838.23*(Z/X)**3-546.94
1*(Z/X)**4+141.25*(Z/X)**5
Y(1+2)=1.435-1.7466*(Z/X)+.30862*(Z/X)**2
Y(1+3)=-31091+1.5504*(Z/X)-1.7556*(Z/X)**2
GO TO 10
8 Y(1)=.88531+1.104*(Z/X)+.44657*(Z/X)**2
Y(1+1)=1.4366-9.5497*(Z/X)+82.897*(Z/X)**2-383.95*(Z/X)**3+829.38*
1(Z/X)**4-691.74*(Z/X)**5
Y(1+2)=1.0909-.9197*(Z/X)+.13199*(Z/X)**2
Y(1+3)=-.4074+1.0314*(Z/X)-1.0941*(Z/X)**2
10 Y(1+4)=Y(1+3)+(Y(1)**2+Y(1+1)**2+Y(1+2)**2)/2.

```



```
J1=J1+1
WRITE(6,9013)J1,X,(Y(I11),I11=1,NYYY)
9013 FORMAT(14,E14.5,4E13.5/(18X,4E13.5))
WRITE(3)X,(Y(I11),I11=1,NYYY)
X=X+XSTEP
IF(X-XMAX)1,1,9014
9014 X=99999.
WRITE(3)X,(Y(I11),I11=1,NYYY)
STOP
END
/ DATA
.1 7. .01 15
/END
```







TABLE D.1 SAMPLE DATA PRESSURE AND VELOCITY FUNCTIONS

NO	X	Y(1)	Y(2)	Y(3)	Y(4)	Y(5)
1	0.10000E 00	0.16687E 01	0.10063E 01	-0.29798E-02	0.10571E 00	0.20044E 01
		0.72578E 01	0.49016E 05	-0.61348E 00	-0.21577E 02	0.12013E 10
		0.20623E 02	0.13188E 07	0.43312E 01	-0.74861E 02	0.86957E 12
2	0.11000E 00	0.16208E 01	0.91386E 00	0.10224E 00	0.26945E 00	0.20057E 01
		0.61661E 01	0.26908E 05	-0.83534E 00	-0.17266E 02	0.36201E 09
		0.17138E 02	0.76886E 06	0.28181E 01	-0.60917E 02	0.29558E 12
3	0.12000E 00	0.15862E 01	0.83405E 00	0.19382E 00	0.38374E 00	0.20084E 01
		0.53437E 01	0.15346E 05	-0.95789E 00	-0.14028E 02	0.11775E 09
		0.14501E 02	0.46686E 06	0.17482E 01	-0.50384E 02	0.10898E 12
4	0.13000E 00	0.15609E 01	0.74713E 00	0.27408E 00	0.46471E 00	0.19996E 01
		0.47098E 01	0.90307E 04	-0.10173E 01	-0.11540E 02	0.40777E 08
		0.12460E 02	0.29327E 06	0.97839E 00	-0.42243E 02	0.43004E 11
5	0.14000E 00	0.15420E 01	0.66631E 00	0.34489E 00	0.52262E 00	0.19930E 01
		0.42117E 01	0.54541E 04	-0.10359E 01	-0.95908E 01	0.14874E 08
		0.10849E 02	0.18961E 06	0.41750E 00	-0.35827E 02	0.17975E 11
6	0.15000E 00	0.15277E 01	0.59726E 00	0.40776E 00	0.56424E 00	0.19927E 01
		0.38137E 01	0.33661E 04	-0.10280E 01	-0.80390E 01	0.56634E 07
		0.95558E 01	0.12564E 06	0.52595E-02	-0.30687E 02	0.78933E 10
7	0.16000E 00	0.15169E 01	0.53646E 00	0.46393E 00	0.59413E 00	0.19961E 01
		0.34912E 01	0.21154E 04	-0.10026E 01	-0.67856E 01	0.22375E 07
		0.85032E 01	0.85054E 05	-0.29919E 00	-0.26509E 02	0.36171E 10
8	0.17000E 00	0.15085E 01	0.47768E 00	0.51438E 00	0.61544E 00	0.19996E 01
		0.32266E 01	0.13497E 04	-0.96602E 00	-0.57607E 01	0.91900E 06
		0.76354E 01	0.58656E 05	-0.52422E 00	-0.23071E 02	0.17203E 10
9	0.18000E 00	0.15021E 01	0.41373E 00	0.55992E 00	0.63039E 00	0.20009E 01
		0.30070E 01	0.87217E 03	-0.92228E 00	-0.49134E 01	0.38034E 06
		0.69121E 01	0.44117E 05	-0.68993E 00	-0.20211E 02	0.84531E 09
10	0.19000E 00	0.14971E 01	0.33850E 00	0.60123E 00	0.64059E 00	0.19993E 01
		0.28231E 01	0.56953E 03	-0.87421E 00	-0.42061E 01	0.16218E 06
		0.63032E 01	0.29241E 05	-0.81081E 00	-0.17807E 02	0.42752E 09
11	0.20000E 00	0.14933E 01	0.24758E 00	0.63885E 00	0.64721E 00	0.19968E 01
		0.26677E 01	0.37513E 03	-0.82372E 00	-0.36107E 01	0.70363E 05
		0.57862E 01	0.21063E 05	-0.89750E 00	-0.15769E 02	0.22182E 09



APPENDIX E



APPENDIX E

PROGRAMS AND NUMERICAL DATA FOR OPTIMUM FUNCTIONS

This appendix presents the computer programs utilized to generate the data for the functions G_2 , G_4 , V , and P as given in Chapter V.

Table E.1 displays the data for the functions G_2 and G_4 at each X value for different values of the swirl parameter S in the order shown in the following 2×5 matrix:


$$X \text{ value} \begin{bmatrix} G_2^{.25} & G_4^{.25} & G_2^{.45} & G_4^{.45} & G_2^{.55} \\ G_4^{.55} & G_2^{.65} & G_4^{.65} & - & - \end{bmatrix}.$$

The superscripts indicate the value of the S parameter used to calculate each of the functions G_2 and G_4 .

Table E.2 displays the data for the functions V and P at each R value for different values of the Z parameter at $S = 0.65$. The data for these functions is displayed in the order shown in the following 2×5 matrix:

$$R \text{ value} \begin{bmatrix} V_{.1} & P_{.1} & V_{.4} & P_{.4} & V_{.7} \\ P_{.7} & - & - & - & - \end{bmatrix}.$$


The subscripts indicate the value of the Z parameter used to calculate each of the functions V and P .



```

/10 PC05,BRINK,PC05,ONE DIMENSIONAL OPTIMIZATION G2 AND G4 WITH S PAR.
/JO8 GO
/FILE DISK=(3,PTPTPT),VOL=RAXFL1,DISP=(OLD,KEEP)
      DIMENSION Y(21),ZZ(110)
      J1=0
      WRITE(6,9015)
9015 FORMAT(/3H NO,14X,1HX,9X,4HY(1),9X,4HY(2),9X,4HY(3),9X,
14HY(4))
      READ(5)XMIN,XMAX,XSTEP,NYYYY
      X=XMIN
      1 CONTINUE
      H=2.
      G=2.6951
      ZZ(1)=-.25
      ZZ(2)=-.45
      ZZ(3)=-.55
      ZZ(4)=-.65
      LJK=0
      DO 10 I=1,7,2
        IJK=IJK+1
        S=ZZ(IJK)
        Y(I)=X*SQRT(S*H)
        J1=J1+1
10      Y(I+1)=H*(1.-(S/2.)*X**2)-G/2.
        WRITE(6,9013)J1,X,{Y(I11)},I11=1,NYYYY)
9013  FORMAT(14,E14.5,4E13.5/(18X,4E13.5))
        WRITE(3)X,{Y(I111)},I111=1,NYYYY)
        X=X+XSTEP
        IF(X-XMAX)1,1,9014
9014  X=99999.
        WRITE(3)X,{Y(I111)},I111=1,NYYYY)
        STOP
      END
/END
/1.1. .01 8
/END

```

```

/ID PC05,BRINK,PC05,OPTIMUM PRESSURE AND VELOCITY Z PARAMETER
/JOB GO
/FILE DISK=(3,PTPTPT),VOL=RAXFL1,DISP=(OLD,KEEP)
      DIMENSION Y(21),ZZ(10)
      J1=0
      WRITE(6,9015)
9015  FORMAT(/3H NO,14X,1HX,9X,4HY(1),9X,4HY(2),9X,4HY(3),9X,
      14HY(4))
      READ(5)XMIN,XMAX,XSTEP,NYYYY
      X=XMIN
      1 CONTINUE
      ZZ(1)=.1
      ZZ(2)=.4
      ZZ(3)=.7
      IJK=0
      DO 10 I=1,5,2
      IJK=IJK+1
      Z=ZZ(IJK)
      H=Z.
      S=.65
      G=2.6951
      Y(1)=(Z/X)*SQRT(S*H)
      10  Y(1+1)=H*(1.-(S/2.)*(Z/X)**2)-G/2.
      J1=J1+1
      WRITE(6,9013)J1,X,(Y(111),I11=1,NYYYY)
9013  FORMAT(14,E14.5,4E13.5/(18X,4E13.5))
      WRITE(3)X,(Y(1111),I111=1,NYYYY)
      X=X+XSTEP
      IF(X-XMAX)1,1,9014
9014  X=99999.
      WRITE(3)X,(Y(1111),I111=1,NYYYY)
      STOP
      END
/DATA
      .1 7. .1 6
/END

```




TABLE E.1 NUMERICAL DATA FOR OPTIMUM ONE-DIMENSIONAL FUNCTIONS

NO	X	Y(1)	Y(2)	Y(3)	Y(4)	Y(5)
1	0.1000E 00	0.70711E-01	0.64995E 00	0.94868E-01	0.64795E 00	0.10488E 00
2	0.11000E 00	0.64695E 00	0.11402E 00	0.64595E 00	0.64701E 00	0.11537E 00
3	0.12000E 00	0.77782E-01	0.64943E 00	0.10436E 00	0.64459E 00	0.12586E 00
4	0.13000E 00	0.64579E 00	0.12542E 00	0.64459E 00	0.64597E 00	0.13634E 00
5	0.14000E 00	0.84853E-01	0.64885E 00	0.11384E 00	0.64485E 00	0.14683E 00
6	0.15000E 00	0.64453E 00	0.13682E 00	0.64309E 00	0.64363E 00	0.15732E 00
7	0.16000E 00	0.91924E-01	0.64822E 00	0.12333E 00	0.64093E 00	0.16781E 00
8	0.17000E 00	0.64316E 00	0.14822E 00	0.64147E 00	0.63945E 00	0.17830E 00
9	0.18000E 00	0.98995E-01	0.64755E 00	0.13282E 00	0.63787E 00	0.18879E 00
10	0.19000E 00	0.64167E 00	0.15962E 00	0.63971E 00	0.63621E 00	0.19927E 00
11	0.20000E 00	0.10607E 00	0.64682E 00	0.14230E 00	0.63445E 00	0.20976E 00
12	0.21000E 00	0.64008E 00	0.17103E 00	0.63783E 00	0.63261E 00	0.22025E 00
13	0.22000E 00	0.11314E 00	0.64605E 00	0.15179E 00	0.63067E 00	0.23074E 00
14	0.23000E 00	0.63837E 00	0.18243E 00	0.63581E 00	0.62864E 00	0.24123E 00
15	0.24000E 00	0.12021E 00	0.64523E 00	0.16128E 00	0.62653E 00	0.25171E 00
16	0.25000E 00	0.63656E 00	0.19383E 00	0.63367E 00	0.62432E 00	0.26220E 00
		0.12728E 00	0.64435E 00	0.17076E 00		
		0.63463E 00	0.20523E 00	0.63139E 00		
		0.13435E 00	0.64342E 00	0.18025E 00		
		0.63260E 00	0.21663E 00	0.62899E 00		
		0.14142E 00	0.64245E 00	0.18974E 00		
		0.63045E 00	0.22803E 00	0.62645E 00		
		0.14849E 00	0.64143E 00	0.19922E 00		
		0.62819E 00	0.23944E 00	0.62379E 00		
		0.15556E 00	0.64035E 00	0.20871E 00		
		0.62583E 00	0.25084E 00	0.62099E 00		
		0.16263E 00	0.63923E 00	0.21820E 00		
		0.62335E 00	0.26224E 00	0.61806E 00		
		0.16971E 00	0.63805E 00	0.22768E 00		
		0.62077E 00	0.27364E 00	0.61501E 00		
		0.17678E 00	0.63683E 00	0.23717E 00		
		0.61808E 00	0.28504E 00	0.61182E 00		




TABLE E.1 (CONT'D.)

17	0.2600E 00	0.1838E 00	0.6355E 00	0.2466E 00	0.6220E 00	0.2726E 00
18	0.2700E 00	0.1527E 00	0.2964E 00	0.6085E 00	0.6196E 00	0.2831E 00
19	0.2800E 00	0.1909E 00	0.6342E 00	0.2561E 00	0.6171E 00	0.2936E 00
20	0.2900E 00	0.1236E 00	0.3078E 00	0.6050E 00	0.6146E 00	0.3041E 00
21	0.3000E 00	0.1979E 00	0.6328E 00	0.2656E 00	0.6119E 00	0.3146E 00
22	0.3100E 00	0.6093E 00	0.3192E 00	0.6014E 00	0.6092E 00	0.3251E 00
23	0.3200E 00	0.2050E 00	0.6314E 00	0.2751E 00	0.6034E 00	0.3356E 00
24	0.3300E 00	0.6062E 00	0.3306E 00	0.5977E 00	0.6004E 00	0.3461E 00
25	0.3400E 00	0.2121E 00	0.6299E 00	0.2846E 00	0.5973E 00	0.3670E 00
26	0.3500E 00	0.6029E 00	0.3420E 00	0.5939E 00	0.5941E 00	0.3775E 00
27	0.3600E 00	0.2192E 00	0.6284E 00	0.2940E 00	0.5908E 00	0.3880E 00
28	0.3700E 00	0.5996E 00	0.3534E 00	0.5898E 00	0.5874E 00	0.4090E 00
29	0.3800E 00	0.2262E 00	0.6268E 00	0.3035E 00	0.5804E 00	0.4195E 00
30	0.3900E 00	0.5961E 00	0.3648E 00	0.5889E 00	0.5768E 00	0.4300E 00
31	0.4000E 00	0.2335E 00	0.6252E 00	0.3130E 00	0.5730E 00	0.4405E 00
32	0.4100E 00	0.5925E 00	0.3762E 00	0.5816E 00	0.5682E 00	0.4505E 00
33	0.4200E 00	0.2404E 00	0.6235E 00	0.3225E 00	0.5634E 00	0.4605E 00
		0.5887E 00	0.3876E 00	0.5773E 00	0.5605E 00	0.4705E 00
		0.2474E 00	0.6218E 00	0.3320E 00	0.5585E 00	0.4805E 00
		0.5850E 00	0.3990E 00	0.5728E 00	0.5559E 00	0.4905E 00
		0.2545E 00	0.6200E 00	0.3415E 00	0.5535E 00	0.5005E 00
		0.5811E 00	0.4104E 00	0.5682E 00	0.5511E 00	0.5105E 00
		0.2616E 00	0.6182E 00	0.3510E 00	0.5484E 00	0.5205E 00
		0.5771E 00	0.4218E 00	0.5634E 00	0.5464E 00	0.5305E 00
		0.2687E 00	0.6163E 00	0.3605E 00	0.5444E 00	0.5405E 00
		0.5730E 00	0.4332E 00	0.5585E 00	0.5424E 00	0.5505E 00
		0.2757E 00	0.6144E 00	0.3699E 00	0.5404E 00	0.5605E 00
		0.5688E 00	0.4446E 00	0.5535E 00	0.5384E 00	0.5705E 00
		0.2828E 00	0.6124E 00	0.3794E 00	0.5364E 00	0.5805E 00
		0.5644E 00	0.4560E 00	0.5484E 00	0.5344E 00	0.5905E 00
		0.2899E 00	0.6104E 00	0.3889E 00	0.5324E 00	0.6005E 00
		0.5600E 00	0.4674E 00	0.5431E 00	0.5304E 00	0.6105E 00
		0.2969E 00	0.6083E 00	0.3984E 00	0.5284E 00	0.6205E 00
		0.5544E 00	0.4788E 00	0.5377E 00	0.5264E 00	0.6305E 00




TABLE E.1 (CONT'D.)

34	0.43000E 00	0.30406E 00	0.60623E 00	0.40793E 00	0.56925E 00	0.45099E 00
	0.55076E 00	0.49027E 00	0.49027E 00	0.53227E 00		
35	0.44000E 00	0.31113E 00	0.60405E 00	0.41742E 00	0.56533E 00	0.46148E 00
	0.54597E 00	0.50168E 00	0.60168E 00	0.52661E 00		
36	0.45000E 00	0.31820E 00	0.60183E 00	0.42691E 00	0.56133E 00	0.47196E 00
	0.54108E 00	0.51308E 00	0.51308E 00	0.52083E 00		
37	0.46000E 00	0.32527E 00	0.59955E 00	0.43639E 00	0.55723E 00	0.48245E 00
	0.53607E 00	0.52448E 00	0.52448E 00	0.51491E 00		
38	0.47000E 00	0.33234E 00	0.59723E 00	0.44588E 00	0.55305E 00	0.49294E 00
	0.53096E 00	0.53588E 00	0.53588E 00	0.50887E 00		
39	0.48000E 00	0.33941E 00	0.59485E 00	0.45537E 00	0.54877E 00	0.50343E 00
	0.52573E 00	0.54728E 00	0.54728E 00	0.50269E 00		
40	0.49000E 00	0.34648E 00	0.59243E 00	0.46485E 00	0.54440E 00	0.51392E 00
	0.52040E 00	0.55869E 00	0.55869E 00	0.49639E 00		
41	0.50000E 00	0.35355E 00	0.58995E 00	0.47434E 00	0.53995E 00	0.52440E 00
	0.51495E 00	0.57009E 00	0.57009E 00	0.48995E 00		
42	0.51000E 00	0.36062E 00	0.58743E 00	0.48383E 00	0.53541E 00	0.53489E 00
	0.50940E 00	0.58149E 00	0.58149E 00	0.48339E 00		
43	0.52000E 00	0.36770E 00	0.58485E 00	0.49331E 00	0.53077E 00	0.54538E 00
	0.50373E 00	0.59289E 00	0.59289E 00	0.47669E 00		
44	0.53000E 00	0.37477E 00	0.58222E 00	0.50280E 00	0.52605E 00	0.55587E 00
	0.49796E 00	0.60429E 00	0.60429E 00	0.46987E 00		
45	0.54000E 00	0.38184E 00	0.57955E 00	0.51229E 00	0.52123E 00	0.56636E 00
	0.49207E 00	0.61569E 00	0.61569E 00	0.46291E 00		
46	0.55000E 00	0.38891E 00	0.57683E 00	0.52178E 00	0.51632E 00	0.57684E 00
	0.48608E 00	0.62710E 00	0.62710E 00	0.45583E 00		
47	0.56000E 00	0.39598E 00	0.57405E 00	0.53126E 00	0.51133E 00	0.58733E 00
	0.47997E 00	0.63850E 00	0.63850E 00	0.44861E 00		
48	0.57000E 00	0.40305E 00	0.57123E 00	0.54075E 00	0.50625E 00	0.59782E 00
	0.47376E 00	0.64990E 00	0.64990E 00	0.44127E 00		
49	0.58000E 00	0.41012E 00	0.56835E 00	0.55024E 00	0.50107E 00	0.60831E 00
	0.46743E 00	0.66130E 00	0.66130E 00	0.4379E 00		
50	0.59000E 00	0.41719E 00	0.56542E 00	0.55972E 00	0.49581E 00	0.61880E 00
	0.46100E 00	0.67270E 00	0.67270E 00	0.42619E 00		




TABLE E.1 (CONT'D.)

51	0.6000E 00	0.42426E 00	0.56245E 00	0.56921E 00	0.49045E 00	0.62928E 00
		0.45445E 00	0.68410E 00	0.41845E 00		
52	0.61000E 00	0.43133E 00	0.55943E 00	0.57870E 00	0.48501E 00	0.63977E 00
		0.44780E 00	0.69551E 00	0.41059E 00		
53	0.62000E 00	0.43841E 00	0.55635E 00	0.58818E 00	0.47947E 00	0.65026E 00
		0.44103E 00	0.70691E 00	0.40259E 00		
54	0.63000E 00	0.44548E 00	0.55323E 00	0.59767E 00	0.47385E 00	0.66075E 00
		0.43416E 00	0.71831E 00	0.39447E 00		
55	0.64000E 00	0.45255E 00	0.55005E 00	0.60716E 00	0.46813E 00	0.67124E 00
		0.42717E 00	0.72971E 00	0.38621E 00		
56	0.65000E 00	0.45962E 00	0.54683E 00	0.61664E 00	0.46233E 00	0.68172E 00
		0.42008E 00	0.74111E 00	0.37783E 00		
57	0.66000E 00	0.46669E 00	0.54355E 00	0.62613E 00	0.45643E 00	0.69221E 00
		0.41287E 00	0.75251E 00	0.36931E 00		
58	0.67000E 00	0.47376E 00	0.54023E 00	0.63562E 00	0.45045E 00	0.70270E 00
		0.40556E 00	0.76392E 00	0.36067E 00		
59	0.68000E 00	0.48083E 00	0.53685E 00	0.64510E 00	0.44437E 00	0.71319E 00
		0.39813E 00	0.77532E 00	0.35189E 00		
60	0.69000E 00	0.48790E 00	0.53343E 00	0.65459E 00	0.43821E 00	0.72368E 00
		0.39060E 00	0.78672E 00	0.34299E 00		
61	0.70000E 00	0.49497E 00	0.52995E 00	0.66408E 00	0.43195E 00	0.73417E 00
		0.38295E 00	0.79812E 00	0.33395E 00		
62	0.71000E 00	0.50205E 00	0.52643E 00	0.67356E 00	0.42561E 00	0.74465E 00
		0.37520E 00	0.80952E 00	0.32479E 00		
63	0.72000E 00	0.50912E 00	0.52285E 00	0.68305E 00	0.41917E 00	0.75514E 00
		0.36733E 00	0.82093E 00	0.31549E 00		
64	0.73000E 00	0.51619E 00	0.51923E 00	0.69254E 00	0.41265E 00	0.76563E 00
		0.35936E 00	0.83233E 00	0.30607E 00		
65	0.74000E 00	0.52326E 00	0.51555E 00	0.70202E 00	0.40603E 00	0.77612E 00
		0.35127E 00	0.84373E 00	0.29651E 00		
66	0.75000E 00	0.53033E 00	0.51183E 00	0.71151E 00	0.39933E 00	0.78661E 00
		0.34308E 00	0.85513E 00	0.28683E 00		
67	0.76000E 00	0.53740E 00	0.50805E 00	0.72100E 00	0.39253E 00	0.79709E 00
		0.33477E 00	0.86653E 00	0.27701E 00		




TABLE E.1 (CONT'D.)

68	0.77000E 00	0.54447E 00	0.50423E 00	0.73049E 00	0.38565E 00	0.80758E 00
69	0.78000E 00	0.32636E 00	0.87793E 00	0.26707E 00	0.37867E 00	0.81807E 00
70	0.79000E 00	0.55154E 00	0.50035E 00	0.73997E 00	0.37161E 00	0.82856E 00
71	0.80000E 00	0.31783E 00	0.88934E 00	0.25699E 00	0.36445E 00	0.83905E 00
72	0.81000E 00	0.55861E 00	0.49643E 00	0.74946E 00	0.35721E 00	0.84953E 00
73	0.82000E 00	0.30920E 00	0.90074E 00	0.24679E 00	0.34987E 00	0.86002E 00
74	0.83000E 00	0.56568E 00	0.49245E 00	0.75895E 00	0.34245E 00	0.87051E 00
75	0.84000E 00	0.30045E 00	0.91214E 00	0.23645E 00	0.33493E 00	0.88100E 00
76	0.85000E 00	0.57276E 00	0.48843E 00	0.76843E 00	0.32733E 00	0.89149E 00
77	0.86000E 00	0.29160E 00	0.92354E 00	0.22599E 00	0.31963E 00	0.90197E 00
78	0.87000E 00	0.57983E 00	0.48435E 00	0.77792E 00	0.31185E 00	0.91246E 00
79	0.88000E 00	0.28263E 00	0.93494E 00	0.21539E 00	0.30397E 00	0.92295E 00
80	0.89000E 00	0.58690E 00	0.48023E 00	0.78741E 00	0.29601E 00	0.93344E 00
81	0.90000E 00	0.27356E 00	0.94634E 00	0.20467E 00	0.28795E 00	0.94393E 00
82	0.91000E 00	0.59397E 00	0.47605E 00	0.79689E 00	0.27981E 00	0.95441E 00
83	0.92000E 00	0.26437E 00	0.95775E 00	0.19381E 00	0.27157E 00	0.96490E 00
84	0.93000E 00	0.60104E 00	0.47183E 00	0.80638E 00	0.26325E 00	0.97539E 00
		0.25508E 00	0.96915E 00	0.18283E 00		
		0.60811E 00	0.46755E 00	0.81587E 00		
		0.24567E 00	0.98055E 00	0.17171E 00		
		0.61518E 00	0.46323E 00	0.82335E 00		
		0.23616E 00	0.99195E 00	0.16047E 00		
		0.62225E 00	0.45885E 00	0.83484E 00		
		0.22653E 00	0.10034E 01	0.14909E 00		
		0.62932E 00	0.45443E 00	0.84433E 00		
		0.21680E 00	0.10148E 01	0.13759E 00		
		0.63640E 00	0.44995E 00	0.85381E 00		
		0.20695E 00	0.10262E 01	0.12595E 00		
		0.64347E 00	0.44543E 00	0.86330E 00		
		0.19700E 00	0.10376E 01	0.11419E 00		
		0.65054E 00	0.44085E 00	0.87279E 00		
		0.18693E 00	0.10490E 01	0.10229E 00		
		0.65761E 00	0.43623E 00	0.88227E 00		
		0.17676E 00	0.10604E 01	0.90266E-01		




TABLE E.1 (CONT'D.)

85	0.94000E 00	0.66468E 00	0.43155E 00	0.89176E 00	0.25483E 00	0.98588E 00
86	0.95000E 00	0.16647E 00	0.10718E 01	0.78112E-01	0.24633E 00	0.99637E 00
87	0.96000E 00	0.67175E 00	0.42683E 00	0.90125E 00	0.23773E 00	0.10069E 01
88	0.97000E 00	0.15608E 00	0.10832E 01	0.65826E-01	0.22905E 00	0.10173E 01
89	0.98000E 00	0.67882E 00	0.42205E 00	0.91074E 00	0.22027E 00	0.10278E 01
90	0.99000E 00	0.14557E 00	0.10946E 01	0.53411E-01	0.21141E 00	0.10383E 01
91	0.10000E 01	0.68589E 00	0.41723E 00	0.92022E 00	0.20245E 00	0.10488E 01
		0.13496E 00	0.11060E 01	0.40866E-01		
		0.69296E 00	0.41235E 00	0.92971E 00		
		0.12423E 00	0.11174E 01	0.28192E-01		
		0.70004E 00	0.40743E 00	0.93920E 00		
		0.11340E 00	0.11288E 01	0.15387E-01		
		0.70711E 00	0.40245E 00	0.94868E 00		
		0.10245E 00	0.11402E 01	0.24509E-02		




TABLE E.2 NUMERICAL DATA FOR OPTIMUM PRESSURE AND TANGENTIAL VELOCITY

NO	X	Y(1)	Y(2)	Y(3)	Y(4)	Y(5)
1	0.10000E 00	0.11402E 01	0.24500E-02	0.45607E 01	-0.97475E 01	0.79812E 01
2	0.20000E 00	-0.31198E 02	0.48995E 00	0.22803E 01	-0.19475E 01	0.39906E 01
3	0.30000E 00	-0.73101E 01	0.58023E 00	0.15202E 01	-0.50310E 00	0.26604E 01
4	0.40000E 00	-0.28006E 00	0.61182E 00	0.11402E 01	0.24500E-02	0.19953E 01
5	0.50000E 00	-0.13382E 01	0.62645E 00	0.91214E 00	0.23645E 00	0.15962E 01
6	0.60000E 00	-0.62155E 00	0.63439E 00	0.76012E 00	0.36356E 00	0.13302E 01
7	0.70000E 00	0.19003E 00	0.63918E 00	0.65153E 00	0.44021E 00	0.11402E 01
8	0.80000E 00	0.14252E 00	0.64229E 00	0.57009E 00	0.48995E 00	0.99765E 00
9	0.90000E 00	0.15479E 00	0.64443E 00	0.50674E 00	0.52406E 00	0.88680E 00
10	0.10000E 01	0.12669E 00	0.64595E 00	0.45607E 00	0.54845E 00	0.79812E 00
11	0.11000E 01	0.11402E 00	0.64708E 00	0.41461E 00	0.56650E 00	0.72557E 00
12	0.12000E 01	0.33395E 00	0.64794E 00	0.38006E 00	0.58023E 00	0.66510E 00
13	0.13000E 01	0.10365E 00	0.64860E 00	0.35082E 00	0.59091E 00	0.61394E 00
14	0.14000E 01	0.87706E-01	0.64913E 00	0.32576E 00	0.59939E 00	0.57009E 00
15	0.15000E 01	0.46399E 00	0.64956E 00	0.30405E 00	0.60623E 00	0.53208E 00
16	0.16000E 01	0.81441E-01	0.64991E 00	0.28504E 00	0.61182E 00	0.49883E 00
		0.51089E 00				
		0.71261E-01				
		0.52804E 00				




TABLE E-2 (CONT'D.)

17	0.17000E 01	0.67069E-01	0.65020E 00	0.26828E 00	0.61646E 00	0.46948E 00
18	0.18000E 01	0.54224E 00	0.65044E 00	0.25337E 00	0.62035E 00	0.44340E 00
19	0.19000E 01	0.55415E 00	0.65065E 00	0.24004E 00	0.62364E 00	0.42007E 00
20	0.20000E 01	0.60009E-01	0.65083E 00	0.22804E 00	0.62645E 00	0.39906E 00
21	0.21000E 01	0.57009E-01	0.65098E 00	0.21718E 00	0.62887E 00	0.38006E 00
22	0.22000E 01	0.57282E 00	0.65111E 00	0.20731E 00	0.63096E 00	0.36278E 00
23	0.23000E 01	0.54294E-01	0.65122E 00	0.19829E 00	0.63279E 00	0.34701E 00
24	0.24000E 01	0.58023E 00	0.65132E 00	0.19003E 00	0.63439E 00	0.33255E 00
25	0.25000E 01	0.47507E-01	0.65141E 00	0.18243E 00	0.63581E 00	0.31925E 00
26	0.26000E 01	0.45607E-01	0.65149E 00	0.17541E 00	0.63707E 00	0.30697E 00
27	0.27000E 01	0.60149E 00	0.65156E 00	0.16892E 00	0.63818E 00	0.29560E 00
28	0.28000E 01	0.43853E-01	0.65162E 00	0.16288E 00	0.63918E 00	0.28504E 00
29	0.29000E 01	0.60533E 00	0.65168E 00	0.15727E 00	0.64008E 00	0.27522E 00
30	0.30000E 01	0.42229E-01	0.65173E 00	0.15202E 00	0.64089E 00	0.26604E 00
31	0.31000E 01	0.60876E 00	0.65177E 00	0.14712E 00	0.64163E 00	0.25746E 00
32	0.32000E 01	0.40721E-01	0.65182E 00	0.14252E 00	0.64229E 00	0.24941E 00
33	0.33000E 01	0.61182E 00	0.65185E 00	0.13820E 00	0.64290E 00	0.24186E 00
		0.39317E-01				
		0.61458E 00				
		0.38006E-01				
		0.61706E 00				
		0.36780E-01				
		0.61931E 00				
		0.35631E-01				
		0.62135E 00				
		0.34551E-01				
		0.62320E 00				




TABLE E-2 (CONT'D.)

34	0.34000E 01	0.33535E-01	0.65189E 00	0.13414E 00	0.64345E 00	0.23474E 00
35	0.35000E 01	0.62490E 00	0.65192E 00	0.13031E 00	0.64396E 00	0.22804E 00
36	0.36000E 01	0.62645E 00	0.65195E 00	0.12669E 00	0.64443E 00	0.22170E 00
37	0.37000E 01	0.31672E-01	0.65198E 00	0.12326E 00	0.64485E 00	0.21571E 00
38	0.38000E 01	0.62787E 00	0.65200E 00	0.12002E 00	0.64525E 00	0.21003E 00
39	0.39000E 01	0.30005E-01	0.65202E 00	0.11694E 00	0.64561E 00	0.20465E 00
40	0.40000E 01	0.29235E-01	0.65204E 00	0.11402E 00	0.64595E 00	0.19953E 00
41	0.41000E 01	0.63151E 00	0.65206E 00	0.11124E 00	0.64626E 00	0.19466E 00
42	0.42000E 01	0.27809E-01	0.65208E 00	0.10859E 00	0.64655E 00	0.19003E 00
43	0.43000E 01	0.63350E 00	0.65210E 00	0.10606E 00	0.64683E 00	0.18561E 00
44	0.44000E 01	0.27147E-01	0.65211E 00	0.10365E 00	0.64708E 00	0.18139E 00
45	0.45000E 01	0.63439E 00	0.65213E 00	0.10135E 00	0.64731E 00	0.17736E 00
46	0.46000E 01	0.25913E-01	0.65214E 00	0.99146E-01	0.64754E 00	0.17351E 00
47	0.47000E 01	0.63600E 00	0.65216E 00	0.97037E-01	0.64774E 00	0.16981E 00
48	0.48000E 01	0.2337E-01	0.65217E 00	0.95015E-01	0.64794E 00	0.16628E 00
49	0.49000E 01	0.63740E 00	0.65218E 00	0.93076E-01	0.64812E 00	0.16288E 00
50	0.50000E 01	0.24259E-01	0.65219E 00	0.91214E-01	0.64829E 00	0.15963E 00
		0.63672E 00				
		0.24787E-01				
		0.63740E 00				
		0.24259E-01				
		0.63803E 00				
		0.23754E-01				
		0.63863E 00				
		0.23269E-01				
		0.63918E 00				
		0.22804E-01				
		0.63971E 00				




TABLE E.2 (CONT'D.)

51	0.51000E 01	0.22356E-01	0.65220E 00	0.89426E-01	0.64845E 00	0.15650E 00
52	0.52000E 01	0.64020E 00	0.65221E 00	0.87706E-01	0.64860E 00	0.15349E 00
53	0.53000E 01	0.64067E 00	0.65222E 00	0.86051E-01	0.64875E 00	0.15059E 00
54	0.54000E 01	0.21513E-01	0.65223E 00	0.84458E-01	0.64888E 00	0.14780E 00
55	0.55000E 01	0.64111E 00	0.65224E 00	0.82922E-01	0.64901E 00	0.14511E 00
56	0.56000E 01	0.20731E-01	0.65224E 00	0.81441E-01	0.64913E 00	0.14252E 00
57	0.57000E 01	0.20360E-01	0.65225E 00	0.80013E-01	0.64925E 00	0.14002E 00
58	0.58000E 01	0.64229E 00	0.65226E 00	0.78633E-01	0.64936E 00	0.13761E 00
59	0.59000E 01	0.19658E-01	0.65226E 00	0.77300E-01	0.64946E 00	0.13528E 00
60	0.60000E 01	0.19325E-01	0.65227E 00	0.76012E-01	0.64956E 00	0.13302E 00
61	0.61000E 01	0.64330E 00	0.65228E 00	0.74766E-01	0.64966E 00	0.13084E 00
62	0.62000E 01	0.18390E-01	0.65228E 00	0.73560E-01	0.64974E 00	0.12873E 00
63	0.63000E 01	0.64389E 00	0.65229E 00	0.72392E-01	0.64983E 00	0.12669E 00
64	0.64000E 01	0.17815E-01	0.65230E 00	0.71261E-01	0.64991E 00	0.12471E 00
65	0.65000E 01	0.64467E 00	0.65230E 00	0.70165E-01	0.64999E 00	0.12279E 00
66	0.66000E 01	0.17541E-01	0.65230E 00	0.69102E-01	0.65006E 00	0.12093E 00
67	0.67000E 01	0.64514E 00	0.65231E 00	0.68070E-01	0.65013E 00	0.11912E 00
		0.64536E 00				






TABLE E.2 (CONT'D.)


68	0.68000E 01	0.16767E-01	0.65231E 00	0.67069E-01	0.65020E 00	0.11737E 00
		0.64556E 00				
69	0.69000E 01	0.16524E-01	0.65231E 00	0.66097E-01	0.65027E 00	0.11567E 00
		0.64576E 00				
70	0.70000E 01	0.16288E-01	0.65232E 00	0.65153E-01	0.65033E 00	0.11402E 00
		0.64595E 00				













MICHIGAN STATE UNIV. LIBRARIES



31293107296851